

List of Tables

1.1	Overview of some of industrial wastes generated worldwide and in India	3
1.2	Major chemical composition of industrial wastes	4
1.3	Chemical composition of red mud generated in different alumina plant	7
1.4	Patents awarded on recovery/extraction of metals from red mud . . .	14
1.5	Previous studies on environmental and agronomic applications	17
1.6	Studies on application of design of experiment in engineering problems	25
2.1	Physical and geotechnical properties of red mud	33
2.2	Chemical properties of red mud and lime	34
2.3	Summaries of factors and their ranges selected for the study	37
2.4	Summary of various design of experiment methods	39
3.1	Summaries of various parameters and their ranges	67
3.2	Method for optimize the exponent	83
3.4	Experimental levels of independent variables for different correlations	90
3.5	Design matrix of input and response of FCC and BB design methods	91
3.6	Summary of various predictive model based on different DOE methods	92
3.7	<i>ANOVA</i> results for FCC design	93
3.8	<i>ANOVA</i> results for BB design	93
3.9	Codification of proposed predictive equations	95
3.10	Statistical performance indices of different predictive models	96
3.11	Correlation matrix between the dependent and independent variables	99
3.13	Experimental levels of independent variables for different correlations for wetting and drying study	101
3.14	Design matrix of input and response of FCC design methods using $\frac{w}{L}$ as fundamental parameter for wetting drying studies	102
3.15	Design matrix of input and response of FCC design methods using $\frac{w}{L_v}$ as fundamental parameter for wetting-drying study	103
3.16	Optimized results for application in pavement layers based on study type E and F	109
3.17	Results of leachate test of red mud with and without treatment . . .	110
4.1	Range of input and output parameters with descriptive statistics con- sidered for conventional design approach	114

4.2	Range of the input parameters in terms of coded and actual factors	115
4.3	Design matrix of input and response based on experimental designed approach	116
4.4	Statistical performance for the conventional designed experimental data sets in UCS based on conventional and response surface methodology designed ANN models	121
4.5	Final connection weights and biases based on conventional designed ANN	122
4.6	Final connection weights and biases based on central composite designed ANN	122
4.7	Final connection weights and biases based on Box-Behnken designed ANN model	122
5.1	Minimum unconfined compressive strength (q_u) criteria for lime stabilized soil in pavement layers	130
5.2	Red mud-lime mix suitable for pavement layers	131
5.3	Mix compositions using for preparation of unfired brick	133
5.4	Selection of stabilized red mud mix for use in pavement	135
A.1	Data sets of UCS results based on conventional designed approach	178
B.1	Design matrix of input and response of FCC and BB design methods for model type B	184
B.2	Summary of various predictive model based on FCC and BB design for model type B	185
B.3	<i>ANOVA</i> results for FCC design for model B	185
B.4	<i>ANOVA</i> results for BB design for model B	186
B.5	Design matrix of input and response of FCC and BB design methods for model type C	186
B.6	Summary of various predictive model based on FCC and BB design for model type C	187
B.7	<i>ANOVA</i> results for FCC design for model C	187
B.8	<i>ANOVA</i> results for BB design for model C	188
B.9	Design matrix of input and response for split tensile strength based on <i>FCCDB</i> and <i>FCCDC</i>	188
B.10	<i>ANOVA</i> results for split tensile strength based model <i>FCCDB</i>	189
B.11	<i>ANOVA</i> results for BB design for model <i>FCCDC</i>	189