

## LIST OF FIGURES

---

<b>Figure 1.1</b> Different Auto-ID techniques .....	1
<b>Figure 1.2</b> Schematic diagram of an RFID system .....	3
<b>Figure 1.3</b> A tree diagram of the thesis .....	10
<b>Figure 2.1</b> RFID system components.....	14
<b>Figure 2.2</b> A semi-rigid differential probe test fixture.....	24
<b>Figure 2.3</b> (a) Schematic configuration of measurement setup with differential probe, (b) impedance measurement setup with VNA.....	24
<b>Figure 3.1</b> Geometry of the linearly tapered meander line cross dipole CP antenna.....	55
<b>Figure 3.2</b> Intermediate stages of the evolution of the designed antenna structure, (a) Linear dipole, (b) Meander line antenna, (c) Linearly tapered meander line antenna, and (d) Cross dipole CP antenna .....	56
<b>Figure 3.3</b> Fabricated prototype of the cross dipole CP antenna .....	59
<b>Figure 3.4</b> Impedance measurement setup of cross dipole CP antenna with VNA ...	60
<b>Figure 3.5</b> Simulated and experimental input resistance of the cross dipole CP antenna.....	60
<b>Figure 3.6</b> Simulated and experimental input reactance of the cross dipole CP antenna.....	61
<b>Figure 3.7</b> Simulated and experimental reflection coefficient of the cross dipole CP antenna and simulated axial ratio .....	62
<b>Figure 3.8</b> Simulated input impedance characteristics of the antenna with variation in length of the semi-circular curve (Lsc) .....	63
<b>Figure 3.9</b> Simulated electric field ratio ( $E_x/E_y$ ) and phase difference characteristics of the antenna with variation in length of the semi-circular curve (Lsc).....	63
<b>Figure 3.10</b> Simulated axial ratio characteristics of the antenna with variation in length of the semi-circular curve (Lsc).....	64
<b>Figure 3.11</b> Simulated surface current density of the cross dipole CP antenna at 915 MHz at different time phases (a) $wt=0^0$ , (b) $wt=90^0$ , (c) $wt=180^0$ , (d) $wt=270^0$ .....	64
<b>Figure 3.12</b> Simulated radiation pattern of the cross dipole antenna at 915 MHz (a) XZ plane, and (b) YZ plane .....	65
<b>Figure 3.13</b> Maximum read range of the cross dipole CP antenna .....	66

<b>Figure 4.1</b> Schematic representation of passive RFID tags (A) Conventional (B) Dual antenna .....	74
<b>Figure 4.2</b> Configuration of the dual-band dual antenna structure.....	75
<b>Figure 4.3</b> Fabricated prototype of the dual band dual antenna with a differential probe.....	77
<b>Figure 4.4</b> Simulated and measured input impedance of the receiving antenna .....	78
<b>Figure 4.5</b> Simulated and measured reflection coefficient against frequency for the receiving antenna .....	78
<b>Figure 4.6</b> Isolation between receiving and backscattering antenna .....	79
<b>Figure 4.7</b> Input impedance of the receiving antenna with backscattering antenna being short circuit ( $Z_L=0$ ) and open circuit ( $Z_L=\infty$ ).....	79
<b>Figure 4.8</b> Radiation patterns of the dual antenna at 866 MHz (a) XZ plane, (b) YZ plane.....	80
<b>Figure 4.9</b> Radiation patterns of the dual antenna at 915 MHz (a) XZ plane, (b) YZ plane.....	81
<b>Figure 4.10</b> Simulated and measured input impedance variation of the backscattering antenna .....	81
<b>Figure 4.11</b> Backscattering RCS of the dual antenna when the receiving antenna is conjugately matched and backscattering antenna in two states (open and short).....	82
<b>Figure 4.12</b> Backscattering RCS of conventional single antenna when in two states (match and short).....	83
<b>Figure 4.13</b> Detection range comparison of the dual antenna and conventional antenna .....	84
<b>Figure 4.14</b> Simulated input impedance of the receiving antenna with different size of metallic surfaces .....	85
<b>Figure 5.1</b> One slot based CP antenna (a) Square- shaped slot, (b) Circular-shaped slot, (c) Cross- shaped slot, (d) Meandered cross-shaped slot (L is 70 mm) .....	89
<b>Figure 5.2</b> Simulated reflection coefficient with frequency of the one slot based CP antenna .....	90
<b>Figure 5.3</b> Axial-ratio at boresight versus frequency of the one slot based CP antenna .....	91
<b>Figure 5.4</b> Simulated result of gain at boresight versus frequency of the one slot based CP antenna .....	91
<b>Figure 5.5</b> A fabricated prototype of the single meandered-cross shaped slot antenna .....	93
<b>Figure 5.6</b> Simulated and measured reflection coefficient with frequency of the single Meandered-cross slot CP antenna .....	93

<b>Figure 5.7</b> Simulated and measured axial-ratio at boresight versus frequency of the single Meandered-cross slot CP antenna .....	94
<b>Figure 5.8</b> Simulated and measured Radiation patterns of the single Meandered-cross slot CP antenna at 915 MHz (a) XZ (b) YZ planes .....	94
<b>Figure 5.9</b> Meandered cross-shaped slot based CP antenna (a) One-, (b) Two-, (c) Four- slot (W= 62 mm).....	95
<b>Figure 5.10</b> Simulated reflection coefficient of one-, two- and four- slot meandered cross-shaped CP antennas .....	96
<b>Figure 5.11</b> Simulated axial ratio at the boresight of one-, two- and four- slot meandered cross-shaped CP antennas .....	97
<b>Figure 5.12</b> Simulated results of gain at the boresight of one-, two- and four- slot meandered cross-shaped CP antennas .....	97
<b>Figure 5.13</b> Simulated surface current distribution for the meandered cross-shaped four-slot LHCP antenna at 915 MHz in the phase of (a) $0^0$ , (b) $90^0$ , (c) $180^0$ , (d) $270^0$ .....	98
<b>Figure 5.14</b> A fabricated prototype of the designed four meandered cross-shaped slot antenna .....	99
<b>Figure 5.15</b> Simulated and measured reflection coefficient of four meandered cross-shaped slot antenna .....	100
<b>Figure 5.16</b> Simulated and measured axial ratio at boresight of four meandered cross-shaped slot antenna .....	100
<b>Figure 5.17</b> Simulated and measured gain of the four meandered cross-shaped slot antenna .....	101
<b>Figure 5.18</b> Simulated and measured Radiation patterns of the four meandered cross-shaped slot antenna at 915 MHz (a) XZ (b) YZ planes .....	101