

## REFERENCES

---

- Agarwal, B.K. "X-ray Spectroscopy", 2nd ed, Springer-verlag, Berlin (1991).
- Ahmed, R.N. and Ramesh, C.S. "Tribological properties of cast copper-sic-graphite hybrid composites", International Symposium of Research Students on Materials Science and Engineering, December 20-22 (2004).
- Aikin, Jr. R.M. and Christodoulou, L. "The role of equiaxed particles on yield stress of composites", Scripta Metallurgica et Materialia, Vol. 25, pp.9-14 (1991).
- Aikin, R.M. "The mechanical properties of in-situ composites", Journal of the Minerals, Metals & Materials Society, Vol. 8, pp.35-39 (1997).
- Akbarpour, M.R., Salahi, E., Hesari, F.A., Simchi, A. and Kim, H.S. "Fabrication, characterization and mechanical properties of hybrid composites of copper using the nanoparticulates of SiC and carbon nanotubes", Materials Science & Engineering A Vol. 572, pp.83–90 (2013).
- Akhtar, F., Askari, S.J., Shah, K.A., Du, X. and Guo, S. "Microstructure, mechanical properties, electrical conductivity and wear behavior of high volume TiC reinforced Cu-matrix composites", Materials Characterization, Vol. 60, pp.327–336 (2009).
- Alaneme, K.K. and Odoni, B.U. "Mechanical properties, wear and corrosion behavior of copper matrix composites reinforced with steel machining chips", Engineering Science and Technology, an International Journal, Vol.19, pp.1593–1599 (2016).
- Alidokht, S. A., Abdollah-zadeh, A. and Assad, H. "Effect of applied load on the dry sliding wear behaviour and the subsurface deformation on hybrid metal matrix composite", Wear, Vol. 305, pp.291–298 (2013).

- Alpas, A.T. and Zhang, J. "Effect of microstructure (particulate/size and volume fraction) and counter face materials on the sliding wear resistance of particulate-reinforced aluminum matrix composites", *Metallurgical and Materials Transactions A*, Vol. 25A, pp.969-983 (1994).
- Ananthi, T., Delphine, S.M., Freeda, M.M., Priya, R.K. and Almusallam, A.W. "Growth and characterization of doped ADP crystal", *Recent Research in Science and Technology*, Vol. 3, pp.32-40 (2011).
- Anil, P.M., Kumar, R. and Sethuramiah, A. "Effect of initial roughness and oxidation on the running-in wear of machined surfaces under dry sliding", *International Journal of Surface Science and Engineering*, Vol. 11, pp.45–64 (2017).
- Arboui, J., Schmitt, Y., Pierrot, J.L. and Royer, F.X. "Experimental bending behaviour of multi-layer sandwich structures", *Archives of Metallurgy and Materials*, Vol. 54, pp.1192-1198 (2009).
- Archard, J.F. "Contact and rubbing of flat surfaces", *Journal of Applied Physics*, Vol. 24, pp.981–988 (1953).
- Arsenault, R.J. "Strengthening of metal matrix composites due to dislocation generation through CTE mismatch", Academic Press, Inc, San Diego, CA, USA, pp.79-100 (1991).
- Ayyappadas, C., Muthuchamy, A., Annamalai, A.R. and Agrawal, D.K. "An investigation on the effect of sintering mode on various properties of copper-graphene metal matrix composite", *Advanced Powder Technology*, Vol. 28, pp.1760–1768 (2017).

- Bagheri, G.H.A. "The effect of reinforcement percentages on properties of copper matrix composites reinforced with TiC particles", *Journal of Alloys and Compounds*, Vol. 676, pp.120-126 (2016).
- Bhagyashekar, M.S. "Wear characteristic of HSS cutting tool during turning operation of cast aluminium alloy-SiC/graphite composite". M.Sc., Engg. Thesis, University of Mysore (1997).
- Bhanu Prasad, V.V., Bhat, B.V.R., Mahajan, Y.R. and Ramakrishnan, P. "Structure–property correlation in discontinuously reinforced aluminium matrix composites as a function of relative particle size ratio", *Materials Science and Engineering A*, Vol. 337, pp.179-186 (2002).
- Bowden, F.P. and Tabor, D. "The Friction and Lubrication of Solids", Part I, Clarendon Press, Oxford (1954).
- Bowden, F.P. and Tabor, D. "The Friction and Lubrication of Solids, Part II", Clarendon Press, Oxford (1964).
- Callister, W.D. "Materials Science and Engineering", John Wiley & Sons, (2007)
- Casati R, and Vedani M, *Metals* 4 (2014).
- Chandrakanth, R.G., Rajkumar, K. and Aravindan, S. "Fabrication of copper–TiC–graphite hybrid metal matrix composites through microwave processing", *International Journal of Advanced Manufacturing Technology*, Vol. 48, pp.645–653 (2010).
- Chawla, K. "Composite Materials, Science and Engineering", third ed., Springer Verlag, New York (2012).
- Chawla, K.K and Metzger, M. "Initial dislocation distributions in tungsten fibre-copper composites", *Journal of Materials Science*, Vol. 7, pp.34-39 (1972).

- Chawla, N. and Shen, Y.L. “Mechanical behavior of particle reinforced metal matrix composites”, *Advanced Engineering Materials*, Vol. 31438-1656/01/0606-0357 (2001).
- Chen, R., Tan, Y., Fang, H., Luo, L., Ding, H., Su, Y., Guo, J. and Hengzhi Fu. “Macro/microstructure evolution and mechanical properties of Ti33.3Al alloys by adding WC particles”, *Materials Science & Engineering A*, Vol. 725, pp.171–180 (2018).
- Chen, X., Tao, J., Yi, J., Liu, Y., Li, C. and Bao, R. “Strengthening behavior of carbon nanotube-graphene hybrids in copper matrix composites”, *Materials Science & Engineering A*, Vol. 718, pp.427–436 (2018)
- Chen, Z., Liu, P., Verhoeven, J.D. and Gibson, E.D. “Tribological behavior of Cu 20%Nb and Cu-15%Cr *in-situ* composites under dry sliding conditions”, *Wear*, Vol. 199, pp.74-81 (1996).
- Daoush, W.M., Lima, B.K., Moa, C.B., Nama, D.H. and Hong, S.H. “Electrical and mechanical properties of carbon nanotube reinforced copper nanocomposites fabricated by electroless deposition process”, *Materials Science and Engineering A*, Vol. 513–514, pp.247–253 (2009).
- Eyre, T.S. "Wear characteristics of metals", *Tribology International*, Vol. 11, pp.203-212 (1976).
- Gautam, R.K., Ray, S., Jain, S.C. and Sharma, S.C. “Tribological behavior of Cu–Cr–SiCp *in situ* composite”, *Wear*, Vol. 265, pp.902–912 (2008).

- Gillman, P.S., Zedalis, M.S., Bryant, J.D. and Das, S.K. “High-temperature discontinuously reinforced aluminum”, *JOM: Journal of the Minerals, metals, and Materials Society*, Vol. 43, pp.29-31 (1991).
- Goldstein, J.I. “Scanning Electron Microscopy and X-ray Microanalysis”, 3rd ed, Plenum Press, New York (2003).
- Grant, J.N., Lee, A. and Lou, M. “Multiple hardening of mechanisms for high strength, high temperature, high conductivity copper base alloys”, *Proc. Con. on High Conductivity Copper and Aluminium Alloys*, Warrendale, Pa, USA, The Metallurgical Society of AIME, pp.103–111 (1984).
- Hashim, J., Looney, L. and Hashmi, M.S.J. “Metal matrix composites: production by the stir casting method”, *Journal of Materials Processing Technology*, Vol. 92-93, pp.1-7 (1999).
- Hasmuddin, M., Singh, P., Shkir, P., Abdullah, M.M., Vijayan, N., Bhagavannarayana, G. and Wahab, M.A. “Structural, spectroscopic, optical, dielectric and mechanical study of pure and L-Proline doped ammonium dihydrogen phosphate single crystals”, *Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy*, Vol.123, pp.376–384 (2014).
- Hassan, A.M., Alrashdan, A., Hayajneh, M.T. and Mayyas A.T. “Wear behavior of Al–Mg–Cu–based composites containing SiC particles”, *Tribology International*, Vol. 42, pp.1230–1238 (2009).
- Hassan, S.F. and Gupta, M. “Development of high strength magnesium copper based hybrid composites with enhanced tensile properties”, *Materials Science and Technology*, Vol. 19, pp.253–259 (2003).

- Haubold, T.R., Bohn, R., Birringer and Gleiter. H. “Nanocrystalline intermetallic compounds-structure and mechanical Properties”, *Materials Science and Engineering, A*, Vol. 153, pp.679-683(1992).
- Hu, Q. Zhaon, H. and Ge, J. “Microstructure and mechanical properties of (B<sub>4</sub>C+Al<sub>3</sub>Ti)/Al hybrid composites fabricated by a two-step stir casting process”, *Materials Science & Engineering A* Vol. 650, pp.478–482 (2016).
- Huang, Z., Zheng, Z., Zhao, S., Dong, S., Luo, P. and Chen, L. “Copper matrix composites reinforced by aligned carbon nanotubes: Mechanical and tribological properties”, *Materials and Design*, Vol. 133, pp.570–578 (2017).
- Jacob, M., Thomas, S. and Varughese, K.T. “Mechanical properties of sisal/oil palm hybrid fiber reinforced natural rubber composites”, *Composites Science & Technology*, Vol. 64, pp.955-965 (2004).
- Jahanmir, S. and Suh, N.P. “Surface topography and integrity effects on sliding wear”, *Wear*, Vol. 44, pp.87–99 (1977).
- Janbozorgi, M., Shamanian, M., Sadeghian, M. and Sepehrinia, P. “Improving tribological behavior of friction stir processed A413/SiCp surface composite using MoS<sub>2</sub> lubricant particles’, *Transactions of Nonferrous Metals Society of China*, Vol. 27, pp.298-304 (2017).
- Jha, P., Gautam, R.K., Tyagi, R. and Kumar, D. “Sliding wear behavior of TiC-reinforced Cu-4 wt.% Ni matrix composites”, *Journal of Materials Engineering and Performances*, Vol. 25, pp.4210–4218 (2016).
- Jia, S.G., Liu, P., Ren, F.Z., Tian, B.H., Zheng, M.S. and Zhou, G.S. “Sliding wear behavior of copper alloy contact wire against copper-based strip for high-speed electrified railways”, *Wear*, Vol. 262, pp.772–777 (2007).

Kainer, K.U. "Basics of metal matrix composites", Development, pp.89-96, (2006).

Kamat, S. R., Heera, S. S., Potdar, P. V., Shah, S. V., Bhambure, N. M. and Mahashur, A. A. "Bombay experience in intensive respiratory care over 6 years", Journal of Postgraduate Medicine, Vol. 35, pp.123-134 (1989).

Kanagaraj, S., Mathew, M.T., Fonseca, A., Oliveira, M.S.A., Simoes, J.A.O. and Rocha, L.A. "Tribological characterization of carbon nanotubes/ultrahigh molecular weight polyethylene composites: the effect of sliding distance", International Journal of Surface Science and Engineering, Vol. 4, pp.305–321 (2010).

Kelly, A. "Strong Solids", Oxford, U.K.: Clarendon Press, p.123 (1966).

Kim, H. J., Jang, Y.J., Choi, J.W., Kown, B., Lee, K. and Ko, Y.S. "Tribological approaches to material removal rate during chemical mechanical polishing", Metals and Materials International, Vol. 19(2), pp.335–339 (2013).

Kim, Y., Lee, J., Yeom, M.S., Shin, J.W., Kim, H., Cui, Y., Kysar, J.W., Hone, J., Jung, Y., Jeon, S. and Han, S.M. "Strengthening effect of single-atomic-layer graphene in metal-graphene nano layered composites", Nature Communications, 4:2114. doi: 10.1038/ncomms3114 (2013).

Kumar, A., Jha, P.K. and Mahapatra, M.M. "Abrasive wear behavior of *in-situ* TiC reinforced with Al-4.5%Cu matrix", Journal of Materials engineering and performances, Vol. 23, pp.743-752 (2014).

Kumar, K.R., Kiran, K. and Sreebalaji, V.S. "Micro structural characteristics and mechanical behaviour of aluminium matrix composites reinforced with titanium carbide", Journal of Alloys and Compounds, Vol. 723, pp.795-801 (2017).

- Kumar, S., Chattopadhyay, K., Singh, S.R. and Singh, V. “Surface nanostructuring of Ti-6Al-4V alloy through ultrasonic shot peening”, *International Journal of Surface Science and Engineering*, Vol. 11, pp.23–35 (2017).
- Lakshmipathy, J. and Kulendran, B. “Reciprocating wear behavior of 7075 Al/SiC in comparison with 6061 Al/Al<sub>2</sub>O<sub>3</sub> composites”, *International Journal of Refractory Metals and Hard Materials*, Vol. 46, pp.137-144 (2014).
- Li, J.F., Zhang, L., Xiao, J.K. and Zhou, K.C. “Sliding wear behavior of copper-based composites reinforced with graphene nano-sheets and graphite”, *Transactions of Nonferrous Metals Society of China*, Vol. 25, pp.3354-3362 (2015).
- Lin, J., Wang, L. and Chen, G. “Modification of graphene platelets and their tribological properties as a lubricant additive”, *Tribology Letters*, Vol. 41, pp.209–215 (2011).
- Lin, Y.C., Li, H.C., Liou, S.S. and Shie M.T. “Mechanism of plastic deformation of powder metallurgy metal matrix composites of CuSn/SiC and 6061/SiC under compressive stress”, *Materials Science and Engineering A*, Vol. 373, pp.363-369 (2004).
- Liu, Y., Lim, S.C., Ray, S. and Rohatgi, P.K. “Friction and wear of aluminum–graphite composite: the Smearing process of graphite during sliding”, *Wear*, Vol. 159, pp.201-205 (1992).
- Lo, S. H.J., Dionne, S. and Sahoo, M. “Mechanical and tribological properties of zinc-aluminium metal-matrix composites”, *Journal of Materials Science*, Vol. 27, pp.5681-5691 (1992).
- Thwe, M.M. and Liao, K. *Composite Science and Technology*, Vol. 63, pp.375 (2003).
- Mai, Y.J., Chen, F.X., Lian, W.Q., Zhang, L.Y., Liu, C.S. and Jie, X.H. “Preparation and tribological behavior of copper matrix composites reinforced with nickel



- nanoparticles anchored graphene nanosheets”, *Journal of Alloys and Compounds*, Vol. 756, 1-7 (2018).
- Majumdar, A. and Bhushan, B. “Fractal model of elastic-plastic contact between rough surfaces”, *Transactions ASME, Journal of Tribology*, Vol. 113, pp.1-11 (1991).
- Maji, P. Dube, R.K. and Basu, B. “Enhancement of wear resistance of copper with tungsten addition ( $\leq 20$  wt %) by powder metallurgy route”, *Journal of Tribology*, Vol. 131, pp.2-11 (2009).
- Mallikarjuna, H.M., Ramesh, C.S., Koppad, P.G., Keshavamurthy, R. and Sethuram, D. “Nano indentation and wear behaviour of copper-based hybrid composites reinforced with SiC and MWCNTs synthesized by spark plasma sintering”, *Vacuum*, Vol. 145, pp.320-333 (2017).
- Mallikarjuna, H.M., Ramesh, C.S., Koppad, P.G., Kashyap, K.T. and Keshavamurthy, R. “Microstructure and microhardness of carbon nanotube-silicon carbide/copper hybrid nanocomposite developed by powder metallurgy”, *Indian Journal of Science and Technology*, Vol. 9(14), DOI: 10.17485/ijst/2016/v9i14/84063 (2016).
- Mallikarjuna, H.M., Ramesh, C.S., Koppad, P.G., Keshavamurthy, R. and Kashyap, K.T. “Effect of carbon nanotube and silicon carbide on microstructure and dry sliding wear behavior of copper hybrid nanocomposites”, *Transactions of Nonferrous Metals Society of China*, Vol. 26, pp.3170–3182 (2016).
- Manoharan, M., and Lewandowski, J.J., “Effects of aging condition on the fracture toughness of 2XXX and 7XXX series aluminum alloy composites”, *Scripta Metallurgica*, Vol. 23, pp. 301-304 (1989).

- Monikandan, V.V., Joseph, M.A. and Rajendrakumar, P.K. “Dry sliding wear studies of aluminum matrix hybrid composites”, *Resource-Efficient Technologies*, Vol. 2, pp.S12–S24 (2016).
- Moustafa, S.F., El-Badry, S.A., Sanad, A.M., Kieback, B, “Friction and wear of copper-graphite composites made with Cu-coated and uncoated graphite powders”, *Wear*, Vol. 253, pp.699–710 (2002).
- Nadkarni, V.A. and Synk, E.J. “Metals Handbook”, Powder Metallurgy ASM, Metals Park OH (1984).
- Nardone, V.C. and Prewo, K.M. “On the strength of discontinuous silicon carbide reinforced aluminum composites”, *Scripta Metallurgica*, Vol. 20, pp.43-48 (1986).
- Nardone, V.C. “Assessment of models used to predict the strength of discontinuous silicon carbide reinforced aluminum alloys”, *Scripta Metallurgica*, Vol. 21, pp.1313-1318 (1987).
- Nath, S.K., Ray, S., and Kapoor, M.L. “A single-particle model for theoretical estimation of tensile strength of two phase metals”, *Metals Materials and Processes*, Vol. 14, pp.241-254 (2002).
- Nguyen, Q.B. and Gupta, M. “Increasing significantly the failure strain and work of fracture of solidification processed AZ31B using nano- $\text{Al}_2\text{O}_3$  particulates”, *Journals of Alloys Compounds*, Vol. 459, pp.244–250 (2008).
- Nguyen, Q.B. and Gupta, M. “Microstructure and mechanical characteristics of AZ31B/ $\text{Al}_2\text{O}_3$  nanocomposite with addition of Ca”, *Journal of Composite Materials*, Vol. 43, pp.5-17 (2009).

- Nguyen, Q.B. and Gupta, M. “Enhancing compressive response of AZ31B using nano- $\text{Al}_2\text{O}_3$  and copper additions”, *Journal of Alloys and Compounds*, Vol. 490, pp. 382-387 (2010).
- Nguyen, Q.B. and Gupta, M. “Enhancing compressive response of AZ31B magnesium alloy using alumina nanoparticulates”, *Composites Science and Technology*, Vol. 68, pp.2185–92 (2008).
- Prabhu, T.R., Varma, V.K. and Vedantam, S. “Effect of SiC volume fraction and size on dry sliding wear of Fe/SiC/graphite hybrid composites for high sliding speed applications”, *Wear*, Vol. 309, pp.1-10 (2014).
- Prabhu, T.R., Varma, V.K. and Vedantam, S. “Tribological and mechanical behavior of multilayer Cu/SiC + Gr hybrid composites for brake friction material applications”, *Wear*, Vol. 317, pp.201-212 (2014).
- Prasad, B.K. “Investigation into sliding wear performance of zinc-based alloy reinforced with SiC particles in dry and lubricated conditions”, *Wear*, Vol. 262, pp.262–73 (2007).
- Prasad, P.R., Ray, S., Gaindhar, J.L. and Kapoor, M.L. “Mechanical properties of Al-10% Cu alloy particulate composites”, *Scripta Metallurgica*, Vol. 19, pp.1019-1022 (1985).
- Rajkovic, V., Bozic, D., Stasic, J., Wang, H. and Jovanovic, M.T. “Processing, characterization and properties of copper-based composites strengthened by low amount of alumina particles”, *Powder Technology*, Vol. 268, pp.392–400 (2014).
- Rajkumar, K. and Aravindan, S. “Tribological performance of microwave sintered copper–TiC–graphite hybrid composites”, *Tribology International*, Vol. 44, pp.347–358 (2011).

- Rajmohan, T., Palanikumar, K. and Ranganathan, S. "Evaluation of mechanical and wear properties of hybrid aluminium matrix composites", Transactions of Nonferrous Metals Society of China, Vol. 23, pp.2509-2517 (2013).
- Rajmohan, T., Palanikumar, K. and Arumugam, S. "Synthesis and characterization of sintered hybrid aluminium matrix composites reinforced with nano copper oxide particles and micro silicon carbide particles", Composites: Part B, Vol. 59, pp.43-49 (2014).
- Ramesh, C.S., Ahmed, R.N., Mujeebu, M.A. and Abdullah, M.Z. "Development and performance analysis of novel cast copper-SiC-Gr hybrid composites", Materials and Design, Vol. 30, pp.1957-1965 (2009).
- Ramesh, C.S., Ahmed, R.N., Mujeebu, M.A. and Abdullah, M.Z. "Fabrication and study on tribological characteristics of cast copper-TiO<sub>2</sub>-boric acid hybrid composites", Materials and Design, Vol. 30, pp.1632-1637 (2009).
- Rao, R.N., Das, S., Mondal, D.P. and Dixit, G. "Dry sliding wear behavior of cast high strength aluminium alloy (Al-Zn-Mg) and hard particle composites", Wear, Vol. 267, pp.1688-1695 (2009).
- Rath, C., Mallick, P., Pandey, D., Sa, D., Banerjee, A. and Mishra, N.C. "Anomalous X-ray diffraction peak broadening and lattice strains in Zn<sub>1-x</sub>CoxO dilute magnetic semiconductors", Journal of Physics: Condensed Matters, Vol. 21, pp.75-80 (2009).
- Ravindran, P., Manisekar, K., Kumar, S.V. and Rathika, P. "Investigation of microstructure and mechanical properties of aluminum hybrid nano-composites with the additions of solid lubricant", Materials and Design, Vol. 51, pp.448-456 (2013).

- Riaz, A. A., Prakash M.K., Paravasu A., Sivanandam A. “Drilling of hybrid Al-5%SiCp-5%B4Cp Metal Matrix Composites”, International Journal of Advance Manufacturing Technology, Vol. 49, pp.871–877 (2010).
- Rino, J. J., Chandramohan, D. and Jebin, V. D. “Research review on corrosion behaviour of metal matrix composites”, International Journal of Current Research, Vol. 4, pp.179-186 (2012).
- Rohatgi, P.K., Asthana, R., Yadav, R.N. and Ray, S. “Energetics of particle transfer from gas to liquid during solidification processing of composites”, Metallurgical and Materials Transactions A, Vol. 21A, pp.2073-2082 (1990).
- Rohatgi, P.K. “Future directions in solidification of metal matrix composites”, Key Engineering Materials, Vol. 104-107, pp.293-312 (1995).
- Rohini, D.G. and Rama, R.K. “Carbon-Carbon Composites-An Overview”, Defence Science Journal, Vol. 43, pp.369-383 (1993).
- Rosso, M. “Ceramic and metal matrix composites: Routes and properties”, Journal of Materials Processing Technology, Vol. 175, pp.364–375 (2006).
- Saka, N., Szeto, N.K. and Erturk, T. “Friction and wear of fiber-reinforced metal-matrix composites”, Wear, Vol. 157, pp.339-357 (1992).
- Samal, C.P., Parihar, J.S. and Chaira, D. “The effect of milling and sintering techniques on mechanical properties of Cu–graphite metal matrix composite prepared by powder metallurgy route”, Journal of Alloys and Compounds, Vol. 569, pp.95–101 (2013).
- Samal, P.K. and Newkirk, J.W. “Powder Metallurgy”, ASM International, Materials Park, OH (1998).

- Sapate, S.G., Uttarwar, A., Rathod, R.C. and Paretkar R.K. “Analyzing dry sliding wear behaviour of copper matrix composites reinforced with pre-coated SiCp particles”, *Materials and Design*, Vol. 30, pp.376–386 (2009).
- Sathiskumar, R., Murugan, N., Dinaharan, I. and Vijay, S.J. “Characterization of boron carbide particulate reinforced in situ copper surface composites synthesized using friction stir processing”, *Materials Characterization*, Vol. 84, pp.16–27 (2013).
- Sharma, P., Sharma, S. and Khanduja, D. “A study on microstructure of aluminium matrix composites”, *Journal of Asian Ceramic Societies*, Vol. 3, pp.240-244 (2015).
- Shen, M.J., Wang, X.J., Ying, T., Zhang, M.F. and Wu, K. “Microstructure and tensile properties of AZ31B alloy and AZ31B-SiCp deformed through a multi-step process”, *Journal of Materials Engineering and Performances*, Vol. 25, pp.4608-4616 (2016).
- Show, B.K., Mondal, D.K., Biswas, K. and Maity, J. “Development of a novel 6351 Al–(Al<sub>4</sub>SiC<sub>4</sub>+SiC) hybrid composite with enhanced mechanical properties”, *Materials Science & Engineering A*, Vol. 579, pp.136–149 (2013).
- Silva, J.I., Alves, A.C., Pinto, A.M., Silva, F.S. and Toptan, F. “Dry sliding wear behaviour of Ti-TiB-TiN<sub>x</sub> in-situ composite synthesized by reactive hot pressing”, *International Journal of Surface Science and Engineering*, Vol. 10, pp.317–329 (2016).
- Sin, H.C., Saka, N. and Suh, N.P. “Abrasive wear mechanisms and grit size effect”, *Wear*, Vol. 55, pp.163-90 (1979).
- Skibo, D.M. Schuster, D.M. and Jolla, L. “Process for preparation of composite materials containing nonmetallic particles in a metallic matrix, and composite materials made by, US Patent No. 4 786 467 (1988).

- Slipenyuk, A. Kuprin, V., Milman, Yu., Spowart, J.E. and Miracle, D.B. “The effect of matrix to reinforcement particle size ratio (PSR) on the microstructure and mechanical properties of a P/M processed AlCuMn/SiCp MMC”, *Materials Science and Engineering A*, Vol. 381, pp.165–170 (2004).
- Slipenyuk, V., Kuprin, Yu., Milman, V. and Goncharuk, J. “Properties of P/M processed particle reinforced metal matrix composites specified by reinforcement concentration and matrix-to-reinforcement particle size ratio”, *Acta Materialia*, Vol. 54, pp.157-166 (2006).
- Song, J.F. and Voburger, T.V. “Friction, lubrication and wear technology”, *Surface Texture, ASM Handbook*, Vol. 18, pp.334-345 (1992).
- Sorkhe, Y.A., Aghajani, H., Tabrizi, A.T. “Mechanical alloying and sintering of nanostructured TiO<sub>2</sub> reinforced copper composite and its characterization”, *Materials and Design*, Vol. 58, pp.168–174 (2014).
- Sreekala, M.S., George, J., Kumaran, M.G. and Thomas, S., “The mechanical performance of hybrid phenol-formaldehyde-based composites reinforced with glass and oil palm fibres”, *Composites Science and Technology*, Vol. 62, pp.339-353 (2002).
- Srinivasan, K. “Composite materials: production, properties, testing and applications”, *Alpha Science International Limited.*, 1-200 (2009).
- Straumal, B.B., Polyakov, S.A., Bischoff, E., Gust, W. and Mittemeijer, E.J. “Faceting of  $\Sigma 3$  and  $\Sigma 9$  grain boundaries in copper”, *Interface Science*, Vol. 9, pp.287-292 (2001).
- Straumal, B.B., Polyakov, S.A. and Mittemeijer, E.J. “Temperature influence on the faceting of  $\Sigma 3$  and  $\Sigma 9$  grain boundaries in Cu”, *Acta Materialia*, Vol. 54, pp.167-172 (2006).
- Suh, N.P. “An overview of the delamination theory of wear”, *Wear*, Vol. 44, pp.1-16 (1977).

- Suh, N.P. “The delamination theory of wear”, *Wear*, Vol. 25, pp.111-24 (1973).
- Suh, N.P. and Nagao, T. “Implications of wear theories on surface quality and functional requirements”, *CIRP Annals: The International Academy for Production Engineering*, Vol. 25, pp.513-519 (1976).
- Surappa, M.K. “Microstructure evolution during solidification of DRMMCs (discontinuously reinforced metal matrix composites): state of art”, *Journal of Materials Processing Technology*, Vol. 63, pp.325-333 (1997).
- Szaraz, Z., Trojanova, Z., Cabbibo, M. and Evangelista, E. “Strengthening in a WE54 magnesium alloy containing SiC particles”, *Materials Science and Engineering A*, Vol. 462, pp.225–229 (2007).
- Tabandeh, K. M., Jenabali, J. S.A. and Moshksar, M.M. “Mechanical properties of tri-modal Al matrix composites reinforced by nano- and submicron-sized Al<sub>2</sub>O<sub>3</sub> particulates developed by wet attrition milling and hot extrusion”, *Materials and Design*, Vol. 31, pp.3880–3884 (2010).
- Tang, Y., Yang, X., Wang, R. and Li, M. “Enhancement of the mechanical properties of graphene–copper composites with graphene–nickel hybrids”, *Materials Science & Engineering A*, Vol. 599, pp.247–254 (2014).
- Taya, M. “Strengthening mechanisms of metal matrix composites”, *Materials Transactions, Japan Institute of Metals*, Vol. 32, pp.1-19 (1991).
- Thomas, T.R. and Sayles, E.R. Thomas. T.R. “Rough Surfaces”, Ed., Longman London, pp.231-233 (1982).



- Thwe, M.M. and Liao, K. “Durability of bamboo-glass fiber reinforced polymer matrix hybrid composites”, *Composites Science and Technology*, Vol. 63, pp.375 (2003).
- Tjong, S.C. “Recent progress in the development and properties of novel metal matrix nanocomposites reinforced with carbon nanotubes and graphene nanosheets”, *Materials Science and Engineering*, Vol. R74, pp.281-350 (2013).
- Tjong, S.C. and Lau, K.C. “Abrasive behavior of TiB<sub>2</sub> particle-reinforced copper matrix composites”, *Materials Science Engineering A*, Vol. 282, pp.183–186 (2000).
- Tjong, S.C. and Lau, K.C. “Tribological behaviour of SiC particle-reinforced copper matrix composites”, *Materials Letters*, Vol. 43, pp.274–280 (2000).
- Tjong, S.C. and Ma, Z.Y. “Microstructural and mechanical characteristics of *in-situ* metal matrix composites”, *Materials Science and Engineering*, Vol. 29, pp.49-113 (2000).
- Tjong, S.C., Wu, S.Q. and Zhu, H.G. “Wear behavior of in situ TiB<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub>/Al and TiB<sub>2</sub>-Al<sub>2</sub>O<sub>3</sub>/Al-Cu composites”, *Composites Science and Technology*, Vol. 59, pp.1341-1347 (1999).
- Tokutomi, J., Uemura, T., Sugiyama, S., Shiomi, J. and Yanagimoto, J. “Hot extrusion to manufacture the metal matrix composite of carbon nanotube and aluminum with excellent electrical conductivities and mechanical properties”, *CIRP Annals-Manufacturing Technology*, Vol. 64, pp.257–260 (2015).
- Tu, J.P., Rong, W., Guo, S.Y. and Yang, Y.Z. “Dry sliding wear behavior of *in-situ* Cu-TiB<sub>2</sub> nanocomposites against medium carbon steel”, *Wear*, Vol. 255, pp.832-835 (2003).
- Venkatesh, R. and Rao, V.S. “Thermal, corrosion and wear analysis of copper based metal matrix composites reinforced with alumina and graphite”, *Defence Technology*, Vol. xxx, pp.1-10 (2018).

- Vettivel, S.C., Selvakumar, N., Leema, N. and Lenin, A.H. “Electrical resistivity, wear map and modeling of extruded tungsten reinforced copper composite”, *Materials and Design*, Vol. 56, pp.791–806 (2014).
- Walid, M.D., Byung, K.L., Chan, B.M., Dong, H.N. and Soon, H.H. “Electrical and mechanical properties of carbon nanotube reinforced copper nanocomposites fabricated by electroless deposition process”, *Materials Science Engineering A*, Vol. 513-514, pp.247–53 (2009).
- Wang, Q., Ding, H., Zhang, H., Chen, R., Guo, J. and Fu, H. “Influence of Mn addition on the microstructure and mechanical properties of a directionally solidified  $\gamma$ -TiAl alloy”, *Materials Characterization*, Vol. 137, pp.133–141 (2018).
- Wang, J., Li, Z, Fan, G., Pan, H., Chen, Z and Zhang, D. “Reinforcement with graphene nanosheets in aluminum matrix composites”, *Scripta Materialia*, Vol. 66, pp.594-597 (2012).
- Wang, S., Zhu, S., Cheng, J., Qiao, Z., Yang, J. and Liu, W. “Microstructural, mechanical and tribological properties of Al matrix composites reinforced with Cu coated  $Ti_3AlC_2$ ”, *Journal of Alloys and Compounds*, Vol. 690, pp.612-620 (2017).
- Williamson, G.K. and Hall, W.H. “X-ray line broadening from filed aluminium and wolfram”, *Acta Metallurgica*, Vol. 1, pp.22–31 (1953).
- Wilson, S. and Alpas, A.T. “Wear Mechanism Maps for Metal Matrix Composites”, *Wear*, Vol. 212, pp.41-49 (1997).
- Wood, J.T., Embury, J.D. and Ashby, M.F. “An approach to materials processing and selection for high-field magnet design”, *Acta materialia*, Vol. 45, pp.1099-1104 (1997).

- Xu, D. and Xue, D. “Chemical bond analysis of the crystal growth of KDP and ADP”, *Journal of Crystal Growth*, Vol. 286, pp.108–113 (2006).
- Yu, G.Q., Tay, B. K. and Sun, Z. “Fluorinated amorphous diamond- like carbon films deposited by plasma-enhanced chemical vapor deposition”, *Surface and Coating Technology*, Vol. 191, pp.236–241 (2005).
- Yuan, L., Han, J., Liu, J. and Jiang, Z. “Mechanical properties and tribological behavior of aluminum matrix composites reinforced with in-situ  $AlB_2$  particles”, *Tribology International*, Vol. 98, pp.41-47 (2016).
- Yuanyuan, H., Hong, G., Fazhang, Y., Ximin, Z., Ke, C. and Yeming, F. “Microstructure and thermal conductivity of copper matrix composites reinforced with mixtures of diamond and SiC particles”, *Rare Metals*, Vol. 31, 58 DOI: 10.1007/s12598-012-0463-1 (2012).
- Zhan, Y., Zhang, G. and Zhuang, Y. “Wear transitions in particulate reinforced copper matrix composites”, *Materials Transaction*, Vol. 45, pp.2332–2338 (2004).
- Zhan, Y.Z. and Zhou, H.Y. “Effect of sliding condition and wear surface state on the tribological behaviour of SiCp/Cu composite”, *Journal of Materials Science & Technology*, Vol. 21, pp.841–846 (2005).
- Zhang, X., Zhang, Q. and Hu, H. “Tensile behaviour and microstructure of magnesium AM60-based hybrid composite containing  $Al_2O_3$  fibers and particles”, *Materials Science and Engineering A*, Vol. 607, pp.269–276 (2014).
- Zhang, Z. and Chen, D.L. “Contribution of Orowan strengthening effect in particulate-reinforced metal matrix nanocomposites”, *Materials Science and Engineering A*, Vol. 483–484, pp.148–152 (2008).

Zhang, Z., Tremblay, R. and Dube, D. “Microstructure and mechanical properties of ZA104 (0.3–0.6 Ca) die-casting magnesium alloys”, *Materials Science and Engineering A*, Vol. 385, pp.286–91 (2004).

Zhou, S., Wu, C., Zhang, T. and Zhang, Z. “Carbon nanotube- and FeP-reinforced copper–matrix composites by laser induction hybrid rapid cladding”, *Scripta Materialia*, Vol. 76, pp.25–28 (2014).

Zuhailawati, H. and Yong, T.L. “Consolidation of dispersion strengthened copper–niobium carbide composite prepared by in situ and ex situ methods”, *Materials Science and Engineering A*, Vol. 505, pp.27–30 (2009).