LIST OF FIGURES

Figure No.	Figure Caption	Page No.
Figure 2.1	Knowledge domain structure	39
Figure 2.2	Flowchart for offline tuning of controllers with optimization techniques	42
Figure 2.3	Flowchart for controller tuning in dynamical mode	43
Figure 2.4	Generalized control structure	44
Figure 3.1	Multi-Machine power system	52
Figure 3.2	Transfer function block diagram of low-frequency oscillation studies	64
Figure 3.3	Block diagram of PSS model	65
Figure 3.4	Two Area power network with UPFC	67
Figure 3.5	Two Area Four Machine power system	85
Figure 3.6	Six Area Six Machine power system	86
Figure 3.7	Ten Area Fifty Machine power system	87
Figure 3.8	Flowchart of MSLQR controller	94
Figure 3.9	Flowchart of Integrated MSLQR-POD controller	96
Figure 3.10	Two Area Four Machine power system with UPFC	99
Figure 3.11	Perturbation response for different controllers with UPFC (Two Area Four Machine System)	101
Figure 3.12	Perturbation response for different controllers with STATCOM (Area 5 and Area 6) – Case I	104
Figure 3.13	Perturbation response of Six Area system for all the controllers with SSSC – Case II	107
Figure 3.14	Perturbation response of Six Area system for different controllers with UPFC (Area 5 and Area 6) – Case III	110
Figure 3.15	Flowchart for Modified-Multi Stage LQR controller	113
Figure 3.16	Variation in all state variables for both controllers with UPFC - Case IV	115
Figure 4.1	Flowchart of particle swarm optimization to develop knowledge domain structure	130
Figure 4.2	Flowchart of firefly algorithm to develop knowledge	133

	domain structure	
Figure 4.3	Flowchart of gravitational search algorithm to develop knowledge domain structure	136
Figure 5.1	Layered structure of knowledge domain based hierarchy of control	143
Figure 5.2	Sample Six Area test system 1	144
Figure 5.3	Perturbed responses for Area 6 with proposed concept (FA driven KDIM) for Case 5.1	145
Figure 5.4	Perturbed responses for Area 6 with proposed concept (FA driven KDIM) for Case 5.2	146
Figure 5.5	Perturbed responses for Area 6 with proposed concept (FA driven KDIM) for Case 5.3	147
Figure 5.6	Sample Six Area test system 2	149
Figure 5.7	Perturbed responses of Area 3 with proposed concept (FA driven KDIM) for Case 5.4 (only PSS)	150
Figure 5.8	Perturbed responses with proposed concept (FA driven KDIM) for Case 5.5 (only PSS)	151
Figure 5.9	Perturbation response for Area 6 of system state without PSO and with PSO driven knowledge domain at time t_1 (t_1=0 sec) (Case 5.6)	155
Figure 5.10	Perturbation responses for Area 6 of system states with PSO driven knowledge domain as load increased by 10 % after time t_2 (1 second) (Case 5.6)	156
Figure 5.11	Perturbation responses for Area 3 of system states with GSA driven knowledge domain as load reduced after time t_2 (2.5 seconds) (Case 5.7)	158
Figure 5.12	States response with all the three optimization techniques driven KD states mapping concept for Six Area System (Case 5.8)	160
Figure 5.13	Ten Area Fifty Machines power system - PSS with each generator	163
Figure 5.14	Angular speed deviation for all the generators connected in Area 2 (Case 5.9)	164

Figure 5.15	Phase angle deviation for all the generators in Area 2 (Case 5.9)	165
Figure 5.16	Perturbation responses of state variables of Area 1 (Case 5.10)	169
Figure 5.17	Angular speed deviation for all the generators connected in Area 2 (Case 5.11)	173
Figure 5.18	Phase angle deviation for all the generators connected in Area 2 (Case 5.11)	174
Figure 5.19	Sample Six Area system with STATCOM between area 3 and 4	178
Figure 5.20	Perturbation responses of system states for Case 5.12 for Six Area system with PSS only (Area 3)	179
Figure 5.21	Perturbation responses of system states for Case 5.12 for Six Area system with STATCOM supplements PSS (Area 3)	179
Figure 5.22	Six Area system with SSSC between area 1 and 3	181
Figure 5.23	States response when PSS fails to stabilize as line length of transmission line increases (Case 5.13)	183
Figure 5.24	States response of PSS with SSSC (Case 5.13)	184
Figure 5.25	Sample Six Area test system 1	185
Figure 5.26	Perturbation response of system states with load (Ld2) for Area 3 (only PSS) (Case 5.14)	186
Figure 5.27	Perturbation response of system states with load (Ld2) for Area 3 (PSS with UPFC) (Case 5.14)	187
Figure 5.28	Ten Area Fifty Machines power system - PSS with each generator	188
Figure 5.29	Angular speed deviation for all the generators connected in Area 2 with PSS only (Case 5.15)	189
Figure 5.30	Phase angle deviation for all the generators connected in area 2 with PSS only (Case 5.15)	190
Figure 5.31	Angular speed deviation for all the generators connected in Area 2 with UPFC supplements PSS (Case 5.15)	191
Figure 5.32	Phase angle deviation for all the generators connected in	192

	Area 2 with UPFC supplements PSS (Case 5.15)	
Figure 5.33 (a)	PSCAD/EMTDC model of Two Area Four Machine system	194
Figure 5.33 (b)	PSCAD/EMTDC model of generator	195
Figure 5.34	Two Area Four Machine test system	195
Figure 5.35	System response of generator 1 with case 5.16 (PSCAD/EMTDC)	197
Figure 5.36	System response of generator 2 with case 5.16 (PSCAD/EMTDC)	198
Figure 5.37	System response of generator 3 with case 5.16 (PSCAD/EMTDC)	199
Figure 5.38	System Response of generator 4 with case 5.16 (PSCAD/EMTDC)	200
Figure 5.39	Perturbation response of generator 1 with case 5.16 (MATLAB)	201
Figure 5.40	Perturbation response of generator 2 with case 5.16 (MATLAB)	202
Figure 5.41	Perturbation response of generator 3 with case 5.16 (MATLAB)	203
Figure 5.42	Perturbation response of generator 4 with case 5.16 (MATLAB)	204
Figure 5.43	PSCAD model for Two Area Four Machine test system with STATCOM	206
Figure 5.44	PSCAD model of STATCOM device	206
Figure 5.45	System response with the effect of STATCOM in addition to PSS for generator 1 with Case Study 5.17 (PSCAD Software)	207
Figure 5.46	System response of generator 1 only with PSS (when PSS alone fails to stabilize the system) Case 5.17 in MATLAB Software	208
Figure 5.47	System response of generator 1 when STATCOM supplements PSS - Case 5.17 (MATLAB Software)	209