LIST OF FIGURES

Figure 1. 1: Different technical measures on the CO ₂ emission
Figure 2. 1: Specific Strength of different materials
Figure 2. 2: Specific stiffness of different materials
Figure 2. 3: General classification of applications magnesium alloys
Figure 2. 4: Applications of magnesium alloys parts in an automobile
Figure 2. 5: (a) AZ80 compressor wheel produced by closed-die forging; (b) WE43 impeller with twisted blades; (c) WE43 compressor upper case for air conditioning system produced by closed- die forging; (d) AZ31B eurocopter antenna support produced by deep drawing; (e) AZ80- forged airbus window frame; (f) AZ80- forged door stop fitting
Figure 2. 6: Different parts of the helicopter where magnesium alloy is used
Figure 2. 7: Application of Magnesium alloy in sports and leisure equipment
Figure 2. 8: Application of magnesium alloy as an orthopedic implant
Figure 2. 9: Die-cast magnesium alloy laptop computer case (Image courtesy of Stihl and spotlight metal)
Figure 2. 10: Use of magnesium alloy in the housing a) digital camera and b) handy cam
Figure 2. 11: Thixomolded magnesium compound edge eyewear
Figure 2. 12: Circular power saw made by die-cast magnesium bases and blade guard.17
Figure 2. 13: Showing the effect of magnesium melt protection
Figure 2. 14: Schematic of the Ellingham diagram for selected oxides, the magnesium oxidation is marked with a dashed line
Figure 2. 15: The hazardless of one standard cylinder 52 kg of SF ₆ equivalent to CO ₂ emission by 240 U.S. passenger for one year or absorption of it by planting 210 acres of trees
Figure 2. 16: Schematic of stir casting set-up for magnesium casting
Figure 2. 17: Metal matrix composites types

Figure 2. 18: Contact angle (θ) between solid-liquid, solid	d-gas, and liquid –gas37
Figure 2. 19: Experimental and theoretical CTE value models as a function of weight percentage of (25 µm) in Mg matrix	f SiC reinforcement particulate
Figure 2. 20: The Experimental and theoretical elastic models, as a function of the amount	of SiC in the aluminum matrix
Figure 2. 21: Schematic illustrations of the stresses of a re-	ectangular platelet44
Figure 2. 22: The six stages in the coefficient of relationship	
Figure 3. 1: Morphology of SiC particulates	61
Figure 3. 2 : EDAX of SiC particulates	
Figure 3. 3: Morphology of TiC particulates	
Figure 3. 4: EDAX of TiC particulates	
Figure 4. 1: General schematic view of stir casting set-up	70
Figure 4. 2: Schematic of the general stir casting set-up	71
Figure 4. 3: Photograph of first experimental stir casting s	set-up72
Figure 4. 4: Initial stirrer motor.	73
Figure 4. 5: Modified Stirrer motor.	73
Figure 4. 6: First magnesium alloy casting a) Backside b)	Front side74
Figure 4. 7: Schematic of the vacuum-assisted inert atmos	sphere experimental set-up 75
Figure 4. 8: Furnace with other attachments	76
Figure 4. 9: Metallic crucible with flange	77
Figure 4. 10: Different position of stirrer motor assembly	78
Figure 4. 11: Pneumatic high-pressure cylinder arrangement the pouring valve	
Figure 4. 12: a) Die holder with die b) two-part die of ca	st iron79

Figure 4. 13: Pressure variation at different time frame a) normal condition b) vacuum reaction c) melting and pouring
Figure 4. 14: Different modes of reinforcement addition in molten metal a) through anti-chamber b) aluminum foil capsule c) array of the hole
Figure 4.15: Photograph of Cast product
Figure 5.1: Optical Micrograph of AZ91 Magnesium Alloy at different magnifications a) 50X b) 100X c) 200X d)500X
Figure 5.2: Optical Micrograph of AZ91 Magnesium Alloy at different places with magnifications 200X
Figure 5.3: Optical Micrograph of AZ91/SiC Magnesium Alloy composite at different weight percentage a) 3 % SiC b) 6% SiC c) 9% SiC d) 12 % SiC
Figure 5.4: SEM micrograph showing distribution of SiC particulate in AZ91 magnesium alloy (a) 3 % SiC (b) 6% SiC (c) 9% SiC (d) 12% SiC
Figure 5.5: X-ray diffraction analysis of magnesium alloy and its composites with different (3%, 6%,9% and 12%) weight percentage
Figure 5. 6: Variation of Vickers microhardness at the load of 9.81N at different location of the alloy and composites with different percentage of SiC particulates
Figure 5. 7: Average Vickers microhardness of alloy and composite with different percentage of SiC particulates at the load of 9.81 N
Figure 5. 8: Engineering stress-strain curve of AZ91 and its composite reinforced with SiC particulates
Figure 5. 9: Variation of ultimate tensile strength and yield strength with a variation of SiC particulates
Figure 5. 10: Representation of ultimate compressive strength of alloy and composites with different percentage of SiC
Figure 5. 11: SEM micrograph of cast magnesium alloy AZ91
Figure 5. 12: SEM micrograph of cast magnesium alloy AZ91 based composites a) 3% SiC b) 6% SiC c) 9% SiC d) 12% SiC
Figure 5. 13: Fractured samples in a compression test
Figure 5. 14 SEM micrograph of the fracture surface of AZ91 at different magnification a) 41X b) 100X c) 200X d)500X

Figure 5. 15: SEM micrograph of fracture surface of AZ91 based composites reinforced with a) 3% SiC b) 6% SiC c) 9% SiC d) 12% SiC
Figure 5. 16: The variation of wear weight loss with normal load at a constant sliding speed of 1.39 m/s
Figure 5. 17: The variation of wear rate with an applied normal load of AZ91 magnesium alloy and its composite reinforced by SiC particulates 105
Figure 5. 18: Average coefficient of friction of the AZ91 magnesium alloy and its composites at different normal load
Figure 5. 19: Variation average coefficient of friction of the AZ91 magnesium alloy and its composites at a different weight percentage of SiC and different normal load
Figure 5. 20: Variation of wear loss of AZ91 magnesium alloy at different velocity and different applied normal load
Figure 5. 21: Variation of wear loss of 3 weight percent SiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 5. 22: Variation of wear loss of 6 weight percent SiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 5. 23: Variation of wear loss of 9 weight percent SiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 5. 24: Variation of wear loss of 12 weight percent SiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 5. 25: SEM micrographs of the worn surfaces of AZ91 magnesium alloy a) 39.24 N, 2.6 m/s and 200X b) 19.62 N, 2.6 m/s and 1000X c) 39.24 N, 1.39 m/s and 500X d) 39.24 N, 1.39 m/s and 1000X
Figure 5. 26: SEM micrographs of the worn surfaces of SiC reinforced AZ91 magnesium alloy composite a) 39.24 N, 1.3 m/s and 6% SiC b) 19.62 N, 2.6 m/s 3% SiC c) 58.86, 2.6 m/s 9% SiC d) 39.24 N, 2.6 m/s 12% SiC.111
Figure 5. 27: Energy-dispersive X-ray spectroscopy of worn surfaces
Figure 6. 1: Optical micrograph of TiC/AZ91 magnesium alloy composite at different weight percentage a) 3 % TiC b) 6% SiC c) 9% TiC d) 12 % TiC118
Figure 6. 2: Optical Micrograph of TiC/AZ91 magnesium alloy composite at higher magnifications a) 3 % TiC b) 6% TiC c) 9% TiC d) 12 % TiC118

Figure 6. 3: SEM micrograph showing distribution of TiC particulate in AZ91 magnesium alloy (a) 3 % TiC (b) 6% TiC (c) 9% TiC (d) 12% TiC 119
Figure 6. 4: X-ray diffraction analysis of magnesium alloy and its composites with different (3%, 6%,9% and 12%) weight percentage of TiC particulates 120
Figure 6. 5: Comparative plot of peaks of TiC particulates and AZ91 magnesium alloy
Figure 6. 6: Variation of Vickers micro hardness of magnesium alloy and its composites reinforced
Figure 6. 7: Average Vickers micro hardness of AZ91 alloy and its composite with different percentage of TiC particulates reinforcement
Figure 6. 8: Engineering stress-strain curve of AZ91 and its composite reinforced with SiC particulates
Figure 6. 9: Variation of ultimate tensile strength and yield strength with variation of SiC particulates
Figure 6. 10: Representation of ultimate compressive strength of AZ91 alloy and its composites reinforced with different weight percentage of TiC
Figure 6. 11: SEM micrograph of cast magnesium alloy AZ91 based composites a) 3% TiC b) 6% TiC c) 9% TiC d) 12% TiC
Figure 6. 12: SEM micrograph of 6 % TiC reinforced magnesium alloy composites at different magnification a) 49X b) 500X c) 2000X d) 5000X
Figure 6. 13: The variation of wear weight loss with different normal load at sliding speed 1.39 m/s
Figure 6. 14: The variation of wear rate with applied normal load of AZ91 magnesium alloy and its composite reinforced by TiC particulates
Figure 6. 15: Average coefficient of friction of the AZ91 magnesium alloy and its composites reinforced with TiC particulates at different applied normal load
Figure 6. 16: Variation average coefficient of friction of the AZ91 magnesium alloy and its composites at different weight percentage of TiC and different applied normal load
Figure 6. 17: Variation of wear rate of AZ91 magnesium alloy at different velocity and different applied normal load

Figure 6.	18: Variation of wear rate of 3 percent weight of TiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 6.	19: Variation of wear loss of 6 percent weight of TiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 6. 2	20: Variation of wear loss of 9 percent weight of TiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 6. 2	21: Variation of wear loss of 12 percent weight of TiC in AZ91 magnesium alloy at different velocity and different applied normal load
Figure 6.	22: SEM micrographs of the worn surfaces of TiC reinforced AZ91 magnesium alloy composite a) 39.24 N, 1.3 m/s and 6% TiC b) 19.62 N, 2.6 m/s 3% TiC c) 58.86, 2.6 m/s 9% TiC d) 39.24 N, 2.6 m/s 12% TiC

LIST OF TABLES

Table 2. 1: ASTM designation system of magnesium alloy [18], [70]22
Table 2. 2 Temper designation for magnesium alloy [18]23
Table 2. 3: List of some typical matrix materials [86], [88]–[90]
Table 2. 4: Some common reinforcements and their properties
Table 3. 1: The composition (% wt.)of commercial alloy AZ9160
Table 4. 1: Different pats/ dimension and its specifications
Table 4. 2: Effect of a different mode of reinforcement addition with the decision 82
Table 5.1: Density and porosity measurements of AZ91 alloy and its composite (AZ91/SiC)
Table 5. 2: Vickers microhardness of magnesium alloy and its composite
Table 5. 3: The ultimate tensile strength and yield Strength
Table 5. 4: Ultimate Compressive strengths of AZ91 alloy and its composites 95
Table 5. 5: Parameters for the pin on disk dry sliding wear test
Table 5. 6: Summary of wear mechanisms for different combination of normal load sliding speed and pin materials
Table 6. 1: Density and porosity measurements of AZ91 alloy and its composite reinforced with TiC particulates
Table 6. 2: The average Vickers microhardness of magnesium alloy and its composite
Table 6. 3: The ultimate tensile strength and yield strength
Table 6. 4: Ultimate compressive strength of AZ91 alloy and its composites reinforced with different weight percent of TiC
Table 6. 5: Parameters for the pin on disk dry sliding wear test
Table 6. 6: Prediction of wear mechanisms for a different combination of normal load sliding speed and pin materials