

List of Tables

Table No.	Name of Table	Page No.
Table 1.1	Different group of commercially available aluminum alloys	3
Table 1.2	literature review summery of aluminum alloys and with different heat treatments	7
Table 1.3	Literature review summery of metal matrix composites of aluminum alloys	9
Table 1.4	Literature review summery of micro-structural investigation	10
Table 1.5	Literature review summery of theoretical analysis of LCF	11
Table 1.6	Literature review summery of empirical analysis of LCF	11
Table 1.7	Literature review summery of numerical analysis of LCF	12
Table 3.1	Chemical composition and EDAX analysis for as-received AA6063-T6 alloy at room temperature	76
Table 3.2	Tensile properties for as-received AA6063-T6 alloy at room temperature	79
Table 3.3	Comparison of values of n, K and $\sigma_{fracture}^{true}$	79
Table 3.4	Torsion test data for as-received AA6063-T6 alloy at room temperature	80
Table 3.5	Vickers micro hardness for As Received AA6063-T6 alloy at different load	81

List of Tables

Table 3.6	Vickers Macro hardness for As Received AA6063-T6 alloy at different load	82
Table 3.7	Cyclic data for cantilever beam fatigue test of as-received AA6063-T6 at room temperature	83
Table 3.8	Strain-controlled fatigue properties of as received AA6063-T6 aluminum alloy	84
Table 3.9	Comparison of values of n' and K'	85
Table 3.10	Comparison of experimental, numerical and theoretical results for elastic strain as received AA6063 alloy	86
Table 3.11	Comparison of experimental, numerical and theoretical results for plastic strain AA6063 as received	86
Table 3.12	and modified R^2 values for elastic , plastic and total strain for as received AA6063-T6 alloy	90
Table 4.1	The monotonic properties of AA6063 at different heat treatment temperatures with same soaking time	95
Table 4.2	Comparison of values of n, k and $\sigma_{fracture}^{true}$ for AA6063 (100°C_2hour)	95
Table 4.3	Comparison of values of n, k and $\sigma_{fracture}^{true}$ for AA6063 (200°C_2hour)	95
Table 4.4	Comparison of values of n, k and $\sigma_{fracture}^{true}$ for AA6063 (350°C_2hour)	95

List of Tables

Table 4.5	Torsion test data for AA6063 for different heat treatment temperatures with same soaking time	98
Table 4.6	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 100°C with soaking time of 2 hours	101
Table 4.7	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 200°C with soaking time of 2 hours	102
Table 4.8	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 350°C with soaking time of 2 hours	104
Table 4.9	Low cycle fatigue properties of aluminum alloy AA6063 at different heat treatment temperatures with same soaking time	106
Table 4.10	Comparison of experimental, numerical and empirical results of elastic strain for AA6063 with different heat treatment temperature at same soaking time	108
Table 4.11	Comparison of experimental, numerical and empirical results of Plastic strain for AA6063 with different heat treatment temperature at same soaking time	109
Table 4.12	R^2 and modified R^2 values for elastic , plastic and total strain for AA6063 with different heat treatment temperature at same soaking time	119

List of Tables

Table 5.1	The monotonic properties of AA6063 at same heat treatment temperature 350°C with different soaking time	125
Table 5.2	Comparison values of n, k and $\sigma_{fracture}^{true}$ for AA6063 heat treated at 350°C with 4hours soaking time	125
Table 5.3	Comparison values of n, k and $\sigma_{fracture}^{true}$ for AA6063 heat treated at 350°C with 6hours soaking time	126
Table 5.4	Comparison values of n, k and $\sigma_{fracture}^{true}$ for AA6063 heat treated at 350°C with 8hours soaking time	126
Table 5.5	Torsion test data for AA6063 samples at different soaking times with same heat treatment temperature of 350°C	130
Table 5.6	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 350°C and with soaking time of 2 hours	132
Table 5.7	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 350°C and with soaking time of 4 hours	134
Table 5.8	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 350°C and with soaking time of 6hours	135
Table 5.9	Cyclic data for rotating cantilever low cycle fatigue test of AA6063 alloy heat treated at 350°C and with soaking time of 8 hours	136

List of Tables

Table 5.10	Low cycle fatigue parameters of aluminum alloy AA6063 at different soaking time and same heat treatment temperature of 350°C	137
Table 5.11	Comparison of experimental, numerical and empirical results for elastic strain for AA6063 at different soaking times for same heat treatment temperature of 350°C	141
Table 5.12	Comparison of experimental, numerical and empirical results for Plastic strain for AA6063 at different soaking times for same heat treatment temperature of 350°C	141
Table 5.13	R ² and modified R ² values for elastic , plastic and total strain for AA6063 with different soaking time and at same heat treatment temperature of 350°C	152
Table 6.1	The monotonic properties of AA6063 at different volume fraction of SiCp reinforcement particle	158
Table 6.2	Comparison values of n, k and $\sigma_{fracture}^{true}$ for AA6063/SiCp p (2% Vf) MMC	158
Table 6.3	Comparison values of n, k and $\sigma_{fracture}^{true}$ for AA6063/SiCp p (8% Vf) MMC	158
Table 6.4	Torsion test data	161
Table 6.5	Cyclic data for rotating cantilever low cycle fatigue test of AA6063/SiCp (2% Vf) MMC	164

List of Tables

Table 6.6	Cyclic data for rotating cantilever low cycle fatigue test of AA6063/SiCp (8% V_f) MMC	165
Table 6.7	Low cycle fatigue properties of aluminum alloy AA6063+ SiCp with different volume fraction V_f % of reinforcement particle size	166
Table 6.8	Comparison of experimental, numerical and empirical results for elastic strain AA6063 for Metal Matrix Composite at different volume fraction of SiCp reinforcement particle	170
Table 6.9	Comparison of experimental, numerical and empirical results for Plastic strain AA6063 for Metal Matrix Composite at different volume fraction of SiCp reinforcement particle	170
Table 6.10	R^2 and modified R^2 values for elastic , plastic and total strain for AA6063/SiCp MMC with different volume fraction V_f of SiCp reinforcement particle	177
Table 7.1	Tensile properties of the as received alloy AA6063-T6	181
Table 7.2	Variation of number of reversals to failure (2Nf) with different components of strain amplitude at RT for the alloyAA6063 at fracture point of each sample	199
Table 8.1	JCPDF data for intensity and crystallites as-received condition-T6 with loading and without loading	204

List of Tables

Table 8.2	Crystallite size and diameter for as-received condition AA6063-T6 at different loads	204
Table 8.3	Crystallite size and diameter of sample at fracture data for AA6063 with different heat treatment temperature for same soaking time of 2 hours	208
Table 8.4	Crystallite size and diameter of sample at fracture data for AA6063 with different soaking time for same heat treatment temperature of 350°C	212
Table 8.5	Crystallite size and diameter of sample at fracture data for AA6063/SiCp MMC	216
Table A.1	X-RD experimental data for as-received AA6063-T6 alloy without loading	257
Table A.2	X-RD experimental data for as-received AA6063-T6 alloy at 4.5 kg loading	258
Table A.3	X-RD experimental data for as-received AA6063-T6 alloy at 6.9 kg loading	258
Table A.4	X-RD experimental data for as-received AA6063-T6 alloy at 7.389 kg loading	258
Table A.5	X-RD experimental data for as-received AA6063-T6 alloy at 8.55 kg loading	259
Table A.6	X-RD experimental data for AA6063-200°C with soaked time 2hours	259
Table A.7	X-RD experimental data for AA6063-350°C with soaked time 2hours	260
Table A.8	X-RD experimental data for AA6063-350°C with soaked time 4hours	260

List of Tables

Table A.9	X-RD experimental data for AA6063-350C with soaked time 6hours	260
Table A.10	X-RD experimental data for AA6063-350 with soaked time 8hours	261
Table A.11	X-RD experimental data for AA6063/SiCp MMC with 2% V_f reinforcement particle	261
Table A.12	X-RD experimental data for AA6063/SiCp MMC with 8% V_f reinforcement particle	262