

## LIST OF FIGURES

<b>Figure 1.1:</b> 2015 World electricity generation by different types of fuels.....	1
<b>Figure 1.2:</b> Possible sources of mechanical energy harvesting (left) and possible applications in sensing and actuation (right) for piezoelectric devices.....	5
<b>Figure 1.3:</b> The relation between electric charge and elastic phenomena.....	8
<b>Figure 1.4:</b> A molecular model to explain the piezoelectric effect (a) An undisturbed molecule with no dipoles or polarization (b) on the application of an external force (F) it induces polarization (P) (c) the overall effect of polarization on the surface after application of external force.....	9
<b>Figure 1.5:</b> Axis nomenclature.....	10
<b>Figure 1.6:</b> Polymerization of vinylidene fluoride to form PVDF.....	15
<b>Figure 1.7:</b> Chemical structures of copolymers of PVDF.....	16
<b>Figure 1.8:</b> $\alpha$ , $\beta$ and $\gamma$ -conformations of PVDF.....	18
<b>Figure 1.9:</b> (a) XRD pattern of (i) Pure PVDF, nanocomposite with (ii) 0.1 wt%, (iii) 0.5 wt% and (iv) 1.0 wt% AlO-rGO content (b) FTIR spectra of neat P(VDF-HFP) film and ZnO nanoparticle etched porous film.....	23
<b>Figure 1.10:</b> SEM images of pure PVDF showing spherulites and its hybrid with nanoclay showing needle like morphology.....	24
<b>Figure 1.11:</b> (a) output voltage and power density with respect to load resistance of PVDF-activated carbon composite (b) Power density as function of load resistance for PVDF-natural sugar nanofibers, inset shows the glowing LED using the device (c) output voltage and power density with load resistance for ytterbium-PVDF composite, inset shows the glowing LED's by device.....	25
<b>Figure 2.1:</b> Organic modifier used for modification of nanoclay.....	31
<b>Figure 2.2:</b> Hybrid preparation through solution route.....	33

<b>Figure 3.1:</b> Structure of layered silicate.....	40
<b>Figure 3.2:</b> Structure and nanostructure a) Bright field transmission electron micrograph of HFP nanohybrid, b) nanostructure of hybrid and changes in interlayer spacing of clay after polymer insertion c) UV-vis absorption spectra of HFP and nanohybrid. Inset figure shows the absorption spectra of pristine organically modified nanoclay, d) XRD deconvoluted diffractograms of HFP and nanohybrid, showing different phases, and, e) FTIR spectra of pure HFP and nanohybrid indicating different peaks positions for $\alpha$ -, $\beta$ - and $\gamma$ -phases.....	42
<b>Figure 3.3:</b> Effect of stretching a) Stress-Strain curve for Pure HFP and nanohybrid samples stretched at different temperature, corresponding (b) toughness and (c) modulus d) FTIR spectra of pure HFP and nanohybrid stretched samples, e) wide angle X-ray diffraction pattern of pure HFP and nanohybrid stretched samples at 90°C. Inset figures show the deconvoluted diffractograms of stretched specimen, and, f) Phase fraction of unstretched and stretched samples showing percentage of $\alpha$ -, $\beta$ - and $\gamma$ -phases.....	44
<b>Figure 3.4:</b> a) DSC thermograms of pure HFP and nanohybrid unstretched and stretched samples; HFP-S and NH-S represent specimens after stretching of respective sample, b) Polarizing optical microscope images of pure HFP and nanohybrid. No birefringence is observed in nanohybrid whereas spherulites were present in pure HFP, and, c) Scanning electron microscope image of pure HFP and nanohybrid. Inset figures show corresponding stretched sample images.....	47
<b>Figure 3.5:</b> a) Bar diagram showing piezoelectric coefficient for pure HFP and nanohybrid before and after stretching at different temperatures b) Image of a fabricated unimorph, inset figure shows representation of assembly of device and, c) Output voltage response as a function of time.....	49

**Figure 4.1:** (a) Stress-strain curve of PVDF at elevated temperature (90 °C), polarized optical (lower images), and scanning electron microscopy images (top images) for corresponding marked (\*) positions (initial and final); (b) XRD patterns before stretching (P) and after stretching (P-S) showing intermediate pattern of taking sample (P-S') at middle asterisk marked position in stress-strain curve (inset diagram, phase fractions of different crystalline forms); and (c) FTIR patterns before and after stretching of the sample indicating absorption bands of various crystalline forms.....54

**Figure 4.2:** (a) X-ray diffraction pattern for unpoled and poled samples (b) Piezoelectric coefficient and (c) unimorph responses of stretched and poled samples.....56

**Figure 4.3:** (a) open circuit voltage on finger pressing; (b) corresponding power of indicated unstretched, stretched, and poled samples.....58

**Figure 4.4:** (a) open circuit voltage and (b) power density at different modes of application of stress like bending, twisting, foot tapping and walking.....59

**Figure 4.5:** Schematic representation showing induction and orientation of piezoelectric phase in PVDF (red,  $\alpha$ -phase; blue,  $\beta$ -phase; green, amorphous phase).....60

**Figure 4.6:** Working Principle of charge generation in device.....61

**Figure 5.1:** (a) Stress-strain curves and toughness for pure PVDF and nanohybrid at 90°C showing high elongation at break; (b) TEM images of nanohybrid before and after stretching (arrow indicates the stretching direction); (c) XRD patterns for pure PVDF and nanohybrid before and after stretching (inset shows deconvoluted diffractograms for stretched samples) and other deconvolution patterns have been shown in supporting information; (d) phase fraction from the deconvoluted patterns; a,  $\alpha$  and  $\beta$  represent the content of amorphous,  $\alpha$ - and  $\beta$ -phase, respectively; (e) XRD of PVDF and nanohybrid at lower angle, schematic shows the origin of diffraction peak (f) UV-visible spectra for

pure PVDF and nanohybrid samples. Inset shows the UV-vis spectra for nanoclay (g) FTIR patterns of PVDF and nanohybrid before and after stretching indicating the presence of different phases; and (h) DSC thermograms of PVDF and nanohybrid before and after stretching showing the change in melting temperature due to phase change.....66

**Figure 5.2:** Schematic representation of phase transformation in nanohybrid and change in structure of single island or domain.....69

**Figure 5.3:** (a) Polarized optical microscope images of pure PVDF and its nanohybrid showing spherulite in pure PVDF and no birefringence in nanohybrid; (b) SEM images of pure PVDF and nanohybrid before and after stretching indicating the direction of stretching; (c) Piezo force microscopy images of nanohybrid samples before and after stretching; (d) Piezo force microscopy of P, PC, P-S and PC-S samples showing average profiles of magnitude; and (e) phase angle of the indicated samples. Inset figure suggests the magnified view of the respective profiles.....70

**Figure 5.4:** Average profiles for (a) magnitude and (b) phase of P, PC, P-S and PC-S.....73

**Figure 5.5:** (a) enhancement in piezoelectric coefficient of samples after stretching; (b) schematic of unimorph made by stretched and poled film samples; and (c) comparison of output voltage measured by impact load.....74

**Figure 5.6:** (a) open circuit voltage for unstretched, stretched and poled samples of pure PVDF and nanohybrid and (b) corresponding power density of the samples.....76

**Figure 6.1:** (a) Schematic of egg layers, (b) XRD and (c) SEM of eggshell membrane.....81

**Figure 6.2:** XRD pattern of (a) P-ESM hybrids, (b) PC-ESM hybrids with different ESM content, showing structural changes; (c) deconvolution of XRD pattern of PC-

ESM40 for the calculation of phase fraction; (d) Plot of  $\beta$ -phase fraction with ESM content showing higher  $\beta$ -phase in PC-ESM. Dashed line indicate  $\beta$ -phase for PC and vertical arrow shows the jump in piezo-phase content; (e) FTIR spectra of Pure PVDF, P-ESM40 and PC-ESM40 hybrids indicating peak position of different phases and (f) FTIR spectra of eggshell membrane.....83

**Figure 6.3:** (a) Polarized optical images of indicated specimens showing spherulite in P and P-ESM and absence of spherulite in PC-ESM; (b) Scanning electron microscope images for pure PVDF, P-ESM and PC-ESM nanohybrids; (c) Piezo force microscopic images for pure PVDF, P-ESM40 and PC-ESM40 nanohybrids, inset shows the Phase profile of the specimens obtained from PFM images.....85

**Figure 6.4:** (a) Open circuit voltage from the devices using pure PVDF, P-ESM and PC-ESM nanohybrids with 40 wt.% ESM; Output OCVs from the devices fabricated using indicated ESM content in (b) P-ESM, (c) PC-ESM; (d) variation in power density with resistance in devices made from pure PVDF, P-ESM and PC-ESM nanohybrids with 40 wt.% ESM content; (e) Power density variation with ESM content from the devices made of P-ESM and PC-ESM nanohybrids. The dashed line indicate the power output value using device made of PC (PVDF and nanoclay); (f) Open circuit voltage from device fabricated with PC-ESM (40 wt.% ESM content) nanogenerator with increasing number of stacks as indicated; (g) Schematics showing local ordering in different nanohybrids demonstrating induced structure in presence of only ESM and combined effect of ESM and nanoclay; and (h) Power output from the device as a function of ESM content in PC-ESM nanohybrid demonstrating synergism of nanoclay and ESM which exhibit significantly high output.....88

**Figure 6.5:** Demonstration of practical applications of the nanogenerator to harvest energy by applying normal human movements *e.g.*(a) Twisting; (b) Bending; (c) coin

dropping; (d) Walking; (e) Foot tapping; and (f) Hand slapping; (g) Mechanical and durability test of the device after obtaining the device performance for sufficiently long time showing almost similar output voltage; and (h) The ability of output power from the device to charge a capacitor followed by discharging kinetics using the device made of PC-ESM40 (i) the LEDs glowing on the finger tapping.....92

**Figure 6.6:** Photographic images of orange peel and synthesized hybrid showing its high flexibility and mechanical stability.....95

**Figure 6.7:** (a) XRD patterns of PVDF and hybrid showing different crystalline planes, inset shows the XRD plot of pure orange peel; (b) deconvolution of XRD plot (c) percentage of different phases present in PVDF and hybrid P-OR40 (d) FTIR spectra of orange peel (e) FTIR spectra of PVDF and hybrid indicating peaks corresponding to different phases; (f) melting thermograms of PVDF and hybrid. Dashed lines indicate the deconvoluted patterns of  $\beta$ - and  $\gamma$ -phase of hybrid; (g) Schematic for crystallization of PVDF at the interface of orange peel and (h) thermal stability of PVDF, peel and hybrid as measured through thermogravimetric studies.....97

**Figure 6.8:** (a) Polarized optical microscopic images of as cast PVDF and hybrid thin films indicating various phase of crystallites; (b) Surface morphology of PVDF, hybrid and orange peel showing different crystallites and fiber as observed through SEM; and (c) schematic of PVDF crystallization at the edge of peel fibers demonstrating the appearance of electroactive induced phases in polymer matrix.....99

**Figure 6.9:** Polarized optical Microscopy images of a) PVDF and b) hybrid with changing temperature.....100

**Figure 6.10:** (a) Open circuit voltage obtained from devices made of indicated hybrids or pure PVDF (inset shows the schematic of prepared device). The numbers after P-OR represent the amount of orange peel (w/w); (b) output power from the devices under

varying applied resistance; Voltage generation from the device under different body movements (c) bending, (d) twisting and (e) walking on the device. Inset figures show the type of loading on the device; (f) charging and discharging nature of a capacitor from the energy produced by the device under finger tapping; (g) lightening of LEDs from energy produced by the device from household door sliding.....102

**Figure 6.11:** (a) Photographic image of Pomegranate, peel and its hybrid with PVDF (b) X-ray diffraction pattern of pure PVDF and hybrid, inset shows the XRD of pomegranate peel (c) FTIR of pomegranate peel (d) FTIR of pure PVDF and hybrid (e) DSC of PVDF and hybrid, (f) Thermogravimetric analysis of for pure PVD, hybrid and pomegranate peel powder. (Here hybrid with 40% filler taken for comparison).....107

**Figure 6.12:** (a) POM images of pure PVDF and hybrid (b) SEM images of pomegranate peel and (c) peel powder and (d) PVDF and hybrid (e) AFM images of pure PVDF and hybrid and (f) corresponding height profiles.....109

**Figure 6.13:** (a) Open circuit voltage and (b) corresponding power density of pure PVDF and hybrids with different filler contents. Open circuit voltage on (c) bending, (d) twisting and (e) walking (f) capacitor charging on finger tapping and (g) LED lightening and corresponding circuit.....111

