

# List of Figures

<b>Figure</b>	<b>Caption</b>	<b>Page no.</b>
1.1	Schematic diagram of a generic multiple-DER microgrid	7
3.1	Frame transformation	24
3.2	AC Microgrid Architecture	26
3.3	Block diagram of Autonomous AC Microgrid	29
3.4	Local to global reference frame transformation	31
3.5	Block diagram of PLL	31
3.6	Block diagram of Power Controller.	32
3.7	Block diagram of Voltage Controller	33
3.8	Block diagram of current controller	34
3.9	Grid-tied Microgrid Architecture	40
3.10	Schematic of the grid-tied microgrid system	42
3.11	Reference frame transformations	43
3.12	Block diagram of PLL	43
3.13	Diagram of Power Computation block	44
3.14	Block diagram of Power Controller	45
3.15	Block diagram of Current controller	46
3.16	Block diagram of PV-fuel cell based DC microgrid system	50
3.17	PV and fuel cell with DC/DC boost converter	51
3.18	Circuit diagram of DC microgrid interconnections	54
3.19	Droop control mechanism	56
3.20	Measured frequency by PLL	62
3.21	Autonomous Microgrid System Profile	63
3.22	Grid-tied Microgrid System Profile	66
4.1	Flowchart of PSO	73
4.2	Flowchart of the ABC algorithm	76
4.3	Mixed norm based objective function formulation	84
4.4	Flow of process for reduced order modelling of DC microgrid	85
4.5	Time scales in different dynamics	86
4.6	Principle of time-scale separation used for DC microgrid system	86

4.7	Objective function formulation for fast subsystem of DC microgrid	87
4.8	Time responses of full order and reduced order autonomous microgrid system	92
4.9	Model order reduction of the perturbed and unperturbed transfer function $\frac{i_{oQ1}(s)}{v_{bD1}(s)}$ for AC microgrid in autonomous mode	92
4.10	Bodeplot of full order and reduced order transfer functions of autonomous microgrid	95
4.11	HSV plot showing the energies of various states	97
4.12	Original and reduced order transfer functions of grid-tied microgrid	101
4.13	Bode plot for full and reduced order transfer function of grid-tied microgrid	102
4.14	Convergence curve for PSO and ABC optimizations with parametric variations	105
4.15	Hankel singular values of 27 state fast subsystem	107
4.16	Fast subsystem time response in DC microgrid	109
4.17	Case 1: Load voltage variations on original, approximate and reduced order model	112
4.18	Case 2: Effect of variation of anode and cathode delay time of fuel cell	113
4.19	Typhoon HIL 402 interfaced with console PC through USB cable	113
4.20	Schematic of the grid-tied microgrid system in Typhoon HIL software	117
4.21	Output responses of the original and reduced order system on Typhoon HIL platform	117
5.1	Bar graph representation of participation factors in AC microgrid in autonomous mode	125-126
5.2	Eigenvalue Plot of AC microgrid in grid-tied mode	129
5.3	Bar graph representation of participation factors in AC microgrid in grid-tied mode	131
5.4	Eigenvalue plot of original and reduced order DC microgrid system	133
5.5	Participation factor of the dominant mode in fast subsystem	133
6.1	Block diagram of Hybrid Microgrid	142
6.2	Basic feedback configuration	143
6.3	Circuit diagram of Interlinking Converter	146
6.4	Block diagram of the closed-loop system with PID/FOPID controller	149

6.5	H-infinity loop shaping controller design formulation	151
6.6	H-infinity loop shaping controller configuration for IC	154
6.7	Singular value plots for sensitivity and complementary sensitivity functions along with corresponding weights and loop shaping control	160
6.8	Closed loop system with full order and reduced order H-infinity controller	160
6.9	Singular values of full order and reduced order $H_{\infty}$ controller and their sensitivity functions for the system under consideration	162
6.10	Inductor current(d axis) with step changes in switching	162
6.11	Inductor current (dq) with a change in plant parameter	162
6.12	Inductor current (dq) with a change in the controller parameter	163
6.13	Inductor current (dq) with a change in plant operating point	163
6.14	Bode-plot for PID, FOPID and loop shaping controller based closed-loop transfer functions for inductor currents	167