

LIST OF FIGURES

Figure No	Title	Page No.
2.1	Working principal of MMA welding	7
2.2	Schematic of GMAW process	8
2.3	The essential element of a basic GMAW process	9
2.4	Block diagram of GMAW set up	9
2.5	Effect of welding current on weld bead geometry	11
2.6	Effect of arc voltage on weld bead shape and its size	11
2.7	Effect of welding speeds on weld bead width and its profile	13
2.8	Welding current Vs wire feed speed for various diameters of carbon steel	14
2.9	Shows the microstructure of weldment at different heat input	16
2.10	Shows the micrograph of weldment at different heat input	17
2.11	Optical micrograph showing the microstructure of (a) weld metal, (b) fusion boundary, and HAZ at low, medium and high heat input	17
2.12	Effect of different shielding gases on weld bead profile and penetration	18
2.13	a-d. Microstructure of (a) base plate (b)weldment sample S1,(c) sample S4 (d) sample F1	19
2.14	Optical microstructures of the samples welded under the shielding of 1.5% H ₂ -Ar with different welding current: weld metal structure welded with (a) 140A, (b) 180A, (c) 240A and (d) transition zone structure welded with 140A	21
2.15	Metallographic micrograph of ST 37-2 (82% Ar + 18% CO ₂) weld pool etched in 2% Nital, AF: acicular ferrite, WF: Widmanstatten ferrite, PF: polygonal ferrite	22
2.16	Schematic of metal transfer process in GMAW	23
2.17	Effect of electrode size on an amount of re-austenitised and tempered weld metal in multi-run welding, cross sections as a function of weld diameter, white areas represent re-austenitised and tempered weld metal. The electrode diameters are mention in the bottom right- hand corner of each figure	24
2.18	Plot of Heat-Transfer Efficiency to Base Metal V _s Electrode-Speed	25
2.19	Schematic diagram showing the interaction between the heat source and the base metal in different zones	28
2.20	Schäffler - De Long diagram	28
2.21	Types of grain morphologies that can form in a fusion zone (weld zone)	30
2.22	Sketch showing the three regions of a weldment (BM=base metal, HAZ=heat affected zone and FZ=fusion zone)	31
2.23	Schematic of CGHAZ formations	32
2.24	Schematic diagram of the different zone in a heat affected zone of a low carbon steel weldment	33

2.25	Iron-carbon phase diagram, showing the different equilibrium phases of carbon and iron with respect to varying the carbon concentration and temperature	36
2.26	Schematic diagram showing different constituents of the primary microstructure in the columnar austenite grains of a steel weld	38
2.27	Schematic diagram of grain boundary allotriomorphic ferrite, and intragranular idiomorphic ferrite	39
2.28	Mixture of allotriomorphic ferrite, widmanstatten ferrite, and pearlite for low carbon Steel	41
2.29	Shows the primary and secondary phases of widmanstatten ferrite	42
2.30	Shows the ferrite (White) and Pearlite (Black) in the low carbon steel weldment	43
2.31	Morphological classification systems for bainite according to Bramfitt and Speer	45
2.32	Schematic representation of the transition path of upper and lower bainite	46
2.33	Shows the structure of martensite, cementite, and ferrite in a microstructure	47
2.34	The Bain model for martensite formation in steels	47
2.35	Shows the formation of martensite, bainite etc	48
2.36	Classifications of Steels	53
2.37	Effect of temperature gradient G and growth rate R on the morphology and size of solidification microstructure	55
2.38	Schematic illustrations of competitive grain growth in welds. (a) Early growth of grains near the fusion line. (b) Continued growth of favorably orientated grains at a later time	56
2.39	Proposed mechanisms for the formation of different ferrite morphologies in weld metals solidified in FA mode	57
2.40	Schematic diagram of continuous cooling transformation depict the development of weldment microstructure in low-alloy steel	58
3.1	Schematic of experimental approach of the present study	62
3.2	AISI 304 plates after welding in Fixture	67
3.3	AISI 304 plates during welding	67
3.4	AISI 304 plates after weld	68
3.5	IS 2062 welded plate after cutting	68
3.6	Detail of tensile test specimen as per ASTM	68
3.7	Dimensions of V-groove and tensile test samples in mm	69
3.8	Actual photograph for the tensile test of IS 2062 steel	70
3.9	Actual photograph for a tensile test of AISI 304	70
3.10	Dimensions (mm) of “sub size” Charpy V-notch test samples	71
3.11	Actual photograph for Charpy test samples	71
3.12	Charpy test samples after fracture	72
3.13	Samples for microstructure & Vickers hardness test	73
4.1	Effect of wire feed speed on the yield strength of IS 2062 steel at 25V with	

	different Shielding gas flow rate at 3.22 kJ/mm heat input	77
4.2	Effect of wire feed speed on the yield strength of IS 2062 steel at 26V with different Shielding gas flow rate at 3.58 kJ/mm heat input	77
4.3	Effect of wire feed speed on the yield strength of IS 2062 steel at 27V with different Shielding gas flow rate at 3.88 kJ/mm heat input	78
4.4	Effect of wire feed speed on the yield strength of IS 2062 steel at 28V with different Shielding gas flow rate at 4.47 kJ/mm heat input	78
4.5	Effect of wire feed speed on the Ultimate tensile strength of IS 2062 steel at 25V with different shielding gas flow rate at 3.22 kJ/mm heat input	79
4.6	Effect of wire feed speed on the Ultimate tensile strength of IS 2062 steel at 26V with different shielding gas flow rate at 3.58 kJ/mm heat input	80
4.7	Effect of wire feed speed on the Ultimate tensile strength of IS 2062 steel at 27V with different shielding gas flow rate at 3.88 kJ/mm heat input	80
4.8	Effect of wire feed speed on the Ultimate tensile strength of IS 2062 steel at 28V with different shielding gas flow rate at 4.47 kJ/mm heat input	81
4.9	Effect of wire feed speed on Toughness of IS 2062 steel at 25V with different shielding gas flow rate at 3.22 kJ/mm heat input	82
4.10	Effect of wire feed speed on toughness of IS 2062 steel at 26V with different shielding gas flow rate at 3.58 kJ/mm heat input	83
4.11	Effect of wire feed speed on toughness of IS 2062 steel at 27V with different shielding gas flow rate at 3.88 kJ/mm heat input	83
4.12	Effect of wire feed speed on toughness of IS 2062 steel at 28V with different shielding gas flow rate at 4.47 kJ/mm heat input	84
4.13	Effect of wire feed speed on microhardness (VHN) of IS 2062 steel at 25V with different shielding gas flow rate at 3.22 kJ/mm heat input	85
4.14	Effect of wire feed speed on microhardness (VHN) of IS 2062 steel at 26V with different shielding gas flow rate at 3.58 kJ/mm heat input	86
4.15	Effect of wire feed speed on microhardness (VHN) of IS 2062 steel at 27V with different shielding gas flow rate at 3.88 kJ/mm heat input	86
4.16	Effect of wire feed speed on microhardness (VHN) of IS 2062 steel at 28V with different shielding gas flow rate at 4.47 kJ/mm heat input	87
4.17	Effect of wire feed speed on % age elongation of IS 2062 steel at 25V with different shielding gas flow rate at 3.22 kJ/mm heat input	88
4.18	Effect of wire feed speed on % age elongation of IS 2062 steel at 26V with different shielding gas flow rate at 3.58 kJ/mm heat input	89
4.19	Effect of wire feed speed on % age elongation of IS 2062 steel at 27V with different shielding gas flow rate at 3.88 kJ/mm heat input	89
4.20	Effect of wire feed speed on % age elongation of IS 2062 steel at 28V with different shielding gas flow rate at 4.47 kJ/mm heat input	90
4.21	Optical micrograph as –received IS 2062 steel.	91
4.22	Optical micrograph as –received AISI 304 steel	91

4.23	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 7.62m/min produced at 3.22kJ/mm heat input	92
4.24	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 8.89 m/min produced at 3.22 kJ/mm heat input	94
4.25	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 10.16m/min produced at 3.22kJ/mm heat input	96
4.26	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 11.43 m/min produced at 3.22 kJ /mm heat input	98
4.27	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 7.62m/min produced at 3.58 kJ /mm heat input	100
4.28	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 8.89 m/min produced at 3.58 kJ/mm heat input	102
4.29	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 10.16 m/min produced at 3.58 kJ/mm heat input	104
4.30	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 11.43 m/min produced at 3.58 kJ/mm heat input	106
4.31	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 7.62 m/min produced at 3.88 kJ/mm heat input	108
4.32	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 8.89m/min produced at 3.88 kJ/mm heat input	110
4.33	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 10.16 m/min produced at 3.88 kJ/mm heat input	112
4.34	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 11.43 m/min produced at 3.88 kJ/mm heat input	114
4.35	microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 7.62m/min produced at 4.47 kJ/mm heat input	116
4.36	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 8.89m/min produced at 4.47 kJ/mm heat input	118

4.37	(a-d) microstructure photograph of heat affected zone (HAZ) of IS 2062 steel weldment at 10-25 l/m shielding gas flow rate, at 10.16 m/min produced at 4.47 kJ/mm heat input	120
4.38	Effect of wire feed speed on the Yield strength of AISI 304 steel at 20V at a different shielding gas flow rate at 1.89 kJ/mm heat input	121
4.39	Effect of wire feed speed on the Yield strength of AISI 304 steel at 21V at a different shielding gas flow rate at 2.17 kJ/mm heat input	121
4.40	Effect of wire feed speed on the Yield strength of AISI 304 steel at 22V at a different shielding gas flow rate at 2.78 kJ/mm heat input	122
4.41	Effect of wire feed speed on the Yield strength of AISI 304 steel at 23V at a different shielding gas flow rate at 3.01 kJ/mm heat input	122
4.42	Effect of wire feed speed on the Ultimate tensile strength of AISI 304 steel at 20V at a different shielding gas flow rate at 1.89 kJ/mm heat input	123
4.43	Effect of wire feed speed on the Ultimate tensile strength of AISI 304 steel at 21V at a different shielding gas flow rate at 2.17 kJ/mm heat input	124
4.44	Effect of wire feed speed on the Ultimate tensile strength of AISI 304 steel at 22V at a different shielding gas flow rate at 2.78 kJ/mm heat input	124
4.45	Effect of wire feed speed on the Ultimate tensile strength of AISI 304 steel at 23V at a different shielding gas flow rate at 3.01 kJ/mm heat input	125
4.46	Effect of wire feed speed on Toughness of AISI 304 steel at 20V at a different shielding gas flow rate at 1.89 kJ/mm heat input	126
4.47	Effect of wire feed speed on Toughness of AISI 304 steel at 21V at a different shielding gas flow rate at 2.17 kJ/mm heat input	127
4.48	Effect of wire feed speed on Toughness of AISI 304 steel at 22V at a different shielding gas flow rate at 2.78 kJ/mm heat input	127
4.49	Effect of wire feed speed on Toughness of AISI 304 steel at 23V at a different shielding gas flow rate at 3.01 kJ/mm heat input	128
4.50	Effect of wire feed speed on microhardness (VHN) of AISI 304 steel at 20V at a different shielding gas flow rate at 1.89 kJ/mm heat input	129
4.51	Effect of wire feed speed on microhardness (VHN) of AISI 304 steel at 21V at a different shielding gas flow rate at 2.17 kJ/mm heat input	129
4.52	Effect of wire feed speed on microhardness (VHN) of AISI 304 steel at 22V at a different shielding gas flow rate at 2.78 kJ/mm heat input	130

4.53	Effect of wire feed speed on microhardness (VHN) of AISI 304 steel at 23V at a different shielding gas flow rate at 3.01 kJ/mm heat input	130
4.54	Effect of wire feed speed on the %age elongation of AISI 304 steel at 20V at a different shielding gas flow rate at 1.89 kJ/mm heat input	132
4.55	Effect of wire feed speed on the %age elongation of AISI 304 steel at 21V at a different shielding gas flow rate at 2.17 kJ/mm heat input	132
4.56	Effect of wire feed speed on the %age elongation of AISI 304 steel at 22V at a different shielding gas flow rate at 2.78 kJ/mm heat input	133
4.57	Effect of wire feed speed on the %age elongation of AISI 304 steel at 23V at a different shielding gas flow rate at 3.01 kJ/mm heat input	133
4.58	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 6.35m/min produced at 1.89 kJ/mm heat input	136
4.59	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 7.62m/min produced at 1.89 kJ/mm heat input	138
4.60	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 8.89m/min produced at 1.89 kJ/mm heat input	140
4.61	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 10.16m/min produced at 1.89 kJ/mm heat input	142
4.62	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 6.35m/min produced at 2.17 kJ/mm heat input	144
4.63	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 7.62m/min produced at 2.17 kJ/mm heat input	146
4.64	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 8.89m/min produced at 2.17 kJ/mm heat input	148
4.65	microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, at 10.16m/min produced at 2.17 kJ/mm heat input	150
4.66	(a-d) microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 10-25 l/m shielding gas flow rate, and at 2.78 kJ/mm heat input	152
4.67	microstructure photograph of heat affected zone (HAZ) of AISI 304 steel weldment at 3.01 kJ/mm heat input	153
4.68	SEM image (Fracture morphology) of tensile specimen of IS 2062 steel weldment fractured at room temperature	154
4.69	Typical EDAX spectrums: the distribution of alloying elements	155
4.70	Fracture morphology (SEM image) of Charpy test specimen fractured at room temperature	156
4.71	SEM images of the fracture surface of samples under low, medium and high heat input	157
4.72	(a), (b) & (c).Fractography of AISI 304 welded joint after the tensile test at room temperature	157

4.73	Energy-dispersive spectroscopy (EDS) analysis results of inclusions	158
4.74	Impact test samples after fracture	159
4.75	Macro images and SEM images of Impact fracture samples for Morphology	159