

- Figure 4.8** AFM images of BHFC ceramic at compositions $x = 0.1$ **(a)** two dimensional image for grain boundary **(b)** three dimensional for surface roughness **(c)** depth histogram graph and **(d)** bar diagram for particle size distribution 111
- Figure 4.9** The polarization versus Electric field (P–E) hysteresis loop of BHFC ceramic at room temperature for compositions $x = 0.0, 0.05$ and 0.1 . 112
- Figure 4.10** The variation of **(a)** Dielectric constant (ϵ') and **(b)** dielectric loss ($\tan \delta$) with temperatures at few selected frequencies for BHFC ceramic sintered at $1150\text{ }^\circ\text{C}$ for 12 h. 114
- Figure 4.11** Frequency dependent **(a)** dielectric constant (ϵ') and **(b)** dielectric loss ($\tan \delta$) at few selected temperatures of BHFC ceramic 115
- Figure 4.12** Frequency dependence of AC conductivity for BHFC ceramic for few selected concentrations and at 303 K temperature. 117
- Figure 4.13** plots of AC conductivity with inverse of temperature Frequency for few selected concentrations and at 100 Hz frequency. 118
- Figure 4.14** **(a and b)** show CV and EIS plots of BHFC ceramic sintered at $1150\text{ }^\circ\text{C}$ for 12 h. 120
- Figure 4.15** M-H hysteresis plots of BHFC ceramic with compositions $x = 0.0, 0.05$ and 0.1 sintered at $1150\text{ }^\circ\text{C}$ for 12 h. 122
- Figure 5.1** Shows XRD diffraction patterns of $\text{BaFe}_{12-x}\text{Ni}_x\text{O}_{19}$ ($x = 0.0, 0.05, 0.1, \text{ and } 0.2$) ceramic a sintered at $1200\text{ }^\circ\text{C}$ for 6 h. 127
- Figure 5.2** Le-Bail full pattern matching analysis of XRD patterns for $\text{BaFe}_{12-x}\text{Ni}_x\text{O}_{19}$ (BHFC) ceramic with compositions $x = 0.0, 0.05, 0.1, \text{ and } 0.2$ sintered at $1200\text{ }^\circ\text{C}$ for 6 h. 128

- Figure 5.3** FTIR spectra of $\text{BaFe}_{12-x}\text{Ni}_x\text{O}_{19}$ (BHFC) ceramic with compositions $x = 0.0, 0.05, 0.1,$ and 0.2 ceramic sintered at $1200\text{ }^\circ\text{C}$ for 6 h. 130
- Figure 5.4** (a, a', a'', a''') Bright field TEM image (b, b', b'', b''') selected area diffraction (SAED) pattern (c, c', c'', c''') High-resolution TEM image of BHNF ceramic sintered $1200\text{ }^\circ\text{C}$ for 6 h. 131
- Figure 5.5** (a-d) indicate SEM image of BHNF ceramic with compositions $x = 0.0, 0.05, 0.1,$ and 0.2 sintered at $1200\text{ }^\circ\text{C}$ for 6 h. 132
- Figure 5.6** (a) EDX spectra corresponding to the composition $x = 0.2$ (b) EDX mapping of BHNF ceramic sintered at sintered $1200\text{ }^\circ\text{C}$ for 6 h. 133
- Figure 5.7** AFM images of BHFC ceramic at compositions $x = 0.2$ (a) two dimensional image for grain boundary (b) three dimensional for surface roughness (c) depth histogram graph and (d) bar diagram for particle size distribution. 134
- Figure 5.8** indicates P-E hysteresis loop for the compositions ($x = 0.0, 0.05, 0.1$ and 0.2) for BHNF ceramic. 135
- Figure 5.9** the variation of magnetization with magnetic field at 100 K temperature and different compositions of BHNF ceramic sintered at $1200\text{ }^\circ\text{C}$ for 6 h. 137
- Figure 5.10** the dielectric constant and dielectric loss of BHNF ceramic with the composition $x = 0.0, 0.05, 0.1$ and 0.2 as a function of temperature at 10 kHz . 139
- Figure 5.11** the variation of dielectric constant and dielectric loss with frequency and various compositions and at 343 K temperature of BHNF ceramic. 140
- Figure 5.12** plots of AC conductivity versus frequency at few selected compositions at 303 K temperature. 142
- Figure 5.13** plots of $\ln \sigma$ vs. $10^3/T$ of BHNF ceramic with the composition $x = 0.0, 0.05, 0.1$ and $0.2,$ at 100 Hz and certain concentrations. 143

- Figure 5.14** Impedance plane plots of Z' vs Z'' of $\text{BaFe}_{12-x}\text{Ni}_x\text{O}_{19}$ with the compositions $x = 0.0, 0.05, 0.1,$ and 0.2 (a) grain boundaries at low frequency (b) grain at low frequency. 145
- Figure 6.1** Plots of bulk densities with sintering temperature of BHF-BCT nanocomposite. 152
- Figure 6.2** X-ray diffraction pattern of BHF-BCT nanocomposite (a) calcined at 1073 K and (b) sintered at 1173 K for 8 h, respectively. 154
- Figure 6.3** Le-bail analysis of XRD patterns for BHF-BCT nanocomposite sintered at 1173 K for 8 h. The black line demonstrates experimental, red line represents calculated, Blue line indicates the difference between experimental and calculated diffraction patterns and vertical tick marks in the second and third rows represent peak positions. 155
- Figure 6.4** FTIR spectrum of BHF-BCT nanocomposite synthesized at 1173 K for 8 h. 156
- Figure 6.5**(a and b)show bright field TEM images (c) High-resolution TEM image corresponding to their d spacing (d) selected area diffraction (SAED) pattern of BHF-BCT nanocomposite. 158
- Figure 6.6**(a) SEM image (b) Energy dispersive X-ray (EDX) spectrum for elemental composition and (c) – (h) EDX mapping of indivisible elements related with BHF-BCT nanocomposite sintered at 1173 K for 8 h. 159
- Figure 6.7**Atomic force microscopy (AFM) images (a)two dimensional for grain and grain boundaries (b)3D for roughness of particles (c) Histogram graph for particle size distribution and (d) peak distribution curve for grain roughness. 160
- Figure 6.8** P–E unsaturated hysteresis loop of BHF-BCTO nanocomposite at few selected temperatures. 161

-
- Figure 6.9**(a) Temperature-dependence of Zero cooled field (ZFC) and Field cooled (FC) at $H=100$ Oe and ± 2 T (b) M-H hysteresis curve of BHF–BCT nanocomposite at two different temperature (5 and 300 K). 163
- Figure 6.10** Temperature dependent inverse magnetic susceptibility at $H= 100$ Oe of the BHF–BCT nanocomposite. 165
- Figure 6.11** Plots of (a) real (ϵ') (b) imaginary (ϵ'') dielectric constant and (c) tangent loss ($\tan \delta$) vs temperature at few selected frequencies of BHF–BCT nanocomposite. 166
- Figure 6.12** Variation of (a) real (ϵ') (b) imaginary (ϵ'') part of dielectric constant dielectric constant and (c) dielectric loss ($\tan \delta$) vs frequency at few selected temperatures. 167
- Figure 6.13** Frequency dependence of AC conductivity at few selected temperatures for BHF–BCT nanocomposite. 168
- Figure 6.14** Variation of conductivity with inverse of temperature at few selected frequencies of BHF–BCT nanocomposite. 170
- Figure 6.15** Impedance plots (z' vs z'') of BHF–BCT nanocomposite at few selected temperature sintered at 1173 K for 8 h. 171