

---

---

## LIST OF FIGURES

---

---

<b>Figure 1.2:</b> Flow chart of the plan of the experimental work.	<b>24</b>
<b>Figure 2.1:</b> Schematic sketch of (a)Cyclic and (b)Isothermal test	<b>27</b>
<b>Figure 2.2:</b> Salt coating on 904L sample: (a)hot plate with a sample, (b)salt spray gun and (c)salt coated sample.	<b>29</b>
<b>Figure 2.3:</b> Optical micrograph showing microstructure of the SASS 904L solution treated at 1100 °C for 1h and water quenched.	<b>30</b>
<b>Figure 3.1:</b> Weight change per unit area ( $\Delta W$ ) during oxidation of the SASS 904L in air at 500, 550, 600 and 650 °C up to 100 h.	<b>36</b>
<b>Figure 3.2:</b> Variation of square of weight gain per unit area $(\Delta W)^2$ with time from oxidation of the SASS 904L in air at 500, 550, 600 and 650 °C, up to 100 h.	<b>37</b>
<b>Figure 3.3:</b> Activation energy plot (kp vs 1/T) for the 1 <sup>st</sup> stage (upto 25h) cyclic oxidation from 500-650 °C).	<b>38</b>
<b>Figure 3.4:</b> XRD patterns of the SASS 904L (a) in solution treated condition; following oxidation for 100 h at: (b)500, (c)550, (d)600 and (e)650 °C.	<b>39</b>
<b>Figure 3.5:</b> Surface morphologies of the samples oxidized for 100 h at different temperatures: (a)500, (b)550, (c)600 and (d)650 °C. Compositional analysis by EDS was carried out from the rectangular enclosed regions.	<b>40</b>
<b>Figure 3.6:</b> Cross-sectional SEM-EDS of the samples oxidized at different temperatures: (a)500, (b)550, (c) 600 and (d)650 °C for 100 h.	<b>41</b>
<b>Figure 3.7:</b> EPMA analysis of cross-sections of the samples exposed at 500 to 650 °C up to 100 h.	<b>42</b>
<b>Figure 3.8:</b> Schematic process of oxidation of the SASS 904L from 100 h of exposure at different temperatures: (a)500, (b)550, (c)600 and (d)650 °C.	<b>47</b>
<b>Figure 4.1:</b> Plots of (a) $\Delta W$ vs $t$ , (b) $\Delta W^2$ vs $t$ and (c) Raman spectra of the samples	

exposed for 25 and 100 h at 500, 550, 600 and 650 °C.	51
<b>Figure 4.2:</b> XRD spectra of the samples isothermally oxidized for 25, 50, 75 and 100 h at 500-650 °C.	52
<b>Figure 4.3:</b> SE and BSE images showing surface morphology of: (A,a)as-polished (unexposed) sample and the samples exposed isothermally for 25 and 100 h at: (B,C,b,c)500; (D,E,d,e)550; (F,G,f,g)600; and (H,I,h,i)650 °C, respectively in air atmosphere.	54
<b>Figure 4.4:</b> EDX analysis of the oxidized surface from: (a) clusters of pores and (b) clusters of oxides.	55
<b>Figure 4.5:</b> EPMA analysis of cross section of the sample exposed for 25 h at 650 °C.	56
<b>Figure 4.6:</b> EPMA analysis of cross section of the sample exposed for 50 h at 650 °C.	57
<b>Figure 4.7:</b> EPMA analysis of cross section of the sample exposed for 75 h at 650 °C.	57
<b>Figure 4.8:</b> EPMA analysis of cross section of the sample exposed for 100 h at 650 °C.	58
<b>Figure 5.1:</b> Photographs of the samples corroded at 500-650 °C for 100 h by: (a,b,c,d) SM1 and (e,f,g,h) SM2.	65
<b>Figure 5.2:</b> Weight change per unit area ( $\Delta W$ ) versus time plots of the samples exposed at 500-650 °C up to 100 h and corroded from coatings of (a)SM1(Cl:S=40:60) and (b)SM2(Cl:S=60:40).	67
<b>Figure 5.3:</b> Square of weight gain per unit area ( $\Delta W$ ) <sup>2</sup> versus time plots of the samples exposed at 500-650 °C up to 100 h and corroded from coatings (a)SM1(Cl:S=40:60) and (b)SM2(Cl:S=60:40).	67
<b>Figure 5.4:</b> Phase analysis of the corrosion products by XRD, resulting from exposure at 500-650 °C up to 100 h and corroded by: (a) SM1 and (b) SM2.	70
<b>Figure 5.5:</b> Surface morphology of the samples exposed up to 100 h at 500 °C and corroded by: (a) SM1 and (b) SM2.	73

<b>Figure 5.6:</b> Surface morphology of the samples exposed up to 100 h at 550 °C and corroded by: (a) SM1 and (b) SM2.	<b>73</b>
<b>Figure 5.7:</b> Surface morphology of the samples exposed up to 100 h at 600 °C, corroded by (a) SM1 and (b) SM2.	<b>74</b>
<b>Figure 5.8:</b> Surface morphology of the samples coated with SM1 and exposed at 650 °C up to 100 h showing: (a) spallation and (b) no spallation.	<b>75</b>
<b>Figure 5.9:</b> Surface morphology of the sample coated with SM2 and exposed at 650 °C, up to 100 h showing: (a) no spallation and (b) region below the spalled scale.	<b>76</b>
<b>Figure 5.10:</b> SEM micrographs showing cross sectional features of the samples hot corroded by SM1 up to 100 h at: (a) 500, (b) 550, (c) 600 and (d) 650 °C; up to 100 h.	<b>77</b>
<b>Figure 5.11:</b> SEM micrographs showing cross section of the samples hot corroded by SM2 up to 100 h at: (a) 500, (b) 550, (c) 600 and (d) 650 °C	<b>78</b>
<b>Figure 5.12:</b> EPMA mapping of cross section of the sample hot corroded by SM1 at 650 °C up to 100 h.	<b>80</b>
<b>Figure 5.13:</b> EPMA mapping of cross section of sample hot corroded by SM2 salt mixture and exposed at 650 °C up to 100 h.	<b>81</b>
<b>Figure 5.14:</b> EPMA line scans of cross sections of the samples showing variation in concentration of the elements Fe, Ni, Mn, Mo, Cu and O, exposed at 650 °C for 100 h in air, coated with (a) SM1 and (b) SM2.	<b>82</b>
<b>Figure 6.1:</b> Plots showing corrosion behavior of SASS 904L coated by SM1, during isothermal exposure at 500-650 °C from 25-100 h: (a)( $\Delta W$ ) vs time and (b)( $\Delta W$ ) <sup>2</sup> vs time.	<b>95</b>
<b>Figure 6.2:</b> Plots showing corrosion behavior of SASS 904L coated by SM2, during isothermal exposure at 500-650 °C from 25-100 h: (a)( $\Delta W$ ) vs time and (b)( $\Delta W$ ) <sup>2</sup> vs time.	<b>95</b>
<b>Figure 6.3:</b> Phase analysis of the SM1 coated samples, isothermally exposed at 500-650 °C for 25-100 h.	<b>96</b>
<b>Figure 6.4:</b> Phase analysis of the SM2 coated samples, isothermally exposed at 500-650 °C for 25-100 h.	<b>97</b>

<b>Figure 6.5:</b> Morphology and analysis of surface of the samples isothermally exposed at 500 °C: (a,b,c,d) coated with SM1 and (e,f,g,h) coated with SM2.	<b>101</b>
<b>Figure 6.6:</b> Morphology and analysis of surface of the samples isothermally exposed at 550 °C: (a,b,c,d) coated with SM1 and (e,f,g,h) coated with SM2.	<b>102</b>
<b>Figure 6.7:</b> Morphology and analysis of surface of the samples isothermally exposed at 600 °C: (a,b,c,d) coated with SM1 and (e,f,g,h) coated with SM2.	<b>103</b>
<b>Figure 6.8:</b> Morphology and analysis of surface of the samples isothermally exposed at 650 °C: (a,b,c,d) coated with SM1 and (e,f,g,h) coated with SM2.	<b>104</b>
<b>Figure 6.9:</b> Cross sections of the SM1 coated sample isothermally exposed at 650 °C for 25 h, showing EDS peaks of different elements and mapping of O, Fe, Cr and Ni.	<b>105</b>
<b>Figure 6.10:</b> Cross sections of the SM2 coated sample isothermally exposed at 650 °C for 25 h, showing EDS peaks of different elements and mapping of O, Fe, Cr and Ni.	<b>106</b>
<b>Figure 6.11:</b> Cross sections of the SM1 coated sample isothermally exposed at 650 °C for 100 h, showing EDS peaks of different elements and mapping of O, Fe, Cr and Ni.	<b>107</b>
<b>Figure 6.12:</b> Cross sections of the SM2 coated sample isothermally exposed at 650 °C for 100 h, showing EDS peaks of different elements and mapping of O, Fe, Cr and Ni.	<b>108</b>
<b>Figure 6.13:</b> EPMA of cross section of the SM2 coated sample isothermally exposed at 650 °C for 100 h.	<b>108</b>
<b>Figure 7.1:</b> Bar representation of the weight gain/area ( $\Delta W$ ) from exposure under cyclic and isothermal condition from 500-650 °C for 25, 50, 75 and 100 h.	<b>117</b>

**Figure 7.2:** Bar data representation of the weight gain/area ( $\Delta W$ ) for the corroded samples exposed cyclically and isothermally under SM1 salt coating at 500 to 650 °C, at 25, 50, 75 and 100 h. **119**

**Figure 7.3:** Bar data representation of the weight gain/area ( $\Delta W$ ) for the corroded samples exposed cyclically and isothermally under SM2 salt coating at 500 to 650 °C, at 25, 50, 75 and 100 h. **119**