

LIST OF TABLES

Table	Title	Page No.
2.1	Available literature in wet process of removal of SO ₂ and NO	64
3.1	Apparatus used for experimentation	74
3.2	The purities and specifications of gases and chemicals used for experimentation	82
3.3	Experimental conditions and sample description, for bubble column with NaClO	87
3.4	Experimental conditions and sample description for magnetic stirrer vessel with NaClO	93
3.5	Experimental conditions and sample description for magnetic stirrer vessel with Ca(OCl) ₂	94
3.6	Experimental conditions and sample description for magnetic stirrer vessel with NaClO/NaOH	95
3.7	Experimental conditions in continuous spray column with NaClO	99
3.8	Experimental conditions and sample description for magnetic stirrer vessel with NaClO/NH ₃	101
4.1	Comparison of maximum removal efficiency of SO ₂ and NO _x in semi-batch column	135
4.2	Equilibrium constant at different temperatures with NaClO	142
4.3	The equilibrium partial pressure under different conditions with NaClO	143
4.4	Comparison of results in continuous absorption column with some published works	154

4.5	Equilibrium constant at different temperatures with NaClO/NH ₃	159
4.6	The equilibrium partial pressure value under different conditions with NaClO/NH ₃	159
A1	Data for removal efficiency with time using NaClO in bubble column (initial SO ₂ concentration 6348 ppm, initial NO concentration 1804 ppm, initial pH 5.6, initial NaClO concentration 0.032 M, temperature 305 K)	202
A2	Data for removal efficiency with NaClO concentration in bubble column (initial SO ₂ concentration 6348 ppm, initial NO concentration 1804 ppm, temperature 305 K, initial pH 5.6)	204
A3	Data for removal efficiency with absorbent temperature using NaClO in stirred vessel (initial SO ₂ concentration 6348 ppm, initial NO concentration 1804 ppm, initial pH 5.6, initial NaClO concentration 0.032 M)	205
A4	Data for removal efficiency with time using NaClO in stirred vessel (initial SO ₂ concentration 6340 ppm, initial NO concentration 816 ppm, initial NaClO concentration 0.01 M, temperature 313 K)	206
A5	Data for removal efficiency with NaClO concentration in stirred vessel (initial SO ₂ Concentration 6340 ppm, initial NO Concentration 816 ppm, temperature 313 K)	207
A6	Data for removal efficiency with absorbent temperature using NaClO in stirred vessel (initial SO ₂ concentration 6340 ppm, initial NO concentration 816 ppm, initial NaClO concentration 0.01 M)	208
A7	Data for removal efficiency with initial SO ₂ concentration using NaClO in stirred vessel (initial NO concentration 816 ppm, initial	208

	NaClO concentration 0.01 M, temperature 313 K)	
	Data for removal efficiency with initial NO concentration using	
A8	NaClO in stirred vessel (initial SO ₂ concentration 6340 ppm, initial NaClO concentration 0.01 M, temperature 313 K)	209
	Data for removal efficiency with initial pH of NaClO in stirred vessel	
A9	(initial SO ₂ concentration 6340 ppm, initial NO concentration 816 ppm, initial NaClO concentration 0.01 M, temperature 313 K)	210
	Data for removal efficiency with Ca(OCl) ₂ concentration in stirred	
A10	vessel (initial SO ₂ concentration 6126 ppm, initial NO concentration 876 ppm, temperature 313 K)	211
	Data for removal efficiency with absorbent temperature using	
A11	Ca(OCl) ₂ in stirred vessel (initial SO ₂ concentration 6126 ppm, initial NO concentration 876 ppm, absorbent concentration 5 g/100ml)	212
	Data for removal efficiency with mole ratio of absorbent blend	
A12	NaOH/NaClO in magnetic stirred vessel (initial SO ₂ concentration 6829 ppm, initial NO concentration 850 ppm, temperature 313 K, initial pH 5.9, NaClO concentration 0.024 M)	213
	Data for removal efficiency with absorbent temperature in magnetic	
A13	stirrer vessel using NaOH/NaClO blend (initial SO ₂ concentration 6829 ppm, initial NO concentration 850 ppm, initial pH 5.9, mole ratio of NaOH/NaClO 3)	214
A14	Data for estimation of k_{SO_2g} with NaClO	214
A15	Data for estimation of reaction order for NO with NaClO	215
A16	Data for enthalpy change with temperature using NaClO	215
A17	Data for Gibbs free energy change with temperature using NaClO	216

A18	Data for removal efficiency with time using NaClO in spray column (gas flow rate 600 mL/min, liquid flow rate 1500 mL/min, initial NaClO concentration 0.024 M, distributor diameter 1 mm, temperature 313 K)	217
A19	Data for removal efficiency with absorbent (NaClO) concentration in spray column (gas flow rate 600 mL/min, liquid flow rate 1500 mL/min, temperature 313 K, distributor diameter 1 mm, time 120 min)	218
A20	Data for removal efficiency with reaction temperature using NaClO in spray column (gas flow rate 600 mL/min, liquid flow rate 1500 mL/min, initial NaClO concentration 0.024 M, distributor diameter 1 mm, time 120 min)	219
A21	Data for removal efficiency with initial SO ₂ concentration using NaClO in spray column (gas flow rate 600 mL/min, liquid flow rate 1500 mL/min, initial NaClO concentration 0.024 M, distributor diameter 1 mm, temperature 313 K, time 120 min)	220
A22	Data for removal efficiency with initial NO concentration using NaClO in spray column (gas flow rate 600 mL/min, liquid flow rate 1500 mL/min, initial NaClO concentration 0.024 M, distributor diameter 1 mm, temperature 313 K, time 120 min)	221
A23	Data for removal efficiency with initial pH of absorbent using NaClO in spray column (gas flow rate 600 mL/min, liquid flow rate 1500 mL/min, initial NaClO concentration 0.024 M, distributor diameter 1 mm, temperature 313 K, time 120 min)	212
A24	Data for removal efficiency with addition of CO ₂ to simulated gas	223

	stream using NaClO in spray column (initial NO concentration 600 ppm, initial SO ₂ concentration 2600 ppm, initial CO ₂ concentration 50000 ppm, initial NaClO concentration 0.024 M, temperature 313 K, distributor diameter 1 mm)	
A25	Data for enthalpy change with temperature using NaClO/NH ₃	224
A26	Data for Gibbs free energy change with temperature using NaClO/NH ₃	224
A27	Data for estimation of equilibrium time in semi batch stirred with NaClO/NH ₃ (initial SO ₂ concentration 1807 ppm, initial NO concentration 1020 ppm, temperature 313 K, initial pH 5.5, NaClO concentration 0.032 M, mole ratio of NH ₃ to NaClO 1)	225
A28	Data for estimation of optimal molar ratio in semi batch stirred with NaClO/NH ₃ (initial SO ₂ concentration 1807.58 ppm, initial NO concentration 1020.51 ppm, temperature 313 K, initial pH 5.5, NaClO concentration 0.032 M, time 180 min)	228
A29	Data for estimation of optimal temperature in semi batch stirred with NaClO/NH ₃ (initial SO ₂ concentration 1807.58 ppm, initial NO concentration 1020.51 ppm, initial pH 5.5, NaClO concentration 0.032 M, time 180 min, mole ratio of NH ₃ to NaClO 1)	230
A30	Data for estimation of optimal pH in semi batch stirred with NaClO/NH ₃ (initial SO ₂ concentration 1807.58 ppm, initial NO concentration 1020.51 ppm, temperature 313 K, NaClO concentration 0.032 M, time 180 min, mole ratio of NH ₃ to NaClO 1)	231
A31	Data for removal efficiency with initial SO ₂ concentration in semi	232

	batch stirred with NaClO/NH ₃ (initial NO concentration 1020.51 ppm, temperature 313 K, NaClO concentration 0.032 M, initial pH 5.5, time 180 min, mole ratio of NH ₃ to NaClO 1)	
A32	Data for removal efficiency with initial NO concentration in semi batch stirred with NaClO/NH ₃ (initial SO ₂ concentration 1807.58 ppm, temperature 313 K, NaClO concentration 0.032 M, initial pH 5.5, time 180 min, mole ratio of NH ₃ to NaClO 1)	223
A33	Data for NO removal efficiency change in both semi batch and spray column with NaClO/NH ₃	234
A34	Data for SO ₂ removal efficiency change in both semi batch and spray column with NaClO/NH ₃	235
B1	Standard Gibbs free energy, enthalpy, entropy change and specific heat capacities of the components	236