

List of Figures

Figure 1.1 A unit cell of ABO ₃ type cubic perovskite oxide structure.	35
Figure 1.2 Schematic crystal structures of n = 1, 2 and 3 members of Ruddlesden–Popper type A _{n+1} B _n O _{3n+1} [75].	46
Figure 1.3 Unit cell of A ₂ BO ₄ and arrangement of A-O ₉ and B-O ₆ arrangement.	48
Figure 1.4 (a) Relaxed configuration of the La ₂ CoO _{4+δ} model. Circled region represents an interstitial oxygen atom; and (b) migration paths in simulation. (I) indicates an interstitial migration (II) shows an interstitialcy migration mechanism [75].	56
Figure 1.5 (a) Crystal structure of Sr ₂ MnO _{3.5} with equatorial oxygen vacancies along bc plane (b) Crystal structure of Sr ₂ MnO _{3.5} with atoms displacing oxygen atoms from their apical positions thus causing the oxygen atoms to fill the equatorial vacancies, such that the fluorinated material reverts to I4/mmm symmetry (green- Sr, white-Mn, red- O, yellow- vacant site) [114].	58
Figure 1.6 (a) 3D representation of oxygen vacancy migration within the CoO ₆ octahedron (pink and red), between the equatorial and the apical (green and blue) positions in La _{0.8} Sr _{1.2} CoO _{3.9} ; (b) 3D representation of oxygen interstitial migration in La _{1.2} Sr _{0.8} CoO _{4.1} . Each oxygen involved in the migration event is represented by a different color. Spheres of the same color indicate the positions occupied by a specific atom over the simulation time [75].	60
Figure 2.1 Schematic representation of mechanical alloying method.	76
Figure 2.2 TGA-DSC facility. Figure 2.3 A typical non-isothermal TGA-DSC Curve.	78
Figure 2.4 Balance with density kit [Sartorius, BSA2245CW]	80

Figure 2.5 Visualization of Bragg's law.	80
Figure 2.6 Schematic representation of $\theta/2\theta$ diffraction in Bragg-Brentano geometry.....	81
Figure 2.7 XRD facilities, Central Instrument Facility (CIF) IIT (BHU).....	82
Figure 2.8 A typical FullProf software interface during Rietveld refinement process.	85
Figure 2.9 Experimental set-up used for Raman Measurement. (CRF IIT Kharagpur).	92
Figure 2.10 Schematic presentation of the principle of Raman Spectroscopy.	93
Figure 2.11 Principle of FT-IR spectroscopy and experimental set-up for FTIR measurement facility.	94
Figure 2.12 Interaction of electron beam with sample specimen.	96
Figure 2.13 The Schematic view of a Transmission Electron Microscope (TEM).	96
Figure 2.14 (a) TEM facility at IIT-BHU (b) TEM grid for measurement (c) HR-TEM image of sample (d) Distribution function for spherical grains.....	98
Figure 2.15 FESEM facilities, IIT (BHU).	100
Figure 2.16 (a) Mechanism of X-ray Photoelectron Spectroscopy (b) Experimental set-up for XPS measurement.....	102
Figure 2.17 Experimental Set-up for UV-Vis measurement (IIT BHU).	103
Figure 2.18 Tauc plot generated by Eq. 2.21.	104
Figure 2.19 (a) Principle of photoluminescence spectroscopy (b) Experimental set-up used in the present investigation.	105
Figure 2.20 MPMS 3 setup (IIT BHU).	107
Figure 2.21 Experimental Set-up used for Electrical Characterization of sample (IIT BHU).	108

Figure 2.22 Equivalent circuit for polycrystalline ceramic sample and their frequency response in complex Impedance plot.....	112
Figure 2.23 Equivalent circuit for polycrystalline ceramic sample and corresponding frequency response in the complex Modulus plots.....	113
Figure 2.24 Conductivity spectra of a polycrystalline material.....	116
Figure 3.1 Simultaneous TGA/DSC curve of (a) raw material SnO ₂ (b) raw material SrCO ₃ (c) mixture of raw material SrCO ₃ and SnO ₂ (d) Derivative of thermogravimetric (DTG) curve of a mixture of raw materials.....	121
Figure 3.2 Powder X-ray diffraction pattern of the prepared mixture calcined at different temperatures.....	123
Figure 3.3 Core-shell model for the phase formation of Sr ₂ SnO ₄ using raw materials SrCO ₃ and SnO ₂	124
Figure 3.4 Rietveld refined pattern of X-ray diffraction data.....	125
Figure 3.5 Room temperature Raman Spectrum of Sr ₂ SnO ₄	128
Figure 3.6 Fourier transform of Infra-red spectra of Sr ₂ SnO ₄	129
Figure 3.7 (a) SEM micrograph (b) Histogram generated for average grain.....	129
Figure 3.8 (a) Survey scan report of Sr ₂ SnO ₄ (b-d) Core-level XPS spectra of individual element Sr (3d), Sn (5d) and O (1s).....	131
Figure 3.9 UV-Visible absorption spectra and Tauc plot of Sr ₂ SnO ₄	133
Figure 3.10 Variation of (a) Dielectric constant (b) Dissipation factor with temperature at different frequencies.....	134

Figure 3.11 Variation of (a) Real part of modulus (M') (b) Imaginary part of modulus fitted with Eq. (3.9), with frequency at different temperatures. (c) KWW parameter with respect to temperature (d) Nyquist plot (e) Variation of $\log f_{max}$ with $1000/T$ (f) Scaled Modulus against scaled frequency at various temperatures.....	137
Figure 3.12 (a) Logarithmic conductivity with logarithmic frequency (fitted with power law) (b) Arrhenius plot (c) Power exponent (n) with temperature (d) logarithmic of ac conductivity with the temperature at a constant frequency (10 KHz).....	140
Figure 3.13 Scaled conductivity vs. scaled frequency spectrum at different temperatures..	141
Figure 4.1 (a) Room temperature powder X-ray diffraction pattern of prepared samples and (b) enlarge view of (116) and (123) diffraction peak (c) Room temperature XRD pattern refined using the Rietveld method.....	147
Figure 4.2 (a) Structure of prepared solid solution SSB2 (b) Variation of lattice parameter a, b, c with respect to the composition of Sr.....	151
Figure 4.3 Fourier Transform Infrared (FTIR) spectra of all samples.....	152
Figure 4.4 (a) Bright field TEM image (b) Histogram of distribution of particle size (c) (SAED) pattern and (d) High-resolution transmission electron image of the sample SSB2.	153
Figure 4.5 High-Resolution Scanning electron micrograph of freshly fractured surface of the sintered pellets (a) SSB0 (b) SSB1 (c) SSB2 (d) SSB4 (e) SSB8 (f) SSB10.....	154
Figure 4.6 Histogram fitted with Gaussian function of sample (a) SSB0 (b) SSB1 (c) SSB2 (d) SSB4 (e) SSB8 (f) SSB10.....	155
Figure 4.7 (a) X-ray photoelectron spectroscopy (XPS) survey scan report for sample SSB4, (b-e) fitted core level XPS spectrum of Ba, Sn, Sr and O elements.....	157

Figure 4.8 Variation of (a) dielectric constant (b) dissipation factor with temperature for solid solutions; Variation of (c) dielectric constant and (d) dissipation factor (D) against frequency at several temperatures (Temperature in °C). 160

Figure 4.9 (a) Real part of modulus M' with frequency for all compositions at 400°C (b) Variation of Real part of modulus M' with frequency at several temperatures (c) Variation of Imaginary part M'' with frequency at several temperatures fitted with Eq. (11) (d) Arrhenius plot for relaxation frequency (e) Variation of KWW parameter with temperature (f) Scaled modulus vs. scaled frequency at several temperatures (Temperature in °C). 161

Figure 4.10 Nyquist plot for modulus fitted with cole-cole equation at 400°C. 164

Figure 4.11 (a) Frequency-dependent conductivity spectra at different temperature fitted with Eq. (2.36) shown by solid line. (b) Variation of dc conductivity (σ_{dc}) with inverse of temperature (Inset shows the compositional dependent dc conductivity at 400°C). 166

Figure 4.12 (a) Scaled conductivity with respect to scaled frequency at different temperature for sample SSB2 (b) Scaled conductivity with respect to scaled frequency for all solid solutions at 400°C. 168

Figure 4.13 Summerfield scaling by taking as scaled frequency (a) $\sigma_{dc} * T$ (b) $\sigma_{dc}.T x$ for solid solutions. 169

Figure 5.1 Room temperature powder X-ray diffraction pattern of all samples and theoretical XRD generated from COD database of Sr_2SnO_4 174

Figure 5.2 (a) The Rietveld refinement pattern of calcined powders. Here Y_{obs} , Y_{cal} , $Y_{obs}-Y_{cal}$ and Bragg positions represent the experimental data, calculated data, the difference between both and Bragg position respectively. (b) Crystal structure of SSL4 obtained using VESTA software. 175

Figure 5.3 Variation of (a) Degree of distortion (R) and (b) lattice parameters with composition of La (x).....	177
Figure 5.4 Size-strain plots (SSP) for the determination of crystallite size and lattice strain.	178
Figure 5.5 (a) Transmission electron micrograph of a representative sample SSL4, (b) Distribution function fitted with Gaussian Function and (c) Selected Area Electron Diffraction (SAED) pattern.....	180
Figure 5.6 Room temperature Raman spectrum of the prepared samples.	182
Figure 5.7 (a) Room temperature Fourier transform infrared (FTIR) spectrum of the sample (b) Enlarge view of band corresponding to stretching mode of Sr-O and Sn-O ₆	183
Figure 5.8 Scanning electron micrograph of the fracture surface of sintered sample (a) SSL0 (b) SSL1 (c) SSL2 (d) SSL4 (e) SSL6 (f) SSL10.	184
Figure 5.9 Histogram between no. of grains and grain size (a) SSL0 (b) SSL1 (c) SSL2 (d) SSL4 (e) SSL6 (f) SSL10.	185
Figure 5.10 (a) Survey scan report of SSL4 (b-e) Core level spectra of Sr (3d), La (3d), Sn (3d) and O (1s) spectra.....	187
Figure 5.11 Room temperature UV-Visible absorption spectrum of the prepared samples.	188
Figure 5.12 Tauc plot (by putting m=1/2 for direct band gap and m=2 for indirect band gap) obtained from absorption data of the samples.	190
Figure 5.13 (a) Variation of AC conductivity with logarithmic of frequency, (b) Arrhenius plot generated for all sample using Eq. (13) (c) Arrhenius plot generated for all sample using hopping frequency (d) Variation of dc conductivity vs. hopping frequency for all sample..	194
Figure 5.14 Variation of dc conductivity with composition of La (x) at 400°C.....	195

Figure 5.15 (a) Variation of power exponent, n with temperature (b)-(f) Variation of ac conductivity with temperature fitted with Eq. (3.11).....	196
Figure 5.16 Variation of (a) Real part of modulus (M') (b) Imaginary part of modulus (M''), with frequency at different temperatures (in °C) (c) Arrhenius plot for max. Frequency generated by Eq. (3.8) (d) KWW parameter, β with respect to temperature for all samples (e) Scaled Modulus vs. scaled frequency for sample SSL4 (f) Scaled Modulus vs. Scaled frequency for all samples at 400°C.....	199
Figure 6.1 (a) Room temperature powder X-ray diffraction pattern of all samples. (b) The Rietveld refinement pattern of calcined powders. Here Y_{obs} , Y_{cal} , $Y_{obs}-Y_{cal}$ and Braggs positions represent the experimental data, calculated data, the difference between both and Braggs position respectively.	207
Figure 6.2 (a) Variation of lattice parameters (b) Degree of distortion ($R=c/a$) with composition. (c) Structure obtained using VESTA for sample SSN4 (d) SSP plot for all samples.....	209
Figure 6.3 (a) Transmission electron micrograph of a representative sample SSN4, (b) Distribution function fitted with Gaussian Function (c) HR-TEM image of different crystallographic planes (d-h) and (i) Selected Area Electron Diffraction (SAED) pattern. ..	212
Figure 6.4 Room temperature Raman spectrum of all samples.	213
Figure 6.5 Fourier transform infrared (FTIR) spectra of all samples.	214
Figure 6.6 (a) Survey scan report for a sample SSN10, Core level XPS spectra of (b) Sr 3d (c) Sn 3d (d) Nd 3d (e) O 1s.	217
Figure 6.7 Room temperature absorbance spectra of SSN samples (Inset shows onset absorption and various absorption of Nd^{3+}	219

Figure 6.8 Tauc plot generated for both direct and indirect band gap of all SSN samples using Eq. (2.21).....	220
Figure 6.9 (a) Room temperature excitation spectra of samples for emission $\lambda_{emi.} = 1060\text{ nm}$ (b) Room temperature emission spectra for all samples under excitation wavelength $\lambda_{exc.} = 596\text{ nm}$	222
Figure 6.10 Room temperature M-H curve for all samples.	225
Figure 7.1 (a) X-ray diffraction pattern of all samples (b) Enlarged view of peak (103) & (110).....	231
Figure 7.2 (a) Rietveld refinement pattern of Eu-doped samples (b) Unit Cell of a sample SSE4 generated by VESTA software.	232
Figure 7.3 Room temperature Fourier transform infrared (FTIR) spectra of all samples.	235
Figure 7.4 Field emission scanning electron micrograph (FESEM) of sintered samples (a) SSE0 (b) SSE1 (c) SSE2 (d) SSE4 (e) SSE6 (f) SSE10.	236
Figure 7.5 Histogram fitted with Gaussian function (a) SSE0 (b) SSE1 (c) SSE2 (d) SSE4 (e) SSE6 (f) SSE10.....	237
Figure 7.6 (a) Survey scan report of $\text{Sr}_2\text{Sn}_{0.99}\text{Eu}_{0.01}\text{O}_4$, Core level XPS spectra of (b) Sr 3d (c) Sn 3d (d) O 1s.	239
Figure 7.7 (a) UV-Vis spectra of all samples (b-f) Tauc plot generated from absorption for both direct and Indirect Band gap.....	241
Figure 7.8 (a) Excitation spectra of a reference sample SSE4 for emission $\lambda_{em} = 612\text{ nm}$ (b) Emission spectra of all samples under excitation wavelength $\lambda_{exc} = 466\text{ nm}$	242
Figure 7.9 (a) Energy band diagram of Eu-doped Sr_2SnO_4 sample (b) CIE coordinate of all sample.	245

Figure 7.10 Decay time curve for wavelength (a) 535 nm (b) 572 nm (c) 614 nm (d)
Variation of life time with composition.....247