

## **List of Tables**

<b>Table 1.1</b> Comparison between different types of fuel cells.....	5
<b>Table 1.2</b> Tolerance factor of different crystal structure.....	21
<b>Table 2.1</b> Specification of materials used in synthesis.....	60
<b>Table 3.1</b> Parameters obtained from Rietveld refinement of XRD data of SrCeO <sub>3</sub> . .....	108
<b>Table 3.2</b> Values of relaxation frequency, resistance and capacitance evaluated from Z" Versus log (f) plots.....	113
<b>Table 4.1</b> Structural parameters obtained from Rietveld refinement analysis of XRD data of the samples.....	131
<b>Table 4.2</b> Crystallite size, lattice strain determined from size strain plots (SSP) method and optical band gap from Tauc plots of the samples. ....	133
<b>Table 4.3</b> Values of average grain size, % porosity, DC conductivity and activation energy, of the samples.....	146
<b>Table 5.1</b> Various parameters obtained from Rietveld refinement analysis of XRD data of the prepared system SrCe <sub>1-x</sub> Gd <sub>x</sub> O <sub>3</sub> (0.00 ≤ x ≤ 0.10). .....	161
<b>Table 5.2</b> Crystallite size, lattice strain determined from size strain plots (SSP) method, optical band gap from Tauc plots, average grain size, electrical conductivity and activation energy of the prepared system SrCe <sub>1-x</sub> Gd <sub>x</sub> O <sub>3</sub> (0.00 ≤ x ≤ 0.10).....	163
<b>Table 6.1</b> Various parameters obtained from Rietveld refinement analysis of XRD data of the prepared system SrCe <sub>1-x</sub> La <sub>x</sub> O <sub>3</sub> (0.00 ≤ x ≤ 0.10). .....	191
<b>Table 6.2</b> Various parameters for the powders obtained by calcination at 1100 °C for 12 h.	
.....	193