

LIST OF FIGURES

| | | |
|---------------------|--|-----------|
| Figure 1.1: | A basic block diagram of a radar system. | 5 |
| Figure 1.2: | Different types of radar. | 7 |
| Figure 1.3: | Pulsed radar waveform. | 9 |
| Figure 1.4: | SFCW waveform (a) Frequency versus Time plot; (b) Amplitude versus Time plot. | 11 |
| Figure 1.5: | Human target detection study. | 13 |
| Figure 2.1: | (a) Simplified block diagram of stepped frequency radar; (b) Simplified block diagram of a two-port VNA connected to a DUT. | 30 |
| Figure 2.2: | Schematic diagram of the experimental setup for target localization within the anechoic chamber. | 35 |
| Figure 2.3: | Region of sensing for omnidirectional antenna. | 36 |
| Figure 2.4: | Common region of sensing (CROS). | 38 |
| Figure 2.5: | Determination of target localization for (a) Acute angle case; (b) Obtuse angle case. | 39 |
| Figure 2.6: | Flowchart of the processing methodology involved in the target localization. | 40 |
| Figure 2.7: | Algorithm for decision making for a subregion within the CROS. | 41 |
| Figure 2.8: | Target localization of the object using two antenna systems for (a) Free space and; (b) Through the wall environments. | 42 |
| Figure 2.9: | Generated range profiles for node position (3, 2) on the rectangular grid with and without target from (a) Antenna A and; (b) Antenna B. | 43 |
| Figure 2.10: | Actual target range generated for node position (3, 2) on the rectangular grid by subtraction of reference for (a) Antenna A and; (b) Antenna B. | 43 |
| Figure 2.11: | Detected location of the target using two antenna based system. | 44 |
| Figure 2.12: | (a) Determination of positions of the target without wall correction; (b) Correction involved to eliminate the positional error for a 1.1 cm thick wall. | 46 |
| Figure 2.13: | (a) Determination of positions of the target with wall correction; (b) Correction involved to eliminate the positional error for a 1.1 cm thick wall. | 47 |
| Figure 2.14: | (a) Determination of positions of the target without wall correction; (b) Correction involved to eliminate the positional error for a 2.2 cm thick wall. | 48 |
| Figure 2.15: | (a) Determination of positions of the target with wall correction; (b) Correction involved to eliminate the positional error for a 2.2 cm thick wall. | 48 |

| | | |
|---------------------|---|------------|
| Figure 3.1: | Time-frequency plot of the SFCW system for multiple consecutive sweeps. | 55 |
| Figure 3.2: | Command and data flow chart. | 57 |
| Figure 3.3: | Data arrangement and vital sign frequency extraction process. | 59 |
| Figure 3.4: | Radar return power spectral density (PSD). | 61 |
| Figure 3.5: | (a) Frequency response of an MTI filter; (b) Output from an MTI filter. | 62 |
| Figure 3.6: | (a) Single delay line canceler; (b) Double delay line canceler and; (c) Delay line canceler with feedback. | 63 |
| Figure 3.7: | Experimental setup schematic placed within the anechoic chamber along with the human subject. | 65 |
| Figure 3.8: | (a) Range profile generated from a randomly selected single sweep data; (b) Stacked data image by arranging the 400 range profiles. | 66 |
| Figure 3.9: | (a) Range profile generated from a single sweep data after clutter reduction; (b) Stacked data image by arranging the 400 range profiles after clutter reduction. | 67 |
| Figure 3.10: | Detected human target location and heartbeat frequency in the range- Doppler (RD) plane. | 69 |
| Figure 4.1: | Micro-Doppler classification process. | 75 |
| Figure 4.2: | Adopted methodology. | 77 |
| Figure 4.3: | (a) Experimental setup synthesized for micro- Doppler experiments; (b) Five different human movement classes under consideration of the experiment. | 78 |
| Figure 4.4: | (a) Support vector machine hyper plane; (b) One versus all classification. | 84 |
| Figure 4.5: | Generated spectrograms for one set of data from all the five experimental classes. | 87 |
| Figure 4.6: | Background-clipped spectrogram velocity-time representation for all the human movements. | 88 |
| Figure 4.7: | (a) Variation of feature 1 (entropy) with collected data; (b) Variation of feature 2 (mean) and feature 3 (variance) with collected data; (c) Variation of feature 4 (skewness) and feature 5 (kurtosis) with collected data. | 90 |
| Figure 4.8: | (a) Classification accuracy of the proposed model with individual features; (b) Training model validation accuracy with increase training features. | 92 |
| Figure 5.1: | (a) Network layer details; (b) Adopted methodology. | 98 |
| Figure 5.2: | Used fully connected DNN regression model. | 100 |
| Figure 5.3: | Two different types of movers present in the single channel. | 107 |
| Figure 5.4: | The decomposition of mix micro-Doppler data of a rotating table fan (TF) and forward moving human (FH) (a) Spectrogram of mixed signal in single channel; (b) Separated spectrogram of | 108 |

| | | |
|--------------------|---|------------|
| | rotating table fan from the mixed micro-Doppler information; (c) Separated spectrogram of forward moving human target. | |
| Figure 5.5: | Time domain target responses actual and estimated after separation algorithm (a) Forward moving human; (b) Table fan target. | 109 |
| Figure 5.6: | Field test spectrogram of (a) Time domain response when TF and FH two target classes were present; (b) Separated TF class; (c) Separated FH class targets. | 110 |
| Figure 5.7: | Three different types of movers present in the single channel. | 111 |
| Figure 5.8: | (a) The spectrogram of the mixed three targets (FH, BH and TF) response; (b) Extracted desired target FH response; (c) Undesired or noise remaining response. | 113 |