

## **LIST OF FIGURES**

---

<b>Figure No.</b>	<b>Caption</b>	<b>Page No.</b>
Figure 1.1	Schematic representation of graphite aerosol generation and nuclear material transport during air ingress accident	3
Figure 1.2	Definition of particle size depending on particles properties and behaviour	5
Figure 1.3	Aerosol effects on environment	9
Figure 1.4	Effects of aerosol on human health	10
Figure 1.5	Method and instrument of particles measurement	14
Figure 1.6	Structure of graphite	15
Figure 1.7	Progressive model	23
Figure 1.8	Shrinking core model	24
Figure 1.9	Oxidation regimes in graphite	25
Figure 1.10	Block diagram of work plan	30
Figure 2.1	Schematic diagram of experimental set-up	43
Figure 2.2	Picture of the experimental set-up	43
Figure 2.3	Furnace picture and schematic diagram	45
Figure 2.4	PID controller	45
Figure 2.5	Flow homogenizer device	47
Figure 2.6	Picture of flange and its drawing	47
Figure 2.7	Systematic diagram of clean air supply unit	50
Figure 2.8	Component of clean air supply unit	50

Figure 2.9	Sampling ports in borosilicate tube	51
Figure 2.10	Isokinetic probe	53
Figure 2.11	Heat exchanger	54
Figure 2.12	Picture of diluter and schematic of its internal circuit	55
Figure 2.13	Flow splitter	56
Figure 2.14	Picture of (a) Nanoscan (b) Optical Particle Sizer	57
Figure 2.15	Schematic diagram of Nanoscan working principle	58
Figure 2.16	Schematic of differential mobility analyzer	59
Figure 2.17	Schematic diagram of OPS working principle	60
Figure 2.18	Gas analyser	61
Figure 3.1	Temperature measurement in experiment	67
Figure 3.2	Temperature recorded at different flow rates	67
Figure 3.3	Sampling ports in borosilicate tube	69
Figure 3.4	Temperature variation at the ports at different flow rate with a constant furnace temperature	69
Figure 3.5	Schematic diagram of the sampling at (a) isokinetic (b) super-isokinetic (c) sub-isokinetic conditions	72
Figure 3.6	Variation of the Stokes number with the probe diameter at different flow rate	74
Figure 3.7	Comparison of isokinetic and anisokinetic sampling	77
Figure 3.8	Variation of diffusion and gravitational loss with particle mean diameter at different flow rates	82
Figure 3.9	Variation of thermophoresis loss with particle mean diameter	84
Figure 4.1	Picture of (a) bare graphite and (b) alumina coated graphite	88
Figure 4.2	XRD pattern of graphite sample	89

Figure 4.3	EDS of graphite sample	89
Figure 4.4	TGA of graphite sample	90
Figure 4.5	Furnace heating rate	94
Figure 4.6	Block diagram of the experimental procedure	94
Figure 5.1	SEM analysis of residual samples after burning in air at constant temperatures for 2-hours	99
Figure 5.2	Particle number concentration at different temperatures for 2-hours combustion duration at 25 Lmin <sup>-1</sup>	101
Figure 5.3	Particle size distribution after 2-hours of combustion	102
Figure 5.4	Particle mass concentrations at different temperatures	103
Figure 5.5	Time evolution of size segregated particles at 700 °C	103
Figure 5.6	Particle number concentration at different flow rates for 2-hours combustion (burning temperature: 700 °C)	104
Figure 5.7	Carbon monoxide evolution at different temperatures for 2-hours graphite heating	105
Figure 5.8	Carbon dioxide evolution at different temperatures for 2-hours graphite heating	106
Figure 5.9	Percentage of graphite converted to combustion products	108
Figure 5.10	Total number concentration of generated particles at different heating rates and flowrates (a) 10 Lmin <sup>-1</sup> (b) 15 Lmin <sup>-1</sup> (c) 20 Lmin <sup>-1</sup> (d) 25 Lmin <sup>-1</sup>	110
Figure 5.11	Particle size distribution at different heating rates and flow rates (a) 10 Lmin <sup>-1</sup> (b) 15 Lmin <sup>-1</sup> (c) 20 Lmin <sup>-1</sup> (d) 25 Lmin <sup>-1</sup>	112
Figure 5.12	Carbon monoxide evolution at different heating rates and flow rates (a) 10 Lmin <sup>-1</sup> (b) 15 Lmin <sup>-1</sup> (c) 20 Lmin <sup>-1</sup> (d) 25 Lmin <sup>-1</sup>	113

Figure 5.13	Carbon dioxide evolution at different heating rates and flow rates (a) 10 Lmin <sup>-1</sup> (b) 15 Lmin <sup>-1</sup> (c) 20 Lmin <sup>-1</sup> (d) 25 Lmin <sup>-1</sup>	114
Figure 5.14	Percentage of mass loss at different heating rates and flow rates	115
Figure 5.15	SEM analysis of residual Al <sub>2</sub> O <sub>3</sub> coated graphite samples without removing coating layer	117
Figure 5.16	SEM analysis of residual coated graphite samples after removing coating layer	118
Figure 5.17	Particle generation in bare and coated graphite at different temperatures	120
Figure 5.18	Particle size distribution for generated particles from bare and coated graphite samples	122
Figure 5.19	Carbon monoxide generation at different temperatures for bare and Al <sub>2</sub> O <sub>3</sub> coated graphite	124
Figure 5.20	Carbon dioxide generation at different temperatures for bare and Al <sub>2</sub> O <sub>3</sub> coated graphite	125
Figure 5.21	Weight loss percentage in bare and coated graphite samples after burning for 2-hours	126
Figure 5.22	XRD of (a) bare and (b) coated graphite after burning at different temperatures	127
Figure 5.23	Block diagram of categories of particle generation	128
Figure 5.24	Block diagram of particle graphite particle formation	128
Figure 5.25	Block diagram of smaller/ larger particle formation	129
Figure 5.26	Block diagram of reaction occurs in graphite	130
Figure 5.27	Block diagram of particle generation at different temperatures	132