

LIST OF FIGURES

Figure 1.1.	Comparison of average power versus frequency for various types of devices.	6
Figure 1.2.	Dispersion diagrams showing the operating regions of interaction for (a) gyrotron, (b) gyro-TWT, (c) CARM, (d) gyro-BWO, and (e) SWCA.	12
Figure 1.3.	TE_{0n} mode RF electric field in a waveguide with electron beamlets.	15
Figure 1.4.	Illustration of phase bunching phenomenon in an annular electron beam (a) random distribution, and (b) phase bunched electrons in their cyclotron orbits.	16
Figure 1.5.	Time evolution of electrons phase distribution (shown as \odot) in the Larmor orbit [taken permission for use from Singh (2012)].	18
Figure 1.6.	Schematic of conventional gyrotron with (a) axial output RF coupling and (b) radial <i>output RF coupling</i> .	21
Figure 1.7.	A 2D axial symmetric view of tapered cylindrical RF interaction cavity.	23
Figure 2.1.	A schematic view of quasi optical mode converter system.	44
Figure 2.2.	Geometric optical description of a wave beam in a cylindrical waveguide (a) Side view; (b) top view.	49
Figure 2.3.	The unrolled waveguide surface at a constant radius R_0 and the Vlasov launcher cuts are highlighted.	50
Figure 2.4.	Vlasov launcher with a cut.	52
Figure 2.5.	Mode variations profile along the length of the $TE_{22,6}$ mode at 110GHz launcher for eight satellite modes.	66
Figure 2.6.	Wall field intensities on the dimple launcher of $TE_{22,6}$ mode at 110GHz for four satellite modes.	66
Figure 2.7.	Mode variations profile along the length of the $TE_{22,6}$ mode at 110GHz launcher for eight satellite modes.	67

Figure 2.8.	Wall field intensities on the dimple launcher of TE _{22,6} mode at 110GHz for eight satellite modes.	68
Figure 2.9.	Wall Deformation profiles for the TE _{10,4} mode at 95GHz launcher.	69
Figure 2.10.	Mode variations profile along the length of the TE _{10,4} mode at 95GHz launcher.	70
Figure 2.11.	Wall field intensities on the dimple launcher of TE _{10,4} mode at 95GHz.	71
Figure 2.12.	Schematic diagram of single disc type window of thickness d .	72
Figure 2.13.	Equivalent Two port scattering matrix network.	73
Figure 2.14.	(a) Reflection characteristics versus frequency (b) Transmission characteristics versus frequency for Window at various disc thicknesses d .	76
Figure 2.15.	(a) Reflection characteristics versus frequency (b) Transmission characteristics versus frequency for Sapphire Window at various disc thicknesses d .	76
Figure 2.16.	(a) Reflection characteristics versus frequency (b) Transmission characteristics versus frequency for CVD Window at various disc thicknesses d .	77
Figure 3.1.	(a) Voltage depression V_{dep} (kV) versus normalized beam radius $\overline{R}_b (= R_b / R_c)$, and (b) Limiting current I_L (A) versus normalized beam radius $\overline{R}_b (= R_b / R_c)$ for TE _{6,2} - mode.	90
Figure 3.2.	2-D axis symmetric view of the tapered RF interaction cavity of the gyrotron.	91
Figure 3.3.	Normalized axial RF field amplitude profiles for various smoothing transition combinations at 0 mm, 4 mm, 6mm of lengths: $L_d = 13$ mm, $L_c = 20$ mm and $L_{up} = 26$ mm.	93
Figure 3.4.	Beam wave coupling factor C_{mp} curves versus normalized beam radius (\overline{R}_b) for various modes.	95
Figure 3.5.	Start oscillation current I_{soc} (Amp) versus DC magnetic field B in (T) plots for different operating modes.	96
Figure 3.6.	Arrangement of the gyrating electrons in Larmor orbit in the Cartesian as well as cylindrical coordinate systems.	98

Figure 3.7.	Temporal growth of output RF powers P_m (kW) in various modes through time dependent multimode analysis.	102
Figure 3.8.	Interaction efficiency η versus time (ns).	103
Figure 3.9.	PIC simulation results: Normalized axial RF field amplitude profiles hot conditions along with vector field distribution.	104
Figure 3.10.	Temporal growth of operating and competing mode amplitudes A_m (V/m) from PIC Simulation study.	105
Figure 3.11.	Frequency response of the operating and competing modes from PIC simulation study.	106
Figure 3.12.	CST PIC simulation results- Temporal growth of RF powers in the operating and competing modes.	106
Figure 3.13.	Comparisons of output RF powers in the main mode $TE_{6,2}$ - by multimode analysis and PIC simulations for magnetic fields.	107
Figure 3.14.	Variations in the cavity cut-off frequency f_c due to changes in the RF cavity radius R_c .	113
Figure 3.15.	Schematic diagram of typical radial cooling fins on a cylindrical surface ($f_h = f_{in}$ height, $f_w = f_{in}$ width and $s =$ spacing between fins).	115
Figure 3.16.	2D axis symmetric interaction cavity models (a) without and (b) with radial fins simulated in COMSOL ($f_h =$ fin height, $f_w =$ fin width and $s =$ spacing between fins).	119
Figure 3.17.	Wall loading profile (Ohmic power loss density) for operating $TE_{6,2}$ mode of the gyrotron (electrical conductivity $\sigma = 5.8 \times 10^7$ S/m).	119
Figure 3.18.	Radial deformation ΔR_{rad} at the cavity inner surface for various heat transfer coefficient h and cavity thickness δR values (a). Average and (b) Maximum.	122
Figure 3.19.	Temperature at the cavity outer surface T_{out} for various heat transfer coefficient h and cavity thickness δR values (a) Average and (b) Maximum.	122
Figure 3.20.	Range of hydraulic diameter D_h and Water flow rates of the thermal system for the optimized convective heat transfer coefficient h values.	126
Figure 3.21.	3D view of the radial deformation distribution for heat transfer coefficient $h = 15000$ (W/m ² .K) and $\delta R = 5$ mm of RG3 group.	126

Figure 3.22.	3D view of temperature distribution for heat transfer coefficient $h=15000$ (W/m ² .K) and cavity $\delta R= 5$ mm of RG3 group.	126
Figure 3.23.	Initial (red colour) and deformed cavity (blue colour) due to ohmic loss at optimized thermal system parameters.	127
Figure 3.24.	Cold cavity field amplitude profiles for the initial and deformed cavity.	128
Figure 3.25.	Hot cavity electric field profiles of initial and deformed cavity.	129
Figure 3.26.	Comparisons of power levels in the TE _{6,2} for initial and deformed cavity.	129
Figure 4.1.	(a) Voltage depression V_{dep} (kV) versus normalized beam radius $\overline{R}_b (= R_b / R_c)$, and (b) Limiting current I_L (A) versus normalized beam radius $\overline{R}_b (= R_b / R_c)$ for TE _{10, 4} - mode.	140
Figure 4.2.	Normalized axial RF field amplitude profiles for various uniform section lengths: $L_c= 28.00$ mm (solid light), 30.00 mm (solid) and 32.00 mm (dashed light).	141
Figure 4.3.	Beam wave coupling factor C_{mp} curves versus normalized beam radius (\overline{R}_b) for various modes.	143
Figure 4.4.	Start oscillation current I_{soc} (in amperes) versus DC magnetic field B in (tesla) plots for different operating modes.	143
Figure 4.5.	Beam misalignments effects: Location of beam lets for $d = 0$ mm and $d = 0.5$ mm.	146
Figure 4.6.	Temporal growth of output RF powers P_m (kW) in various modes through time dependent multimode analysis.	148
Figure 4.7.	PIC simulation results: Comparisons of Normalized axial RF field amplitude profiles in the cold and hot conditions along with vector field distribution.	149
Figure 4.8.	3D PIC Simulation results- Temporal growth of operating and competing mode amplitudes A_m (V/m) from PIC Simulation study (b). Frequency response of the operating and compete modes.	150
Figure 4.9.	3D PIC Simulation results-(a)Temporal growth of RF powers in the operating and competing modes P_m resulted from PIC simulation (b) Wave particle power transfer (kW) versus time (ns).	152

Figure 4.10.	Comparisons of output RF powers in the main mode $TE_{10,4-}$ through multimode analysis and PIC simulation study.	154
Figure 4.11.	Normalized axial cold cavity field profiles and the corresponding radius profiles that include NLT section vs axial distance of the device.	157
Figure 4.12.	Analytical results: (a) normalized axial cold cavity field profiles and the corresponding radius profiles that include NLT section vs axial distance of the device (b) RF power versus time.	158
Figure 4.13.	(a). Normalized axial E field profile in hot (beam present condition) along with 2D vector field pattern of $TE_{10,4-}$ mode (b). FFT field amplitudes of $TE_{10,4-}$ (Light shade) and $TE_{7,5+}$ (dark shade) modes.	159
Figure 4.14.	3D PIC Simulation results- temporal growth of amplitudes across various modes A_m (V/m) (a) : $TE_{7,5+}$ overrides $TE_{10,4-}$ (while plotting) (b) vice versa.	159
Figure 4.15.	3D PIC Simulation results- (a) temporal growth of mode powers and (b) wave particle power transfer versus time.	160
Figure 4.16.	Temporal growth of power developed across various modes P_m as well Wave-particle power transfer.	161
Figure 4.17.	Inner maximum radial deformations versus convective heat transfer coefficient h for various cavity thickness δR_{rad} at electrical conductivities (a) $5.8e7$ S/m (b) $2.9e7$ S/m.	161
Figure 4.18.	Outer maximum radial cavity temperatures T_{out} (K) versus convective heat transfer coefficient h at various cavity thickness δR_{rad} at electrical conductivities (a) $5.8e7$ S/m (b) $2.9e7$ S/m.	162
Figure 4.19.	3D view of surface displacements and surface temperatures for heat transfer coefficient $h=2000$ ($W/m^2.K$) and cavity $\delta R=4.5$ mm.	163
Figure 5.1.	Dependence of Relativistic factor and cyclotron frequency with respect to Beam voltage.	175
Figure 5.2.	% change of cyclotron frequency versus magnetic field B (T).	176
Figure 5.3.	Beam wave coupling factor C_{mn} versus normalized beam radius $\overline{R}_b = R_b / R_c$.	177
Figure 5.4.	Axial mode profiles at beam absent conditions for various q of proposed RF interaction cavity.	179

Figure 5.5.	Start Oscillation currents for TE _{5,3,q} mode $q = 1$ to 6 versus magnetic field.	180
Figure 5.6.	% of voltage depression versus beam voltages for the various beam current values.	181
Figure 5.7.	Operating frequencies and RF power levels for various axial variations, $q=1$ to 6 in magnetic tuning at $I_b = 400$ mA.	183
Figure 5.8.	Operating frequencies and RF power levels for various axial variations, $q = 1$ to 6 in magnetic tuning at $I_b = 20$ mA.	183
Figure 5.9.	Resonant frequencies and RF power levels for various axial variations, $q=1$ to 6 in electrical tuning at $I_b= 400$ mA.	184
Figure 5.10.	Resonant frequencies and RF power levels for various axial variations, $q = 1$ to 6 in electrical tuning at $I_b = 20$ mA.	185
Figure 5.11.	Reflection characteristics r (dB) versus frequency (GHz) at various disc thickness $d = N d_0$ of window radius thickness.	186
Figure 5.12.	Transmission characteristics T (dB) versus frequency (GHz) at various disc thickness $d = N \times d_0$.	187
Figure 6.1.	Normalized cold cavity axial RF field amplitude profiles for various axial mode indices TE _{0,3,q} , where $q = 1, 2, 3$ of Joye <i>et al.</i> (2006).	195
Figure 6.2.	Start oscillation current I_{soc} (mA) versus DC magnetic field B (Tesla) plots of TE _{0,3,q} for different axial mode indices q of Joye <i>et al.</i> (2006).	196
Figure 6.3.	Normalized cold cavity axial RF field amplitude profiles of modified cavities for various axial mode indices TE _{0,3,q} , for $q = 1, 2, 3$, and 4.	198
Figure 6.4.	Start oscillation current I_{soc} (in amperes) versus DC magnetic field B in (tesla) plots for different axial operating modes of TE _{0,3,q} for modified RF cavity dimensions.	199
Figure 6.5.	Comparisons of RF power (a) versus time using multimode analysis and (b) with respect to magnetic fields for cavities of Colin D Joye <i>et al.</i> (2006) and modified design.	201
Figure 6.6.	PIC Simulation results - (a-b) hot axial RF field profiles (c-d) frequency response of the operating mode TE _{0,3,q} with axial index $q = 1$ for cavities of Joye <i>et al.</i> (2006) and modified designs, respectively.	202
Figure 6.7.	PIC Simulation results - Temporal growth of mode TE _{0,3,1} (a - b) amplitudes (c - d) power values for cavities reported design by Joye	203

et al. (2006) and as per our modified design, respectively.