LIST OF TABLES

| Table No. | Table Caption | Page No. |
|-----------------|--|------------|
| Table 3.1 | Training and testing conditions considered on first test | 61 |
| T 11 2 2 | system | < - |
| Table 3.2 | Faults classification accuracy percentage obtained by K- | 65 |
| | NN technique based scheme | |
| Table 3.3 | Variation of obtained accuracy percentage with respect to | 66 |
| | change in 'K' values | |
| Table 3.4 | Confusion matrix for the KNN based scheme (First test | 66 |
| | system) | |
| Table 3.5 | Faults classification accuracy percentage obtained by SVM | 67 |
| | technique based scheme | |
| Table 3.6 | Confusion matrix for the SVM based scheme (First test | 68 |
| | system) | |
| Table 3.7 | Faults classification accuracy percentage obtained by PNN | 69 |
| | technique based scheme | |
| Table 3.8 | Time of response of different non-parametric ML scheme | 74 |
| Table 3.9 | Comparative study of average classification accuracy achieved by proposed scheme with previously reported approaches | 74 |
| Table 3.10 | Training and testing conditions considered on second test | 75 |
| | system | |
| Table 3.11 | Faults classification accuracy percentage obtained by K- | 78 |
| | NN technique based scheme | |
| Table 3.12 | Confusion matrix for KNN based scheme (second test | 79 |
| | system) | |
| Table 3.13 | Faults classification accuracy percentage obtained by SVM | 80 |
| | technique based scheme | |
| Table 3.14 | Confusion matrix for SVM based scheme (Second test | 80 |
| | system) | |
| Table 3.15 | Faults classification accuracy percentage obtained by PNN | 81 |
| | technique based scheme | |

| Table 3.16 | Training and testing conditions for assessing evolving fault events | 84 |
|------------|--|-----|
| Table 3.17 | Identification of evolving fault events using KNN classifier | 86 |
| | based scheme | |
| Table 3.18 | Identification of evolving fault events using SVM classifier | 86 |
| | based scheme | |
| Table 3.19 | Evolving fault events classification percentage obtained by | 87 |
| | PNN based scheme | |
| Table 3.20 | Performance of proposed classifier models during saturation at three different burden impedances | 91 |
| Table 4.1 | Training and testing condition considered on first test system | 98 |
| Table 4.2 | Faults classification accuracy percentage obtained by K- NN technique based scheme | 104 |
| Table 4.3 | Confusion matrix for the KNN based scheme (First test system) | 105 |
| Table 4.4 | Faults classification accuracy percentage obtained by SVM | 106 |
| | technique based scheme | |
| Table 4.5 | Confusion matrix for the SVM based scheme (First test | 106 |
| | system) | |
| Table 4.6 | Faults classification accuracy percentage obtained by PNN | 107 |
| | technique based scheme | |
| Table 4.7 | Time of response of different non-parametric ML scheme | 109 |
| Table 4.8 | Comparative study of average classification accuracy | 109 |
| | achieved by proposed scheme with previously reported | |
| | approaches | |
| Table 4.9 | Training and testing conditions considered on second test | 111 |
| | system | |
| Table 4.10 | Faults classification accuracy percentage obtained by K- | 116 |
| | NN technique based scheme | |
| Table 4.11 | Confusion matrix for KNN based scheme (second test system) | 116 |
| Table 4.12 | Faults classification accuracy percentage obtained by SVM | 117 |

technique based scheme

| Table 4.13 | Confusion matrix for SVM based scheme (Second test | 118 |
|------------|--|-----|
| | system) | |
| Table 4.14 | Faults classification accuracy percentage obtained by PNN | 118 |
| | technique based scheme | |
| Table 4.15 | Training and testing conditions for assessing evolving fault | 121 |
| | events | |
| Table 4.16 | Identification of evolving fault events using KNN classifier | 127 |
| | based scheme | |
| Table 4.17 | Identification of evolving fault events using SVM classifier | 127 |
| | based scheme | |
| Table 4.18 | Evolving fault events classification percentage obtained by | 128 |
| | PNN based scheme | |
| Table 5.1 | Training and testing conditions considered on first test | 140 |
| | system | |
| Table 5.2 | Faults classification accuracy percentage obtained by | 144 |
| | ensemble learning (bagging) technique based scheme | |
| Table 5.3 | Confusion matrix for the ensemble learning based scheme | 145 |
| | (First test system) | |
| Table 5.4 | Time of response of ensemble learning based scheme | 146 |
| Table 5.5 | Comparative analysis of average classification accuracy | 146 |
| | achieved by proposed scheme with previously reported | |
| | approaches | |
| Table 5.6 | Training and testing conditions considered on second test | 147 |
| | system | |
| Table 5.7 | Faults classification accuracy percentage obtained by | 150 |
| | bagging technique based scheme | |
| Table 5.8 | Confusion matrix for ensemble learning based scheme | 151 |
| | (second test system) | |
| Table 5.9 | Training and testing conditions used on third test system | 152 |
| Table 5.10 | Faults classification accuracy percentage obtained by | 156 |
| | ensemble learning based scheme | |
| Table 5.11 | Performance of proposed classifier models during | 159 |

saturation at three different burden impedances

| Table 5.12 | Identification of CCF events using ensemble classifier models | 162 |
|------------|---|-----|
| Table 5.13 | Identification of evolving fault events using bagging classifier model | 164 |
| Table 5.14 | Training and testing conditions considered on first test system | 177 |
| Table 5.15 | Faults classification accuracy percentage obtained by DNN based scheme | 178 |
| Table 5.16 | Confusion matrix for the DNN based scheme (First test system) | 180 |
| Table 5.17 | Time of response of DNN based events classification scheme | 181 |
| Table 5.18 | Comparative analysis of average classification accuracy achieved by proposed DNN based scheme with previously reported approaches | 181 |
| Table 5.19 | Faults classification accuracy percentage obtained by DNN based scheme | 182 |
| Table 5.20 | Confusion matrix for DNN based scheme (second test system) | 182 |
| Table 5.21 | Acquired accuracy percentage obtained by DNN technique based scheme | 183 |
| Table 5.22 | Identification of CCF events in the network using DNN model based scheme | 184 |
| Table 5.23 | Identification of evolving fault events using DNN model based scheme | 185 |
| Table 6.1 | Fault events distance estimation using FFNN based distance estimator model | 200 |
| Table 6.2 | Fault events distance estimation using LNN based distance estimator model | 201 |
| Table 6.3 | Fault events distance estimation using GRNN based | 202 |
| Table 6.4 | Fault events distance estimation using CFNN model on | 205 |

different fault inception angles at 35 % of line compensation

- Table 6.5Fault events distance estimation using CFNN model on
different fault inception angles at 45 % of line
compensation208Table 6.6Fault events distance estimation using CFNN based
distance estimator model on second test system214
- Table 6.7Fault events distance estimation using CFNN based220distance estimator model on third test system
- Table 6.8Distance estimation of evolving faults using CFNN based224distance estimator model (second test system)
- Table 6.9Distance estimation of evolving faults using CFNN based225distance estimator model (third test system)
- Table 6.10Comparision of distance estimation error for locating EFE227in the network