

## LIST OF TABLES

---

| Table Caption  | Page No.     |
|--|--------------|
| <b>Table 1.1</b> General comparison between organic and inorganic semiconductors.  | <b>4</b>     |
| <b>Table 1.2</b> Contact Characteristics   | <b>34</b>    |
| <b>Table 1.3</b> Various applications of self-assembled PATs prepared by different techniques.                             | <b>50</b>    |
| <b>Table 1.4</b> Various applications of self-assembled PATs based blends and copolymers prepared by different techniques. | <b>51</b>    |
| <b>Table 1.5</b> Graphene/Metal Oxide nanocomposite for Gas sensor applications  | <b>52</b>    |
| <b>Table 1.6</b> Various applications of hybrid material synthesised by different procedures.                              | <b>53-54</b> |
| <b>Table 3.1</b> Electrical device parameters  | <b>95</b>    |
| <b>Table 4.1</b> Device parameters of as-fabricated devices.   | <b>108</b>   |
| <b>Table 5.1</b> Various parameters associated with different samples excited at wavelength 369 nm.                        | <b>129</b>   |
| <b>Table 5.2</b> Device parameters of all materials  | <b>129</b>   |
| <b>Table 7.1</b> Refinement parameters used in Reitveld and lattice parameter of SnO <sub>2</sub> obtained after Reitveld. | <b>159</b>   |