
List of Figures

Fig. No.	Title	Page No.
Fig. 1.1	Schematic diagram of oxy-fuel combustion based CCS (adapted from Cormos, 2016)	4
Fig. 2.1	CFD modelling of pulverized coal combustion: An overview of basic modules (Adopted from Sankar et al., 2019)	21
Fig. 3.1	The geometry of (a) oxy-fuel furnace and (b) swirl burner (all dimensions are in mm)	38
Fig. 3.2	Schematic diagram of the formation/destruction of fuel NO _x (Adopted from Al-Abbas et al., 2012)	55
Fig. 3.3	Computational mesh used in the present 2D axisymmetric simulation	59
Fig. 3.4	Radial profile of (a) axial velocity (m/s) and (b) temperature (K) at axial location 0.05 m for grid independence test	60
Fig. 3.5	Comparison of RANS prediction of axial velocity (m/s) with LES result and experimental data at different axial locations from burner (a) 0.025 m (b) 0.05 m (c) 0.2 m and (d) 0.3 m	61
Fig. 3.6	Comparison of RANS prediction of tangential velocity (m/s) with experimental data at different axial locations from burner (a) 0.025 m (b) 0.05 m (c) 0.2 m and (d) 0.3 m	63
Fig. 3.7	Comparison of RANS prediction of temperature (K) with LES result and experimental data at different axial locations from burner (a) 0.05 m (b) 0.2 m (c) 0.3 m and (d) 0.5 m	64
Fig. 3.8	Comparison of RANS prediction of O ₂ mole fraction (%) with LES result and experimental data at different axial locations from burner (a) 0.05 m (b) 0.2 m (c) 0.3 m and (d) 0.5 m	66
Fig. 4.1	Axial velocity (m/s) contour for different swirl numbers (a)	71

	S=0.06 (b) S=0.57 (c) S=1.0 (d) S=1.25	
Fig. 4.2	Radial variation of axial velocity (m/s) for different swirl number at axial location (a) 0.05 m and (b) 0.2 m	72
Fig. 4.3	Radial variation of tangential velocity (m/s) for different swirl number at axial location (a) 0.05 m and (b) 0.2 m	72
Fig. 4.4	Contour of temperature (K) distribution for different swirl numbers (a) S=0.06 (b) S=0.57 (c) S=1.0 (d) S=1.25	73
Fig. 4.5	Radial variation of temperature (K) for different swirl number at axial location (a) 0.05 m and (b) 0.2 m	73
Fig. 4.6	Contour of axial velocity (m/s) under different combustion conditions (a) 21% O ₂ /79% CO ₂ (b) 25% O ₂ /75% CO ₂ (c) 30% O ₂ /70% CO ₂ (d) 35% O ₂ /65% CO ₂	75
Fig. 4.7	Contour of temperature (K) under different combustion conditions (a) 21% O ₂ /79% CO ₂ (b) 25% O ₂ /75% CO ₂ (c) 30% O ₂ /70% CO ₂ (d) 35% O ₂ /65% CO ₂	77
Fig. 4.8	Radial variation of gas temperature (K) under different combustion environment at axial locations (a) 0.05 m and (b) 0.2 m	77
Fig. 4.9	Predicted char burning rate inside combustion chamber under (a) oxy-21 (b) oxy-25 (c) oxy-30 and (d) oxy-35 combustion conditions	78
Fig. 4.10	Predicted oxygen mole fraction inside combustion chamber under (a) oxy-21 (b) oxy-25 (c) oxy-30 and (d) oxy-35 combustion conditions	79
Fig. 4.11	Radial variation of O ₂ mole fraction under different combustion environment at axial locations (a) 0.05 m and (b) 0.2 m	79
Fig. 4.12	Axial variation of gas temperature (K) for various combustion cases	82
Fig. 4.13	Axial variation of surface incident radiation (kW/m ²) along the	82

	lateral wall from burner for various combustion case	
Fig. 4.14	Temporal history of particle volatile mass fraction for (a) different particle sizes under oxy-21 combustion atmosphere (b) 95.9 μm particle under various combustion atmosphere	84
Fig. 4.15	Temporal history of particle char mass fraction for (a) different particle sizes under oxy-21 combustion atmosphere (b) 95.9 μm particle under various combustion atmosphere	85
Fig. 4.16	Variation of particle temperature history for (a) different particle sizes under oxy-21 combustion atmosphere (b) 95.9 μm particle under various combustion atmosphere	85
Fig. 4.17	Contour of axial velocity (m/s) for different inlet feed gas temperatures (a) 313 K (b) 500 K and (c) 800 K	87
Fig. 4.18	Radial variation of axial velocity (m/s) for different inlet feed gas temperatures at axial locations (a) 0.05 m and (b) 0.2 m	88
Fig. 4.19	Contour of temperature (K) for different inlet feed gas temperatures (a) 313 K (b) 500 K and (c) 800 K	89
Fig. 4.20	Radial variation of temperature (K) for different inlet feed gas temperatures at axial locations (a) 0.05 m and (b) 0.2 m	89
Fig. 4.21	Axial velocity (m/s) contour for different inlet feed gas pressures (a) 1.0 Bar (b) 5.0 Bar (c) 10 Bar	91
Fig. 4.22	Radial variation of axial velocity (m/s) for different inlet pressures at axial locations (a) 0.05 m and (b) 0.2 m	91
Fig. 4.23	Temperature contour (K) for different inlet feed gas pressures (a) 1 Bar (b) 5 Bar (c) 10 Bar	93
Fig. 4.24	Radial variation of temperature (K) for different inlet pressures at axial locations (a) 0.05 m and (b) 0.2 m	93
Fig. 4.25	The effect of swirl strength, combustion environment, inlet temperature and pressure of feed gas on length of IRZ (m) and flame length (m)	95

Fig. 5.1	Contour of axial velocity distribution (m/s) under the studied combustion cases having (a) 0% H ₂ O (b) 10% H ₂ O (c) 20% H ₂ O (d) 30% H ₂ O (e) 40% H ₂ O (f) 50% H ₂ O and (g) oxy-steam combustion	100
Fig. 5.2	Axial profile of axial velocity (m/s) along centerline for the studied combustion cases	101
Fig. 5.3	Contour of temperature distribution under various oxy-fuel combustion cases having (a) 0% H ₂ O (b) 10% H ₂ O (c) 20% H ₂ O (d) 30% H ₂ O (e) 40% H ₂ O (f) 50% H ₂ O and (g) oxy-steam combustion	101
Fig. 5.4	Axial variation of temperature under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	103
Fig. 5.5	Influence of various combustion environment obtained by varying steam content of oxidizer on (a) length of internal recirculation zone (IRZ) and (b) maximum temperature (K)	103
Fig. 5.6	Contour of oxygen mole fraction distribution under various oxy-fuel combustion cases having (a) 0% H ₂ O (b) 10% H ₂ O (c) 20% H ₂ O (d) 30% H ₂ O (e) 40% H ₂ O (f) 50% H ₂ O and (g) oxy-steam combustion	105
Fig. 5.7	Axial variation of incident radiation under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	105
Fig. 5.8	Temporal variation of particle volatile mass fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case (d=95.9 μm)	106
Fig. 5.9	Temporal variation of particle char mass fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case (d=95.9 μm)	106

List of Figures

Fig. 5.10	Axial variation of O ₂ mole fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	108
Fig. 5.11	Axial variation of CO ₂ mole fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	109
Fig. 5.12	Axial variation of H ₂ O mole fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	109
Fig. 5.13	Axial profile of CO mole fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	111
Fig. 5.14	Axial profile of H ₂ mole fraction under various oxy-fuel combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case	111
Fig. 5.15	Axial variation of predicted temperature with and without consideration of gasification reaction	113
Fig. 5.16	Axial variation of predicted CO ₂ and H ₂ O mass fraction with and without consideration of gasification reaction	113
Fig. 5.17	Profiles of particle char mass fraction v/s residence time	114
Fig. 5.18	Comparison of current numerical result of NO _x concentration (ppm) with experimental data and available numerical result at different axial locations from burner (a) 0.05 m (b) 0.2 m (c) 0.3 m and (d) 0.5 m	116
Fig. 5.19	Distribution of NO _x concentration (ppm) inside the combustion chamber under various oxy-coal combustion cases (a) 21% O ₂ /79% CO ₂ (b) 25% O ₂ /75% CO ₂ (c) 30 % O ₂ /70% CO ₂ (d) 35 % O ₂ /65% CO ₂	117
Fig. 5.20	Influence of various oxy-coal combustion atmosphere on radial	119

	profile of NO _x concentration (ppm) at axial different locations (a) 0.05 m (b) 0.2 m (c) 0.3 m and (d) 0.5 m	
Fig. 5.21	Distribution of NO _x concentration (ppm) inside the combustion chamber under various inlet feed gas temperature (a) 313 K (b) 500 K (c) 800 K	121
Fig. 5.22	Effect of the inlet feed gas temperature on radial profile of NO _x concentration (ppm) at axial locations (a) 0.05 m and (b) 0.2 m	121
Fig. 5.23	Distribution of NO _x concentration (ppm) inside the combustion chamber under various inlet feed gas pressure (a) 1 Bar (b) 5 Bar and (c) 10 Bar	123
Fig. 5.24	Effect of the inlet feed gas pressure on radial profile of NO _x concentration (ppm) at axial locations (a) 0.05 m and (b) 0.2 m	123
Fig. 5.25	Distribution of NO _x concentration (ppm) inside the combustion chamber under various wet oxy-coal combustion cases having (a) 0% H ₂ O (b) 20% H ₂ O (c) 40% H ₂ O and (d) oxy-steam combustion case	125
Fig. 5.26	Radial variation of NO _x concentration (ppm) under various oxy-coal combustion cases having 0-50% H ₂ O in oxidizer and oxy-steam combustion case at axial locations (a) 0.05 m and (b) 0.2 m	125
Fig. 5.27	Influence of (a) various oxy-coal combustion atmosphere (b) inlet temperature of feed gas (c) inlet feed gas pressure and (d) H ₂ O concentration in oxidizer on NO _x concentration (ppm) obtained at the outlet of combustion chamber	127
Fig. 6.1	Schematic diagram of 660 MW supercritical power plant working under conventional air-fired pulverized coal combustion without CO ₂ capture	131
Fig. 6.2	Schematic of 660 MW power plant comprising of (a) ASU, supercritical Rankine cycle and CPU retrofitted to oxy-fuel combustion	133

List of Figures

Fig. 6.3	Flowsheet of oxy-coal combustion of pulverized coal	134
Fig. 6.4	Influence of oxygen concentration on the CO ₂ and CO produced in the flue gas (RR=0.7)	143
Fig. 6.5	Influence of oxygen concentration on the NO _x and N ₂ produced in the flue gas (RR=0.7)	143
Fig. 6.6	Influence of oxygen concentration on the SO ₂ and SO ₃ produced in the flue gas (RR=0.7)	144
Fig. 6.7	Influence of oxygen concentration on the power consumption of ASU, CPU and total power consumption (RR=0.7)	144
Fig. 6.8	Influence of oxygen concentration on the CO ₂ product purity and CO ₂ recovery rate (RR=0.7)	146
Fig. 6.9	Influence of oxygen concentration on the Specific energy consumptions of CO ₂ and O ₂ (RR=0.7)	146
Fig. 6.10	Influence of recycle ratio (RR) on the CO ₂ and CO produced in the flue gas (25 mol % O ₂)	149
Fig. 6.11	Influence of recycle ratio (RR) on the NO _x and N ₂ produced in the flue gas (25 mol % O ₂)	149
Fig. 6.12	Influence of recycle ratio (RR) on the SO ₂ and SO ₃ produced in the flue gas (25 mol % O ₂)	150
Fig. 6.13	Influence of recycle ratio (RR) on the CO ₂ product purity and CO ₂ recovery rate (25 mol % O ₂)	150
Fig. 6.14	Influence of recycle ratio (RR) on the Specific energy consumptions of CO ₂ and O ₂ (25 mol % O ₂)	151
Fig. 6.15	Influence of recycle ratio (RR) on the power consumption of ASU and CPU	151
Fig. 6.16	Variation of optimal recycle ratio (RR) and CPU power consumption corresponding to the different O ₂ concentrations from ASU	153
Fig. 6.17	Sensitivity analysis for the different O ₂ concentrations from ASU	153

Fig. 6.18	Schematic of environmental interaction of conventional air-fired supercritical power plant	155
Fig. 6.19	Schematic of environmental interaction of oxy-fired supercritical power plant	155