

## List of figures

<b>Figures</b>		<b>Page No.</b>
Figure 1.1	Classification of membrane separation processes.	2
Figure 1.2	Membrane separation processes, pore sizes, molecular weight cut-off (MWCO) and examples of sizes of solutes and particles.	6
Figure 1.3	Classification of membranes.	10
Figure 1.4	Schematic diagram of cross flow filtration and dead end filtration process.	13
Figure 1.5	Membrane preparation by NIPS method.	15
Figure 3.1	Schematic diagram of the membrane preparation process.	53
Figure 3.2	Concept of contact angle measurement of hydrophobic surface and hydrophilic surface.	55
Figure 3.3	Schematic diagram of the filtration experiment.	57
Figure 4.1a	Surface morphology of the top surface of membranes and Energy-dispersive X-ray spectroscopy data for the membrane samples M1-M3.	67
Figure 4.1b	Surface morphology of the top surface of membranes and Energy-dispersive X-ray spectroscopy data for the membrane samples M4 and M5.	68
Figure 4.2	Thermal gravimetric analysis of membranes.	70
Figure 4.3	XRD patterns of pure PVC membrane, pristine alumina particles and alumina composite membranes M1-M5.	71
Figure 4.4	Pure water fluxes and permeates flux for feed conditions 10mg/L, 20mg/L and 40 mg/L Humic acid solution.	78
Figure 4.5	Fouling ratio for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	79
Figure 4.6	Rejection for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	80

Figure 4.7	Flux Recovery for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	81
Figure 4.8	Relatives flux of the membranes for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	82
Figure 4.9	Intrinsic and total resistance to membranes for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	83
Figure 5.1a	Surface morphology of the top surface of membranes and Energy-dispersive X-ray spectroscopy data for the membrane samples M1-M3.	89
Figure 5.1b	Surface morphology of the top surface of membranes and Energy-dispersive X-ray spectroscopy data for the membrane samples M4 and M5.	89
Figure 5.2	Thermal gravimetric analysis of membranes.	90
Figure 5.3	XRD patterns of pure PVC membrane, pristine nano bentonite particles and bentonite composite membranes M1-M5.	92
Figure 5.4	Pure water fluxes and permeates flux for feed conditions 10mg/L, 20mg/L and 40 mg/L Humic acid solution.	95
Figure 5.5	Fouling ratio for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	96
Figure 5.6	Rejection for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	99
Figure 5.7	Flux Recovery for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	100
Figure 5.8	Relatives flux of the membranes for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	101
Figure 5.9	Intrinsic and total resistance to membranes for 10 mg/L, 20 mg/L and 40 mg/L Humic acid solution.	102