

List of Figure

Figure 1.1	(a) Trend of increase in world population from 2015 to 2020 and (b) increase in demand of energy from 2015 to 2020	2
Figure 1.2	Major sources of energy in (a) India and (b) World	3
Figure 1.3	Major constituents of biomass (a) cellulose (b) hemicellulose and (c) lignin	7
Figure 1.4	Effect of pretreatment on structure of biomass	12
Figure 1.5	Schematic for calculation of angle of repose	19
Figure 3.1	Schematic diagram of experimental set-up: 1-nitrogen cylinder, 2-mass flow controller, 3-temperature measuring unit, 4- split tube furnace (NSW-104) controller, 5-long tube fixed bed reactor, 6-K-type thermocouple, 7- split tube furnace (NSW-104), 8-condenser, 9-oil collector, 10- chiller (Eyela CA-1112CE), 11-gas collector, 12-biomass with ceramic wool bed (Singh et al., 2020b).	55
Figure 3.2	Variation of solid yield with temperature and residence time	64
Figure 3.3	Van Krevelen diagram for raw and torrefied biomass	68
Figure 3.4	Color appearance of raw and torrefied biomass	70
Figure 3.5	(a) Particle size distribution of raw and torrefied biomass (b) Cumulative mass distribution for raw and torrefied biomass	74
Figure 3.6	(a) Moisture sorption test of raw and torrefied biomass in open environment	75
Figure 3.6	(b) Moisture sorption test of raw and torrefied biomass using contact angle measurement	77
Figure 3.7	Thermogravimetric analysis of raw and torrefied biomass (a) TGA analysis (b) DTG analysis	81
Figure 3.8	FTIR analysis of raw and torrefied biomass	82
Figure 3.9	SEM and EDX images of raw and torrefied biomass: (a) and (b) DAN, (c) and (d) TAN220-40, (e) and (f) TAN250-40 and (g) and (h) TAN280-40	85
Figure 4.1	TGA analysis of DAN and torrefied biomass at different heating rate: (a) DAN (b) TAN-220 (c) TAN-250, and (d) TAN-280	102
Figure 4.2	DTG analysis of DAN and torrefied biomass at different heating rate: (a) DAN (b) TAN-220 (c) TAN-250, and (d) TAN-280	103
Figure 4.3	Kinetic plots for DAN using (a) KAS, (b) OWF, (c) Friedman, and (d) Starink models	106
Figure 4.4	Kinetic plots for TAN-220 using (a) KAS, (b) OWF, (c) Friedman, and (d) Starink models	107
Figure 4.5	Kinetic plots for TAN-250 using (a) KAS, (b) OWF, (c) Friedman, and (d) Starink models	108
Figure 4.6	Kinetic plots for TAN-280 using (a) KAS, (b) OWF, (c) Friedman, and (d) Starink models.	109

Figure 4.7	Variation of activation energy with conversion using different models: (a) DAN, (b) TAN-220 (c) TAN-250, and (d) TAN-280	110
Figure 4.8	Theoretical and experimental plots for prediction of solid state reaction mechanism using Criado method (Z-master plot): (a) DAN, (b) TAN-220 (c) TAN-250, and (d) TAN-280	113
Figure 5.1	Relationship between actual and predicted values of model (a) HHV and (b) EY	130
Figure 5.2	Three dimensional response surface and contour plots of HHV showing the effect of (a) and (b) temperature and retention time; (c) and (d) temperature and heating rate; (e) and (f) heating rate and retention time	135
Figure 5.3	Three dimensional response surface and contour plots of EY showing the effect of (a) and (b) temperature and retention time; (c) and (d) temperature and heating rate; (e) and (f) heating rate and retention time	138
Figure 5.4	Thermogravimetric analyses of DAN and TAN252-60-5 (a) TGA (b) DTG	145
Figure 5.5	FTIR spectra of DAN and TAN252-60-5	147
Figure 5.6	SEM and EDX images: (a) and (b) for DAN, (c) and (d) for TAN252-60-5	148
Figure 5.7	XRD spectra of DAN and TAN252-60-5	150
Figure 5.8	Moisture absorption characteristics of DAN and TAN252-60-5	152
Figure 6.1	Relationship between actual and predicted values of pyrolysis oil	165
Figure 6.2	Three dimensional response surface and contour plots of pyrolysis oil yield depicting the effect of (a) and (b) temperature and retention time, (c) and (d) temperature and heating rate, (e) and (f) temperature and sweeping gas flow rate, (g) and (h) retention time and heating rate, (i) and (j) retention time and sweeping gas flow rate, (k) and (l) heating rate and sweeping gas flow rate	171
Figure 6.3	FTIR spectra of pyrolysis oil from DAN and TAN-252-60-5 at optimum condition	176
Figure 6.4	GC-MS spectrum of pyrolysis oil from pyrolysis of DAN and TAN-252-60-5 at optimum condition (a) PO-DAN, (b) PO-TAN	180
Figure 6.5	The relative amount of different type of compound present in pyrolysis oil from DAN and TAN-252-60-5 obtained at optimum condition	181
Figure 6.6	¹³ C NMR spectrum of pyrolysis oil obtained at optimum condition (a) PO-DAN, (b) PO-TAN	183
Figure 6.7	The relative amount of different type of carbon present in pyrolysis oil obtained at optimum condition (a) PO-DAN, (b) PO-TAN	184
Figure 6.8	SEM-EDX analysis of biochar at optimum condition (a) Biochar-DAN (b) Biochar-TAN	189
Figure 6.9	FTIR spectra of biochar from DAN and TAN-252-60-5 at optimum condition of pyrolysis	191
Figure 6.10	Composition of pyrolytic gases from pyrolysis of DAN and TAN-252-60-5 at optimum condition	193
Figure 6.11	Proposed way to increase the sustainability of integrated torrefaction-pyrolysis process	196

Figure 6.12	Possible applications of pyrolysis oil from pyrolysis of TAN-252-60-5 (adapted from references (Bridgwater, 2012; Dhyani & Bhaskar, 2018))	197
Figure 7.1	Point of zero charge (pH_{pzc}) for Biochar-DAN and Biochar-TAN	207
Figure 7.2	XRD analysis of Biochar-DAN and Biochar-TAN	208
Figure 7.3	SEM-EDX analysis of Biochar-DAN before and after adsorption (a) Bare Biochar-DAN (b) MB loaded Biochar-DAN	210
Figure 7.4	SEM-EDX analysis of Biochar-TAN before and after adsorption (a) Bare Biochar-TAN (b) MB loaded Biochar-TAN	211
Figure 7.5	FTIR analysis of Biochar-DAN and Biochar-TAN before and after adsorption (a) Bare and MB loaded Biochar-DAN (b) Bare and MB loaded Biochar-TAN	213
Figure 7.6	Effect of operating parameters on uptake capacity of adsorption process using Biochar-TAN (a) effect of time and concentration (at fixed pH = 10, Temp = 298 K, adsorbent dose = 2 g/L) (b) effect of pH and dose (at fixed Temp = 298 K, MB concentration = 50 mg/L, time = 200 min) (c) effect of temperature and concentration (at fixed pH = 10, adsorbent dose = 2 g/L, time = 200 min)	217
Figure 7.7	Effect of operating parameters on uptake capacity of adsorption process using Biochar-DAN (a) effect of time and concentration (at fixed pH = 10, Temp = 298 K, adsorbent dose = 2 g/L) (b) effect of pH and dose (at fixed Temp = 298 K, MB concentration = 50 mg/L, time = 200 min) (c) effect of temperature and concentration (at fixed pH = 10, adsorbent dose = 2 g/L, time = 200 min)	218
Figure 7.8	Kinetic model for adsorption of MB dye on Biochar-TAN (a) pseudo-first-order (b) pseudo-second-order and (c) Elovich	224
Figure 7.9	Kinetic model for adsorption of MB dye on Biochar-DAN (a) pseudo-first order (b) pseudo-second-order and (c) Elovich	225
Figure 7.10	Mass transfer model for adsorption of MB dye on Biochar-TAN (a) Weber and Morris model (b) Boyd model	230
Figure 7.11	Mass transfer model for adsorption of MB dye on Biochar-TAN (a) Weber and Morris model (b) Boyd model	231
Figure 7.12	Adsorption isotherms for adsorption of MB dye on Biochar-TAN (a) Langmuir isotherm (b) Freundlich isotherm (c) Tempkin isotherm (d) Sips isotherm	234
Figure 7.13	Adsorption isotherms for adsorption of MB dye on Biochar-DAN (a) Langmuir isotherm (b) Freundlich isotherm (c) Tempkin isotherm (d) Sips isotherm	235
Figure 7.14	van't Hoff plot (a) Biochar-TAN (b) Biochar-DAN	238
Figure 7.15	Possible mechanisms for adsorption of MB onto biochar	241