List of Tables

Table 1.1	Constituents of selected biomass (wt% composition)	4
Table 1.2	Demerits of raw biomass	11
Table 2.1	Effect of torrefaction on proximate and ultimate analysis of biomass	24
Table 2.2	Effect of torrefaction on mass yield, energy yield and higher heating value of biomass	29
Table 2.3	Optimization of process parameters for torrefaction of different biomass	35
Table 2.4	Optimization of process parameters for pyrolysis of different biomass	38
Table 2.5	Effect of torrefaction on quality of bio-oil obtained from pyrolysis of torrefied biomass	43
Table 2.6	Application of biochar from pyrolysis raw biomass towards aqueous methylene blue removal	46
Table 3.1	List of controlled and measured variable during experiment	55
Table 3.2	Specifications/detail of instruments/variables used in experimental setup and procedure	56
Table 3.3	Different ASTM standards used to calculate engineering properties of torrefied biomass	58
Table 3.4	Proximate and ultimate analysis of raw and torrefied biomass	66
Table 3.5	ICP-MS analysis of raw and torrefied biomass	69
Table 3.6	Fuel and flow properties, different types of densities of raw and torrefied biomass	71
Table 3.7	Characteristic flow properties of biomass (Lumay et al., 2012; Szalay et al., 2015)	78
Table 4.1	Models of pyrolysis reaction with different values of $f(\alpha)$ and g (α)	96
Table 4.2	Fiber analysis of DAN and torrefied biomass and solid yield during torrefaction	99
Table 4.3	The activation energy of DAN and torrefied biomass at different level of conversion using KAS, OWF, Friedman and Starink methods	111
Table 4.4	Predicted models for DAN and torrefied biomass (TAN-220, TAN-250, and TAN-280)	115
Table 4.5	Thermodynamic parameters for pyrolysis of DAN and torrefied biomass at a heating rate of 10 K/min	119
Table 5.1	Experimental design matrix and actual, predicted and residual value of responses obtained using RSM	127
Table 5.2	ANOVA for quadratic model of response**:** HHV and EY	132
Table 5.3	Experimental and predicted values of responses at optimum condition	139
Table 5.4	Characteristics of DAN and TAN252-60-5	141
Table 5.5	Crystalline parameters of DAN and TAN252-60-5	150

Table 6.1	Coded levels of experimental variables used in CCD method	158
Table 6.2	Experimental design matrix, actual and predicted value of responses	159
Table 6.3	ANOVA of quadratic model for pyrolysis oil response and corresponding model terms	168
Table 6.4	Independent variables and response as constraints for optimization	173
Table 6.5	Experimental and predicted values of pyrolysis oil yield at optimum condition	173
Table 6.6	The average **y**ield of pyrolysis oil, pyrolytic gases and biochar at optimum condition from pyrolysis of DAN and TAN-252-60-5	174
Table 6.7	Chemical composition of pyrolysis oil identified by GC-MS analysis at optimum condition of pyrolysis of DAN and TAN-252-60-5	177
Table 6.8	Physicochemical properties of pyrolysis oil (PO-DAN and PO-TAN) at optimum condition and comparison with ASTM grade oil and mineral oils (Dhyani & Bhaskar, 2018; Oasmaa et al., 2009)	186
Table 6.9	Characteristics of biochar obtained at optimum condition from pyrolysis of DAN and TAN-252-60-5	188
Table 7.1	Specification of various analytical instruments used for characterization of biochar and batch adsorption process	204
Table 7.2	Different experimental conditions and their ranges studied during batch adsorption of MB dye	206
Table 7.3	BET surface area analysis of Biochar-DAN and Biochar-TAN	209
Table 7.4	Functional groups detected in Biochar-DAN and Biochar-TAN before and after adsorption of MB dye	215
Table 7.5	Adsorption kinetics and related parameters for adsorption of MB dye onto Biochar-DAN and Biochar-TAN	226
Table 7.6	Mass transfer models and related parameters for adsorption of MB dye onto Biochar-DAN and Biochar-TAN	228
Table 7.7	Linear and non-linear forms of isotherms	233
Table 7.8	Isotherm and related parameters for adsorption of MB dye onto Biochar-DAN and Biochar-TAN	236
Table 7.9	Thermodynamic parameters for adsorption of MB dye onto Biochar-DAN and Biochar-TAN	239