

LIST OF FIGURES

Figure No.	Figure description	Page No.
Figure 1.1	Inverse-time overcurrent relay's characteristics curve.	6
Figure 1.2	Different Protection issues with DGs.	12
Figure 2.1	Test Distribution system	40
Figure 2.2	Comparison between Tr_{sum} obtained by the proposed CRRC and the Conv. for far-end faults for all 7 possible operating modes in Case-1 in Meshed configuration	48
Figure 2.3	Comparison between the Tr_{sum_allM} obtained by the proposed CRRC and the Conv. in Case-2 in Meshed Configuration	48
Figure 2.4	Overall Percentage Reduction in the constraints and convergence time with respect to the Conv in Case-2	49
Figure 2.5	Flowchart for the proposed CRRC method	53
Figure 3.1	Comparison of relays operating times (Tr) obtained using PMS_{old} and $HPMS$ for the Fault case (LLG fault with $R_f=4.3$ at z_4) in Meshed Grid-connected operating mode with syn_DGs	65
Figure 3.2	Flowchart for the proposed Hybrid_algo	70
Figure 4.1	Generation of the FDb for a sample radial-meshed network	74
Figure 4.2	Generation of RDb: a) When, fault current's direction is the same of the direction of FDb (b) When, fault current's direction is opposite of the direction of FDb	74
Figure 4.3	A typical feeder network of a z^{th} zone	76
Figure 4.4	Example: A region for protecting three zones upto B1 hierarchy level	78
Figure 4.5	Proposed DFZD_algo algorithm	81
Figure 4.6	Detection of FSz for Case 1 to Case4	82
Figure 4.7	Detection of FSz for Case 5 and Case6	84
Figure 4.8	Detection of FSz for Case 5 and Case-6	85
Figure 4.9	Detection of FSz for Case 7	85

Figure 4.10	Detection of FSz in a typical network when all DGs are connected	89
Figure 4.11	Detection of FSz in a typical network when DG_B is disconnected.	89
Figure 4.12	Matlab coding results for Case-5	92
Figure 4.13	Matlab coding results for Case-6	93
Figure 4.14	Matlab coding results for Case-7	94
Figure 4.15	Matlab coding results for Case-8	94
Figure 5.1	Pre-determined RHs for variable operating mode	98
Figure 5.2	A sample network	100
Figure 5.3	Proposed RHs-algo algorithm	102
Figure 5.4	Stages of determining RHs for z1's d-side relays using RHs-algo	104
Figure 5.5	Comparative Reduction by RHs_prop in relays operating times in different FRC conditions in Meshed Grid-connected operating mode	110
Figure 5.6	Comparative Reduction by RHs_prop in relays operating times in different FRC conditions in Islanding op_mode for LLG fault ($R_f=15$) at z29	110
Figure 5.7	A sample radial feeder network	113
Figure 6.1	A sample feeder network of z th zone	118
Figure 6.2	Block Diagram of the CAPS	123
Figure 6.3	Workflow of the CAPS-1	122
Figure 6.4	Transfer data from relays to RCU in Stage-2	120
Figure 6.5	Workflow of the CAPS-2	144
Figure 6.6(a)	Reduction by CAPS-1 in total fault clearing time (Tot_FCT) in different stages (as described in Table 6.25).	154
Figure 6.6(b)	Reduction by CAPS-2 in total fault clearing time (Tot_FCT) in different stages (as described in Table 6.26).	154