

LIST OF TABLES

Table No.	Table description	Page No.
Table 1.1	Constant and exponent for various relay characteristic from IEEE standards C37.112	07
Table 2.1	Operating modes Possible with three DGs With Fixed Sizes	34
Table 2.2	Operating modes Possible with three DGs With Variable Sizes	33
Table 2.3	Operating modes Possible with DG-3, 4, and 5 With Fixed Sizes	42
Table 2.4	Relays TMS Obtained for Case-1: With particular size and location of DGs	42
Table 2.5	Comparative Performance of the CRRC Method for Faulted z-32 zone In Different Operating Modes (Case-1)	44
Table 2.6	Comparative performance of the CRRC method for faulted z-31 zone in different operating modes (Case-1)	45
Table 2.7	Overall Comparison Results for Case-1	46
Table 2.8	Performance of The CRRC In Case-2	46
Table 2.9	Obtained Relays Operating Times Using CRRC Method for Intermediate Operating modes With Variable DG-Size (Case-3)	49
Table 2.10	Overall Comparison of Table 2.8 Results for Scenario-2	50
Table 2.11	Impact of Increasing Proliferation of DGs on total Number of Operating Modes	51
Table 3.1	Comparative performance of HPMS for meshed grid-connected mode with synchronous-DGS	61
Table 3.2	Comparative performance of HPMS for in Meshed Islanding-Mode with IBDGs	62
Table 3.3	Online Conventional PMS and Hybrid PMS for the relays shown in Table 3.1and Table 3.2	63

Table 3.4	Total Sum of Operating Times of Relays In various Fault cases in Grid-connected Mode	63
Table 3.5	Total Sum of Operating Times of Relays In various Fault cases in Islanding Mode with IBDGs Interconnections	66
Table 3.6	Q Weightages of the parameters Experienced by relay R25u When the Faulted Zone is z4 in the operating mode (Grid connected, radial, Syn-DGs)	67
Table 3.7	Q Weightages of the parameters Experienced by relay R29u When the Faulted Zone is z29 in the Operating Mode (Island, Mesh, IBDGs)	68
Table 4.1	FSz detection by the existing FZD method in possible normal and abnormal situations	77
Table 4.2	Possible combinations of the RDb of an end-relay with respect to the RDb of near and far relays located at kth adjacent zone	80
Table 4.3	Conversion Table	86
Table 4.4	FSz and FRC Determiner Table	87
Table 4.5	Output of the DFZD method and Running time for different cases	90
Table 5.1	Outputs of RHs-algo	100
Table 5.2	Comparative performance of RHs_algo in Meshed Islanding-Mode with IBDGs (With PMSold)	105
Table 5.3	Comparative performance of RHs_algo in Meshed Grid-connected Mode with Synchronous-DGs (With HPMS)	106
Table 5.4	Total Sum of Operating Times of Relays In various Fault cases in Grid-connected Mode (with HPMS)	107
Table 5.5	Total Sum of Operating Times of Relays In various Fault cases in Islanding Mode with IBDGs Interconnections (with HPMS)	107
Table 5.6	Advantages by adapting the relays hierarchies considering the FRC events	109
Table 5.7	Enhanced protection in the presence of only z3 feeder zone with BBT (i.e. 1 BBT) while all other zones with UBT.	112

Table 5.8	Enhanced protection in the presence of all BBT compared to 1 BBT with both PMSold and HPMS	112
Table 5.9	Contingency analysis with BBT and UBT for Case-1	113
Table 5.10	Contingency analysis with BBT and UBT for Case-2	114
Table 6.1	Different Online and Offline Parameters	118
Table 6.2	CAPS-1 at Stage 1	118
Table 6.3	CAPS-1 at Stage 2	120
Table 6.4	CAPS-1 at Stage 3	120
Table 6.5	Comparative Performance of CAPS-1 in Meshed Grid-connected Mode with Synchronous-DGs	124
Table 6.6	Comparative performance of caps-1 in meshed islanding-mode with IBDGS	124
Table 6.7	Total Sum of Operating Times of Relays (in s) In various Fault cases in Grid-connected Mode	126
Table 6.8	Total Sum of Operating Times of Relays (in s) In various Fault cases in Islanding Mode with IBDGs Interconnections	126
Table 6.9	Performance Results for NDG =2 In Case-B	132
Table 6.10	Selection of operating modes by SCRRC Method (With Info-1) For Case-a with variable DGs sizes	135
Table 6.11	Selection of operating modes by the SCRRC Method (With Info-2) For Case-a with variable DGs sizes	135
Table 6.12	Total Operating modes Selected by Different Methods	137
Table 6.13	Operating Modes Possible With 4 DGs	139
Table 6.14	Comparative Performance Results of SCRRC For Scenario-1, Case-1: {NDG=3 (DG2,3,4), NDG _{max} =4 (DG1,2,3,4), Fault-event(A)}	140

Table 6.15	Comparative Performance Results of SCRRC For Scenario-1 Case-2: {NDG=2 (DG1,2), NDG _{max} =4 (DG1,2,3,4), Fault-event(A)}	141
Table 6.16	Some Operating Modes for Variable Size DGs In Case-3	141
Table 6.17	Comparative Performance Results of SCRRC For Scenario-2 Case-3: {NDG =2 (DG1,2), NDG _{max} =3, (DG1,2, 3)}	142
Table 6.18	Online Modification in offline RDb bits	146
Table 6.19	Comparative Performance of CAPS-2 in Case-A1	148
Table 6.20	Comparative Performance of CAPS-2 in Case-A2	148
Table 6.21	Cumulative Performance of The Proposed Algorithms in CAPS-1 When only number of DGs is variable (Case-A1)	150
Table 6.22	Cumulative Performance of The Proposed Algorithms in CAPS-1 When both number and sizes of DGs are variable (Case-A2)	151
Table 6.23	Cumulative Performance of The Proposed Algorithms in CAPS-2 When only number of DGs is variable (Case-A1)	152
Table 6.24	Cumulative Performance of The Proposed Algorithms in CAPS-2 When only number of DGs is variable (Case-A2)	153
Table 6.25	Description of Stages shown in Figure 6.6(a)	154
Table 6.26	Description of Stages shown in Figure 6.6(b)	154