

Contents

| | |
|--|-------------|
| Abstract | v |
| List of Figures | xiii |
| List of Tables | xvii |
| Nomenclature | xix |
| 1 Introduction | 1 |
| 1.1 Background | 1 |
| 1.2 Research motivation and Problem Statement | 6 |
| 1.3 Literature survey | 8 |
| 1.3.1 Distribution Network Reconfiguration and Service Restoration . . . | 8 |
| 1.3.2 Volt-VAR Control and Conservation Voltage Reduction | 13 |
| 1.3.3 Distributed Energy Resources allocation | 16 |
| 1.4 Research objectives | 20 |
| 1.5 Organization of the thesis | 20 |
| 2 Combined Impact of Network Reconfiguration and Volt-VAR Control Devices on Energy Savings in Presence of Distributed Generation | 23 |
| 2.1 Introduction | 23 |
| 2.2 Functional smart Distribution Network | 24 |
| 2.3 Problem formulation | 25 |
| 2.3.1 Objective function | 26 |
| 2.3.2 Load model | 27 |
| 2.4 Solution approach | 28 |
| 2.4.1 Overview of GWO algorithm | 28 |

| | | |
|----------|---|-----------|
| 2.4.2 | Modified Binary Grey wolf optimization (MBGWO) | 29 |
| 2.4.3 | Implementation of MBGWO algorithm on reduction of energy demand | 33 |
| 2.4.4 | Implementation of MBGWO algorithm for service restoration . . . | 34 |
| 2.4.5 | Implementation of MBGWO algorithm under sudden variation of generation/load | 35 |
| 2.5 | Simulation results and discussions | 35 |
| 2.5.1 | Test systems description | 37 |
| 2.5.2 | Validation of centralized control using proposed MBGWO algorithm for energy demand reduction | 40 |
| 2.5.3 | Effect of different load models under different scenarios | 48 |
| 2.5.4 | Service restoration considering voltage regulation and peak demand reduction | 51 |
| 2.5.5 | Performance of proposed algorithm with association of PVSI droop control considering cloudy condition | 54 |
| 2.6 | Conclusion | 56 |
| 3 | Minimization of Operational Cost in Active Distribution System considering Network Reconfiguration and Soft Open Point | 57 |
| 3.1 | Introduction | 57 |
| 3.2 | Modelling of Soft Open Points (SOP) | 58 |
| 3.3 | Problem formulation | 60 |
| 3.3.1 | Objective function | 60 |
| 3.3.2 | System operational constraints | 61 |
| 3.4 | Implementation of proposed modified binary GWO (MBGWO) | 62 |
| 3.5 | Simulation results and discussions | 62 |
| 3.5.1 | Modified 69 bus system | 62 |
| 3.5.2 | Impact of soft open point | 69 |
| 3.5.3 | Comparative analysis of different cases: | 74 |
| 3.5.4 | Performance of modified grey wolf optimization (MBGWO) | 78 |
| 3.5.5 | Cost benefit analysis of SOP | 80 |
| 3.5.6 | Impact of high penetrated photovoltaic (PV)-based distributed generation | 81 |

| | |
|--|------------|
| 3.6 Conclusion | 85 |
| 4 Optimal Coordination of PV smart inverter and traditional Volt-VAR control devices for energy cost savings and voltage regulation | 87 |
| 4.1 Introduction | 87 |
| 4.2 Proposed hierarchical coordinated VVO methodology | 88 |
| 4.3 Problem formulation | 89 |
| 4.3.1 Objective functions | 90 |
| 4.3.2 Operational and system constraints | 91 |
| 4.3.3 Voltage dependent Load models (VDLM) | 92 |
| 4.3.4 Conservation voltage reduction (CVR) | 93 |
| 4.4 Implementation of proposed hierarchical coordinated control scheme | 93 |
| 4.4.1 Centralised control algorithm | 95 |
| 4.4.2 Local control algorithm | 96 |
| 4.5 Simulation Results and Discussions | 98 |
| 4.5.1 Performance of centralised control algorithm considering multi objective | 100 |
| 4.5.2 Performance of local control algorithm considering cloudy condition | 113 |
| 4.5.3 Impact of forecast error | 116 |
| 4.6 Conclusion | 118 |
| 5 Real-time Validation of a Hierarchical Coordinated Voltage Control Approach in high PV Penetrated Distribution System | 121 |
| 5.1 Introduction | 121 |
| 5.2 Proposed Hierarchical Coordinated Voltage Control Approach | 122 |
| 5.3 Problem formulation | 123 |
| 5.4 Implementation of Proposed Hierarchical Coordinated Voltage Control Approach in Real-Time | 125 |
| 5.5 Simulation results and discussions | 126 |
| 5.5.1 Modified 33 bus system | 127 |
| 5.5.2 centralised control stage | 127 |
| 5.5.3 Real time co-simulation platform | 132 |
| 5.6 Conclusion | 135 |

| | |
|--|------------|
| 6 Coordinated Planning and Scheduling of DER and SOP in Active Distribution Network | 139 |
| 6.1 Introduction | 139 |
| 6.2 Framework of Proposed Two-Layer coordinated optimization model | 140 |
| 6.2.1 Stochastic Variable Module (SVM) for uncertainties | 141 |
| 6.2.2 Voltage dependant loads | 143 |
| 6.3 Proposed Problem formulation | 143 |
| 6.3.1 objective function | 143 |
| 6.3.2 constraints | 145 |
| 6.3.3 Implementation of proposed solution methodology | 146 |
| 6.4 Simulation results and discussions | 148 |
| 6.4.1 Simulation platform | 148 |
| 6.4.2 Data and assumptions | 148 |
| 6.4.3 Discussions on numerical results | 149 |
| 6.4.4 Effect of voltage profile | 153 |
| 6.4.5 Effect of energy losses and consumption | 156 |
| 6.4.6 Effect of energy not served and carbon emissions | 156 |
| 6.4.7 Performance of proposed hybrid optimization solver | 157 |
| 6.5 Conclusion | 159 |
| 7 Conclusions and Future Scope | 161 |
| 7.1 Conclusions | 161 |
| 7.2 Salient benefits of proposed methodologies | 162 |
| 7.3 Future Scope | 163 |
| A Parameters | 165 |
| A.1 The PSO, MBGWO algorithm parameters and PVSI droop parameters | 165 |
| A.2 PVSI droop parameters and battery energy storage parameters | 165 |
| B List of Publications | 167 |
| B.1 Journal papers | 167 |
| B.2 Conference papers | 168 |