

List of Tables

1.1	Energy consumption worldwide in 2018	2
1.2	Network reconfiguration solution technique and its objective	11
1.3	Summary of DER planning studies	19
2.1	Test system information	39
2.2	Four scenarios	39
2.3	Simulation results of TS-1 and TS-2 under TVVC and four Scenarios	41
2.4	optimal opened RCS of TS-1 and TS-2 under Scenario 3 and Scenario 4	41
2.5	Performance of various algorithms for Scenario 4 at peak loading hour for TS-1 and TS-2	45
2.6	Performance of MBGWO and DICOPT for Scenario 4 at peak loading hour for TS-1 and TS-2	46
2.7	Simulation results of unbalanced 33 bus distribution system under TVVC and four Scenarios	48
2.8	simulations results of TS-1 and TS-2 under multiple line faults at peak demand	53
2.9	PV output during clear sky, partly and fully cloud day condition	54
2.10	Status of VVC devices, DNR and PVSİ reactive power using proposed algorithm during 13:00 to 14:00 hours	54
2.11	Summary of results during clear sky, partly and full cloudy condition for TS-1	55
2.12	Summary of results during clear sky, partly and full cloudy condition for TS-2	56
3.1	value of k_p and k_q and their location	63

3.2	cost parameters	64
3.3	summary of results under different cases	66
3.4	status of RCS, OLTC and SCBs under case 2 to case 4	68
3.5	status of RCS, OLTC and SCBs under case 6 and case 7	73
3.6	Results of CGWO and proposed MBGWO	79
3.7	Results of cost benefit analysis of SOP	81
3.8	Cost benefit analysis in presence of high penetration of DG	83
4.1	modified 33 bus distribution system information	99
4.2	value of k_p and k_q and their location	99
4.3	Cases studied	100
4.4	Set of non-inferior solutions of the objectives OF1 and OF2 under case 2 and case3	102
4.5	set of non-inferior solutions of the objectives OF1 and OF2 under case 4 and case 5	106
4.6	Results of three different cases of 33 bus system	106
4.7	load and PV output during clear sky, partly and fully cloud day condition	114
4.8	optimal setting of control devices using centralised control algorithm	115
5.1	simulation results under different scenarios	129
5.2	opened RCS under scenario 1 and 5	131
5.3	optimal scheduling of control devices obtained by centralised control stage at 14:00 hour	133
6.1	Different cases studied	150
6.2	Results of different cases over planning horizon	151
6.3	Percentage power share between RES and grid in different cases	151
6.4	Optimal location and size of DER and SOP for different cases at initial year	152
6.5	Optimal location and size of DER and SOP for different cases at initial year	153
6.6	Optimal capacities of DER and SOP for different cases in each year	154
6.7	optimal opened RCS* of case C and case E in each year	155
6.8	Performance of proposed hybrid solver and CGWO for case E	159