

2.3.3	Route Maintenance Process	79
2.3.4	Management of Routing Table	81
2.3.5	Management of Local Connectivity	81
2.3.6	Advantages and Disadvantages	82
2.4	Route Maintenance/Configuration Parameters	83
2.5	Active_Route_Timeout (ART)	86
2.5.1	Impact of ART on Connectivity	87
2.6	Delete_Period_Constant (DPC)	88
2.7	Determining Factors	88
2.7.1	Mobility of Node	89
2.7.2	Transmission Range of Node	90
2.7.3	Network Load Density (NLD)	90
2.7.4	ANs/SD Pair	91
Chapter 3: ART & DPC on the Performance of AODV Routing for CBR Traffic Generator by using NS-3 & QUALNET		93-127
3.1	Introduction and Objective	93
3.2	AODV Performance Observation for Constant Scenario by using NS-3	93
3.2.1	Simulation Overview	94
3.2.2	Simulation Environment	95
3.2.2.1	Scenario	95
3.2.2.2	Node Characteristics	96
3.2.3	Simulation Results	97
3.2.3.1	Graphical Analysis of Net Throughput	99
3.2.3.2	Graphical Analysis of PDR	101
3.2.3.3	Analysis of Net Throughput and PDR for each ART	104
3.3	Conclusion	107
3.4	AODV Performance Observation for Different SD Pair by using QUALNET	108
3.4.1	Simulation Environment	108
3.4.2	Simulation Results	110
3.4.2.1	Graphical Analysis of Throughput	114
3.4.2.2	Graphical Analysis of Average End-to-End Delay	116
3.4.2.3	Graphical Analysis of Average Jitter	117
3.4.2.4	Graphical Analysis of Percentage (%) of Loss/Drop Packet	119
3.4.2.5	Analysis of QoS Metrics for each ART	120
3.5	Conclusion	126

Chapter 4: In AODV Routing: Comparative Studies for CBR & VBR Traffic under the Influence of Route Maintenance Parameters	129-148
4.1 Introduction	129
4.2 Simulation Objective and Overview	130
4.3 Simulation Environment	132
4.4 Simulation Results	133
4.4.1 Analysis for variable ART at fixed “NLD & SD Pair”	135
4.4.1.1 Graphical Analysis of Throughput for CBR & VBR Traffic	136
4.4.1.2 Graphical Analysis of Average End-to-End Delay for CBR & VBR Traffic	138
4.4.1.3 Graphical Analysis of Average Jitter for CBR & VBR Traffic	140
4.4.2 Analysis for variable SD Pair at fixed “NLD & ART”	142
4.4.2.1 Graphical Analysis of Throughput for CBR & VBR Traffic	143
4.4.2.2 Graphical Analysis of Average End-to-End Delay for CBR & VBR Traffic	144
4.4.2.3 Graphical Analysis of Average Jitter for CBR & VBR Traffic	145
4.5 Conclusion	146
Chapter 5: In AODV Routing: Determining Factors along with the Route Maintenance Parameters	149-171
5.1 Introduction	149
5.2 Simulation Objective	151
5.3 Scenario Overview	151
5.4 Simulation Outline	153
5.4.1 Simulation Parameters	153
5.5 Analysis of Simulation Scenarios and Results	155
5.5.1 Simulation Scenario-1	155
5.5.1.1 Results Discussion: Case-1 of Scenario-1	156
5.5.1.2 Results Discussion: Case-2 of Scenario-1	160
5.5.2 Simulation Scenario-2	162
5.5.2.1 Results Discussion: Case-1 of Scenario-2	163
5.5.2.2 Results Discussion: Case-2 of Scenario-2	167
5.6 Conclusion	169

Chapter 6: Comparative Performance Analysis of Various Routing Protocols under Varying Pause Time Environment	173-185
6.1 Introduction	173
6.2 Objective of Study	174
6.3 Overview of Routing Protocols for Current Analysis and Evaluation	175
6.3.1 Ad-hoc On-demand Distance Vector (AODV)	175
6.3.2 Dynamic Source Routing (DSR)	175
6.3.3 Dynamic MANET On-demand (DYMO)	175
6.3.4 Intrazone Routing Protocol (IARP)	175
6.3.5 Inter Zone Routing Protocol (IERP)	176
6.4 Scenario Overview	176
6.5 Simulation Parameters for Scenario Creation	177
6.6 Graphical Representation of QoS Metrics, and Discussion of Results	178
6.6.1 Graphical Representation of Throughput	178
6.6.2 Graphical Representation of End-to-End Delay	180
6.6.3 Graphical Representation of Jitter	180
6.6.4 Graphical Representation of Packet Delivery Ratio (PDR)	181
6.6.5 Results Discussion of QoS Metrics	182
6.7 Conclusion	184
 Chapter 7: Summary and Conclusions	 187-201
7.1 Scope for Further Studies	200
 References	 203-213
 List of Publications	 215-217
 International Research Fellowship & Short Term Courses	 219