List of figures

Reach of renewable-based power from 2007 to 2016 [6]	4
Growth in the capacity of different renewable-based off-grid systems [6].	4
Applications of different types of wind turbine.	8
Block diagram Representation of a rooftop wind energy conversion system.	9
Block diagram representation of squirrel cage induction generator con-	
nected to the grid through an anti-parallel thyristor-based soft-starter	13
Wound rotor induction generator with extra resistance in the rotor circuit	
to control the speed of the generator.	14
Block diagram representation of a self-excited squirrel-cage induction	
generator	14
Block diagram representation of a doubly-fed induction generator con-	
nected to the grid	15
Permanent magnet synchronous generator-based wind energy conversion	
system with gearboxes	16
Permanent magnet synchronous generator-based wind energy conversion	
system without gearboxes.	17
Axial-flux permanent magnet generator topologies [50]	19
Stator laminations of an Axial-flux permanent magnet generator	21
Axial-flux permanent magnet generator with segmented stator [53]	21
	Reach of renewable-based power from 2007 to 2016 [6].Growth in the capacity of different renewable-based off-grid systems [6].Applications of different types of wind turbine.Block diagram Representation of a rooftop wind energy conversion system.Block diagram representation of squirrel cage induction generator connected to the grid through an anti-parallel thyristor-based soft-starter.Wound rotor induction generator with extra resistance in the rotor circuitto control the speed of the generator.Block diagram representation of a self-excited squirrel-cage inductiongenerator.Block diagram representation of a doubly-fed induction generator connected to the grid.Permanent magnet synchronous generator-based wind energy conversionsystem with gearboxes.Permanent magnet synchronous generator-based wind energy conversionsystem without gearboxes.Axial-flux permanent magnet generator topologies [50].Axial-flux permanent magnet generator with segmented stator [53].

1.14	Magnetic gear, as proposed by Atallah et al. [55]	22
1.15	Permanent magnet synchronous generator integrated to Grid through a	
	two-level back-to-back power converter.	26
1.16	Three-level neutral-point diode clamped (NPC) back-to-back power con-	
	verter	28
1.17	Single-phase equivalent circuit diagram of three-level H-bridge (HB) back-	
	to-back power converter.	29
1.18	Single-phase equivalent circuit diagram of Five-level H-bridge back-to-	
	back power converter.	30
1.19	Two-level back-to-back H-bridge multicell converter connected in parallel	
	and series.	31
1.20	Two-level back-to-back H-bridge multicell converter connected in series	
	at generator end and parallel at grid end	31
1.21	A transformer less topology using two-level back-to-back H-bridge con-	
	verter and multi-winding generator topology with open windings	32
2.1	Use of eddy current brakes to ristrict the overspeed of generator	36
2.2	Topological variations in electrically-excited variable flux permanent mag-	
	net machine	38
2.3	A Doubly Excited Synchronous Machine with permanent magnets and DC	
	field coils on the rotor [90]	40
2.4	Hybrid stepper motor with series flux weakening without risking perma-	
	nent magnets	40
2.5	A Schematic diagram of the Consequent pole PM machine	41
2.6	A 2-D diagram of imbricated hybrid synchronous machine	42
2.7	Effect of shift of rotors with respect to other rotor in a dual-rotor topology.	45
2.8	A 2-D diagram of a dual-rotor sandwitched split-stator axial-flux PMSG.	46

2.9	A 2-D diagram of a switched-flux permanent magnet generator [128]	47
2.10	2-D diagrams of mechanically switched-flux PM machine with different	
	field-weakening position [129]	48
2.11	2-D diagram of the rotor cross-section of an inserted PM on rotor type	
	PMSG topology showing adjustable iron bar for field-weakening in the	
	same [130]	48
2.12	2-D diagram of the rotor cross-section of an inserted PM on rotor type	
	PMSG topology showing adjustable weakening permanent magnets for	
	field-weakening in the same [131]	48
3.1	Pancake-shaped stator cores of topology T2 and T3	53
3.2	Stators with tooth windings in topology T1	56
3.3	Slot-vector diagram of 12 slots, 2 phase, 6 pole concentrated tooth winding.	56
3.4	Winding layout of 12 slots, 2 phase, 6 poles, double layer concentrated	
	tooth winding	57
3.5	Stators with distributed windings in topology T2	59
3.6	Stators with distributed windings in topology T3	59
3.7	Slot-vector diagram of 18 slots, 3 phase, 4 poles, double layer distributed	
	winding	60
3.8	Winding layout of 18 slots, 3 phase, 4 poles, double layer distributed	
	winding	61
3.9	Interconnections of Stationary Stator and Rotatable Stator windings	62
3.10	Phasor diagrams of Stationary Stator and Rotatable Stator windings	62
3.11	Plot of variation in generator output voltage (rms) as per stator displace-	
	ment angle.	63
3.12	Variations in Generator phase voltage (rms) against stator displacement	
	angle (mechanical degree) for a six pole generator at 1000 rpm rotor speed.	63

3.13	Flux path in the top-view of the DSAF PMSG	64
3.14	Rotor fitted on the shaft through flange support and magnets pasted on	
	both sides of the rotor surface.	65
3.15	Variations in Generator phase voltage against stator displacement angle	
	(Stator bolted to a potting arrangement)	66
3.16	Stator-potting arrangement resting on the stepping on the shaft through	
	ball-bearing	66
3.17	Assembly of the dual-stator axial-flux permanent magnet synchronous	
	generator with provision of displacing one of the stator with respect to the	
	other stator.	68
4.1	Proposed rooftop wind energy conversion system with voltage regulation	
	achieved via the mechanical field weakening method	70
4.2	Simulated plot of turbine power vs rotor speed at different wind speed	73
4.3	Simulated plot of power coefficient vs $\boldsymbol{\lambda}$ for the wind turbine emulator	73
4.4	Wind turbine characteristic and DC-motor characteristics at different chop-	
	per duty ratio	74
4.5	Control circuit diagram of wind turbine emulator	75
4.6	DC chopper circuit diagram.	76
4.7	DC motor armature current response during step change of wind velocity.	76
4.8	Rotor speed response during step change of wind velocity	77
4.9	Wind turbine emulator performance	77
5.1	Control circuit diagram of the proposed DC-link voltage controller	82
5.2	Simplified mathematical model of stepper motor.	84
5.3	Simplified control circuit diagram of the Proposed system.	87
5.4	Final control circuit diagram of proposed controller.	87

6.1	Output no-load voltage waveform of Topology T1 at different stator dis-
	placement angles
6.2	Output no-load voltage waveform of Topology T2 at different stator dis-
	placement angles
6.3	Output no-load voltage waveform of Topology T3 at different stator dis-
	placement angles
6.4	Output no-load voltage waveform of Topology T4 at different stator dis-
	placement angles
6.5	Variations in Line voltage for trapezoidal, high peak sinusoidal, and near-
	to-sinusoidal back EMF characteristics as per angular shift of stator in
	electrical degree
6.6	Magnitude of different order of harmonics present in line voltage of differ-
	ent generator topologies upon increase in stator displacement angle 99
6.7	THD content in line voltage of different generator topologies upon increase
	in stator displacement angle
6.8	FFT analysis of generator current profile of Topology T3 at $SDA = 115^{\circ}$. 101
6.9	Effect of mechanical field weakening in topology T3 at load at $SDA = 0^{\circ}$. 102
6.10	Effect of mechanical field weakening in topology T3 at load at $SDA = 75^{\circ}$. 103
6.11	Effect of mechanical field weakening in topology T3 at load at $SDA = 115^{\circ}.104$
6.12	Effect of mechanical field weakening in topology T2 at load at $SDA = 0^{\circ}$. 105
6.13	Effect of mechanical field weakening in topology T2 at load at $SDA = 75^{\circ}$. 106
6.14	Effect of mechanical field weakening in topology T2 at load at $SDA = 115^{\circ}.107$
6.15	Experimental results on proposed system under variable wind and supply-
	ing constant load
6.16	Experimental results on proposed system under constant wind and supply-
	ing variable load

6.17	Schematic diagram showing the effect of grid-fault on the system	115
6.18	V_{dc} voltage dynamics at fault	119
7.1	Block diagram representation of proposed hybrid solar wind system	125
7.2	Block diagram model of proposed rooftop hybrid solar wind system in	
	wind supportive mode.	125
7.3	A typical wind profile during experimentation	128
7.4	Performance evaluation of proposed hybrid solar-wind conversion system.	132