

# List of Tables

2.1	Size of Jacobian matrices of CNR, CINR, Rev-CINR, NR-CINR, and Mod-CINR (where $n$ = Total number of buses, and $p$ = number of PV buses in the system.) . . . . .	23
2.2	Comparison of performance of all NR methods under different loading conditions.( $NC$ = no convergence) . . . . .	26
2.3	Comparison of performance of all NR methods under different $R/X$ ratio condition.( $NC$ = no convergence, $T$ = Tolerance ( $pu$ ) ) . . . .	27
2.4	Computational Time (s) for $CNR$ , $FDBX$ , and $Mod - CINR$ algorithms on different IEEE bus system (NC: Not Converged) . . .	28
3.1	Fixed Dimension Unimodal Functions [2]. ( $D$ = Dimension, $R$ = Range of the search-space, $Fmin$ = minimum of the problem) . . .	46
3.2	Floating Dimension Unimodal Functions [2]. ( $D$ = Dimension, $R$ = Range of the search-space, $Fmin$ = minimum of the problem) . .	47
3.3	Fixed Dimension Multimodal Functions [2]. ( $D$ = Dimension, $R$ = Range of the search-space, $Fmin$ = minimum of the problem) . . .	48
3.4	Floating Dimension <a href="#">Multimodal</a> Functions [2]. ( $D$ = Dimension, $R$ = Range of the search-space, $Fmin$ = minimum of the problem) . .	49
3.5	Result of Fixed Unimodal Functions . . . . .	49
3.6	Result of Unfixed Unimodal Functions . . . . .	50
3.7	Result of Fixed Multimodal Functions . . . . .	51
3.8	Result of Unfixed Multimodal Functions . . . . .	52
4.1	Impedance Matrices for the conductor types (in ohm/mile) . . . . .	64

4.2	Specified real and reactive power and voltage exponents for the test system . . . . .	65
4.3	Results of Re-phasing for different scenarios . . . . .	67
4.4	Re-phasing obtained using constant load model . . . . .	70
4.5	Comparison of voltages after and before Re-phasing for constant load model . . . . .	71
4.6	Re-phasing obtained considering voltage-dependency . . . . .	72
4.7	Comparison of voltages after and before Re-phasing for Voltage-dependent load model . . . . .	73
4.8	Summary of Results of important quantities . . . . .	76
5.1	Optimal location and Sizing of Single base DGs calculated by Butterfly Optimizer . . . . .	98
5.2	Comparison of load distribution of base load without DGs and with DGs . . . . .	105
5.3	Comparison of voltages after and before Re-phasing for constant load model . . . . .	106
5.4	Summary of Results of important quantities . . . . .	107
5.5	Mismatch in results when constant power load model is considered for the voltage dependent loads . . . . .	116
5.6	Mismatch in zero-sequence currents at main feeder for different scenario of voltage dependent loads. . . . .	117
5.7	Mismatch in negative-sequence currents at main feeder for different scenario of voltage dependent loads. . . . .	117