

Contents

| | | |
|------------------|--|----------|
| | CERTIFICATE | |
| | DECLARATION BY THE CANDIDATE | |
| | COPYRIGHT TRANSFER CERTIFICATE | |
| | ACKNOWLEDGMENT | |
| | ABSTRACT | |
| Chapter-1 | Introduction & Background | 1 |
| | 1.1 Background | 1 |
| | 1.2 Introduction | 1 |
| | 1.3 Resources of renewable energy | 2 |
| | 1.4 Classification of renewable energy resources | 3 |
| | 1.5 Biomass feedstocks | 5 |
| | 1.6 Gasification | 5 |
| | 1.7 Biomass gasification technologies | 6 |
| | 1.7.1 Downdraft gasifier | 8 |
| | a) Process zone of downdraft gasifier | 8 |
| | 1.8 Producer gas filtration system | 10 |
| | 1.8.1 Tar filtration techniques | 11 |
| | 1.8.2 Dust and ash particles removal techniques | 20 |
| | 1.9 Need of biodiesel | 21 |
| | 1.10 Findings from the review | 25 |

| | | |
|------------------|--|-----------|
| 1.11 | Research gap | 25 |
| 1.12 | Problem statement | 25 |
| 1.13 | Objectives of the research work | 26 |
| 1.14 | Methodology of the research work | 26 |
| | References | 27 |
| Chapter-2 | Experimental Investigations of the Producer Gas for Tar Removal | 32 |
| | Removal | |
| 2.1 | Introduction | 32 |
| 2.2 | Designed parameters | 33 |
| 2.2.1 | Reactor height | 33 |
| 2.2.2 | Reactor diameter | 33 |
| 2.2.3 | Throat design | 33 |
| 2.2.4 | Hearth load (B_g) | 34 |
| 2.3 | Operating parameters of gasifier system | 34 |
| 2.3.1 | Residence time and heating rate | 34 |
| 2.3.2 | Air flow rate | 34 |
| 2.3.3 | Operating temperature | 35 |
| 2.3.4 | Equivalence ratio | 35 |
| 2.4 | Working principle | 36 |
| 2.4.1 | Technical specification | 40 |
| 2.4.2 | Instrumentation | 41 |
| 2.4.2.1 | Dual fuel running diesel engine | 41 |
| 2.4.2.2 | Gasifier control panel | 42 |
| 2.4.2.3 | Gas chromatograph | 42 |
| 2.4.2.4 | Bomb calorimeter | 43 |

| | | |
|------------------|---|-----------|
| 2.4.3 | Experimental analysis | 43 |
| 2.4.3.1 | Procedure | 44 |
| 2.4.3.2 | Specification of solid biomass feedstock | 45 |
| a) | Coconut shell | 45 |
| a) | Dalbergia Sisoo | 46 |
| 2.4.4 | Experimental observations | 47 |
| 2.4.4.1 | Observations | 48 |
| 2.4.4.2 | Calculations | 59 |
| a) | Calculation for calorific value | 59 |
| b) | Calculation of percentage reduction in diesel consumption | 61 |
| c) | Cost analysis | 64 |
| 2.5 | Needs for cleaning producer gas | 70 |
| 2.5.1 | Tar | 70 |
| 2.5.1.1 | Tar removal approaches | 72 |
| 2.5.1.2 | Classification of catalyst | 73 |
| a) | Minerals | 74 |
| 2.5.1.3 | Methodology | 74 |
| 2.5.1.4 | Observations and analysis | 75 |
| 2.6 | Uncertainty analysis | 77 |
| 2.7 | Conclusions | 79 |
| | References | 81 |
| Chapter-3 | Experimental Investigations of Cyclone Separator for Syngas Production and Effect of Blending with Biodiesel on Emission | 82 |
| 3.1 | Introduction | 82 |

| | |
|---|-----|
| 3.2 Working principle of cyclone separator | 84 |
| 3.3 Cyclone performance parameter | 86 |
| 3.4 Cyclone performance evaluation | 87 |
| 3.4.1 Experimental method | 88 |
| a) Instrumentation | 89 |
| b) Observations and calculations | 90 |
| 3.4.2 Using Leith and Licht model | 93 |
| a) Observations and calculations | 94 |
| b) Viscosity of producer gas | 97 |
| 3.5 Biodiesel | 104 |
| 3.5.1 Biodiesel production procedures | 105 |
| 3.5.2 Storage of biodiesel | 106 |
| 3.5.3 Quality measuring parameters | 107 |
| a) Kinematic viscosity | 107 |
| b) Brake specific fuel consumption | 107 |
| c) Emissions | 108 |
| 3.5.4 Instrumentation | 108 |
| a) Capillary flow viscometer | 109 |
| b) Bomb calorimeter | 110 |
| c) Variable compression ratio (VCR) engine research test setup | 111 |
| 3.6 Biodiesel production procedure | 111 |
| 3.6.1 Viscosity of biodiesel | 115 |
| 3.6.2 Calorific value of biodiesel | 119 |
| 3.6.3 Variable compression ratio (VCR) research test setup | 121 |

| | | |
|------------------|--|------------|
| | 3.7 Experiment | 122 |
| | 3.8 Conclusions | 138 |
| | References | 140 |
| Chapter-4 | Design and Numerical Modelling of a Multi-Stage Filtration Unit for a Gasifier System | 142 |
| | 4.1 Introduction | 142 |
| | 4.2 Computational fluid dynamics model | 150 |
| | 4.2.1 Mesh generation of perforated filters | 153 |
| | 4.2.2 Governing equations | 153 |
| | 4.2.3 Boundary conditions | 154 |
| | 4.2.4 Grid independence test | 155 |
| | 4.2.5 Experimental validation | 155 |
| | 4.3 Results and discussion | 156 |
| | 4.3.1 Velocity and pressure contours | 157 |
| | 4.3.2 Effect of single honeycomb substrate for different hole geometry | 158 |
| | 4.3.3 Effect of multiple filters with different shape of perforation | 162 |
| | 4.4 Correlation development | 167 |
| | 4.5 Conclusions | 170 |
| | References | 171 |
| Chapter-5 | Conclusions and future work | 175 |
| | 5.1 Main results | 175 |
| | 5.2 Future work | 178 |
| | Publications | 179 |

| | | |
|-------------------|---|------------|
| | References | 181 |
| Appendix A | Graphical abstract depicting the methodological pathways | 195 |
| Appendix B | Grid convergence index (GCI) | 197 |