

LIST OF FIGURES

Fig 2.3	Summarized plot of surface modification techniques.	18
Fig 2.2	Schematic diagram physical thermos mechanical process during thermal spraying process.	23
Fig 2.3	Conventional plasma spray process.	25
Fig 2.4	Schematic of the (a) physical plasma spray process and (b) its idealization for modeling.	27
Fig. 2.5	Splat formations after the impact of the spherical powder during spraying.	27
Fig. 2.6	Carrier Gas Flow Rate (a) too low (b) correct (c) too high.	30
Fig. 2.7	SEM examination of splat morphologies obtained from impacting droplets at substrate inclinations of (a) 0°, (b) 10°, (c) 20°, (d) 30°, (e) 40°, (f) 50°, (g) 60°.	32
Fig. 3.1	General arrangement of plasma spraying equipment.	49
Fig. 3.2	Schematic diagram of the ball on disk testing rig.	55
Fig. 4.1	SEM micrographs of feedstock powders of (a) Ni, (b) Al, (c) Ag, (d) MoS ₂ and (e) hBN.	59
Fig. 4.2	XRD pattern of as deposited coatings (a) NAMB0 (b) NAMB5 and (c) NAMB10.	60
Fig. 4.3	Cross-section morphologies of (a) NAMB0 (b) NAMB5 (c) NAMB10 composite coating, and (d) high magnification image of (a), (e) high magnification image of (b), (f) high magnification image of (c).	61
Fig. 4.4	Variation of coefficient of friction with time for NAMB0, NAMB5 and NAMB10 coatings at different loads (a) 5 N, (b) 10 N, (c) 15 N and (d) 20 N.	64
Fig. 4.5	Variation of average coefficient of friction with load for composite coatings.	65

Fig. 4.6	Variation of wear rate of the coatings with load.	65
Fig. 4.7	SEM images of worn surfaces of coating at a load of 5 N (a) NAMB0 (b) NAMB5 (c) NAMB10.	66
Fig. 4.8	SEM images of worn surfaces of coating at a load of 10 N (a) NAMB0 (b) NAMB5 (c) NAMB10.	67
Fig. 4.9	SEM images of worn surfaces of coating at a load of 15 N of (a) NAMB0 (b) NAMB5 (c) NAMB10 coatings with corresponding EDS spectrums.	68
Fig. 4.10	SEM images of worn surfaces of coating at a load of 20 N (a) NAMB0 (b) NAMB5 (c) NAMB10.	69
Fig. 4.11	Worn surfaces of alumina ball slid against (a) NAMB0 (b) NAMB5 (c) NAMB10 composite coating at a load of 5N.	70
Fig. 4.12	Worn surfaces of alumina ball slid against (a) NAMB0 (b) NAMB5 (c) NAMB10 composite coating at a load of 10 N.	71
Fig. 4.13	Worn surface of alumina ball slid against (a) NAMB0 (b) NAMB5 (c) NAMB10 composite coating with EDS aalysis at a load of 15N.	72
Fig. 4.14	Worn surface of alumina ball slid against (a) NAMB0 (b) NAMB5 (c) NAMB10 composite coating at a load of 20 N and corresponding EDS spectrums.	73
Fig. 4.15	XRD patterns of the worn surfaces of (a) NAMB0 (b) NAMB5 (c) NAMB10 coating at 5, 10, 15 and 20 N load.	74
Fig. 4.16	Raman spectra of the worn surfaces of (a) NAMB0 (b) NAMB5 (c) NAMB10 coating at 5, 10, 15 and 20N load.	76
Fig. 4.17	Variation of coefficient of friction with time at (a) Room temperature (RT), (b) 200 °C, (c) 400 °C (d) 600 °C and (e) 800 °C for coatings.	81
Fig. 4.18	Variation of average coefficient of friction with temperature for composite coatings.	82
Fig. 4.19	Variation of wear rate of with temperature for all coatings.	83
Fig. 4.20	SEM images of worn surfaces of NAMB0 coating at: (a) RT; (b) 200 °C; (c) 400 °C; (d) 600 °C and (e) 800 °C.	85

Fig. 4.21	SEM images of worn surfaces of NAMB5 composite coating at (a) RT; (b) 200 °C (c) 400 °C; (d) 600 °C and (e) 800 °C.	86
Fig. 4.22	SEM images of worn surfaces of NAMB10 composite coating at: (a) RT; (b) 200 °C; (C) 400 °C; (d) 600 °C and (e) 800 °C.	87
Fig. 4.23	SEM images of worn surface alumina ball slid against NAMB0 composite coating :(a) RT; (b) 200 °C; (C) 400 °C; (d) 600 °C and (e) 800 °C.	88
Fig. 4.24	SEM images of worn surface alumina ball slid against NAMB5 composite coating :(a) RT; (b) 200 °C; (C) 400 °C; (d) 600 °C and (e) 800 °C and corresponding EDS spectrums.	90
Fig. 4.25	SEM images of worn surface alumina ball slid against NAMB10 composite coating :(a) RT; (b) 200 °C; (C) 400 °C; (d) 600 °C and (e) 800 °C.	91
Fig. 4.26	(a) XRD patterns of wear track of NAMB0 composite coatings at different test temperatures under 0.3 m/s speed.	92
Fig. 4.26	(b) XRD patterns of wear track of NAMB5 composite coatings at different test temperatures under 0.3 m/s speed.	93
Fig. 4.26	(c) XRD patterns of wear track of NAMB10 composite coatings at different test temperatures under 0.3 m/s speed.	94
Fig. 4.27	Raman spectra of worn tracks of the composite coatings (a) NAMB0 (b) NAMB5 (c) NAMB10 after sliding at different test temperatures.	95
Fig. 4.28	Variation of coefficient of friction with time at (a) RT, (b) 200 °C, (c) 400 °C, (d) 600 °C and (e) 800 °C for coatings under 0.3 m/s speed.	105
Fig. 4.29	Variation of coefficient of friction with time at (a) RT, (b) 200 °C, (c) 400 °C, (d) 600 °C and (e) 800 °C for coatings under 0.7 m/s speed.	106
Fig. 4.30	Variation of coefficient of friction with time at (a) RT, (b) 200 °C, (c) 400 °C, (d) 600 °C and (e) 800 °C for coatings under 0.9 m/s speed.	107

Fig. 4.31	Variation of average coefficient of friction with temperature for NAMB0, NAMB5 and NAMB10 coatings (a) 0.3 m/s, (b) 0.5 m/s, (c) 0.7 m/s and (d) 0.9 m/s.	108
Fig. 4.32	Variation of average coefficient of friction with speed at (a) RT, (b) 200 °C; (c) 400 °C; (d) 600 °C and (e) 800 °C for all the coatings.	109
Fig. 4.33	Variation of wear rate with temperature at different speeds for NAMB0, NAMB5 and NAMB10 coatings (a) 0.3 m/s; (b) 0.5 m/s; (c) 0.7 m/s and (d) 0.9 m/s.	111
Fig. 4.34	Variation of wear rate with speed at (a) RT, (b) 200 °C, (c) 400 °C, (d) 600 °C and (e) 800 °C for all the coatings.	112
Fig. 4.35	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB0 coating at 0.3 m/sec sliding speed.	114
Fig. 4.36	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB5 coating at 0.3 m/sec sliding speed.	114
Fig. 4.37	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB10 coating at 0.3 m/sec sliding speed.	115
Fig. 4.38	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB0 coating at 0.7 m/sec sliding speed.	116
Fig. 4.39	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB5 coating at 0.7 m/sec sliding speed.	117
Fig. 4.40	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB10 coating at 0.7 m/sec sliding speed.	117
Fig. 4.41	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB0 coating at 0.9 m/sec sliding speed.	119
Fig. 4.42	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB5 coating at 0.9 m/sec sliding speed.	119
Fig. 4.43	SEM micrographs of the worn surfaces: (a) RT, (b) 400 °C and (c) 800 °C of NAMB10 coating at 0.9 m/sec sliding speed.	120
Fig. 4.44	SEM images of worn surface alumina ball slid against NAMB0 composite coating :(a) RT, (b) 400 °C and (c) 800 °C at 0.3 m/s speed.	121

Fig. 4.45	SEM images of worn surface alumina ball slid against NAMB5 coating :(a) RT, (b) 400 °C and (c) 800 °C under 0.3 m/s speed.	122
Fig. 4.46	SEM images of worn surface alumina ball slid against NAMB10 composite coating :(a) RT, (b) 400 °C and (c) 800 °C at 0.3 m/s speed.	122
Fig. 4.47	SEM images of worn surface alumina ball slid against NAMB0 composite coating :(a) RT, (b) 400 °C and (c) 800 °C at 0.7 m/s speed.	124
Fig. 4.48	SEM images of worn surface alumina ball slid against NAMB5 composite coating :(a) RT, (b) 400 °C and (c) 800 °C at 0.7 m/s speed.	125
Fig. 4.49	SEM images of worn surface alumina ball slid against NAMB10 composite coating :(a) RT (b) 400 °C and (c) 800 °C at 0.7 m/s speed.	125
Fig. 4.50	SEM images of worn surface of alumina ball slid against NAMB0 composite coating at (a) RT, (b) 400 °C and (c) 800 °C at 0.9 m/s speed.	127
Fig. 4.51	SEM images of worn surface alumina ball slid against NAMB5 coating :(a) RT (b) 400 °C and (c) 800 °C under 0.9 m/s speed.	128
Fig. 4.52	SEM images of worn surface alumina ball slid against NAMB10 coating :(a) RT (b) 400 °C and (c) 800 °C under 0.9 m/s speed.	128
Fig. 4.53	(a) XRD patterns of wear track of NAMB0 composite coatings at different test temperatures under 0.3 m/s speed.	130
Fig. 4.53	(b) XRD patterns of wear track of NAMB5 composite coatings at different test temperatures under 0.3 m/s speed.	131
Fig. 4.53	(c) XRD patterns of wear track of NAMB10 composite coatings at different test temperatures under 0.3 m/s speed.	132
Fig. 4.54	(a) XRD patterns of wear track of NAMB0 composite coatings at different test temperatures under 0.7 m/s speed.	133
Fig. 4.54	(b) XRD patterns of wear track of NAMB5 composite coatings at different test temperatures under 0.7 m/s speed.	134

Fig. 4.54	(c) XRD patterns of wear track of NAMB10 composite coatings at different test temperatures under 0.7 m/s speed.	135
Fig. 4.55	(a) XRD patterns of wear track of NAMB0 composite coatings at different test temperatures under 0.9 m/s speed.	136
Fig. 4.55	(b) XRD patterns of wear track of NAMB5 composite coatings at different test temperatures under 0.9 m/s speed.	137
Fig. 4.55	(c) XRD patterns of wear track of NAMB10 composite coatings at different test temperature under 0.9 m/s speed.	138
Fig. 4.56	Raman spectra with in wear track of the coatings (a) NAMB0 (b) NAMB5 (c) NAMB10 at different test temperatures under 0.3 m/sec speed.	139
Fig. 4.57	Raman spectra with in wear track of the coatings (a) NAMB0 (b) NAMB5 (c) NAMB10 at different test temperatures under 0.7 m/sec speed.	140
Fig. 4.58	Raman spectra with in wear track of the coatings (a) NAMB0 (b) NAMB5 (c) NAMB10 at different test temperatures under 0.9 m/sec speed.	141