

REFERENCES

REFERENCES

1. Annavarapu, R.K., Kim, S., Wang, M., Hart, A.J., and Sojoudi, H. Explaining Evaporation-Triggered Wetting Transition Using Local Force Balance Model and Contact Line-Fraction, *Sci. Rep.* 2018.
2. Archard, J.F., Contact and Rubbing of Flat Surfaces, *J. of App. Phys.*, 24, 981-88, 1953.
3. Archard, J.F., Wear theory and mechanisms, *Wear control handbook*, 58, ASME, New York, USA, 1980.
4. Behera, A., Mishra, S.C., *Plasma Surface Engineering: Plasma Spray Coatings*, Lap Lambert Academic Publishing, June 11, 2012, ISBN: 9783659146046
5. Bhushan, B., *Principles and Applications to Tribology*, 2nd ed. New York: John Wiley & Sons, Ltd, 2013.
6. Blau, P.J., Elevated-temperature tribology of metallic materials, *Tribol. Int.*, 43, 1203–1208, 2010.
7. Bowden, F. P., and Tabor, D., *The friction and lubrication of solids, Part I*, Clarendon Press, Oxford, 1954.
8. Cameron, A., *Basic lubrication theory*, Ellis Horwood, 1981.
9. Carrapichano, J.M., Gomes, J.R., and Silva, R.F., Tribological behavior of Si₃N₄-BN ceramic materials for dry sliding applications, *Wear*, 253, 1070-1076, 2002.
10. Chen, H.C., and Pfender, E., Microstructure of plasma-sprayed Ni-Al alloy coating on mild steel, *Thin Solid Films*, 280, 188-198, 1996.
11. Chen, J., An, Y., Yang, J., Zhao, X., Yan, F., Zhou, H., and Chen, J., 2013, Tribological properties of adaptive NiCrAlY-Ag-Mo coatings prepared by atmospheric plasma spraying. *Surf Coat Technol.* 235, 521–528, 2013.
12. Chen, J., Zhao, X.Q., Zhou, H.D., Chen, J.M., An, Y.L., and Yan, F.Y., Microstructure and tribological property of HVOF-sprayed adaptive NiMoAl-Cr₃C₂-Ag composite coating from 20 °C to 800 °C, *Surf. Coat. Technol.*, 258, 1183-1190, 2014.
13. Chen, J., Zhao, X.Q., Zhou, H.D., Chen, J.M., An, Y.L., and Yan, F.Y., HVOF-sprayed adaptive low friction NiMoAl-Ag coating for tribological application from 20 to 800 °C. *Tribol. Lett.*, 56, 55–66, 2014.
14. Chen, Y., Liang, X., Liu, Y., Bai, J., and Xu, B., Finite element modeling of coating formation and transient heat transfer in the electric arc spray process, *International Journal of Heat and Mass Transfer*, 53, 2012-2021, 2010.

15. Chien, S.Y., and Cramer, M.S., Pressure, temperature, and heat flux in high speed lubrication flows of pressurized gases, *Tribol. Int.*, 129, 468-475, 2019.
16. Coddet, C, Thermal Spray: Meeting the Challenges of the 21st Century, Proceedings of the 15th international thermal spray conference, France, Vol. 1, 1998, ISBN 0-87170-659-8.
17. Dai, Z., Wang, G., Liu, L., Hou, Y., Wei, Y., and Zhang, Z., Mechanical behavior and properties of hydrogen bonded graphene/polymer nano-interfaces, *Compo. Sci. Technol.*, 136, 1-9, 2016.
18. Du, L., Huang, C., Zhang, W., Li, T., and Liu, W., Preparation and wear performance of NiCr/Cr₃C₂-NiCr/hBN plasma sprayed composite coating, *Surf. Coat. Technol.*, 205, 3722-3728, 2011.
19. Du, L., Zhang, W., Liu, W., and Zhang, J., Preparation and characterization of plasma sprayed Ni₃Al-hBN composite coating, *Surf. Coat. Technol.*, 205, 2419-2424, 2010.
20. Elvers, B., Hawkins S., and Schultz, G., Ullmann's Encyclopedia of Industrial Chemistry, 1/16, 433, 1990.
21. Erdemir, A., A crystal-chemical approach to lubrication by solid oxides, *Tribol. Lett.*, 8, 97-102, 2000.
22. Fauchais, P., Verdelle, M., Verdelle, A., and Bianchi, L., Plasma Spray: Study of Coating Generation, *Ceramic International*, 22, 295-303, 1996.
23. Feng, X.C., Jia, J.H., Wang, W.Z., and Shan, Y., Mechanical and tribological properties of NiAl-NbC-Ag composites prepared by hot-pressing sintering, *J. Mater. Res.*, 32, 2361-2372, 2017.
24. Fotovvati, B., Namdari, N., and Dehghanhadikolaei, A., On Coating Techniques for Surface Protection: A Review, *J. Manu. Mat. Pro.*, 3, 28, 2019.
25. Funk, W., and Goebe, F., *Thin Solid Film*, 128, 45, 1985.
26. Furlan, K.P., Mello, J.D.B., and Klein, A.N., Self-lubricating composites containing MoS₂: A review, *Tribol. Int.*, 120, 280-289, 2018.
27. Gerdeman D.A., and Hecht, N.L., *Arc Plasma Techno. in Material Science*, Springer-Verlag, Wien, 1972.
28. Guo, H., Han, M., Chen, W., Lu, C., Li, B., Wang, W., and Jia, J., Microstructure and properties of VN/Ag composite films with various silver content, *Vacuum*, 137, 97-103, 2017.
29. Holm, R., *Elektrische Kontakte/Electric Contacts Handbook*, Springer, Berlin Heidelberg, Berlin, Heidelberg, 1958.

30. Holmberg, K., and Erdemir, A., Influence of tribology on global energy consumption, costs and emissions, *Friction*, 5(3), 263-284, 2017.
31. Holmberg, K., Andersson, P., Nylund, N.O., Mäkelä, K., and Erdemir, A., Global energy consumption due to friction in trucks and buses, *Tribol. Int.*, 78, 94-114, 2014.
32. Hou, G., An, Y., Zhao, X., Zhou, H., and Chen, J., Effect of alumina dispersion on oxidation behavior as well as friction and wear behavior of HVOF-sprayed CoCrAlYTaCSi coating at elevated temperature up to 1000 °C, *Acta Materialia*, 95, 164–175, 2015.
33. Hu, J.J., Muratore, C., and Voevodin, A.A., Silver diffusion and high-temperature lubrication mechanisms of YSZ–Ag–Mo based nanocomposite coatings, *Compo. Sci. Technol.*, 67, 336-347, 2007.
34. Huang, C., Du, L., and Zhang, W., Preparation and characterization of atmospheric plasma-sprayed NiCr/Cr₃C₂–BaF₂·CaF₂ composite coating, *Surf. Coat. Technol.*, 203, 3058–3065, 2009.
35. Inman, I.A., Dutta, P.K., Du, H.L., Burnell-Gray, J.S., Pierzgalsky, S., and Lou, Q., Studies of high temperature sliding wear of metallic dissimilar interfaces, *Tribol. Int.*, 38, 812-823, 2005.
36. Inman, I.A., Rose, S.R., and Dutta, P.K., Development of a simple ‘temperature versus sliding speed’ wear map for the sliding wear behavior of dissimilar metallic interfaces, *Wear*, 260, 919-932, 2006.
37. Inman, I.A., Rose, S.R., and Dutta, P.K., Studies of high temperature sliding wear of metallic dissimilar interfaces II: Incoloy MA956 versus Stellite 6, *Tribol. Int.*, 39, 1361-1375, 2006.
38. Kang, C.W., and Ng, H.W., Splat morphology and spreading behavior due to oblique impact of droplets onto substrates in plasma spray coating process, *Surf. Coat. Technol.*, 200, 5462-5477, 2006.
39. Kimura, Y., Wakabayashi, T., Okada, K., Wada, T., and Nishikawa, H., Boron nitride as a lubricant additive, *Wear*, 232, 199-206, 1999.
40. Kong, L., Zhu, S., Qiao, Z., Yang, J., Bi, Q., and Liu, W., Effect of Mo and Ag on the friction and wear behavior of ZrO₂ (Y₂O₃)-Ag-CaF₂-Mo composites from 20 °C to 1000 °C, *Tribol. Int.*, 78, 7-13, 2014.
41. Levingstone, T.J., Optimisation of Plasma Sprayed Hydroxyapatite Coatings, Ph. D thesis, School of Mechanical and Manufacturing Engineering, Dublin City University, Ireland, 2008.
42. Li, B., Gao, Y., Han, M., Guo, H., Wang, W., and Jia, J., Microstructure and tribological properties of NiCrAlY-Mo-Ag composite by vacuum hot-press sintering, *Vacuum*, 143, 1-6, 2017.

43. Li, B., Gao, Y., Jia, J., Han, M., Guo, H., and Wang, W., Influence of heat treatments on the microstructure as well as mechanical and tribological properties of NiCrAlY-Mo-Ag coatings, *J. Alloys Com.*, 686, 503-510, 2016.
44. Li, B., Gao, Y., Li, C., Liu, Z., Guo, H., Zheng, Q., Li, Y., and Kang, Y., Effect of heat treatment on the microstructure, mechanical property and tribological property of plasma-sprayed high temperature lubricating composite coating from nanostructured powder, *J. Alloys Com.*, 816, 152671, 2020.
45. Li, B., Jia, J., Gao, Y., Han, M., and Wang, W., Microstructural and tribological characterization of NiAl matrix self-lubricating composite coatings by atmospheric plasma spraying, *Tribol. Int.*, 109, 563–570, 2017.
46. Li, F., Cheng, J., Qiao, Z., Ma, J., Zhu, S., Fu, L., Yang, J., and Liu, W., A Nickel-Alloy-Based High-Temperature Self-Lubricating Composite with Simultaneously Superior Lubricity and High Strength, *Tribol. Lett.*, 49, 573–577, 2013.
47. Li, J., Xiong, D., Wu, H., Dai, J., and Cui, T., Tribological properties of molybdenized silver-containing nickel base alloy at elevated temperatures, *Tribol. Int.*, 42, 1722–1729, 2009.
48. Liu, E., Wang, W., Gao, Y., and Jia, J., Tribological Properties of Adaptive Ni-Based Composites with Addition of Lubricious Ag_2MoO_4 at Elevated Temperatures, *Tribol. Lett.*, 47, 21–30, 2012
49. Liu, E., Wang, W., Gao, Y., and Jia, J., Tribological properties of Ni-based self-lubricating composites with addition of silver and molybdenum disulfide, *Tribol. Int.*, 57, 235–241, 2013.
50. Liu, E.Y., Gao, Y.M., Bai, Y.P., Yi, G.W., Wang, W.Z., and Zeng, Z.X., Tribological properties of self-lubricating NiAl/Mo-based composites containing AgVO_3 nanowires, *Mater. Char.*, 97, 116–124, 2014.
51. Liu, L., Zhou, M., Jin, L., Li, L., Mo, Y., Su, G., Li, X., Zhu, H., and Tian, Y., Recent advances in friction and lubrication of graphene and other 2D materials: Mechanisms and applications, *Friction*, 7(3), 199-216, 2019.
52. Ludema, K.C., *Friction, wear and lubrication: A textbook in tribology*. CRC Press, Inc., 1996.
53. Meyerson, B.S., UHV/CVD growth of Si and Si: Ge alloys: Chemistry, physics, and device applications, *Proc. IEEE*, 80, 1592–1608, 1992.
54. Murator, C., and Voevodin, A.A., Chameleon coatings: adaptive surfaces to reduce friction and wear in extreme environments, *Annu. Rev. Mater. Res.*, 39, 297-324, 2009.
55. Nash, A.R., Weare N.E., and Walker, D.L., *J. Metals*, 473, 1961.
56. Nemani, S.K., and Sojoudi, H., Barrier Performance of CVD Graphene Films Using a Facile P3HT Thin Film Optical Transmission Test, *J. Nanomater*, 2018, 9681432, 2018.

57. Ng, H.W., and Gan, Z., A finite element analysis technique for predicting as-sprayed residual stresses generated by the plasma spray coating process, *Finite Elements in Analysis and Design* 41, 1235-1254, 2005.
58. Niu, M., Bi, Q., Yang, J., and Liu, W., Tribological performance of a Ni₃Al matrix self-lubricating composite coating tested from 25 to 1000 °C, *Surf. Coat. Technol.*, 206, 3938-3943, 2012.
59. Novak, R.C., *J. Gas Turbines and Power*, 110, 110, 1988.
60. Ouyang, J.H., and Sasaki, S., Tribological characteristics of low-pressure plasma-sprayed Al₂O₃ coating from room temperature to 800 °C, *Tribol. Int.*, 38, 49–57, 2005.
61. Pauschitz, A., Roy, M., and Franek, F., Comparism of high temperature wear behaviour of chromia forming Fe-based and Ni-based alloy, *Tribologie Schmierungstech*, 50, 40-49, 2003.
62. Pauschitz, A., Roy, M., and Franek, F., On the chemical composition of the layers formed during sliding of metallic alloys at high temperature, *Tribologia*, 188, 127-143, 2003.
63. Phakatkar, H.G., and Ghorpade, R.R., *Tribology*, 2nd ed. Pune: Nirali Prakashan, 2009.
64. Prajapati, A.K, Omrani, E., Menezes, P.L., and Rohtagi, P.K., *Self-lubricating composites*, ISBN 978-3-662-56527-8, 2018.
65. Rabinowicz, E., *Friction and wear of metals*, John Willey and Sons, Inc; New York, USA, 1965.
66. Radu, I., and Li, D.Y., Investigation of the role of oxide scale on Stellite 21 modified with yttrium in resisting wear at elevated temperatures, *Wear*, 259, 453-458, 2005.
67. Radu, I., and Li, D.Y., The wear performance of yttrium-modified Stellite 712 at elevated temperatures, *Tribol. Int.*, 40, 254-265, 2007.
68. Ramesh, C.S., Seshadri, S.K., and Iyer K.J.L., A Survey of Aspects of Wear of Metals, *Ind. J. of Tech.*, 29, 179-85, 1991.
69. Roy, M., Pauschitz, A., and Franek, F., In: *Proceedings of the third Aimeta international tribology conference*, Vietri. Sul. Mare., 18–20 September, 2002, Italy.
70. Roy, M., Pauschitz, A., Wernisch, J., and Franek, F., Effect of mating surface on the high temperature wear of 253 MA alloy, *Mater. Corros.*, 55, 259-273, 2004.
71. Sahoo, P., *Engineering Tribology*. New Delhi: PHI learning private limited, 2005.

72. Satpathy, A., Mishra, S.C., Padmanabhan, P.V.A., and SreeKumar, K.P., Development of Ceramic Coatings Using Red Mud- A Solid Waste of Alumina Plants, *Journal of Solid Waste Technology and Management*, 33, 48-53, 2007.
73. Shi, X., Song, S., Zhai, W., Wang, M., Xu, Z., Yao, J., Din, A., and Zhang, Q., Tribological behavior of Ni₃Al matrix self-lubricating composites containing WS₂, Ag and hBN tested from room temperature to 800 °C, *Materials and Design.*, 55, 75–84, 2014.
74. Shi, X., Zhai, W., Wang, M., Xu, Z., Yao, J., Song, S., and Wang, Y., Tribological behaviors of NiAl based self-lubricating composites containing different solid lubricants at elevated temperatures, *Wear.*, 310, 1–11, 2014.
75. Skopp, A., Woydt, M., and Habig, K.H., Tribological behavior of silicon nitride materials under unlubricated sliding between 22 °C and 1000 °C, *Wear*, 181-183, 571-580, 1995.
76. Sliney, H.E., and Graham, J.W., Tribological properties of self-lubricating fluoride-metal composites to 900°C (1650° F) - A review and some new developments, *J. Lubri. Technol.*, 97, 506-509, 1975.
77. Sojoudi, H., Kim, S., Zhao, H., Annavarapu, R.K., Mariappan, D., Hart, A.J., McKinley, G.H., and Gleason, K.K., Stable Wettability Control of Nanoporous Microstructures by iCVD Coating of Carbon Nanotubes. *ACS Appl. Mater. Interfaces*, 9, 43287–43299, 2017.
78. Sojoudi, H., Nemani, S.K., Mullin, K., Wilson, M.G., Al-Adwani, H., Lababidi, H.M., and Gleason, K.K., A Micro/Nanoscale Approach for Studying Scale Formation and Developing of Scale-Resistant Surfaces, *ACS Appl. Mater. Interfaces*, 11, 7330–7337, 2019.
79. Stachowiak, G.W., and Batchelor, A.W., *Engineering Tribology*, Butterworth Heinemann, Team LRN, 2001.
80. Stott, F.H., Lin, D.C, and Wood, G.C., ‘Glazes’ produced on nickel-base alloys during high temperature wear, *Nature*, 242, 75–7, 1973.
81. Stott, F.H., High-temperature sliding wear of metals, *Tribol. Int.*, 35, 489-495, 2002.
82. Stott, F.H., The role of oxidation in the wear of alloys, *Tribol. Int.*, 31, 67-71, 1998.
83. Torres, H., Ripoll, M.R., and Prakash, B., Tribological behaviour of self-lubricating materials at high temperatures, *Int. Mater. Rev.*, 63, 309-340, 2018.
84. Tu, J.P., Jie, X.H., Mao, Z.Y., and Matsumara, M., The effect of temperature on the unlubricated sliding wear of 5 CrNiMo steel against 40 MnB steel in the range 400–600 °C, *Tribol Int.*, 31, 347, 1998.
85. Venkatramani, N., *Bull. Material Sci. (India)*, 18, 741, 1995.

86. Wang, H.M., Yu, Y.L., and Li, S.Q., Microstructure and tribological properties of laser clad $\text{CaF}_2/\text{Al}_2\text{O}_3$ self-lubrication wear-resistant ceramic matrix composite coatings, *Scripta Materialia*, 47, 57–61, 2002.
87. Wang, L., and Li, D.Y., Effects of yttrium on microstructure, mechanical properties and high-temperature wear behavior of cast Stellite 6 alloy, *Wear*, 255, 535-544, 2003.
88. Wang, L.Q., Zhou, J.S., Xin, B.B., Yu, Y.J., Ren, S.F., and Li, Z., Phase transformation and tribological properties of Ag-MoO₃ contained NiCrAlY based composite coatings fabricated by laser cladding, *Optic Laser Technol.*, 93, 79–86, 2017.
89. Wu, L., Holloway, B.C., Beesabathina, D.P., Kalil, C., and Manos, D.M., Analysis of diamond-like carbon and Ti/MoS₂ coatings on Ti-6Al-4V substrates for applicability to turbine engine applications, *Surf. Coat. Technol.*, 130, 207-217, 2000.
90. Xin, B.B., Yu, Y.J., Zhou, J.S., Wang, L.Q., and Ren, S.F., Effect of copper molybdate on the lubricating properties of NiCrAlY laser clad coating at elevated temperatures, *Surf. Coat. Technol.*, 313, 328–336, 2017.
91. Xin, B.B., Yu, Y.J., Zhou, J.S., Wang, L.Q., Ren, S.F., Li, Z., Effect of silver vanadate on the lubricating properties of NiCrAlY laser cladding coating at elevated temperatures, *Surf. Coat. Technol.*, 307, 136–45, 2016.
92. Yi, G., and Yan, F., Effect of hexagonal boron nitride and calcined petroleum coke on friction and wear behavior of phenolic resin-based friction composites, *Mater. Sci. and Engg. A.*, 425, 330-338, 2006.
93. Zhai, W.Z., Shi, X.L., Yao, J., Xu, Z.S., Ibrahim A.M.M., and Zhu, Q.S., Synergetic lubricating effect of WS₂ and Ti₃SiC₂ on tribological properties of Ni₃Al matrix composites at elevated temperatures, *Tribol. Trans.*, 58, 454–466, 2015.
94. Zhang, S., Zhou, J., Guo, B., Zhou, H., Pu, Y., and Chen, J., Preparation and characterization of reactively sintered Ni₃Al-hBN-Ag composite coating on Ni-based super alloy, *J. Alloys Com.*, 473, 462–466, 2009.
95. Zhang, T., Lan, H., Huang, C., Du, L., and Zhang, W., Formation mechanism of the lubrication film on the plasma sprayed NiCoCrAlY-Cr₂O₃-AgMo coating at high temperatures, *Surf. Coat. Technol.*, 319, 47–54, 2017.
96. Zhen, J., Li, F., Zhu, S., Ma, J., Qiao, Z., Liu, W., and Yang, J., Friction and wear behavior of nickel-alloy-based high temperature self-lubricating composites against Si₃N₄ and Inconel 718, *Tribol. Int.*, 75, 1-9, 2014.
97. Zhen, J., Zhu, S., Cheng, J., Qiao, Z., Liu, W., and Yang, J., Effects of sliding speed and testing temperature on the tribological behavior of a nickel-alloy based solid-lubricating composite, *Wear*, 368-369, 45–52, 2016.
98. Zhu, S., Cheng, J., Qiao, Z., and Yang, J., High temperature solid-lubricating materials: A review, *Tribol. Int.*, 133, 206–223, 2019.

99. Zhu, S., Cheng, J., Qiao, Z., and Yang, J., High temperature solid-lubricating materials: A review, *Tribol. Int.*, 133, 206–223, 2019.
100. Zhu, S., Li, F., Ma, J., Cheng, J., Yin, B., Yang, J., Qiao, Z., and Liu, W., Tribological properties of Ni₃Al matrix composites with addition of silver and barium salt, *Tribol. Int.*, 84, 118–123, 2015.
101. Zhu, S.Y., Bi, Q.L., Wu, H.R., Yang, J., and Liu, W.M., NiAl matrix high-temperature self-lubricating composite, *Tribol. Lett.*, 41, 535–540, 2011.
102. Zhu, S.Y., Bi, Q.L., Yang, J., and Liu, W.M., Ni₃Al matrix composite with lubricious tungstate at high temperatures, *Tribol. Lett.*, 45, 251–255, 2012.
103. Zhu, S.Y., Kong, L.Q., Li, F., Yang, J., Ma, J.Q., and Cheng J., NiAl matrix self-lubricating composite at a wide temperature range, *J. Tribol. Trans. ASME.*, 137, 021301-1-6, 2015.