List of figures

Fig.1.1	:	Schematic illustration of overall objectives of the present work	7
Fig.2.1	:	Crystal structure of hydroxyapatite	14
Fig.2.2	:	Schematic diagram, representing the direct piezoelectric effect due to (a) compressive and (b) tensile stresses	20
Fig.2.3	:	Schematic diagram representing the crack deflection	23
Fig.2.4	:	Variation of (a) fracture toughness and (b) bending strength of Al_2O_3 with $LiTaO_3$ content in Al_2O_3 - $LiTaO_3$ composite.	26
Fig.2.5	:	Schematic diagram illustrating the crack deflection at domain boundaries in piezoelectric $LiTaO_3$ grain.	28
Fig.2.6	:	TEM micrographs demonstrating the crack deflections and branching in LiTaO ₃ grains in Al_2O_3 -15 LiTaO ₃ ceramic composite: (a) Crack deflection of about 90° (b) crack deflection less than 90° and crack branching (c) crack deflection less than 90° and (d) crack deflection more than	28
Fig.2.7	:	Schematic diagram representing the (a) cubic to tetragonal phase transition, (b) 180° polarization switching induced by an externally applied electric field above the coercive field and (c) 90° polarization switching induced by a compressive stress.	29
Fig.2.8	:	Variation of bending strength of MgO as a function of $BaTiO_3$ content.	31
Fig.2.9	:	Schematic diagram representing sodium ion migration to interstitial position in sodium silicate glass	33
Fig.2.10	:	Schematic diagram representing the ROS generation on charged	34
Fig.2.11		Schematic diagram representing the ROS generation due to surface charge induced by the polarization of potassium sodium niobate (KNN) sample	35
Fig.2.12		Schematic diagram representing antibacterial action of Ag particle	36
Fig.2.13		Schematic diagram representing biofilm disintegration on HA-ZnO	37
Fig.2.14		Cell viability of untreated and electric field treated (E-field strength: 1 V/cm) L929 cells, cultured on control disk, HA and HA–40 wt. % BaTiO ₃ composite. Asterisk * shows the significant difference among the samples incubated for 5 and 7 days with respect to that incubated for 3 days ** and ***Significant differences among the samples of same incubation period with respect to untreated control disk and HA, respectively at $P < 0.05$.	39
Fig.2.15		Schematic diagram, illustrating the mechanism of cellular response on positively and negatively charged HA - 20 wt. % BaTiO ₃ and HA - 40 wt. % BaTiO ₃ composites.	40
Fig.2.16		: Schematic diagram representing the mineralization of HA in SBF	41
Fig 217		: Diagram, representing the novelty of present work	45

19

		the synthesis of Hydroxyapane (11A)	63
Fig.3.1	2	Flow chart representing the	
		thesis of 45S5 bioglass (BG)	65
Fig. 3.2	2	Flow chart for the synthesis of 1393 bioglass (BG)	67
Fig. 3.3	2	Flow chart for the synthesis of teamples using cold isostatic pressing	69
Fig. 3.4	3	Digital pictographs of compact samp	~0
Ela 25		(CIP) Schematic diagram for indentation on the specimen at 1 kgf load with	71
F1g.5.5	•	10 s dwell time for crack generation on the specimen at 5 kgf load	72
Fig.3.6	-	for 10 s dwell time	71
Fig. 3.7	:	Schematic diagram for rectangular specimen for the corporation of the set	13
Fig. 3.8	:	Schematic diagram for cylindrical specimen for compressive strength	73
Fig. 3.9	:	schematic diagram for polarization of disc shaped samples at 20 kV	75
U		for 30 min using corona poling unit	70
Fig. 3.10	:	Schematic representing the electrical stimulation sequence, adopted during osteogenic cell culture experiments.	18
Fig. 4.1	:	Densification behavior for HA, NKN and HA – $(10 - 30)$ NKN	82
0		composites, synthesized using uniaxial as well as cold isostatic pressings (CIP)	
Fig.4.2	;	X-Ray diffraction patterns for HA, NKN and HA – $(10 - 30)$ NKN	83
T: 12		composite samples.	81
F1g.4.3	-	Fourier transform infra-rea (FTIR) spectra for HA, INKIN and HA –	04
Fig 11		(10 - 50) NKN composite samples. SEM micrographs of (a) HA (b) HA 10 NKN (c) HA 20 NKN and	95
F 1g. 4.4		(d) $HA = 30$ NKN composites .	01
Fig.4.5	1	Variation of mechanical properties of HA with addition of NKN (a)	86
		Hardness and fracture toughness, (b) Compressive strength and flexural strength	
Fig.4.6	:	SEM micrographs revealing crack deflection for (a) monolithic HA.	87
		(b) $HA - 10 NKN$, (c) $HA - 20 NKN$ and (d) $HA - 30 NKN$ composites after indentation fracture	
Fig.4.7	1	Variation of dielectric constant and loss with temperature for (a) H4	90
		(b) NKN, (c) HA-10 NKN, (d) HA-20 NKN and (e) HA-30 NKN composites at few selected frequencies	10
Fig.4.8	1	Variation of dielectric constant and loss with fragments for (a) 114	01
0		(b) NKN, (c) HA-10 NKN, (d) HA-20 NKN and (e) HA-30 NKN at few selected temperatures	91
Fig. 4.9	1	Comparison of dielectric constant between us	05
6		bounds, log mixture rule and present stud	95
		kHz, (b) 100 kHz and (c) 1 MHz	
Fig. 4.10	:	Variation of log σ_{ac} with inverse of terms in	07
		frequencies for (a) HA, (b) NKN, (c) $HA - 10$ NKN, (d) $HA - 20$ NKN and (d) $HA - 30$ NKN composites	9/
Fig. 4.11	1	Variation of log oac with log f at few selected to	00
		HA, (b) NKN, (c) $HA - 10$ NKN, (d) $HA - 20$ NKN and (d) $HA - 30$ NKN composites.	90

(HA

Fig. 4.12 : Complex plane impedance plots for HA, NKN, HA-10 NKN, HA- 20 10^{0}

NKN and HA-30 NKN composites at temperatures (a) 100° C, *(b)* 200° C, *(c)* 300° C, *(d)* 400° C, *(e)* 500° C; *(f), (g) and (h) represent the variation of log (R_g, R_{gb}) vs* 1000/T

- Fig. 4.13 : Impedance and modulus spectroscopic plots for (a) HA, (b) NKN, (c) 102 HA-10 NKN, (d) HA-20 NKN and (e) HA-30 NKN composites
- Fig. 4.14 : Polarization induced antibacterial response of HA, HA-10 NKN, HA- 104 20 NKN and HA-30 NKN composites for (a) gram positive (S. aureus) and (b) gram negative (E. coli) bacteria. Asterisk (*), (**) and (***) mark represent the significant difference in optical density of the bacterial cells for the uncharged, negatively and positively charged samples at p < 0.05, with respect to the monolithic HA
- Fig.4.15 : Fluorescence microscopy images of live (green) and dead (red) S. 106 aureus bacterial cells, cultured on unpolarized, positively and negatively polarized HA and HA-(10-30) NKN composite samples. Scale bar corresponds to 100 µm.
- Fig.4.16 : Fluorescence microscopy images of live (green) and dead (red) E. 107 coli bacterial cells, cultured on unpolarized, positively and negatively polarized HA and HA - (10 - 30) NKN composite samples. Scale bar corresponds to 100 μ m.
- Fig.4.17 : Superoxide production (ROS generation) on unpolarized and 108 polarized HA, HA-10 NKN, HA-20 NKN and HA-30 NKN composites for (a) gram positive (S. aureus) and (b) gram negative (E. coli) bacteria. Asterisk (*), (**) and (***) marks represent the significant difference in superoxide production by the bacterial cells for the uncharged, negatively and positively charged samples at p < 0.05, with respect to the uncharged, negatively and positively monolithic HA.
- Fig. 4.18: The catalase activity/ sec. of (a) S.aureus and (b) E. coli bacteria,
cultured on unpolarized and polarized HA, HA 10 NKN, HA 20
NKN and HA 30 NKN composites. Asterisk (*) mark represents the
significant difference among all composite samples with respect to
unpolarized HA at p < 0.05. Asterisk marks (**) and (***) represents
the significant difference among all composite samples with respect to
negatively polarized and positively polarized HA, respectively, at p < 0.05.
- Fig.4.19 : Lipid peroxidation in terms of MDA equivalent for (a) S.aureus and 112 (b) E. coli bacteria, cultured on polarized and unpolarized HA, HA-(b) E. coli bacteria, cultured on polarized and unpolarized HA, HA-10 NKN, HA-20 NKN and HA-30 NKN composites. Asterisk (*) mark represents the significant difference among all the composite samples with respect to unpolarized HA at p < 0.05. Asterisk marks (**) and (***) represent the significant difference among all composite (***) represent the significant difference among all composite samples with respect to negatively and positively polarized HA, respectively, at p < 0.05
- Fig. 4.20 : respectively, at p < 0.05: The concentration of protein for (a) S. aureus and (b) E. coli bacteria 114 : The concentration of protein for (a) S. aureus and (b) E. coli bacteria 114 cultured on polarized and unpolarized HA, HA – 10 NKN, HA – 20 cultured on polarized and unpolarized HA, HA – 10 NKN, HA – 20 NKN and HA – 30 NKN composites. Asterisk (*) mark represents the significant difference among all the composite samples with respect to unpolarized HA at p < 0.05. Asterisk marks (**) and (***) represent the significant difference among all composite samples with respect to the significant difference among all composite samples with respect to negatively and positively polarized HA, respectively, at p < 0.05.

- Fig.4.21 : Schematic representing the antibacterial activity due to the ROS 116 generation
- Fig. 4.22
- : Combined effect of surface polarization and electric field treatment on 117 in vitro cytocompatibility of HA and HA – 30 NKN composites using MG-63 cells. (*) and (#) represent the significant difference in optical density between uncharged HA and HA – 30 NKN. (**) and (##) show the statistically significant difference in optical density for electric field treated positively polarized HA and HA – 30 NKN composite with respect to positively polarized HA and HA – 30 NKN composite and (***) and (###) show statistically significant difference in optical density for electric field treated negatively polarized HA and HA – 30 NKN NKN with respect to negatively polarized HA and HA – 30 NKN composite

Fig. 4.23

- Fluorescence images, demonstrating the morphology of osteogenic 120 MG63 cells, while cultured for 72 h on (a) uncharged HA, (b) negatively polarized HA, (c) positively polarized HA, (d) E-field treated negatively polarized HA, (e) E-field treated positively polarized HA (f) uncharged HA 30 NKN composite, (g) negatively polarized HA 30 NKN composite, (h) positively polarized HA 30 NKN composite, (i) E-field treated negatively polarized HA 30 NKN composite, (i) E-field treated negatively polarized HA 30 NKN composite, (i) E-field treated negatively polarized HA 30 NKN composite, The E-field treated positively polarized HA 30 NKN composite. The E-field strength was 1 V/cm. The scale bars correspond to 100 μm.
- Fig. 5.1: X-Ray diffraction patterns for sintered (a) 45S5 BG, (b) NKN, (c) BG 13310NKN, (d) BG 20 NKN and (e) BG 30 NKN composite samples.
- Fig.5.2 : Fourier transform infra-red (FTIR) spectra for sintered (a) 45S5 BG, 133
 (b) NKN, (c) BG 10 NKN, (d) BG 20 NKN and (e) BG 30 NKN composite samples
 Fig.5.3 : Variation of mechanical properties of DG and the laboration of mechanical properties of DG.
- Fig.5.3 : Variation of mechanical properties of BG with addition of NKN (a) 135 Hardness and Fracture toughness (K_{IC}), (b) Compressive and flexural strengths
 Fig.5.4 : Variation of dielectric constant on 11
- Fig.5.4 : Variation of dielectric constant and loss with temperature for (a) BG, 138
 (b) BG -10 NKN (c) BG 20 NKN and (d) BG 30 NKN at frequencies of 10 KHz, 100 kHz and 1 MHz, respectively.
 Fig.5.5 : Comparison of dielectric constant and 1 MHz, respectively.
- Fig.5.5 : Comparison of dielectric constant between parallel and series Wiener 140 bounds, log mixture rule and present study at frequencies of (a) 10 kHz, (b) 100 kHz and (c) 1 MHz.
 Fig.5.6 : Variation of log 590 with 6
- Fig.5.6 : Variation of log σac with frequency at few temperatures for 142 composites (a) BG, (b) BG - 10 NKN, (c) BG - 20 NKN and (d) BG -30 NKN composites.
- Fig.5.7 : Complex plane impedance plot for pure BG, BG 10 NKN, BG 20 144 NKN, BG - 30 NKN composites at temperature (a) 100°C, (b) 200°C, (c) 300°C; (d), (e) and (f) represent the variation of log (R_g, R_{gb}) vs
 Fig.5.8 : Impedance and module
- Fig.5.8 : Impedance and modulus spectroscopic plots for (a) BG, (b) BG 10 145 NKN, (c) BG 20 NKN and (d) BG 30 NKN composites.
- Fig.5.9 : Antibacterial response of unpolarized, positively and negatively 14 polarized BG, BG 10 NKN, BG 20 NKN, BG 30 NKN

composites, against (a) gram positive (S. aureus) and (b) gram negative (E. coli) bacteria. Asterisk (*), (**) and (***) marks represent the significant difference in optical density of bacterial cells for the unpolarized, negatively and positively charged composite samples at p < 0.05, with respect to the monolithic BG.

- Antibacterial response of unpolarized (U), negatively (N) and 149 positively (P) polarized BG and BG-(10-30) NKN composite samples for S. aureus bacteria, observed using Kirby-Bauer method. (a), (b), (c) and (d) illustrate the cultured samples after 24 h of incubation in agar plate with S. aureus bacterial cells. (e), (f), (g) and (h) represent the area under the incubated samples. (i), (j), (k) and (l) represent the colony formation (bacterial growth after transferring the swab from the area under the samples to a new agar plate).
- Antibacterial response of unpolarized (U), negatively (N) and 150 Fig. 5.11 positively (P) polarized BG and BG-(10-30) NKN composite samples for E. coli bacteria, observed using Kirby-Bauer method. (a), (b), (c) and (d) illustrate the cultured samples after 24 h of incubation in agar plate with E. coli bacterial cells. (e), (f), (g) and (h) represent the area under the incubated samples. (i), (j), (k) and (l) represent the colony formation (bacterial growth after transferring the swab from the area under the samples to a new agar plate).
- : Live/dead ratio for (a) gram positive (S. aureus) and (b) gram 152 Fig. 5.12 negative (E. coli) bacterial cells, cultured on unpolarized, negatively and positively polarized BG, BG - 10 NKN, BG - 20 NKN and BG - 30 NKN composites. Asterisk (*), (**) and (***) marks represent the significant difference in live/dead ratio for bacterial cells on the unpolarized, negatively and positively polarized composite samples at p < 0.05, with respect to the monolithic BG.
- : Reactive oxygen species (superoxide), generated by (a) gram positive 153 Fig. 5.13 (S. aureus) and (b) gram negative (E. coli) bacterial cells, cultured on unpolarized, negatively and positively polarized BG, BG - 10 NKN, BG - 20 NKN, BG - 30 NKN composites. Asterisk (*), (**) and (***) marks represent the significant difference in superoxide production by the bacterial cells, cultured on the unpolarized, negatively and positively polarized composite samples at p < 0.05, with respect to pure BG
- Combined effect of polarization and electric field treatment on 156 Fig. 5.14 viability of MG 63 cells, cultured on BG and BG-30 NKN composite. (*) and (#) represent the statistically significant difference in optical density for negatively and positively polarized BG and BG – 30 NKN composite with respect to unpolarized BG and BG - 30 NKN composite, (**) and (##) show the statistically significant difference in optical density for electric field treated positively polarized BG and BG - 30 NKN composite with respect to positively polarized BG and BG - 30 NKN composite and (***) and (###) show statistically significant difference in optical density for electric field treated negatively polarized BG and BG – 30 NKN composite with respect to negatively polarized BG and BG – 30 NKN composite. 168
- X-Ray diffraction patterns for sintered (a) 1393 BG, (b) NKN, (c) Fig. 6.1 1393 BG - 10 NKN, (d) 1393 BG - 20 NKN and (e) 1393 BG - 30

Fig. 5.10

160

Fourier transform infra-red (FTIR) spectra for sintered (a) 1393 BG, (b) NKN, (c) 1393 BG - 10 NKN, (d) 1393 BG - 20 NKN and (e) 1393

Densification behavior of 1393 BG and 1393 BG – x NKN (10-30 vol. BG - 30 NKN composite samples. 170

Variation of mechanical properties of 1393 BG with addition of NKN Fig. 6.3 170 %) composites (a) Hardness and fracture toughness, (b) Compressive strength and Fig. 6.4

Polarization induced antibacterial response of 1393 BG, 1393 BG -171 Flexural strength 10 NKN, 1393 BG - 20 NKN, 1393 BG - 30 NKN composites for (a) gram positive (S. aureus) and (b) gram negative (E. coli) bacteria. Fig. 6.5 Asterisk (*), (**) and (***) marks represent the significant difference in optical density of bacterial cells for the uncharged, negatively and positively charged composite samples at p < 0.05, with respect to the

- Superoxide production (ROS generation) on monolithic 1393 BG, 17 1393 BG -10 NKN, 1393 BG-20 NKN and 1393 BG-30 NKN Fig. 6.6 composites for (a) gram positive (S. aureus) and (b) gram negative (E. coli) bacteria. Asterisk (*), (**) and (***) mark represent the significant difference in superoxide production by the bacterial cells for the uncharged, negatively and positively charged samples at p <0.05, with respect to the monolithic HA.
 - Digital camera images, demonstrating the viable bacterial colonies of IT (a) S. aureus and (b) E. coli bacteria, cultured for 8 h on unpolarized and polarized 1393 BG, 1393 BG - 10 NKN, 1393 BG - 20 NKN and 1393 BG - 30 NKN composites
 - Antibacterial ratio for (a) gram positive (S. aureus) and (b) gram In negative (E. coli) bacteria, cultured on monolithic 1393 BG, 1393 BG -10 NKN, 1393 BG-20 NKN and 1393 BG-30 NKN composites. Asterisk (*), (**) and (***) mark represent the significant difference of the uncharged, negatively and positively charged samples at p < 0.05, with respect to the monolithic 1393 BG.
 - Time dependent cell viability of MG 63 cells, cultured on unpolarized 18 and polarized surfaces of 1393 BG and 1393 BG-30 NKN composites along with electric field treatment. (*) and (#) represent the statistically significant difference in optical density for negatively and positively charged 1393 BG and 1393 BG - 30 NKN composite with respect to uncharged 1393 BG and 1393 BG-30 NKN composite, (**) and (##) show the statistically significant difference in optical density for electric field treated positively charged 1393 BG and 1393 BG-30 NKN composite with respect to positively charged 1393 BG and 1393 BG-30 NKN composite and (***) and (###) show statistically significant difference in optical density for electric field treated negatively charged 1393 BG and 1393 BG-30 NKN composite with respect to negatively charged 1393 BG and 1393 BG-30 NKN

Fluorescence images, demonstrating the morphology of MG63 cells, while cultured for 72 h on (a) uncharged 1393 BG, (b) negatively polarized 1393 BG, (c) positively polarized 1393 BG, (d) E-field

Fig. 6.2

Fig. 6.7

Fig. 6.8

Fig. 6.9

Fig. 6.10

treated negatively polarized 1393 BG, (e) E-field treated positively polarized 1393 BG (f) uncharged 1393 BG – 30 NKN composite, (g) negatively polarized 1393 BG – 30 NKN composite, (h) positively polarized 1393 BG – 30 NKN composite, (i) E-field treated negatively polarized 1393 BG – 30 NKN composite and (j) E-field treated positively polarized 1393 BG – 30 NKN composite. The E-field strength was 1 V/cm. The scale bars correspond to 100 μ m

List of Tables

Table 3.1	Composition and nomenclature used for $(1-x)$ HA – x NKN composites	64
Table 3.2	Composition of 45S5 BG	65
Table 3.3	Composition and nomenclature used for (1-x) 45S5 BG-x NKN composites	66
Table 3.4	Composition of 1393 BG	67
Table 3.5	Composition and nomenclature used for $(1-x)$ 1393 BG – x NKN composites	68
Table 3.6	Optimized sintering temperature for various composites	69