

LIST OF FIGURES

Figure No.	Description	Page No.
1.1	Stribeck curve: Dependence of the friction coefficient on viscosity, speed and load for a lubricated sliding system	7
2.1	Four ball lubricant tester	36
2.2	(a) SEM micrograph (magnification 2.00k X) and (b) 2D and 3D AFM images of the plain steel ball	41
3.1	Variation of mean wear scar diameter as a function of additive concentration (392 N, 60 min)	52
3.2	Variation of coefficient of friction as a function of sliding time in paraffin oil with and without different antiwear additives (0.25 % w/v) at 392N applied load for 60 min test duration	53
3.3	Comparative analysis of wear scar diameter and coefficient of friction (COF) of different additives at an optimum concentration of 0.25% (w/v) in paraffin oil (392 N, 60 min)	54
3.4	Variation of mean wear volume of various additives with time at an optimum concentration of 0.25% (w/v)	56
3.5	Variation of frictional torque with time and step loading of 98 N after every 10 min of the test run for the optimized concentration (0.25 %w/v) of different additives	58
3.6	SEM micrographs(magnification 200X and 2.00kX) of the worn surface of steel ball in the presence of base oil and its admixtures (a, b) PO, (c, d) ZDDP, (e, f) OH-BT, (g, h) OH-BTS, (i, j) OH-NT, (k, l) H-NT at 392 N load 60 min test duration	59

3.7	2D and 3D AFM images of the worn steel surface lubricated with different additives in paraffin oil for 60 min test duration at a 392 N applied load (a, b) PO, (c, d) ZDDP, (e, f) OH-BT, (g, h) OH-NT, (i, j) OH-BTS, (k, l) H-NT	60
3.8	EDX spectra for the worn surface of tested specimen balls lubricated with (a) PO, (b) OH-BT, (c) OH-BTS	61
3.9	Equilibrium adsorption configurations of the adsorbates on Fe (110) surface: (1) OH-BT, 2) OH-BTS 3) H-NT 4) OH-NT [full view (with Paraffin oil)] (colour represents in the structure as green: carbon, black: hydrogen, yellow: sulphur, dark yellow: iron, blue: nitrogen, red: oxygen)	62
3.10	(a) The Radial distribution function of nitrogen atoms of Schiff bases with an iron atom at distance r. (b) The radial distribution function of oxygen atoms of Schiff bases with an iron atom at distance r.	64
4.1	FE-SEM images of (a) CCO (b) SCCO (c), (d) IL-CCO and (e) EDX spectra of IL-CCO	71
4.2	TEM images of (a) CCO and (b) IL-CCO	72
4.3	XRD patterns of as-prepared CCO, SCCO and IL-CCO	73
4.4	FT-IR spectra of CCO and IL-CCO	74
4.5	(a) Dispersion stabilities of base oil containing CCO, SCCO and IL-CCO studied by UV-vis spectrophotometry. (b) Optical photographs of additives dispersed in base oil at different within 48	75

	h	
4.6	Variation of mean wear scar diameter as a function of additive concentration (392 N, 60 min)	76
4.7	Comparative analysis of wear scar diameter and coefficient of friction (COF) of different additives at an optimum concentration of 0.2% (w/v) in PO (392N, 60 min)	77
4.8	Variation of the coefficient of friction with time (392 N, 1200 rpm, 3600 sec) for the studied additives in PO	78
4.9	Variation of frictional torque as a function of stepwise loading and time for PO in absence and presence of different nano additives: sliding speed, 600 rpm; temperature, 75°C; concentration of additives, 0.2% w/v	79
4.10	SEM micrographs (magnification 200X and 2.00kX)of the worn steel surface lubricated withparaffin oil with different nano additives (0.2 % w/v) for 60 min test duration at 392 N applied load and EDX spectra of worn surface lubricated with IL-CCO	81
4.11	3D AFM images of the worn steel surface lubricated with blank paraffin oil (PO) and blends of PO with 0.2 % w/v nano additives at 392 N applied load	82
5.1	FE-SEM images of (a) Cu (b) Cu@C, (c) Particle size distribution histogram of Cu@C and (d) EdX spectra of Cu@C	89
5.2	TEM images of Cu@C composite at different magnification (a) 200 nm and (b) 100 nm	90
5.3	XRD patterns of as-prepared Carbon spheres, Cu nanoparticles and Cu@C composite	91
5.4	Raman spectra of Carbon spheres and Cu@C composite	92

5.5	Deconvoluted XPS images of Cu@C composite: C 1s core-level spectra, Cu 2p core-level spectra, and XPS survey spectra	93
5.6	(a) Dispersion stabilities of base oil containing Carbon Spheres, Cu nanoparticles and Cu@C composite studied by UV-vis spectrophotometry. (b) Optical photographs of different nano additives dispersed in base oil at different settling time.	94
5.7	Variation of mean wear scar diameter as a function of additive concentration (392 N, 60 min)	95
5.8	Comparative analysis of wear scar diameter and coefficient of friction (COF) of different additives at an optimum concentration of 0.1% (w/v) in paraffin oil (392N, 60 min)	96
5.9	Variation of the coefficient of friction with time (392 N, 1200 rpm, 3600 sec) for the studied additives in paraffin oil	98
5.10	Variation of mean wear volume of various additives with time at an optimum concentration of 0.1 % (w/v)	99
5.11	Variation of frictional torque with time and step loading of 98 N after every 10 min of the test run for the optimized concentration of different additives	101
5.12	SEM micrographs(magnification 200X and 2.00kX) of the worn surface of steel ball in the presence of base oil and its admixtures at 392 N load 60 min test duration	102
5.13	3D AFM images of the worn steel surface lubricated with different additives in paraffin oil for 60 min test duration at a 392 N applied load (a) C, (b) Cu, (c) Cu@C and (d) line profile of the worn surface of C, Cu and Cu@C	103
5.14	EDX results for the worn surface of tested specimen balls lubricated with (a) paraffin oil (b) Cu@C	104

6.1	FE-SEM images of (a) Ag@C at resolution 3 μm , inset showing resolution 500 nm (b) IL-Ag@C, TEM images of (c) Ag@C, inset showing SAED pattern, (d) IL-Ag@C and (e) EDX spectra of IL-Ag@C	111
6.2	XRD patterns of as-prepared Carbon spheres, Ag@C and IL-Ag@C composite	112
6.3	(a) IR spectra of the synthesized additive C, IL, Ag@C and IL-Ag@C and (b) TGA analysis of the Ag@C and IL-Ag@C	114
6.4	Raman spectra of Ag@C and IL-Ag@C composite	115
6.5	Deconvoluted XPS images of IL-Ag@C composite: (a) C 1s, (b) Ag 3d, (c) B 1s, (d) N 1s (e) F 1s core-level spectra and (f) XPS survey spectra	116
6.6	(a) Dispersion stabilities of base oil containing carbon spheres, IL, Ag@C and IL-Ag@C composites studied by UV-vis spectrophotometry (b) Optical photographs of additives dispersed in base oil within 48 h	117
6.7	Variation of mean wear scar diameter as a function of additive concentration (392 N, 60 min)	118
6.8	(a) Comparative analysis of wear scar diameter and coefficient of friction (COF) of different additives at an optimum concentration of 0.5% (w/v) in PEG (392N, 60 min) (b) Variation of the coefficient of friction with time (392 N, 1200 rpm, 3600 sec and) for the studied additives	120

6.9	Variation of frictional torque with time and step loading of 98 N after every 10 min of the test run for the optimized concentration of different additives	121
6.10	SEM micrographs (magnification 200X and 2.00kX) of the worn surface of a steel ball of the additives in PEG (a) C (b) IL (c) Ag@C and (d) IL-Ag@C at 392 N load 60 min test duration and (e) EDX results for the worn surface of tested specimen balls lubricated with IL-Ag@C	124
6.11	3D AFM images of the worn steel surface lubricated with additives in PEG for 60 min test duration at a 392 N applied load (a) C, (b) IL, (c) Ag@C and (d) IL-Ag@C	126
6.12	Deconvoluted XPS images of the worn surface of IL-Ag@C composite: (a) C 1s, (b) Ag 3d, (c) B 1s, (d) N 1s, (e) F 1s and (f) Fe 2p core-level spectra	128