

LIST OF TABLES

- Table 1.1:** Difference between property of normal ferroelectrics and relaxor perovskite ferroelectrics. **10**
- Table 2.1:** Results of EDS analysis of atomic percentage for 0.65BMT-0.35PT ceramics, calcined at 850°C and sintered at 950°C. **48**
- Table 3.1:** Refined structural parameters of 0.68BMT-0.32PT ceramics monoclinic space group Pm. **64**
- Table 3.2:** Refined structural parameters of 0.65BMT-0.35PT ceramics, using monoclinic space group Pm and tetragonal space group P4mm. **66**
- Table 3.3:** Refined structural parameters of 0.55BMT-0.45PT ceramics using tetragonal space group P4mm. **69**
- Table 3.4:** Refined structural parameters and agreement factors for BMZ-PT ceramics with $x=0.59$ using coexisting cubic (Pm3m)+tetragonal (P4mm) structures. **92**
- Table 3.5:** Refined structural parameters and agreement factors for BMZ-PT ceramics with $x=0.60$ using tetragonal (P4mm) structures. **93**
- Table 4.1:** Refined Lattice parameters obtained by Rietveld profile matching analysis for the poled 30kV/cm and unpoled sample of $(1-x)\text{Bi}(\text{Mg}_{1/2}\text{Ti}_{1/2})\text{O}_3-x\text{PbTiO}_3$ piezoceramics using monoclinic (Pm) and tetragonal (P4mm) structure. **113**