

List of Figures

1.1	Steps of solving a problem using parallel computing.	3
2.1	The dependability tree.	12
2.2	The relationship among fault, error and failure.	14
2.3	Network failure terminology.	15
2.4	Classification of direct network topologies.	20
2.5	Taxonomy of routing algorithms.	21
2.6	XY routing in a mesh with $N = 16$. Messages are routed in a dimension-ordered fashion.	23
2.7	e-cube routing in a hypercube with $N = 16$. Messages are routed in a dimension-ordered fashion.	24
2.8	A taxonomy for adaptive routing protocols.	24
2.9	A 4-dimensional hypercube and its subcubes.	26
2.10	The structure of the dimension in the space.	29
2.11	Hypercube division using free dimension.	29
2.12	A Spanning tree (ST) of the hypercube: First phase.	30
2.13	The modified ST under faulty node: Second reconfiguration phase.	30
2.14	Routing in 4-cube using DFS.	32
2.15	Shortest path routing in 4-cube.	33
2.16	Example of node status in 4-cube.	34
2.17	Example of strongly and ordinary unsafe nodes in 4-cube.	35
2.18	Example of node reachability in 4-cube.	36
2.19	Multicast tree in H_5 with reference to Table 2.2.	37
3.1	Message passing in normal condition.	42

LIST OF FIGURES

3.2	Notification of node/link failures.	42
3.3	Selection of alternative path.	43
3.4	A multipath composed by 4 multistep paths in hypercube.	45
3.5	Reception of <i>acks</i> messages.	47
3.6	Message passing flow diagram.	48
3.7	CPN model of the system.	58
3.8	CPN model of the system after few steps.	61
3.9	CPN model of the system after all steps.	61
3.10	CPN model for the Sender Side.	62
3.11	CPN model of the Receiver acks.	62
3.12	CPN model of the Transmit Message.	63
3.13	CPN model of the Transmit acks.	63
3.14	CPN model of the receiver.	64
3.15	Simulation result for different message lengths with 30% faulty nodes in H_8	65
3.16	Simulation result for different message lengths with 40% faulty nodes in H_8	66
3.17	Simulation result for different message lengths with 50% faulty nodes in H_8	66
3.18	Simulation result for different message lengths with 60% faulty nodes in H_8	67
3.19	Simulation results for different generation rates with 30% faulty nodes in H_8	67
3.20	Simulation results for different generation rates with 40% faulty nodes in H_8	68
3.21	Simulation results for different generation rates with 50% faulty nodes in H_8	68
3.22	Simulation results for different generation rates with 60% faulty nodes in H_8	69
4.1	Embedding is not possible in a faulty 4-cube since no fault-free 3-cube exist.	77

LIST OF FIGURES

4.2	Embedding is not possible in a faulty 4-cube since no fault-free 3-cube exist.	77
4.3	Embedding is possible in a faulty 4-cube since fault-free 3-cube exists. . .	77
4.4	Embedding is possible in a faulty 4-cube since fault-free 3-cube exists. . .	78
4.5	A 5-dimensional hypercube.	81
4.6	CPN model for computing.	84
4.7	CPN model for date generation.	84
4.8	CPN model for task scheduler.	85
4.9	CPN model for computing.	85
4.10	CPN model for computing.	85
4.11	CPN model for computing.	86
4.12	Comparison in terms of path length with failures for node-to-set disjoint path routing in H_8	87
4.13	Comparison in terms of path length without failures for node-to-set disjoint path routing in H_8	87
5.1	The spanning binomial trees with $r = 0$ on H_4	92
5.2	Four pairwise independent spanning trees of H_4 rooted at the vertex 0. . .	95
5.3	Response time of the parallel construction of n ISTs	106
5.4	Ratio b/w faulty links vs total links in reliable broadcasting.	108