

## LIST OF TABLES

**Table 2.1:** Results of EDS analysis of 0.51BNT-0.49PT ceramic calcined at 850<sup>0</sup>C for 6 hours and sintered at 950<sup>0</sup>C for 3 hours. Exp. and Cal. stand for experimental and calculated average atomic percentage of atoms. [63]

**Table 3.1:** Refined structural parameters for the single phase monoclinic (space group Pm) compositions with x=0.41 and 0.42. [86]

**Table 3.2:** Refined structural parameters for the phase coexistence region with x=0.43-0.49 using monoclinic and tetragonal (Pm+P4mm) structures. [87-88]

**Table 3.3:** Refined structural parameters for the compositions with x=0.50, 0.52 to 0.55 using tetragonal (P4mm) structure. [89]

**Table 3.4:** Ni/Ti-O bond lengths for BNT-PT solid solution obtained by using Rietveld refined structural parameters for the composition range  $0.41 \leq x \leq 0.49$  with monoclinic structure (Pm). [92]

**Table 3.5:** Ni/Ti-O bond lengths for BNT-PT solid solution obtained by using Rietveld refined structural parameters for the tetragonal (P4mm) compositions with x=0.50, 0.52 and 0.55. [92]

**Table 4.1:** Refined lattice parameters obtained by Rietveld profile matching for BNT-PT composition with x=0.43 using monoclinic (Pm) + tetragonal (P4mm) structure and x=0.50 using tetragonal (P4mm) structure, poled at 20kV/cm. [113]

**Table 6.1:** Refined structural parameters obtained by Rietveld analysis of BNT-PT/NZFO composite with y=0.5 using tetragonal P4mm and cubic Fd $\bar{3}$ m space groups. [157]

**Table 6.2:** Average grain size ( $\mu\text{m}$ ) of ferroelectric (BNT-PT) and magnetic (NZFO) phases for the composite compositions with y=0.3, 0.7 and 0.8. [167]