

## List of Figures

Fig. No.	Figure Details	Page No
Fig. 1.1	(a) The sigma-pi model for two $sp^2$ -hybridised carbon atoms, as in ethylene, (b) Delocalized $\pi$ -electron-system in a benzene ring consisting of six $sp^2$ -hybridised carbon atoms	5
Fig. 1.2	The energy levels of a $\pi$ -conjugated molecule, the lowest electronic excitation in between the bonding $\pi$ -orbital and the antibonding $\pi^*$ -orbital, (b) collection of molecular orbitals form bands separated by an energy gap	5
Fig. 1.3	Structures of few organic semiconductors	7
Fig. 1.4	(a) Overlapping of $\pi$ -electrons along the chain, (b) Hopping and band transport, (c) Hopping and tunneling between the two delocalized states	8
Fig. 1.5	n-type doping of poly(acetylene)	9
Fig. 1.6	p-type doping of poly(thiophene)	10
Fig. 1.7	Doping mechanisms in OSCs (a) Energy levels of OSCs, (b) n-doping: an electron is transferred from the HOMO of the dopant to the LUMO of the host, (c) p-doping: an electron is transferred from the HOMO of the host to the LUMO of the dopant, generating a hole at the host.	12
Fig. 1.8	Schematic diagram of a resistive thermal evaporation system	14
Fig. 1.9	AFM image of P3HT-nanofibers	17
Fig. 1.10	Picture of today's OFET	19
Fig. 1.11	Cross-sectional view of different OFET device configurations (a) Bottom-gate, bottom-contact (Coplanar), (b) Bottom-gate, top-contact (Staggered), (c) Top-gate, Top-contact (Coplanar), (d) Top-gate, bottom-contact (Staggered).	25
Fig. 1.12	OFET Operation	26
Fig. 1.13	Energy-band diagram showing operating principle of OFETs	27
Fig. 1.14	Working of an OFET (a) Schematic structure of OFET with	30

	applied voltages, (b) linear region, (c) “Pinch-off” condition, (d) saturation region	
Fig. 1.15	The I-V characteristics of a typical OFET (a) Output Characteristics, (b) Transfer Characteristics	31
Fig. 1.16	Applications of OFETs	35
Fig. 1.17	(a) LG Electronics: the world’s largest OLED HDTV presented at the 2012 Consumer Electronics Show (CES) in Las Vegas, it has a display size of 55 inches, weighs a mere 7.5 kg and is only 4 mm thick, (b) Sony: a rollable full color 4.1 inches OLED display driven by OFETs, being wrapped around a thin cylinder, (c) Polymer Vision: ‘Readius’, a flexible electrophoretic (e-ink) display fabricated on plastic substrates using OFET backplanes,(d) PolyIC GmbH & Co. KG: roll-to-roll printing organic RFID tags on plastic substrates.	35
Fig. 1.18	Carriers injection at the metal and semiconductor interface	38
Fig. 1.19	Energy band diagram of gold and P3HT <b>(a)</b> before contact, <b>(b)</b> after the contact	38
Fig. 2.1	Structure of P3HT	43
Fig. 2.2	<b>(a)</b> Preparation of thiophene Grignard monomer and synthesis of P3HT by Kumada catalyst transfer polymerization, <b>(b)</b> Schematic representation for the flow setup using nickel complex 3 and <b>(c)</b> Ni(dppp)Cl <sub>2</sub>	44
Fig. 2.3	Crystal structures of different carbon allotropes: Carbon atom consists of six protons and neutrons inside the nucleus, and two electrons revolve in the 1s orbital whereas the four other electrons are rotating in the next energetic 2s, 2p orbital (middle). The carbon atoms form 0D fullerene (top left), 1D CNT (top right), 2D graphene (bottom right), and 3D graphite structures	46
Fig. 2.4	Chemical structure of TCNQ	48
Fig. 2.5	(a) p <sup>+</sup> -Si/SiO <sub>2</sub> wafer disc, (b) substrate, (c) cleaning of substrates	50
Fig. 2.6	Chemical reaction and interaction among SiO <sub>2</sub> and OTS molecules, (b) Grain size increases after OTS treatment	51
Fig. 2.7	Spin coating unit	52

Fig. 2.8	Picture of furnace	53
Fig. 2.9	Vacuum coating unit	54
Fig. 2.10	Schematic representation of the nickel mask used for the source and drain electrodes deposition, (b) Image of the fabricated OFETs	55
Fig. 2.11	Connection of OFET using silver paste and insulated thin copper wire	55
Fig. 2.12	Semiconductor parameter analyzer	56
Fig. 3.1	Schematic 3-D structure of bottom-gate top-contact OFET	64
Fig. 3.2	The I-V characteristics of P3HT based OFET (a) output, (b) transfer characteristics	65
Fig. 3.3	AFM image of the spin-coat P3HT thin-film. The scan area dimension is $5\ \mu\text{m}\times 5\ \mu\text{m}$ ; inset scan area dimension is $1\ \mu\text{m}\times 1\ \mu\text{m}$	65
Fig. 4.1	Systematic structure of P3HT/graphene nanocomposite based OFET	73
Fig. 4.2	Combined I-V characteristics of OFETs having different concentrations of graphene flaks in their P3HT active channel (a) $I_{\text{DS}}$ Versus $V_{\text{DS}}$ at $V_{\text{GS}} = -60\ \text{V}$ , (b) $I_{\text{DS}}^{1/2}$ Versus $V_{\text{GS}}$ at $V_{\text{DS}} = -60\ \text{V}$ , (c) $\log(I_{\text{DS}})$ Versus $V_{\text{GS}}$ at $V_{\text{DS}} = -60\ \text{V}$	75
Fig. 4.3	SEM image of (a) P3HT/graphene thin-film coated FET channel, (b) P3HT/graphene hybrid nanocomposite material	76
Fig. 5.1	UV-visible absorption spectra for P3HT solution and P3HT-nanofibers suspension in chloroform	85
Fig. 5.2	(a) UV-visible absorption spectra of P3HT solutions of different concentrations, (b) Absorption peak height (at $\lambda = 450\ \text{nm}$ ) versus P3HT concentration (wt%)	87
Fig. 5.3	AFM pictures of the spin coated thin-film prepared by (a) P3HT-nanofibers suspension, (b) P3HT solution. The scan film area dimension is $5\ \mu\text{m}\times 5\ \mu\text{m}$ ; inset scan area dimension is $1\ \mu\text{m}\times 1\ \mu\text{m}$	88
Fig. 5.4	The I-V characteristics of the fabricated P3HT-nanofibers based OFET (a) Output Characteristics, (b) Transfer Characteristics	89
Fig. 6.1	AFM images of P3HT and TCNQ doped P3HT films (a) P3HT, (b) 1% TCNQ, (c) 5% TCNQ, (d) 10% TCNQ, (e) 20% TCNQ and (f) 20% TCNQ with thin-Al coating. The scale bar represents	98

1 $\mu$ m (200 nm in the insets)

- Fig. 6.2 Combined I-V characteristics for a range (0 to 20 %) of TCNQ doped, and Al coated at highly doped (20 %) P3HT channel film based FETs (a) Output characteristics drawn for  $V_{GS} = -60$ , (b) Transfer characteristics  $I_{DS}^{1/2}$  versus  $V_{GS}$  at  $V_{DS} = -60$  V, to estimate the  $V_{TH}$  for all fabricated OFETs, (c)  $\log(I_{DS})$  versus  $V_{GS}$  at  $V_{DS} = -60$  V, to estimate the value of on/off current ratio for all fabricated OFETs, (d) Schematic structure of top-contact OFET, channel covered with Al thin-film (10 nm) 99
- Fig. 6.3 Structure of the OFF- and ON-states of doped-P3HT OFET with thin-Al-coating and the depletion layer formed in the channel. The relative conductance is represented by more darkness 104