

Contents

	Page
Abstract	v
Contents	ix
List of Tables	xiii
List of Figures	xv
List of Abbreviations	xxii
1 Introduction	1
1.1 Motivation	1
1.2 Research Background	2
1.3 Electric Motor for EVs	4
1.4 Permanent Magnet Brushless DC Motor	8
1.5 Traction effort for vehicle movement	10
1.6 Regenerative braking of electric vehicle	12
1.7 Organization of the Thesis	16
2 Review of High Gain Bidirectional Converters	19
2.1 Introduction	19
2.2 Classification of bidirectional DC-DC converter	20
2.2.1 Isolated bidirectional DC-DC converter	21
2.2.2 Non-isolated bidirectional DC-DC converter	25
2.3 Conclusion	38
3 Quadratic Gain Bidirectional DC-DC Converter	39
3.1 Introduction	39

3.2	Step-up or Motoring mode of operation	40
3.2.1	Mode 1 ($0, T_{on}$)	40
3.2.2	Mode 2 (T_{on}, T_s)	41
3.3	Step-down or Regeneartive braking mode of operation	43
3.3.1	Mode 1 ($0, T_{ON}$)	44
3.3.2	Mode 2 (T_{ON}, T_s)	44
3.3.3	Regenerative braking commutation by three switch strategy	46
3.4	Converter Design and Stability Analysis	50
3.4.1	Converter Design	50
3.4.2	Small-signal Analysis	54
3.5	Simulation Results	57
3.6	Validation through developed prototype	61
3.7	Conclusion	67
4	Modified Quadratic Gain Bidirectional DC-DC Converter	69
4.1	Introduction	69
4.2	Operation of the converter	70
4.2.1	Step-up or Motoring Mode Operation	70
4.2.2	Step-down or Regenerative Braking Mode Operation	72
4.2.3	Commutation strategy of VSI during regenerative braking	74
4.3	Converter Design and Stability Analysis	75
4.3.1	Converter Design	75
4.3.2	Stability Analysis	79
4.4	Computational and Experimental results	83
4.4.1	Computational Results	83
4.4.2	Hardware Results	93
4.5	Conclusion	105
5	Coupled Inductor Based Quadratic Gain Bidirectional DC-DC Converter	107
5.1	Introduction	107
5.2	Step-up or Motoring Operation	108
5.2.1	Step-up in CCM	109

5.2.2	Step-up in DCM	112
5.3	Step-down or Regenerative braking Operation	115
5.3.1	Step-down in CCM	116
5.3.2	Step-down in DCM	119
5.3.3	Regenerative braking commutation by single-switch strategy	122
5.4	Small-signal Analysis of the Converter	125
5.5	Simulation and Experimental Results	128
5.5.1	Simulation Results	128
5.5.2	Experimental Results	137
5.6	Conclusion	147
6	Conclusions and Future Scope	149
6.1	Conclusions	149
6.2	Future Scope	151
	References	153
	List of Publication	169

List of Tables

Chapter 1

1.1	Comparison of five most widely used electric motors for EV application . .	7
1.2	PMBLDC motor specification	9

Chapter 2

2.1	Comparison of performance parameters of different isolated bidirectional converter	36
2.2	Comparison of performance parameters of different non-isolated bidirectional converter	37

Chapter 3

3.1	Converter specifications	53
3.2	Converter passive components	53
3.3	Comparison of simulation and experimental results	67
3.4	Comparison of different bidirectional converters with proposed converter .	67

Chapter 4

4.1	Converter specifications.	83
4.2	Converter specifications.	90
4.3	Comparison of simulation and experimental results for output voltage 200 V and operating frequency 20 kHz.	104
4.4	Comparison of simulation and experimental results for output voltage 98 V and operating frequency 15 kHz.	105

4.5 Comparison of different bidirectional converters with proposed converter . 105

Chapter 5

5.1 Converter specifications. 129

5.2 Converter specifications. 133

5.3 Comparison of simulation and experimental results for output voltage 200
V and operating frequency 40 kHz. 146

5.4 Comparison of simulation and experimental results for output voltage 98
V and operating frequency 15 kHz. 147

5.5 Comparison of different bidirectional converters with proposed converter . 147

List of Figures

Chapter 1

1.1	Typical performance characteristics of electric motors for traction.	5
1.2	Types of motors for EV application	6
1.3	PMBLDC motor drive system	9
1.4	PMBLDC motor armature current, back-EMF waveform and switching PWM.	10
1.5	Forces acting on a vehicle.	11
1.6	Belt-drum arrangement system.	12
1.7	Current flowing path single-switch control strategy when (a) switch S_4 ON (b) switch S_4 OFF during RB of PMBLDC motor.	13
1.8	Current flowing path of two-switch control strategy when (a) switch S_4 and S_3 ON (b) switch S_4 and S_3 OFF during RB of PMBLDC motor. . . .	14
1.9	Current flowing path of three-switch control strategy when (a) switch S_4 , S_6 and S_3 ON (b) switch S_4 , S_6 and S_2 OFF during RB of PMBLDC motor.	15

Chapter 2

2.1	The structure of bidirectional DC-DC converter.	20
2.2	The classification of bidirectional DC-DC converters.	20
2.3	Soft-switched bidirectional dual half-bridge dc-dc converter [1].	21
2.4	Isolated bidirectional converter [2].	22
2.5	Isolated bidirectional full-bridge converter with a flyback snubber [3]. . . .	22
2.6	Z-source isolated bidirectional full-bridge converter [4].	23
2.7	High-conversion-ratio isolated bidirectional dc-dc converter [5].	23
2.8	Isolated bidirectional interleaved converter [6].	24

2.9	High voltage gain isolated bidirectional converter [7].	25
2.10	The circuit configurations of conventional converter (a) Buck (b) Boost (c) Buck-Boost presented in 1972 [8].	26
2.11	Non-isolated bidirectional converter proposed in [9].	27
2.12	Basic bidirectional SC structures of (a) two-time and (b) three-time conversion ratio [10].	29
2.13	Interleaved switched-capacitor bidirectional converter proposed in [11]. . .	30
2.14	Interleaved coupled-inductor bidirectional converter proposed in [12]. . . .	30
2.15	Coupled-inductor based high voltage gain bidirectional converter [13]. . . .	31
2.16	A new cascaded buck-boost bidirectional converter [14].	32
2.17	A new interleaved bidirectional converter with built-in transformer [15]. . .	33
2.18	A multi-port bidirectional converter proposed in [16].	34

Chapter 3

3.1	The topology of quadratic gain bidirectional DC-DC converter.	40
3.2	Converters' boost mode operation in Mode-1.	41
3.3	Converters' boost mode operation in Mode-2.	42
3.4	Converter's voltage and current waveforms in boost mode.	43
3.5	Converters' buck mode operation in Mode-1.	44
3.6	Converter's buck mode operation in Mode-2.	45
3.7	Converter's voltage and current waveform in buck mode.	46
3.8	The working waveform of PMBLDC motor and Equivalent circuit for three-switch strategy (a) Back-EMF, armature current and switching signal of PMBLDC motor (b) Bidirectional VSI with equivalent circuit of a PMBLDC motor.	47
3.9	Current flowing path of three-switch strategy (solid line: switches are ON; dotted line: switches are OFF) (a) At 30 electrical degree and (b) At 60 electrical degree.	48
3.10	Equivalent circuits of PMBLDC motor using three-switch strategy at 30 and 60 electrical degree (a) ON state at 30°, (b) OFF state at 30°, (c) ON state at 60° and (d) OFF state at 60°.	49

3.11	Magnitude and Phase plot obtained from CLTF.	57
3.12	Inductor currents I_{L1} and I_{L2} with switching PWM during boost mode. . .	58
3.13	Output voltage V_o , Capacitor Voltage V_{c1} and Battery voltage V_i during boost mode.	58
3.14	Battery voltage and %SOC during motoring and regenerative braking. . .	59
3.15	Inductor current I_{L1} and I_{L2} with switching PWM during regenerative braking.	60
3.16	Voltage stress on switches S_1 and S_2 during boost mode operation of con- verter.	60
3.17	Motor speed characteristics during motoring and regenerative braking. . .	61
3.18	Hardware Setup.	62
3.19	System voltages in steady state boost operation of converter; capacitor C_1 (V_{c1}), battery voltage (V_i), and output voltage (V_o).	62
3.20	Boost mode operation of the converter; output voltage (V_o), I_{L2} , switching PWM, and I_{L1}	63
3.21	Switching PWM, Voltage stress on switches S_1 (V_{S1}), S_2 (V_{S2}), and output voltage (V_o) in boost mode operation of converter	63
3.22	Transition of motor from motoring mode to regenerative braking mode; V_{c1} , I_{L1} , V_o , and I_{L2}	64
3.23	Buck mode operation of converter; switching PWM, I_{L1} , V_o , and I_{L2}	64
3.24	Armature current, battery current, battey voltage, command signal at different braking duty (a) $\delta = 0.4$ (b) $\delta = 0.5$ (c) $\delta = 0.6$ and (d) $\delta = 0.7$. . .	65
3.25	The curve between % Efficiency and output Power during boost mode. . .	66

Chapter 4

4.1	The topology of modified quadratic gain bidirectional DC-DC Converter. .	70
4.2	Current flowing path during step-up mode operation of converter in stage-I.	71
4.3	Current flowing path during step-up mode operation of converter in stage-II.	71
4.4	The working waveform of converter's operation in step-up mode.	72
4.5	Current flowing path during step-down operation of the converter in stage-I.	73
4.6	Current flowing path during step-down operation of the converter in stage-II.	73

4.7	The working waveform of converter's operation in step-down mode.	74
4.8	Working waveform of converter at boundary condition mode during step-up operation.	75
4.9	Working waveform of converter at DCM during step-up operation.	78
4.10	Magnitude and phase plot is obtained from CLTF.	82
4.11	The PWM signal for switches of the proposed converter in MATLAB/Simulink.	84
4.12	The PWM signal of VSI for PMBLDC motor in MATLAB/Simulink.	85
4.13	The steady-state inductor currents I_{L1} and I_{L2} with switching PWM in step-up operation of the converter.	85
4.14	The steady-state inductor currents I_{L1} and I_{L2} with switching PWM in step-down operation of the converter.	86
4.15	The steady-state output voltage, input voltage and capacitor voltage during step-up operation of the converter.	87
4.17	PMBLDC motor speed characteristics during motoring and regenerative braking.	87
4.16	Voltage stress on switches S_1 and S_2 in step-up operation of the converter.	88
4.18	Three phase stator current of PMBLDC motor in motoring mode.	89
4.19	Three phase stator current of PMBLDC motor in regenerative braking mode.	89
4.20	Capacitor Voltage V_c , output voltage V_o and input voltage V_s during step-up operation.	90
4.21	Inductors current I_{L1} , I_{L2} with switching PWM under steady-state during step-up operation.	91
4.22	Voltage stress on switches S_1 (V_{s1}) and S_2 (V_{s2}) during step-up operation.	92
4.23	Inductor current I_{L1} , I_{L2} with switching PWM during step-down operation of converter.	92
4.24	PMBLDC motor speed characteristics.	93
4.25	Experimental setup.	94
4.26	The capacitor voltage V_c , output voltage V_o , and battery voltage V_s during step-up operation.	94
4.27	The output voltage (V_o), Inductor's current I_{L1} , and I_{L2}	95
4.28	Inductor's current I_{L1} , I_{L2} , and output voltage V_o in discontinuous conduction mode.	96

4.29	Output voltage V_o , inductor's current I_{L1} , and I_{L2} in boundary condition mode.	96
4.30	Steady-state three phase stator current of PMBLDC machine in motoring mode.	97
4.31	Plot of voltage stress on Switches S_1 (V_{s1}) and S_2 (V_{s2}).	97
4.32	The transition of output voltage V_o , battery voltage (V_s), inductor currents I_{L1} , and I_{L2} when RB is applied.	98
4.33	Steady-state inductor currents I_{L1} and I_{L2} during step-down operation of converter.	98
4.34	Three phase stator current I_a , I_b , I_c , and output voltage V_o during regenerative braking.	99
4.35	Armature current, battery current, battery voltage, command signal at different braking duty (a) $\delta = 0.4$ (b) $\delta = 0.5$ (c) $\delta = 0.6$ and (d) $\delta = 0.7$	100
4.36	Capacitor voltage (V_c), output voltage (V_o), input current (I_s) and input voltage (V_s) during step-up operation.	101
4.37	Inductors current (I_{L1} , I_{L2}), output voltage (V_o), and switching PWM during step-up operation.	101
4.38	Voltage stress V_{s1} , V_{s2} , input current I_s with PWM during step-up operation.	102
4.39	Inductors current (I_{L1} , I_{L2}), output voltage (V_o), and switching PWM during step-down operation.	102
4.40	Armature current, battery current, battery voltage, command signal at different braking duty (a) $\delta = 0.4$ (b) $\delta = 0.5$ (c) $\delta = 0.6$ and (d) $\delta = 0.7$	103
4.41	Converter efficiency during step-up operation with input voltage $V_s=48$ V.	104

Chapter 5

5.1	The topology of coupled inductor based QGBC.	108
5.2	The current conduction path of the converter during mode I operation.	109
5.3	Current conduction path of the converter in mode II operation.	110
5.4	The working waveform of current and voltage of the converter during step-up operationi CCM.	111

5.5	The working waveform of current and voltage of the converter during step-up operation in DCM.	113
5.6	The current conduction path of the converter during step-up in mode III operation.	114
5.7	Current conduction path of the converter during step-down in mode I operation.	116
5.8	Current conduction path of the converter during step-down in mode II operation.	117
5.9	The working current and voltage waveform of the converter during step-down in CCM operation.	118
5.10	The working current and voltage waveform of the converter during step-down in DCM operation.	120
5.11	The current flowing path of the converter during step-down in mode III of DCM operation.	121
5.12	Bidirectional DC-DC converter and VSI with equivalent circuit of a PMBLDC motor.	122
5.13	Back-EMF and armature current of PMBLDC motor with the switching signal for single-switch strategy.	123
5.14	Current flowing path of single-switch control (solid line: OFF state; dotted line: On state).	124
5.15	Magnitude and phase plot is obtained from CLTF.	128
5.16	Switching PWM for switches S_1 and S_2 during step-up operation of the converter.	129
5.17	Gate signal of voltage source inverter for PMBLDC motor in motoring mode.	130
5.18	Steady-state inductor currents I_{L1} , I_{L2} and switching PWM during step-up operation of the converter.	130
5.19	Steady-state input and output voltage during step-up operation.	131
5.20	Voltage stress on switches S_1 and S_4 during step-up operation of the converter.	131
5.21	Motor speed characteristics.	132
5.22	Output voltage V_o , capacitor voltage V_c and input voltage V_s during step-up operation.	134

5.23	Steady-state inductor currents I_{L1} , I_{L2} and switching PWM during step-up operation.	134
5.24	Voltage stress on switches S_1 and S_2 during step-up operation of the converter.	135
5.25	Inductor current I_{L1} , I_{L2} with switching PWM during step-down operation of the converter.	136
5.26	PMBLDC motor speed characteristics.	136
5.27	Experimental setup.	137
5.28	Steady-state output voltage V_o , input voltage V_s , inductor current I_{L1} , and inductor current I_{L2} in step-up operation.	138
5.29	Output voltage V_o , inductor current I_{L1} , inductor current I_{L2} , and switching PWM of switch in step-up operation.	138
5.30	The voltage stress on switches S_1 and S_2 during step-up operation of the converter.	139
5.31	The steady-state output voltage V_o , output current I_o , input voltage V_s , and input current I_s in step-up operation of the converter.	139
5.32	Steady-state output voltage V_o , inductor currents I_{L1} , and I_{L2} with switching PWM during step-down operation.	140
5.33	Armature current, battery current, battery voltage, command signal at different braking duty (a) $\delta = 0.4$ (b) $\delta = 0.5$ (c) $\delta = 0.6$ and (d) $\delta = 0.7$	141
5.34	Output voltage (V_o), capacitor voltage (V_c), input current (I_s) and input voltage (V_s) during step-up operation converter.	142
5.35	The inductor current I_{L1} , I_{L2} , output voltage V_o with switching PWM during step-up operation pf converter.	143
5.36	The voltage stress on switches S_1 , S_2 , output voltage and input current during step-up operation of converter.	143
5.37	Inductor currents I_{L1} , I_{L2} and output voltage with switching PWM during regenerative braking or step-down operation of converter.	144
5.38	Armature current, battery current, battery voltage, command signal at different braking duty (a) $\delta = 0.4$ (b) $\delta = 0.5$ (c) $\delta = 0.6$ and (d) $\delta = 0.7$	145
5.39	The efficiency curve of the converter in step-up operation.	146