

Contents

Certificate	ii
Acknowledgments	v
Preface	vii
List of Publications	x
Contents	xi
List of Figures	xiv
List of Tables	xvi
Abbreviations	xvii
Symbols	xviii
1 Introduction	1
1.1 Background	6
1.2 Research Goals and Problem Statement	9
1.3 Motivations	10
1.4 Contributions	12
1.5 Thesis Outline	14
2 Preliminaries and Literature Review	18
2.1 Preliminaries	18
2.1.1 Self-stabilizing Conditions	19
2.1.2 Failure Detection	19
2.1.3 System Models for Leader Election	20
2.1.4 Failure Models	21
2.2 Literature Review	23

2.2.1	Algorithms for Regular Network Topology	23
2.2.1.1	Algorithms for Ring Network	23
2.2.1.2	Algorithms for Mesh Network	25
2.2.1.3	Algorithms for 2D Torus Network	27
2.2.2	Algorithms for Arbitrary Network	30
3	FRLLE: A Failure Rate and Load-based Leader Election Algorithm for a Ring Network	33
3.1	System Model	34
3.1.1	Assumptions	34
3.1.2	Definitions	35
3.1.3	Types of Message	38
3.2	Proposed Algorithm	38
3.2.1	Proof of Self-stabilization	43
3.2.2	Complexity Analysis	46
3.2.2.1	Message Complexity	46
3.2.2.2	Time Complexity	47
3.2.3	An Illustrative Example	47
3.3	Empirical Appraisalment	51
3.3.1	Experiment Setup	51
3.3.2	Performance Comparison and Discussion	52
3.4	Summary	57
4	Lea-TN: A Leader Election Algorithm Considering Node and Link Failures in a Torus Network	58
4.1	System Model	59
4.2	Lower Bound	60
4.3	Proposed Methodology	63
4.3.1	Assumptions	63
4.3.2	Definitions	63
4.3.3	Types of Message and Message Sending Pattern	66
4.3.4	Description of Lea-TN	69
4.3.5	Proof of Self-stabilization	81
4.3.6	Performance Analysis	83
4.3.6.1	Message Complexity	83
4.3.6.2	Time Complexity	85
4.3.6.3	Space Complexity	86
4.3.7	Illustrative Example	86
4.4	Empirical Evaluation	89
4.4.1	Experiment Setup	89
4.4.2	Performance Comparison and Discussion	89
4.5	Summary	96

5	Preselection Based Leader Election in Distributed Systems	97
5.1	System Model	98
5.1.1	Assumptions	99
5.1.2	Definitions	99
5.1.3	Types of Message	100
5.2	Proposed Leader Election Algorithm	101
5.2.1	Illustrative Example	104
5.2.2	Complexity Analysis	107
5.2.2.1	Message complexity	107
5.2.2.2	Time complexity	108
5.2.3	Proof of Self-stabilization	108
5.3	Experimental Analysis and Discussion	110
5.4	Summary	113
6	Multi-attribute based self-stabilizing algorithm for leader election in distributed systems	114
6.1	System Model	115
6.1.1	Definitions	116
6.1.2	Assumptions	116
6.2	The Proposed Leader Election Method	117
6.2.1	Identification and prioritization of the quality attributes	117
6.2.2	The leader election algorithm	119
6.2.3	Proof of Self-stabilization	124
6.2.4	Complexity analysis	130
6.2.4.1	Message complexity	130
6.2.4.2	Time complexity	131
6.2.4.3	Bit complexity	131
6.2.5	Illustrative Example	132
6.3	Experiment and result analysis	137
6.4	Summary	143
7	Conclusion and Future Directions	145
7.1	Conclusion	145
7.2	Future Research Directions	148

Bibliography	150
---------------------	------------

List of Figures

1.1	The classical architecture of a distributed system	3
1.2	The client-server architecture of a distributed system	6
1.3	The peer-to-peer architecture of a distributed system	7
1.4	Thesis Structure.	15
2.1	A $T_{4,4}$ network, every column of which is arranged in decreasing order according to the node Id.	28
3.1	All the nodes are connected through a bidirectional ring topology. h, i, j and k are four subsequent nodes in this ring.	40
3.2	Illustrative example of the proposed election algorithm when failed leader recovers during the election.	48
3.3	Illustrative example of the proposed election algorithm when failed leader does not recover during the election.	50
3.4	In the best and worst cases, the total number of exchanged messages of different leader election algorithms.	55
3.5	In the best and worst cases, the total election time of different leader election algorithms.	55
4.1	Details of a $2D$ torus network.	60
4.2	Building a ternary tree from a (4×4) $2D$ torus network	62
4.3	Message sending patterns	68
4.4	Example of the remaining $T_{8,8}$ network, after deleting 48 links from the $T_{8,8}$ network in the manner described above.	78
4.5	Example of the remaining $T_{9,9}$ network, after deleting 60 links from the $T_{9,9}$ network in the manner described above.	79
4.6	Different steps of the election process of the Lea-TN algorithm explained on a 5×5 $2D$ torus network with some link and node failures.	88
4.7	A $T_{4,4}$ network, every column of which is arranged in decreasing order according to the node ID.	92
4.8	These figures represent the simulation results of the ‘‘LEA with One Link Failure [94]’’, the ‘‘Dynamic LEA with Multi Links Failure [8]’’ and the ‘‘Lea-TN algorithm’’ without considering the link failures. Figures (a) and (b) represent the graph of the number of messages exchanged in the best case and worst case, respectively, whereas (c) depicts the time taken to conduct the election.	92

4.9	These figures represent the simulation results of the Lea-TN algorithm considering $N - 2\sqrt{N} - 3$ (if N is odd) or $N - 2\sqrt{N}$ (if N is even) link failures. Here, case 1 represents the scenario where one node with the highest leader factor initiates the election, and case 2 represents the scenario where all nodes initiate the election simultaneously. Graphs in (a) represent the number of exchanged messages by the Lea-TN algorithm to elect a leader in case 1 and case 2. The graph in (b) depicts the time taken to conduct the election both in case 1 and case 2.	93
4.10	These figures represent the simulation results of the Lea-TN algorithm considering the different number of link failures. Here, the x-axis represents the number of link failures, and the y-axis represents the number of exchanged messages to elect the leader. In these figures, N refers to the total number of nodes in a system. Graph (a) represents the simulation result where the node with the highest leader factor initiates the election. Graph (b) represents the simulation result where all the nodes initiate the election simultaneously.	93
5.1	An arbitrary network consisting of 12 nodes and 15 links.	100
5.2	(a) is an arbitrary network consisting of 12 nodes and 15 links. (b), (c), (d), (e) and (f) are the several steps of the proposed algorithm to identify the higher potential nodes of the inner layer.	107
5.3	The total number of exchanged messages required by different algorithms to complete the election process. (a) and (b) represent the number of exchanged messages in the best case and worst case, respectively. (c) and (d) represent the required time in the best case and worst case, respectively	112
5.4	The total time required by different algorithms to complete the election process. (a) and (b) represent the required time in the best case and worst case, respectively	112
6.1	(a) A distributed system consisting of 7 nodes and 9 edges. (b), (c), (d), (e), (f), (g), (h), (i), (j) and (k) are the different steps of the proposed leader election algorithm to elect the leader for the system.	135
6.2	Node and link failures in the network.	136
6.3	(a) eight replicated servers connected through an arbitrary network topology, (b) ten replicated servers connected through an arbitrary network topology and (c) twelve replicated servers connected through an arbitrary network topology	139
6.4	Performance comparison of the PALE algorithm and the proposed algorithm. (a) and (b) show the required time to elect the leader in the best case and worst case, respectively. (c) and (d) show the number of exchanged messages to elect the leader in the best case and worst case, respectively.	143

List of Tables

2.1	The corresponding detour routing for each link failure of a node	28
3.1	Message complexity in terms of O-notation of N and number of exchanged messages in terms of N , where N is the total number of nodes.	56
3.2	Time complexity in terms of O-notation of N and number of required time steps in terms of N , where N is the total number of nodes. . . .	57
4.1	List for store the information of adjacent node and link failures of a node i	66
4.2	This table represents a comparative study between the Lea-TN algorithm and the other existing algorithms that work on different networks. Comparison parameters are message complexity, time complexity, network topology, total number of links, and maximum link failure tolerability. Here, N is the total number of nodes in the system, and complexities are represented using Big O-notation.	95
5.1	Details of the arbitrary network shown in Figure 5.2 (<i>a</i>)	106
5.2	Details of the different arbitrary networks for the simulation.	111
6.1	Time complexity and message complexity in the best case and worst-case scenarios of the proposed algorithm in different regular network topologies.	132
6.2	The weight given by the experts, the minimum value and the maximum value of the attributes.	139
6.3	Information of all the nodes of the system consisting of 8 nodes and 9 links.	139
6.4	Information of all the nodes of the system consisting of 10 nodes and 13 links.	140
6.5	Information of all the nodes of the system consisting of 12 nodes and 22 links.	140