

Contents

List of Figures	xv
List of Tables	xviii
List of Symbols	xx
List of Abbreviations	xxii
Preface	xxiv
1 Introduction	1
1.1 Motivation of the research work	5
1.2 Contributions and organization of the thesis	7
2 Preliminaries and related work	13
2.1 Preliminaries	13
2.1.1 Overview of Fog computing	13
2.1.2 Overview of learning techniques	15
2.2 Related work on task offloading in Fog computing	16
2.3 Related work on seen and unseen classes in dataset	18
2.4 Related work on noisy labels in dataset	21
2.5 Related work on federated learning with heterogeneous participants	23
3 An unseen locomotion mode identification model using multiple semantic matrices	27
3.1 Introduction	27
3.1.1 Motivation of this work	29
3.1.2 Major contributions	30
3.2 Preliminary	31
3.2.1 Problem statement and overview of solution	31

3.3	DeepZero model	32
3.3.1	Construction of attribute matrix	33
3.3.2	Feature extraction	36
3.3.3	Classifier construction	37
3.3.4	Prediction of class label	41
3.4	Feature extraction using deep learning	42
3.4.1	Convolution layer	45
3.4.2	LSTM unit	45
3.5	Evaluation of DeepZero model	46
3.5.1	Data collection	46
3.5.2	SHL dataset	48
3.5.3	Parameter settings during implementation	48
3.5.4	Experimental results	48
3.5.5	Comparison with existing approaches	53
3.6	Conclusion	54
4	A locomotion mode recognition approach with noisy labels	57
4.1	Introduction and major contributions	57
4.2	Preliminaries	60
4.3	LRNL approach	61
4.3.1	Conventional model	62
4.3.2	Noise adaptive model	64
4.3.3	Noise corrective model	67
4.3.4	Ensemble model	72
4.4	Experimental evaluation of LRNL approach	74
4.4.1	Data collection	74
4.4.2	Existing dataset	74
4.4.3	Parameter settings during implementation	75
4.4.4	Experimental results	76
4.4.5	Comparison with existing approaches	82
4.5	Conclusion	83
5	A game theory-based passenger assistance system using Fog computing	85
5.1	Introduction	86
5.2	Preliminary and network topology	89
5.2.1	Network Topology	89

5.2.2	Transmission and computation delays	89
5.2.3	Reputation model	91
5.3	TSF system	92
5.3.1	Phase 1: Selection of secondary Fog devices	92
5.3.2	Phase II: Task offloading	93
5.4	Competitive game model for task offloading	95
5.4.1	Utility of primary Fog device	95
5.4.2	Utility of secondary Fog device	98
5.4.3	Near Nash Equilibrium (NE) between s-FDs:	103
5.5	Prototype setup and performance evaluation	105
5.5.1	Impact of data size	107
5.5.2	Impact of secondary Fog devices	108
5.5.3	Impact of deadline	109
5.5.4	Impact of game parameters	109
5.5.5	Comparison with existing work	110
5.6	Conclusion	112
6	A federated learning technique with heterogeneous devices and networking resources	113
6.1	Introduction	113
6.2	FFL technique	117
6.2.1	Model selection on central server	118
6.2.2	Model training on participant devices	119
6.2.3	Aperiodic global update	122
6.2.4	Deriving expression for halting epoch	125
6.3	Real-world study	129
6.3.1	Participants devices and central server in real-world study	129
6.3.2	Task of study: Locomotion Mode Recognition	130
6.3.3	Challenges observed during study	130
6.4	Performance Evaluation	131
6.4.1	Datasets	131
6.4.2	Baseline techniques	131
6.4.3	Implementation details	132
6.4.4	Validation metrics	133
6.4.5	Experimental results	133
6.5	Conclusion	141

7 Conclusion and future work	143
References	147
List of publications	159

List of Figures

1.1	An illustration of smartphones applications in smart transport.	2
1.2	Example scenarios: (a) seen and unseen locomotion modes and (b) locomotion modes with noisy labels.	3
2.1	An illustration of Fog computing architecture with the hierarchical arrangement of Edge, Fog, and Cloud layers.	14
3.1	An example of locomotion mode recognition using a deep learning based classifier and zero-shot learning.	28
3.2	Overview of DeepZero model.	32
3.3	An example of human-annotated semantic matrix.	34
3.4	Construction of attribute matrix by fusing three semantic matrices. . .	36
3.5	Prediction of class label of a testing instance in DeepZero model.	42
3.6	Feature extraction framework using CNN and LSTM.	44
3.7	User interface of developed application for data collection.	47
3.8	Performance results on LMR and SHL datasets during training.	49
3.9	Performance of the proposed approach for seen classes	50
3.10	Performance of the proposed approach for unseen classes where features are extracted from combination of CNN-LSTM, LSTM, and CNN models. 51	
3.11	Accuracy results of DeepZero with multiple unseen classes.	52
3.12	Impact of attribute matrix on performance for LMR dataset.	52
3.13	Comparison of DeepZero model with existing approaches	54
3.14	Comparison of accuracy results for DeepZero model with its three versions and Nuactive using LMR and SHL datasets.	55
4.1	An example of locomotion mode recognition with noisy labels	58
4.2	Block diagram of LRNL approach with its components.	62
4.3	Overview of conventional model using CNN and LSTM.	64
4.4	Performance results on LMR, SHL, and TMD datasets during training	77

4.5	Value of fractional weights on LMR, SHL, and TMD datasets	78
4.6	Class-wise accuracy of LRNL approach on LMR and SHL datasets with different noise concentrations.	79
4.7	Impact of noisy labels distribution on class-wise accuracy	81
5.1	An example of transportation system using Fog computing.	87
5.2	Network topology for the TSF system	91
5.3	Iterations for convergence of algorithm with 5 FDs	105
5.4	Prototype components: (1) PCs organization, (2) deployment area, (3) smartphone, (4) router, (5) PC in lab, and (6) DELL server	106
5.5	Illustration of p-FD, CL, and TSF schemes.	107
5.6	Impact of data size on delay and system cost using different schemes. .	108
5.7	Impact of s-FDs count on delay, system cost, and FDs utilities.	109
5.8	Impact of change in game parameters	111
5.9	Illustration of comparison with existing work	112
6.1	A scenario of FL with heterogeneous resources	114
6.2	Illustration of the framework for FFL technique	118
6.3	Early halting of the training of the generic model.	122
6.4	Participants devices and central server in real-world study	130
6.5	Illustration of devices and networking resources	135
6.6	Illustration of the requirement of resources for resizing and training . .	136
6.7	Illustration of the accuracy, F_1 -score, and leave-one-out test	138
6.8	Impact of ratio of time threshold with global iteration time interval. . .	141

List of Tables

2.1	An illustration of the existing work on task partitioning and offloading in Fog computing.	18
2.2	Summary of existing literature on mechanisms of handling seen and unseen classes.	20
2.3	A comparative summary of the existing work for handling noisy labels in the dataset.	23
2.4	A comparative summary of existing literature on FL with heterogeneous participants.	25
3.1	Characteristics used in human-annotated semantic matrix.	49
4.1	Performance results of LRNL approach on LMR, SHL, and TMD datasets at different noise concentrations.	78
4.2	Performance of conventional, noise adaptive, and noise corrective models	80
4.3	Accuracy variations of LRNL on collected LMR and SHL datasets . . .	82
4.4	Accuracy comparison of LRNL approach with existing approaches . . .	84
5.1	Accuracy metrics for p-FD, CL, and proposed schemes.	110
6.1	Impact of early halting on participants of \mathbf{T}_7 category.	139
6.2	Fractional contributions of different loss functions on participants . . .	139
6.3	Impact of early halting on participants of \mathbf{T}_3 category.	140