

TABLE OF CONTENTS

| Contents | Page No. |
|--|-----------------|
| Certificates | i-iii |
| Acknowledgement | v-vi |
| Abstract | vii-viii |
| Table of Content | |
| List of Table | xiii |
| List of Figures | xv-xviii |
| Nomenclature | xix-xx |
| Chapter 1 | 1 |
| Introduction and Literature Review | 1 |
| 1.1 Introduction to Electric Automated Manual Transmission (<i>e</i> -AMT) Technology | 2 |
| 1.2 Motivation and Problem Statement | 3 |
| 1.3 Literature Review | 4 |
| 1.3.1 Maintenance Philosophy | 5 |
| 1.3.2 Condition based Maintenance in Auto Industry | 7 |
| 1.3.2.1 Time domain analysis | 12 |
| 1.3.2.2 Frequency Domain Analysis | 14 |
| 1.3.2.3 Time-Frequency Analysis | 14 |
| 1.3.3 Modelling Approaches | 16 |
| 1.3.3.1 Stochastic Modelling Approach | 17 |
| 1.3.3.2 Adaptive Approach | 19 |
| 1.4 Objectives of the Work | 22 |
| 1.5 Organized Structure of the Thesis | 22 |
| Chapter 2 | 25 |
| Remaining Useful Life Methodology | 25 |
| 2.1 Introduction | 25 |
| 2.2 Definition of RUL | 27 |
| 2.3 Theory of RUL Estimation | 27 |
| 2.4 Past RUL Works | 32 |

| | |
|---|-----------|
| Chapter 3 | 37 |
| Experimental Setup and Data Acquisition | 37 |
| 3.1 Introduction | 37 |
| 3.2 Preparation of Experimental Setup | 38 |
| 3.3 Data Generation | 43 |
| 3.4 Role of Motor | 47 |
| 3.4.1 Advantages of PMDC motor | 47 |
| 3.5 Evaluation Criterion | 50 |
| Chapter-4 | 53 |
| Data driven Methodology-Mathematical Background and Associated Computation | 53 |
| 4.1 Introduction | 53 |
| 4.2 Overview of the Data Pre-Processing | 54 |
| 4.2.1 Data Processing | 56 |
| 4.2.1.1 Feature Extraction | 57 |
| 4.2.1.2 Smoothing | 58 |
| 4.2.2 FIR and Health Indicator Determination | 59 |
| 4.2.3 Feature Fusion using PCA | 59 |
| 4.3 Stochastic Approach | 61 |
| 4.3.1 Exponential Degradation Modelling and RUL Prediction | 61 |
| 4.3.2 RUL Computation | 62 |
| 4.4 Adaptive Filtering Technique | 62 |
| 4.4.1 Particle Filter | 63 |
| 4.4.2 Unscented Particle Filter and Improved Unscented Particle Filter | 65 |
| 4.4.2.1 Unscented Particle Filter (UPF) | 66 |
| 4.4.2.2 Improved Unscented Particle Filter (i-UPF) | 68 |
| 4.4.3 Resampling Methodology | 68 |
| 4.4.3.1 Multinomial resampling | 69 |
| 4.4.3.2 Stratified resampling | 69 |
| 4.4.3.3 Systematic resampling | 70 |
| 4.4.3.4 Residual resampling | 70 |
| 4.4.4 RUL Estimation Strategy | 71 |

| | |
|--|------------|
| Chapter 5 | 73 |
| Data Analysis for RUL Estimation | 73 |
| 5.1 Introduction | 73 |
| 5.2 Experimental Details | 73 |
| 5.2.1 Waveforms of the Accelerated Life Cycle Test Data | 74 |
| 5.2.1.1 Strategy I: (50%-70%) | 75 |
| 5.2.1.2 Strategy II: (75%-80%) | 77 |
| 5.2.1.3 Strategy III: (80%-85%) | 81 |
| 5.3 Results and Discussion | 84 |
| 5.3.1 Feature Extraction and Smoothing | 84 |
| 5.3.2 FIR and Condition Indicator | 87 |
| 5.3.3 Stochastic Approach | 90 |
| 5.3.3.1 Exponential Degradation Model and RUL Computation | 90 |
| 5.3.3.2 Performance Analysis | 93 |
| 5.3.4 Adaptive filtering | 96 |
| 5.3.4.1 Strategy-I: (50%-70%) | 96 |
| A. Particle Filter | 97 |
| B. Unscented Particle Filter | 99 |
| C. Improved Unscented Particle Filter | 100 |
| 5.3.4.2 Strategy-II: (75%-80%) | 102 |
| A. Particle Filter | 102 |
| B. Unscented Particle Filter | 104 |
| C. Improved Unscented Particle Filter | 105 |
| 5.3.4.3 Strategy-III: (80%-85%) | 107 |
| A. Particle Filter | 107 |
| B. Unscented Particle Filter | 109 |
| C. Improved Unscented Particle Filter | 110 |
| 5.3.5 Comparison of Prognostic Accuracy Results | 112 |
| 5.4 Summary | 114 |
| Chapter 6 | 115 |
| Comparison of Particle Filter Variants towards RUL Estimation | 115 |
| 6.1 Introduction | 115 |

| | | |
|-------|--|------------|
| 6.2 | Results and Discussion | 116 |
| 6.2.1 | Comparative Results of Resampling Study | 116 |
| 6.2.2 | Optimal Choice of c -value | 122 |
| 6.2.3 | Comparative RUL prediction results of Strategy–I dataset | 124 |
| 6.2.4 | Comparative RUL prediction results of Strategy–II dataset | 125 |
| 6.2.5 | Comparative RUL prediction results of Strategy–III dataset | 126 |
| 6.3 | Verification and Validation | 128 |
| 6.3.1 | Battery Data Set - B0005 | 128 |
| 6.3.2 | Battery Data Set - B0006 | 130 |
| 6.3.3 | Battery Data Set - B0007 | 131 |
| 6.3.4 | Battery Data Set - B0018 | 132 |
| 6.4 | Summary | 134 |
| | Chapter 7 | 135 |
| | Overall Conclusion and Future Scope of Work | 135 |
| 7.1 | Overall Conclusion | 135 |
| 7.2 | Future Scope of Work | 136 |
| | References | 139 |
| | About the Author | 158 |
| | List of Publications | 162 |

LIST OF TABLES

| Table No. | Title | Page No. |
|------------------|---|-----------------|
| Table 1.1 | Industrial Maintenance Practices | 5 |
| Table 2.1 | Data-driven prognostic models for RUL estimation | 28 |
| Table 3.1 | Sensors used during experimentation | 43 |
| Table 3.2 | Sample dataset from HIL experiment | 46 |
| Table 3.3 | Specifications of Motor | 49 |
| Table 3.4 | Specifications of Motor Controller | 50 |
| Table 4.1 | List of extracted features considered in the study | 57 |
| Table 5.1 | Empirically fitted values of the exponential degradation model | 91 |
| Table 5.2 | Prognostic Accuracy Results | 95 |
| Table 5.3 | Empirically fitted cubic polynomial parameters | 96 |
| Table 5.4 | Empirically fitted parameters | 102 |
| Table 5.5 | Empirically fitted parameters | 107 |
| Table 5.6 | Prognostic Accuracy results for Strategy-I | 112 |
| Table 5.7 | Prognostic Accuracy results for Strategy-II | 113 |
| Table 5.8 | Prognostic Accuracy results for Strategy-III | 113 |
| Table 6.1 | Comparison of Quantitative Resampling Results from Strategy-I | 118 |
| Table 6.2 | Comparison of Quantitative Resampling Results from Strategy-II | 119 |
| Table 6.3 | Comparison of Quantitative Resampling Results from Strategy-III | 121 |
| Table 6.4 | Choice of best Resampling for Strategy-I dataset | 124 |
| Table 6.5 | Choice of best Resampling for Strategy-II dataset | 125 |
| Table 6.6 | Choice of best Resampling for Strategy-III dataset | 126 |
| Table 6.7 | B0005-Prognostic Accuracy Results | 130 |
| Table 6.8 | B0006-Prognostic Accuracy Results | 131 |
| Table 6.9 | B0007-Prognostic Accuracy Results | 132 |
| Table 6.10 | B0018-Prognostic Accuracy Results | 134 |

LIST OF FIGURES

| Figure No. | Title | Page No. |
|-------------|--|----------|
| Fig. 1.1 | <i>e</i> -AMT vehicle drive train | 2 |
| Fig. 1.2 | <i>e</i> -AMT motor prognostics | 3 |
| Fig. 1.3 | Increase in asset reliability in using PdM | 7 |
| Fig. 1.4 | Visualizing the prognostics workflow to RUL as a decision making | 8 |
| Fig. 1.5 | Diagram featuring Prognostics and Diagnostics | 9 |
| Fig. 1.6 | Schematic of the major contributions | 21 |
| Fig. 2.1 | Schematic of RUL Prediction | 25 |
| Fig. 2.2 | Data-driven remaining useful life estimation approaches in the present study | 28 |
| Fig. 3.1 | Components of an <i>e</i> -AMT set-up | 37 |
| Fig. 3.2 | System Schematic of <i>e</i> -AMT consisting of ECU, Sensors and Actuators | 39 |
| Fig. 3.3 | Transmission Control Unit Architecture | 40 |
| Fig. 3.4 | Experimental Set-up | 41 |
| Fig. 3.5(a) | Schematic diagram of 12V, 0.5kW PMDC clutch motor actuator assembly with electronic control unit | 44 |
| Fig. 3.5(b) | Clutch sensor position during engagement-disengagement | 44 |
| Fig. 3.6(a) | PMDC Motor | 48 |
| Fig. 3.6(b) | Circuit diagram of a PMDC motor | 48 |
| Fig. 4.1 | Schematic of data-driven RUL estimation methodologies | 53 |
| Fig. 4.2 | Prognostics Protocol Module | 55 |
| Fig. 4.3 | Flowchart of the proposed approach | 56 |
| Fig. 4.4 | Illustration of particle filter variants in motor health prognosis | 63 |
| Fig. 5.1 | Sample representation of a 50% -70% duty cycle input to the motor | 75 |
| Fig. 5.2 | Sample representation of motor current response for 50% - 70% duty cycle | 75 |
| Fig. 5.3 | Sample plot of actuator position (degrees) during 50% -70% duty cycle | 76 |
| Fig. 5.4(a) | Magnified sample plot representing clutch Disengagement | 76 |
| Fig. 5.4(b) | Magnified sample plot representing clutch Engagement | 76 |
| Fig. 5.5 | Variation of duty, current and actuator position for a sample clutch engagement cycle | 77 |
| Fig. 5.6 | Variation of duty, current and actuator position for a sample clutch dis-engagement cycle | 77 |
| Fig. 5.7 | Sample representation of a 75% -80% duty cycle input to the motor | 78 |

| | | |
|--------------|---|----|
| Fig. 5.8 | Sample representation of motor current response for 75% - 80% duty cycle | 78 |
| Fig. 5.9 | Sample plot of actuator position (degrees) during 75% -80% duty cycle | 79 |
| Fig. 5.10(a) | Magnified sample plot representing clutch Disengagement | 79 |
| Fig. 5.10(b) | Magnified sample plot representing clutch Engagement | 79 |
| Fig. 5.11 | Variation of duty, current and actuator position for a sample clutch engagement cycle | 80 |
| Fig. 5.12 | Variation of duty, current and actuator position for a sample clutch dis-engagement cycle | 80 |
| Fig. 5.13 | Sample representation of an 80% -85% duty cycle input to the motor | 81 |
| Fig. 5.14 | Sample representation of motor current response for 80% - 85% duty cycle | 82 |
| Fig. 5.15 | Sample plot of actuator position (degrees) during 80% -85% duty cycle | 82 |
| Fig. 5.16(a) | Magnified sample plot representing clutch Disengagement | 83 |
| Fig. 5.16(b) | Magnified sample plot representing clutch Engagement | 83 |
| Fig. 5.17 | Variation of duty, current and actuator position for a sample clutch engagement cycle | 83 |
| Fig. 5.18 | Variation of duty, current and actuator position for a sample clutch engagement cycle | 84 |
| Fig. 5.19 | Steps of data pre-processing | 85 |
| Fig. 5.20(a) | Smoothened features of the sensor data using classical time domain, frequency domain and time-frequency domain methods Strategy-I | 86 |
| Fig. 5.20(b) | Smoothened features of the sensor data using classical time domain, frequency domain and time-frequency domain methods Strategy-II | 86 |
| Fig. 5.20(c) | Smoothened features of the sensor data using classical time domain, frequency domain and time-frequency domain methods Strategy-III | 87 |
| Fig. 5.21(a) | Ranking of the important pre-processed features Strategy-I | 88 |
| Fig. 5.21(b) | Ranking of the important pre-processed features Strategy-II | 88 |
| Fig. 5.21(c) | Ranking of the important pre-processed features Strategy-III | 89 |
| Fig. 5.22 | Condition indicators for all three strategies obtained after feature fusion | 90 |
| Fig. 5.23 | Bayesian updating of model parameters | 91 |
| Fig. 5.24(a) | Predicted RUL using exponential degradation model Strategy-I | 92 |
| Fig. 5.24(b) | Predicted RUL using exponential degradation model Strategy-II | 92 |

| | | |
|--------------|--|-----|
| Fig. 5.24(c) | Predicted RUL using exponential degradation model Strategy-III | 92 |
| Fig. 5.25(a) | Plot of estimated RUL and true RUL for Strategy-I | 94 |
| Fig. 5.25(b) | Plot of estimated RUL and true RUL for Strategy-II | 94 |
| Fig. 5.25(c) | Plot of estimated RUL and true RUL for Strategy-III | 95 |
| Fig. 5.26 | State prediction scheme using Particle Filter for Strategy-I | 98 |
| Fig. 5.27 | Histogram of RUL for Strategy-I | 98 |
| Fig. 5.28 | State prediction scheme using Unscented Particle Filter for Strategy-I | 99 |
| Fig. 5.29 | Histogram of RUL for Strategy-I | 100 |
| Fig. 5.30 | State prediction scheme using Improved Unscented Particle Filter for Strategy-I | 101 |
| Fig. 5.31 | Histogram of RUL for Strategy-I | 101 |
| Fig. 5.32 | State prediction scheme using Particle Filter for Strategy-II | 103 |
| Fig. 5.33 | Histogram of RUL for Strategy-II | 103 |
| Fig. 5.34 | State prediction scheme using Unscented Particle Filter for Strategy-II | 104 |
| Fig. 5.35 | Histogram of RUL for Strategy-II | 105 |
| Fig. 5.36 | State prediction scheme using Improved Unscented Particle Filter for Strategy-II | 106 |
| Fig. 5.37 | Histogram of RUL for Strategy-II | 106 |
| Fig. 5.38 | State prediction scheme using Particle Filter for Strategy-III | 108 |
| Fig. 5.39 | Histogram of RUL for Strategy-III | 108 |
| Fig. 5.40 | State prediction scheme for Unscented Particle Filter for Strategy-III | 109 |
| Fig. 5.41 | Histogram of RUL for Strategy-III | 110 |
| Fig. 5.42 | State prediction scheme for Improved Unscented Particle Filter for Strategy-III | 111 |
| Fig. 5.43 | Histogram of RUL for Strategy-III | 111 |
| Fig. 6.1 | Comparison of resampling plots in case of <i>i</i> -UPF for Strategy-I dataset | 119 |
| Fig. 6.2 | Comparison of resampling plots in case of <i>i</i> -UPF for Strategy-II dataset | 120 |
| Fig. 6.3 | Comparison of resampling plots in case of <i>i</i> -UPF for Strategy-III dataset | 122 |
| Fig. 6.4 | Optimal choice of <i>c</i> -value for Strategy-I | 123 |
| Fig. 6.5 | Optimal choice of <i>c</i> -value for Strategy-II | 123 |
| Fig. 6.6 | Optimal choice of <i>c</i> -value for Strategy-III | 123 |
| Fig. 6.7 | Comparison of PF, UPF and <i>i</i> -UPF using Strategy-I dataset for motor RUL prediction | 125 |
| Fig. 6.8 | Comparison of PF, UPF and <i>i</i> -UPF using Strategy-II dataset for motor RUL prediction | 126 |

| | | |
|--------------|---|-----|
| Fig. 6.9 | Comparison of PF, UPF and <i>i</i> -UPF using Strategy-III dataset for motor RUL prediction | 127 |
| Fig. 6.10(a) | PF based state prediction for B0005 battery | 129 |
| Fig. 6.10(b) | PF based RUL estimation for B0005 battery | 129 |
| Fig. 6.11(a) | UPF based state prediction for B0005 battery | 129 |
| Fig. 6.11(b) | UPF based RUL estimation for B0005 battery | 129 |
| Fig. 6.12(a) | <i>i</i> -UPF based state prediction for B0005 battery | 129 |
| Fig. 6.12(b) | <i>i</i> -UPF based RUL estimation for B0005 battery | 129 |
| Fig. 6.13(a) | PF based state prediction for B0006 battery | 130 |
| Fig. 6.13(b) | PF based RUL estimation for B0006 battery | 130 |
| Fig. 6.14(a) | UPF based state prediction for B0006 battery | 130 |
| Fig. 6.14(b) | UPF based RUL estimation for B0006 battery | 130 |
| Fig. 6.15(a) | <i>i</i> -UPF based state prediction for B0006 battery | 131 |
| Fig. 6.15(b) | <i>i</i> -UPF based RUL prediction for B0006 battery | 131 |
| Fig. 6.16(a) | PF based state prediction for B0007 battery | 131 |
| Fig. 6.16(b) | PF based RUL estimation for B0007 battery | 131 |
| Fig. 6.17(a) | UPF based state prediction for B0007 battery | 132 |
| Fig. 6.17(b) | UPF based RUL estimation for B0007 battery | 132 |
| Fig. 6.18(a) | <i>i</i> -UPF based state prediction for B0007 battery | 132 |
| Fig. 6.18(b) | <i>i</i> -UPF based RUL prediction for B0007 battery | 132 |
| Fig. 6.19(a) | PF based state prediction for B0018 battery | 133 |
| Fig. 6.19(b) | PF based RUL estimation for B0018 battery | 133 |
| Fig. 6.20(a) | UPF based state prediction for B0018 battery | 133 |
| Fig. 6.20(b) | UPF based RUL estimation for B0018 battery | 133 |
| Fig. 6.21(a) | <i>i</i> -UPF based state prediction for B0018 battery | 133 |
| Fig. 6.21(b) | <i>i</i> -UPF based RUL prediction for B0018 battery | 133 |