

## FIGURES

<b>Fig. 1.1:</b> A schematic of proposed processing route for battery waste	27
<b>Fig. 2.1.</b> Relative frequency distribution of LIB electrode powder vs diameter (in $\mu\text{m}$ ) for particle size analysis	54
<b>Fig. 2.2:</b> XRD pattern of the cathode active material of spent LIBs along with the identified phases	56
<b>Fig. 2.3:</b> SEM-EDAX with elemental analysis of cathode active material of spent LIBs	57
<b>Fig. 2.4:</b> SEM-EDAX analysis with mapping of constituent elements in cathode material of spent LIBs	58
<b>Fig. 2.5.</b> Relative frequency distribution of NiMH battery electrode powder vs diameter (in $\mu\text{m}$ ) for particle size analysis	60
<b>Fig. 2.6:</b> XRD of the spent Ni-MH battery electrode powder	61
<b>Fig. 2.7:</b> SEM-EDAX of the spent NiMH battery electrode powder	62
<b>Fig. 2.8:</b> SEM-EDAX analysis with mapping of the constituent elements in the spent Ni-MH battery material	63
<b>Fig. 3.1:</b> Eh-pH diagram for [a] Li-H <sub>2</sub> O, [b] Ni- H <sub>2</sub> O, [c] Co- H <sub>2</sub> O and [d] Mn- H <sub>2</sub> O system at 298 K	69
<b>Fig. 3.2:</b> Effect of acid concentration on the leaching of cathode active material (a) HCl, (b) H <sub>2</sub> SO <sub>4</sub> , 368 K, 50 g/L pulp density, 240 min.	71
<b>Fig. 3.3:</b> Effect of time on the leaching of metals using 1 M H <sub>2</sub> SO <sub>4</sub> at 368 K and 50 g/L pulp density.	72
<b>Fig. 3.4:</b> Effect of stirring speed on the recovery of metals from cathode active material using 1 M H <sub>2</sub> SO <sub>4</sub> at 368, 50 g/L PD and 240 min	73
<b>Fig. 3.5:</b> Effect of pulp density on the leaching of cathode active material using 1 M H <sub>2</sub> SO <sub>4</sub> at 368 K in 240 min.	74
<b>Fig. 3.6:</b> Effect of temperature on the leaching of cathode active material using 1 M H <sub>2</sub> SO <sub>4</sub> at 50 g/L in 240 min.	75
<b>Fig. 3.7:</b> Recovery of Li, Co, Ni and Mn from spent cathode active material at various temperatures using 1M H <sub>2</sub> SO <sub>4</sub> at 50 g/L in 240 min	76
<b>Fig. 3.8:</b> Chemical controlled kinetic model for the leaching of metals (a- Li, b-Co, c-Ni, d-Mn) in temperature range (308 -368 K)	78
<b>Fig. 3.9:</b> Diffusion controlled kinetic model for the leaching of metals (a- Li, b-Co, c-Ni, d-Mn) in temperature range (308-368 K)	79
<b>Fig. 3.10:</b> Empirical model for kinetics of leaching metals (a- Li, b-Co, c-Ni, d-Mn) in temperature range (308-368 K)	80
<b>Fig. 3.11:</b> Arrhenius plot for empirical kinetic model applied for lithium, cobalt and nickel	81
<b>Fig. 3.12:</b> XRD pattern of the residues obtained in leaching at 368 K and 50 g/L PD in 60 min (a), 120 min (b), and 240 min (c).	83

<b>Fig. 3.13:</b> SEM-EDAX analysis of head sample (A) and residues in 60 min (B), 120 min (C) and 240 min (D) leaching with 1 M H <sub>2</sub> SO <sub>4</sub> at 368 K and 50% PD	84
<b>Fig. 3.14:</b> Effect of NaHSO <sub>3</sub> concentration on the leaching of metals from cathodic powder in 1 M H <sub>2</sub> SO <sub>4</sub> at 368 K and 20 g/L pulp density in 240 min.	86
<b>Fig. 3.15:</b> Effect of time on the leaching of metals using 1 M H <sub>2</sub> SO <sub>4</sub> and 0.075 M NaHSO <sub>3</sub> at 368 K and 20 g/L pulp density.	87
<b>Fig. 3.16:</b> Effect of pulp density on the leaching of cathode active material using 1 M H <sub>2</sub> SO <sub>4</sub> and 0.075 M NaHSO <sub>3</sub> at 368 K in 240 min.	89
<b>Fig. 3.17:</b> Effect of temperature on the leaching of metals from the cathode material using 1 M H <sub>2</sub> SO <sub>4</sub> and 0.075 M NaHSO <sub>3</sub> in 240 min at 20 g/L pulp density.	89
<b>Fig. 3.18:</b> Effect of temperature on the recovery of different metals from LIBs at different time intervals	91
<b>Fig. 3.19:</b> Chemical controlled kinetic model for the leaching of metals (a- Li, b-Co, c-Ni, d-Mn) by NaHSO <sub>3</sub> -H <sub>2</sub> SO <sub>4</sub> in temperature range (308-368 K)	93
<b>Fig. 3.20:</b> Diffusion controlled kinetic model for the leaching of metals (a- Li, b-Co, c-Ni, d-Mn) by NaHSO <sub>3</sub> -H <sub>2</sub> SO <sub>4</sub> in temperature range (308-368 K)	94
<b>Fig. 3.21:</b> Empirical model for the leaching of metals (a- Li, b-Co, c-Ni, d-Mn) by NaHSO <sub>3</sub> -H <sub>2</sub> SO <sub>4</sub> in temperature range (308-368 K)	95
<b>Fig. 3.22:</b> Arrhenius plot for the leaching of the metals from LIBs in the temperature range 308-368 K	96
<b>Fig. 3.23:</b> SEM-EDAX analysis of residue at 240 min with mapping of constituent elements	97
<b>Fig. 3.24:</b> Effect of concentration of H <sub>2</sub> O <sub>2</sub> on leaching of Li, Co, Ni and Mn from cathode active material using 1M H <sub>2</sub> SO <sub>4</sub> , 20 g/L pulp density at 368 K in 240 min	99
<b>Fig.3.25:</b> Eh-pH diagrams (368 K) for H <sub>2</sub> O <sub>2</sub> system: (a) Li-SO <sub>4</sub> , (b) Co-SO <sub>4</sub> , (c) Mn-SO <sub>4</sub> , (d) Ni-SO <sub>4</sub> , in presence of other elements	101
<b>Fig. 3.26:</b> Effect of pulp density on the leaching of metals using 1 M H <sub>2</sub> SO <sub>4</sub> and 5% H <sub>2</sub> O <sub>2</sub> at 368 K in 240 min.	102
<b>Fig. 3.27:</b> Effect of time on the leaching of metals using 1 M H <sub>2</sub> SO <sub>4</sub> and 5% H <sub>2</sub> O <sub>2</sub> at 368 K and 50 g/L pulp density.	103
<b>Fig. 3.28</b> Effect of temperature on leaching of metals in the presence of H <sub>2</sub> O <sub>2</sub> as the reductant at 50 g/L pulp density and 1 M H <sub>2</sub> SO <sub>4</sub> in 240 min.	104
<b>Fig. 3.29:</b> Empirical model in leaching of metals (a- Li, b-Co, c-Ni, d-Mn) by H <sub>2</sub> O <sub>2</sub> -H <sub>2</sub> SO <sub>4</sub> in temperature range (308-368 K)	105

<b>Fig. 3.30:</b> Arrhenius plot for the leaching of Li, Co, Ni and Mn from cathode active material of LIBs at 368 K in presence of H <sub>2</sub> O <sub>2</sub>	106
<b>Fig. 3.31:</b> XRD analysis of residue after treatment of spent cathode powder in 1 M H <sub>2</sub> SO <sub>4</sub> and 5% H <sub>2</sub> O <sub>2</sub> in (a) 1 h, (b) 2 h at 368 K and 50 g/L pulp density	107
<b>Fig. 3.32:</b> SEM-EDAX of leach residue with H <sub>2</sub> O <sub>2</sub> in (a) 60 min, (b) 120 min at optimized conditions	108
<b>Fig. 3.33:</b> Effect of amount of sulfuric acid during baking on the recovery of metals during leaching at 25% PD, 95 °C in 120 min.	110
<b>Fig. 3.34:</b> Effect of baking temperature on the recovery of metals during leaching at 25% PD, 95 °C in 120 min.	111
<b>Fig. 3.35:</b> Effect of baking duration on the recovery of metals during leaching at 25% PD, 95 °C in 120 min.	113
<b>Fig. 3.36:</b> Effect of leaching temperature on the recovery of metals by water leaching of baked cathode active material in 60 min and 25% PD.	115
<b>Fig. 3.37:</b> Effect of pulp density on the recovery of metals by water leaching of baked cathode active material in 60 min and 75 °C.	116
<b>Fig. 3.38:</b> Effect of time on the recovery of metals water leaching of baked cathode active material at 75 °C. 25% PD	117
<b>Fig. 3.39:</b> Effect of addition of glucose on 2 <sup>nd</sup> stage leaching of leach-I residue	120
<b>Fig. 3.40:</b> Effect of temperature on 2 <sup>nd</sup> stage leaching of leach-I residue using 1 M H <sub>2</sub> SO <sub>4</sub> + 0.5 M HNO <sub>3</sub> and 2 % glucose.	122
<b>Fig. 3.41:</b> Effect of time on 2 <sup>nd</sup> stage leaching of leach-I residue using 1 M H <sub>2</sub> SO <sub>4</sub> + 0.5 M HNO <sub>3</sub> and 2 % glucose.	123
<b>Fig. 3.42:</b> Effect of pulp density on 2 <sup>nd</sup> stage leaching of leach-I residue using 1 M H <sub>2</sub> SO <sub>4</sub> + 0.5 M HNO <sub>3</sub> and 2 % glucose.	124
<b>Fig. 3.43:</b> XRD phase analysis of (a) baked cathode material; (b) 1 <sup>st</sup> stage water leached residue; (c) 2 <sup>nd</sup> stage acid leached residue in 60 min at 50 °C; (d) 2 <sup>nd</sup> stage acid leached residue in 120 min at 50 °C.	126
<b>Fig. 3.44:</b> SEM-EDAX analysis of untreated (a) and baked (b) cathode active material	127
<b>Fig. 3.45:</b> SEM-EDAX analysis of leach-I residue after water leaching of baked material	128
<b>Fig. 3.46:</b> SEM-EDAX analysis of residue obtained after leach-II (2 <sup>nd</sup> stage leaching) in 60 min	128
<b>Fig. 3.47:</b> Flowsheet of process intensification by acid baking followed by leaching to extract metallic values from LIB cathode materials	129
<b>Fig. 3.48:</b> Cobalt oxalate synthesized at pH 1.5 using oxalic acid (a-XRD; b-pink precipitate of CoC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O; c-FESEM of tubular rod like	131

Co-oxalate; d-EDAX of Co-oxalate)	
<b>Fig. 3.49:</b> Manganese carbonate synthesized at pH 7.5 (a-XRD; b-brown precipitate of $MnCO_3$ ; c-FESEM showing microspheres of Mn-carbonate; d-EDAX of $MnCO_3$ )	133
<b>Fig. 3.50:</b> Nickel carbonate synthesized at pH 9 (a-XRD; b-light green $NiCO_3$ ; c-FESEM of flakes of nickel carbonate; d-EDAX of $NiCO_3$ powder)	134
<b>Fig. 3.51:</b> Lithium carbonate synthesized at pH 13-14 (a-XRD; b-picture of $Li_2CO_3$ ; c-FESEM of agglomerates of Li-carbonate; d-EDAX of $Li_2CO_3$ )	136
<b>Fig. 3.52:</b> A general flow-sheet developed for extraction and precipitation of Li, Mn, Ni and Co from waste lithium ion batteries	137
<b>Fig. 4.1:</b> Effect of acid concentration (a) HCl and (b) $H_2SO_4$ on the leaching efficiency of spent Ni-MH battery powder	142
<b>Fig. 4.2:</b> Effect of time on the leaching efficiency of electrode powder	143
<b>Fig. 4.3:</b> Effect of pulp density on the leaching efficiency of spent Ni-MH battery powder	144
<b>Fig. 4.4:</b> Effect of temperature on the leaching efficiency of spent Ni-MH battery powder	145
<b>Fig. 4.5:</b> Effect of temperature on the leaching efficiency of different metals from electrode powder at different time intervals	148
<b>Fig. 4.6:</b> Chemical controlled kinetic model of leaching for (a) nickel (b) cobalt (c) iron (d) manganese and (e) zinc in the temperature range 305-348 K.	149
<b>Fig. 4.7:</b> Diffusion controlled kinetic model of leaching for (a) nickel (b) cobalt (c) iron (d) manganese and (e) zinc in the temperature range 305-348 K.	150
<b>Fig. 4.8:</b> Arrhenius plot for the leaching of the metals from electrode powder in the temperature range 305-348 K	151
<b>Fig. 4.9:</b> SEM-EDAX analysis of residue at 30 min with the mapping of constituent elements	152
<b>Fig. 4.10:</b> SEM-EDAX analysis of the residue at 60 min of leaching with the mapping of constituent elements	153
<b>Fig. 4.11:</b> Effect of acid concentration on the leaching of REMs from spent battery powder	156
<b>Fig. 4.12:</b> Effect of time on the leaching of metal from the electrode powder of spent batteries.	157
<b>Fig. 4.13:</b> Effect of pulp density on the leaching of metals from the spent Ni-MH battery powder.	157
<b>Fig. 4.14:</b> Effect of temperature on the leaching of REMs from spent	159

battery powder	
<b>Fig. 4.15:</b> Eh-pH diagram of (a) La-S-H <sub>2</sub> O system at 298 K, [La] =0.02 M; (b) La-S-H <sub>2</sub> O system at 323 K [La] =0.002 M; (c) Ce-S-H <sub>2</sub> O system at 298 K, [Ce] = 0.031 M; (d) Ce-S-H <sub>2</sub> O system at 348 K,[Ce] =0.031 M	160
<b>Fig. 4.16:</b> Effect of temperature on the recovery of rare earth metals from NiMH battery powder at different time intervals	161
<b>Fig. 4.17:</b> Kinetics of leaching of REs together as a group (a) Effect of temperature (b) Chemical control kinetic model in temperature range 305-348 K (c) Arrhenius plot	162
<b>Fig. 4.18:</b> Chemical controlled kinetic model of leaching of (a) Nd (b) Sm (c) Pr and (d) Ce at different temperatures.	165
<b>Fig. 4.19:</b> Arrhenius plot for the leaching of the rare earth metals from Ni-MH in the temperature range 305-348 K.	166
<b>Fig. 4.20:</b> XRD of the (a) leach residue at 30 min; (b) leach residue at 60 min	167
<b>Fig. 4.21:</b> SEM-EDAX of the electrode powder sample (a); residue in 30 min (b) and residue in 60 min (c)	168
<b>Fig. 4.22:</b> XRD phase analysis of mixed rare earth salts.	170
<b>Fig. 4.23:</b> FESEM image of mixed rare earth precipitates at pH~1.8	170
<b>Fig. 4.24:</b> A general flow-sheet developed for extraction and recovery of base and rare earth metals from the spent nickel metal hydride batteries	171
<b>Fig. 4.25:</b> Effect of baking parameters on the recovery of metals in water leaching at 20 g/L PD, 75 °C in 120 min, (a) amount of sulfuric acid; (b) baking temperature; (c) baking time on all metals; (d) baking time on individual rare earths	176
<b>Fig. 4.26:</b> Effect of temperature on leaching of (a) base metals, (b) rare earth metals from baked electrode material with 20 g/L PD in 60 min	178
<b>Fig. 4.27:</b> Effect of pulp density on leaching of (a) base metals, (b) rare earth metals from baked electrode material at 75°C in 60 min	179
<b>Fig. 4.28:</b> Effect of time on leaching of (a) base metals, (b) rare earth metals from baked electrode material at 75°C, 100 g/L PD in 60 min	179
<b>Fig. 4.29:</b> XRD phase analysis of (a) baked electrode material; (b) 1 <sup>st</sup> stage water leached residue	184
<b>Fig. 4.30:</b> SEM-EDAX analysis of untreated electrode material	185
<b>Fig. 4.31:</b> SEM-EDAX analysis of baked electrode material	185
<b>Fig. 4.32:</b> SEM-EDAX analysis of leach-I residue after water leaching of baked material	186
<b>Fig. 4.33:</b> SEM-EDAX analysis of residue obtained after leach-II (2 <sup>nd</sup> stage leaching) in 60 min	186