

---



---

## List of Figures

---



---

Figure No.	Caption of Figures	Page No.
<b>Figure 1.1:</b>	Classification of broadband antennas	<b>6</b>
<b>Figure 1.2:</b>	Dipole and monopole antennas	<b>7</b>
<b>Figure 1.3:</b>	Geometries of various non-planar and planar broadband antennas	<b>9</b>
<b>Figure 1.4:</b>	Geometries of different frequency independent antennas	<b>10</b>
<b>Figure 1.5:</b>	Geometry of trapezoidal toothed log-periodic antenna	<b>12</b>
<b>Figure 1.6:</b>	Circular patch antenna with full and partial ground planes	<b>15</b>
<b>Figure 1.7:</b>	Principle of overlapping resonant modes of the planar monopole antenna	<b>15</b>
<b>Figure 1.8:</b>	Self-complementary structures	<b>17</b>
<b>Figure 1.9:</b>	Geometries of different quasi-self-complementary antennas (QSCAs)	<b>17</b>
<b>Figure 3.1:</b>	Geometry of (a) conventional MS-to-Parallel Strip balun, (b) proposed MS-to-CPS transition, and (c) prototype of MS-to-CPS transition	<b>46</b>
<b>Figure 3.2:</b>	Unloaded metal trapezoidal toothed log-periodic antenna (a) geometry and (b) Prototype	<b>48</b>
<b>Figure 3.3:</b>	Configuration of unloaded metal TTLPA along with (a) MS-to-parallel strip line balun, (b) MS-to-CPS transition; and (c) prototype of unloaded metal TTLPA along with MS-to-CPS transition	<b>49</b>
<b>Figure 3.4:</b>	Simulated and measured reflection coefficients-frequency characteristics of the unloaded metal TTLPA (along with transition).	<b>51</b>
<b>Figure 3.5:</b>	Simulated-input impedance-frequency characteristics of unloaded metal TTLPA along with transition	<b>52</b>
<b>Figure 3.6:</b>	Simulated current distributions on the unloaded metal TTLPA surface at different frequencies	<b>53</b>
<b>Figure 3.7:</b>	Simulated vector current distributions on MS line-to-CPS transition at different frequencies	<b>54</b>

<b>Figure 3.8:</b>	2D (simulated and measured) and 3D (simulated) radiation patterns of the unloaded metal TTLPA (along with transition) at different frequencies	<b>55</b>
<b>Figure 3.9:</b>	Simulated and/or measured realized gain- and total efficiency-frequency characteristics of unloaded metal TTLPA	<b>56</b>
<b>Figure 3.10:</b>	Geometrical configuration of (a) trapezoidal toothed log-periodic antenna, (b) MS-to-CPS transition, and (c) different parts of antenna	<b>57</b>
<b>Figure 3.11:</b>	Three-dimensional (3D) views of proposed antenna along with transition (a) unloaded metal TTLPA, (b) dielectric-loaded metal TTLPA (antenna A2), and (c) prototype of antenna A2	<b>59</b>
<b>Figure 3.12:</b>	Effect of dielectric constant ' $\epsilon_r$ ' of loaded dielectric material on reflection coefficient-frequency characteristic of the proposed dielectric-loaded metal TTLPA	<b>61</b>
<b>Figure 3.13:</b>	Effect of thickness ' $t_d$ ' of loaded dielectric material on reflection coefficient-frequency characteristic of the proposed dielectric-loaded metal TTLPA	<b>61</b>
<b>Figure 3.14:</b>	Reflection coefficient-frequency characteristics of TTLPAs	<b>63</b>
<b>Figure 3.15:</b>	Simulated surface current distributions of antennas A1 and A2	<b>64</b>
<b>Figure 3.16:</b>	Radiation patterns of antennas A1 and A2	<b>65</b>
<b>Figure 3.17:</b>	Realized gain-frequency characteristics of TTLPAs	<b>66</b>
<b>Figure 3.18:</b>	Total efficiency-frequency characteristics of TTLPAs	<b>68</b>
<b>Figure 4.1:</b>	Design methodology of flower-shape (a) spline based curves, (b) comparison of circular and flower-shaped patches, and (c) flower-shaped patch along with its important geometrical parameters	<b>73</b>
<b>Figure 4.2:</b>	Geometries of CPW-fed (a) conventional circular patch antenna, (b) flower-shaped patch antenna; and (c) fabricated antenna	<b>74</b>
<b>Figure 4.3:</b>	The effects of geometrical parameters (a) R1 and (b) R4 on the input VSWR-frequency characteristic of the proposed CPW-fed flower-shaped patch antenna	<b>76</b>
<b>Figure 4.4:</b>	Simulated and measured input VSWR-frequency characteristics of proposed CPW-fed flower-shaped antenna	<b>79</b>

<b>Figure 4.5:</b>	Simulated input VSWR-frequency characteristics of the CPW-fed circular patch and the proposed flower-shaped patch antennas	<b>79</b>
<b>Figure 4.6:</b>	Simulated surface current distributions on the proposed CPW-fed flower-shaped patch at 3, 5, 8, and 10 GHz	<b>80</b>
<b>Figure 4.7:</b>	Simulated and measured radiation patterns of CPW-fed flower-shaped patch antenna at 3, 5, 8, and 10 GHz	<b>81</b>
<b>Figure 4.8:</b>	Simulated and/or measured realized gain- and total efficiency-frequency characteristics of proposed CPW-fed flower-shaped patch antenna	<b>82</b>
<b>Figure 4.9:</b>	Excited and received pulses for face-to-face and side-by-side orientations of proposed CPW-fed flower-shaped patch antennas at a distance of 30 cm	<b>83</b>
<b>Figure 4.10:</b>	Far-field group delays of CPW-fed flower-shaped patch antenna for different orientations at a distance of 30 cm	<b>84</b>
<b>Figure 4.11:</b>	Design steps concerning MS-fed flower-shaped patch antenna	<b>85</b>
<b>Figure 4.12:</b>	MS-fed flower-shaped patch antenna (a) geometry, (b) front view of prototype, and (c) back view of prototype	<b>85</b>
<b>Figure 4.13:</b>	Simulated input VSWR-frequency characteristics of the proposed MS-fed flower-shaped patch antenna for different configurations of feed line and ground plane	<b>88</b>
<b>Figure 4.14:</b>	Simulated and measured input VSWR-frequency characteristics of the proposed MS-fed and CPW-fed flower-shaped patch antennas	<b>89</b>
<b>Figure 4.15:</b>	Simulated surface and volume current distributions on the proposed MS line-fed and CPW-fed flower-shaped patch antennas	<b>90</b>
<b>Figure 4.16:</b>	Simulated and measured radiation patterns of the proposed MS-fed antenna at 3, 6, 9, and 12 GHz	<b>91</b>
<b>Figure 4.17:</b>	Realized gain- and total efficiency-frequency characteristics of the proposed MS-fed and CPW-fed antennas	<b>92</b>
<b>Figure 4.18:</b>	Excited and received pulses for face-to-face and side-by-side orientations of MS-fed flower-shaped patch antennas at a distance of 30 cm	<b>93</b>

<b>Figure 4.19:</b>	Simulated far-field group delays of MS-fed flower-shaped patch antenna for different orientations at a distance of 30 cm	<b>94</b>
<b>Figure 5.1:</b>	Geometries of (a) trapezoidal toothed log-periodic antenna, (b) castor leaf, (c) castor leaf-shaped QSCA with sharp corners, and (d) castor leaf-shaped QSCA with smooth corners	<b>99</b>
<b>Figure 5.2:</b>	Geometry of the proposed single element QSCA having (a) sharp corners designated as A1, (b) smooth corners designated as A2, (c) the prototype having smooth corners	<b>100</b>
<b>Figure 5.3:</b>	Reflection coefficient-frequency characteristics of single element QSCA having smooth/sharp corners	<b>101</b>
<b>Figure 5.4:</b>	Geometry of the proposed two element MIMO antenna (a) without resonators and (b) with resonators; Prototype of the proposed antenna (c) without resonators and (d) with resonators	<b>102</b>
<b>Figure 5.5:</b>	Vector surface current distributions on the proposed antenna patch at 3.5 and 5.5 GHz for deducing resonators' lengths	<b>104</b>
<b>Figure 5.6:</b>	Variations of $S_{11}$ -frequency characteristics of the MIMO antenna with slit parameter (a) $s_1$ , (b) $s_2$ , (c) $s_3$ , and (d) $t_1$	<b>106</b>
<b>Figure 5.7:</b>	Variations of $S_{11}$ -frequency characteristics of the antenna with HSRS parameter (a) $p_1$ , (b) $p_2$ , and (c) $t$	<b>107</b>
<b>Figure 5.8:</b>	Variations of $S_{11}$ -frequency characteristics of the antenna loaded with only slit, only HSRS, and both slit and HSRS	<b>108</b>
<b>Figure 5.9:</b>	Experimental setup for measuring total efficiency of proposed antenna using Wheeler cap method	<b>109</b>
<b>Figure 5.10:</b>	S-parameters-frequency characteristics of the proposed MIMO antenna (a) $S_{11}$ and (b) $S_{21}$	<b>111</b>
<b>Figure 5.11:</b>	Simulated current distributions on the surface of the proposed MIMO antenna with port 1 excited and port 2 match-terminated	<b>112</b>
<b>Figure 5.12:</b>	3D radiation patterns of the proposed MIMO antenna when port 1/2 is excited while port 2/1 is match-terminated	<b>114</b>
<b>Figure 5.13:</b>	2D radiation patterns of the proposed MIMO antenna when port 1 excited and port 2 match-terminated	<b>115</b>

<b>Figure 5.14:</b>	Realized gain-frequency characteristics of the proposed MIMO antenna	<b>116</b>
<b>Figure 5.15:</b>	Total efficiency-frequency characteristics of proposed MIMO antenna	<b>117</b>
<b>Figure 5.16:</b>	Variations of envelope correlation coefficients of the proposed MIMO antenna with frequency	<b>117</b>
<b>Figure 6.1:</b>	Geometrical configuration of proposed shared radiator MIMO antenna	<b>122</b>
<b>Figure 6.2:</b>	Evolution steps of proposed antenna	<b>123</b>
<b>Figure 6.3:</b>	Prototype of fabricated antenna (a) front view and (b) back view	<b>123</b>
<b>Figure 6.4:</b>	S-parameter-frequency characteristics of different antenna configurations when exciting port 1 (a) $S_{11}$ and (b) $S_{21}$	<b>127</b>
<b>Figure 6.5:</b>	S-parameter-frequency characteristics of the proposed antenna (a) reflection coefficient and (b) transmission coefficients $S_{21}$ and $S_{12}$	<b>129</b>
<b>Figure 6.6:</b>	Simulated surface current distributions of different antenna configurations	<b>131</b>
<b>Figure 6.7:</b>	3D radiation patterns of the proposed MIMO antenna when exciting port1/2 while match-terminating port 2/1	<b>133</b>
<b>Figure 6.8:</b>	2D radiation patterns of the proposed MIMO antenna when exciting port 1 while match-terminating port 2	<b>133</b>
<b>Figure 6.9:</b>	Realized Gain-frequency characteristics of the proposed MIMO antenna when exciting port 1 and match-terminating port 2	<b>134</b>
<b>Figure 6.10:</b>	Total efficiency-frequency characteristics of the proposed MIMO antenna when exciting port 1 and match-terminating port 2	<b>135</b>
<b>Figure 6.11:</b>	Envelope correlation coefficient-frequency characteristics of the proposed MIMO antenna when exciting port 1 and match-terminating port 2	<b>136</b>