
Contents

Certificate	i
Supervisors' certificate	iii
Declaration by the candidate	v
Copyright transfer certificate	vii
Acknowledgements	ix
Table of Contents	xi
List of Figures	xv
List of Tables	xxiii
Abstract	xxvii
1 Introduction	1
1.1 Turbulent jet	1
1.1.1 Free jet:	2
1.1.2 Wall jet:	2
1.1.3 Offset jet:	3
1.1.4 Impinging jet:	3
1.2 Description of wall jet:	5
1.3 Research methodology	8
1.4 Objective of the Research	10
1.5 Thesis structure	12
2 Literature Review	13
2.1 Outline	13
2.1.1 Literature related to different initial conditions	14

2.1.2	Literature related to different boundary conditions	22
2.1.2.1	Literature related to heat transfer characteristics	22
2.1.2.2	Literature related to mean and turbulent flow characteristics .	27
2.1.3	Summary of the literature	33
3	Experimental setup and Computational method	35
3.1	Experimental details	35
3.1.1	Wall jet facility	36
3.1.2	Measurement procedure	37
3.1.3	Description of experimental test sections and experimental test conditions with jet inlet profiles	39
3.1.3.1	Effect of initial conditions	39
3.1.3.2	Effect of sidewalls	40
3.1.3.3	Effect of sidewall width	41
3.1.4	Uncertainty analysis	42
3.1.5	Experimental setup validation	45
3.1.5.1	Fluid flow validation	45
3.1.5.2	Heat transfer validation	45
3.2	Computational methods	46
3.2.1	Governing equations	47
3.2.2	Justification of using YS and LS turbulence models	48
3.2.3	Computational domains and jet inlet conditions	49
3.2.3.1	Initial condition	49
3.2.3.2	With and without sidewalls	50
3.2.3.3	Sidewall enclosure width	50
3.2.4	Boundary conditions of different wall jet configurations	51
3.2.5	Numerical Scheme and method of Solution	52
3.2.6	Validation of the numerical code and grid independence test	53
3.2.6.1	Effect of Initial conditions	53
3.2.6.2	Effect of sidewalls	56
3.2.6.3	Effect of sidewall enclosure width	61
4	Effect of initial conditions on mean and turbulent flow characteristics of a three-dimensional turbulent wall jet	65
4.1	Experimental results for initial conditions	65
4.1.1	Inlet jet profile	66
4.1.2	Velocity variation in the lateral and wall-normal planes	67

4.1.3	Variation of jet half-width	68
4.1.4	Decay of maximum mean velocity	72
4.1.5	Local Reynolds number variation	73
4.1.6	Self-similar behaviour	75
4.2	Numerical results for the effect of initial conditions	77
4.2.1	Decay of maximum streamwise velocity	77
4.2.2	Variation of y_{max}/h	81
4.2.3	Variation of jet half-widths	83
4.2.4	Velocity and turbulent kinetic energy distribution	86
4.2.5	Similarity solution	91
4.2.6	Skin friction coefficient	93
4.2.7	Reynolds shear stresses	96
4.3	Conclusion	100
5	Effect of sidewalls on the three-dimensional wall jet	103
5.1	Experimental results of with and without sidewall configurations	104
5.1.1	Centerline bottom wall temperature decay	104
5.1.2	Lateral temperature variation of the bottom wall	106
5.1.3	Centerline temperature variation	106
5.1.4	Temperature distribution in the lateral ($y/h = 0.5$) and wall-normal ($z/h = 0.0$) directions	109
5.1.5	Thermal half-width	112
5.1.6	Similarity profile	114
5.1.7	Thermal turbulent structure	116
5.1.7.1	Temperature fluctuation at different sections in lateral and wall-normal directions	117
5.1.7.2	Temperature fluctuation along the center line	119
5.1.8	Probability density function of temperature fluctuations	119
5.1.9	Skewness and Flatness of fluctuating temperature	122
5.2	Numerical results of with and without sidewall configurations	127
5.2.1	Centerline temperature and maximum velocity decay	128
5.2.2	Temperature and velocity contour	130
5.2.3	Generation of maximum turbulent kinetic energy and dissipation	131
5.2.4	Skin friction coefficient	134
5.2.5	Entrainment rate	137
5.2.6	Reynolds stresses	138
5.2.7	Turbulent heat flux	142

5.3 Conclusion	144
6 Effect of the width of sidewall enclosure on three-dimensional turbulent wall jet	147
6.1 Experimental results for SWEs effect	148
6.1.1 Velocity variation in lateral and wall-normal directions	148
6.1.2 Decay of jet maximum streamwise mean velocity	148
6.1.3 Spread in wall-normal and lateral direction	152
6.1.4 Self-similar profile	153
6.1.5 Velocity distribution in cross-flow plane ($z-y$)	157
6.1.6 Centerline temperature decay	161
6.1.7 Lateral and wall-normal thermal spreads	164
6.1.8 Lateral and wall-normal thermal similarity	167
6.1.9 Sidewall Effect	170
6.1.10 Statistical analysis	175
6.1.10.1 Probability density function	175
6.1.10.2 Skewness and Flatness factors of different SWEs	180
6.2 Numerical results for SWE effect	181
6.2.1 Maximum streamwise velocity decay	181
6.2.2 Entrainment	183
6.2.3 Local Reynolds number	184
6.2.4 Spread width and Spread ratio	185
6.2.5 Wall Shear stress	187
6.2.6 Reynolds shear stresses	188
6.3 Conclusions	191
7 Conclusions and future work	195
7.1 Conclusions	196
7.2 Recommendation of future works	198
Bibliography	201
Author's Personal Profile and Publication List	215

List of Figures

1.1 Schematic diagram of the free jet	2
1.2 Schematic diagram of the three-dimensional wall jet	3
1.3 Schematic diagram of the three-dimensional offset jet	4
1.4 Schematic diagram of the three-dimensional impinging jet	4
1.5 Three dimensional turbulent wall jet with sidewall	11
2.1 Characterization of the flow domain of a plane wall jet	14
2.2 circular, elliptic, square, rectangular, and equilateral triangular orifices to generate the three-dimensional wall jet investigated by Rajaratnam and Pani [1]	18
2.3 Schematic of circular orifices segment to generate the three-dimensional wall jet investigated by Padmanabham and Gowda [2, 3]	19
2.4 Initial velocity profile at nozzle exit investigated by Sun and Ewing [4]	19
2.5 Schematic diagram of nozzle geometries investigated by Rahman et al. [5]	21
2.6 Schematic diagram of nozzle lip thickness investigated by McIntyre et al. [6]	21
2.7 Characterisation of the flow domain of a three-dimensional heated wall jet	23
2.8 Geometrical boundary condition of the three dimensional wall jet investigated by Koso and Ohashi [7]	25
2.9 Bottom wall-surface roughness (a) Strip roughness and (b) Flower shaped roughness (all dimensions are in mm), investigated by Wu and Rajaratnam [8]	30

3.1 Schematic of the experimental setup (1. Air blower, 2. Air filter, 3. Flow stabilizer, 4. Heater, 5. Reducer duct 1, 6. Flow straightener, 7. Reducer duct 2, 8. Square nozzle, 9. Test section, 10. Transversing mechanism for anemometer, 11. Anemometer, 12. Transversing mechanism for thermocouple, 13. Thermocouple)	36
3.2 Adiabatic surface	37
3.3 Centerline surface temperature decay	38
3.4 Schematic of the test section of initial conditions with Cartesian coordinate .	39
3.5 Jet exit velocity profiles for different nozzle length (a) Non-dimensional jet exit velocity profile, and (b) Dimensional jet exit velocity profile	40
3.6 Schematic of the test section of with and without sidewalls with cartesian coordinate	40
3.7 Initial jet profiles of with and without sidewalls conditions (a) Non-dimensional jet exit profiles, (b) Dimensional jet exit profiles for 200mm nozzle	42
3.8 Temperature fluctuation profile at the jet exit	43
3.9 Schematic of the test section of sidewall enclosures with cartesian coordinate	43
3.10 Validation of experimental setup for fluid flow characteristics	46
3.11 Validation of the experimental setup	46
3.12 Computational domain	50
3.13 Computational domain for numerical simulation (a) Configuration 1 (b) Configuration 2	51
3.14 Computational domain of SWE	52
3.15 Code validation of the velocity profiles for YS and LS models in lateral direction for (a) $l/h = 10$, (b) $l/h = 50$, (c) $l/h = 90$, and in wall-normal direction for (d) $l/h = 10$, (e) $l/h = 50$, (f) $l/h = 90$	54
3.16 Grid independence test for different initial conditions of the jet	55
3.17 Temperature validation in lateral direction	57
3.18 Temperature validation in wall-normal direction	58
3.19 Velocity validation in lateral direction	59
3.20 Velocity validation in wall-normal direction	60
3.21 Variation of decay of normalized maximum mean velocity for different grid densities	61
3.22 Code validation of the velocity distribution for (a) 140mm SWE in lateral direction, (b) 160mm SWE in lateral direction, (c) 180mm SWE in lateral direction and (d) 200mm SWE in lateral direction	62

3.23 Code validation of the velocity distribution for (a) 140mm SWE in wall-normal direction, (b) 160mm SWE in wall-normal direction, (c) 180mm SWE in wall-normal direction and (d) 200mm SWE in wall-normal direction	63
3.24 Variation of the wall-normal velocity at (a) $x/h = 10$, and (b) $x/h = 30$ for different grid density as described in labels	64
4.1 Distribution of mean velocity profile at nozzle exit (a) Non-dimensional jet exit velocity profile, and (b) Dimensional jet exit velocity profile	66
4.2 Mean streamwise velocity profiles for $l/h=10$, $l/h=50$, and $l/h=90$ at $y/h = 0.5$ and (a) $x/h = 2$, (b) $x/h = 15$, (c) $x/h = 25$ and (d) $x/h = 45$	67
4.3 Wall-normal mean velocity profiles for $l/h=10$, $l/h=50$, and $l/h=90$ at $y/h=0.5$ and (a) $x/h=2$, (b) $x/h=15$, (c) $x/h=25$ and (d) $x/h=45$	69
4.4 Jet half-width (a) $y_{1/2}/h$ Vs x/h for nozzle $l/h=10$, 50, and 90 (b) Zoom view of jet half-width in near field ($x/h \leq 10$) ((c) Comparison of $y_{1/2}/h$ Vs x/h for $l/h=90$ with Hall and Ewing [9], Inoue et al. [10], Padmanabham and Gowda [2], Agelin-Chaab and Tachie [11] and Abrahamsson et al.[12]	70
4.5 Jet half-width (a) $z_{1/2}/h$ Vs x/h for nozzle $l/h=10$, 50, and 90 (b) Comparison of $z_{1/2}/h$ Vs x/h for $l/h = 90$ with Hall and Ewing [9] and Inoue et al. [10], Padmanabham and Gowda [2], Agelin-Chaab and Tachie [11] and Abrahamsson et al. [12]	71
4.6 (a) Decay of jet exit velocity (b) Zoom view of jet exit velocity	72
4.7 Maximum mean velocity comparison with Agelin-Chaab and Tachie [11], Kwakye et al. [13], Hall and Ewing [9], Kumar and Das [14]	74
4.8 Development of the local Reynolds number for different initial conditions ($l/h=10$, 50 and 90)	74
4.9 Self-similar profile for nozzle (a) $l/h=10$, (b) $l/h=50$ and (c) $l/h=90$	76
4.10 Self-similar profile comparison at (a) $x/h = 15$ and (b) $x/h = 30$ for nozzle $l/h=90$ with Hall and Ewing [9] and Rajaratanam and Subramanya [15]	77
4.11 Self-similar profile for Nozzle (a) $l/h=10$, (b) $l/h=50$ and (c) $l/h=90$	78
4.12 Self-similar profile comparison for Nozzle $l/h=90$ with Hall and Ewing [9]	79
4.13 Decay of maximum streamwise velocity for the nozzle $l/h=10$, $l/h=50$, and $l/h=90$ for (a) YS model (b) LS model and (c) Comparison with present experiment for nozzle $l/h=90$, Hall and Ewing [9], Agelin-Chaab and Tachie [11] and Kwakye et al. [13]	80
4.14 (a) Variation of y_{max}/h along the downstream direction (b) y_{max}/h comparison with Padmanabham and Gowda [2], Inoue et al. [10], Tang et al. [16] and Naqavi et al. [17]	82

4.15 (a) Variation of jet half-width in wall-normal direction for YS and LS model (b) Zoom view of jet half-width in near field for YS model	83
4.16 Comparison of jet half-width for nozzle $l/h = 90$ with Padmanabham and Gowda [2], Hall and Ewing [9], Inoue et al. [10] and Agelin-Chaab and Tachie [11]	84
4.17 Variation of jet half-width in wall lateral direction	85
4.18 Comparison of jet half-width for nozzle $l/h = 90$ with Hall and Ewing [9] and Agelin-Chaab and Tachie [11]	86
4.19 u/u_{jet} velocity contours at (a) $x/h = 5$ for $l/h = 10$, (b) $x/h = 5$ for $l/h = 90$, (c) $x/h = 15$ for $l/h = 10$ (d) $x/h = 15$ for $l/h = 90$, (e) $x/h = 25$ for $l/h = 10$ (f) $x/h = 25$ for $l/h = 90$ (g) $x/h = 30$ for $l/h = 10$ and (h) $x/h = 30$ for $l/h = 90$	87
4.20 v/u_{jet} velocity contours at (a) $x/h = 5$ for $l/h = 10$, (b) $x/h = 5$ for $l/h = 90$, (c) $x/h = 15$ for $l/h = 10$ (d) $x/h = 15$ for $l/h = 90$, (e) $x/h = 25$ for $l/h = 10$ (f) $x/h = 25$ for $l/h = 90$ (g) $x/h = 30$ for $l/h = 10$ and (h) $x/h = 30$ for $l/h = 90$	88
4.21 w/u_{jet} velocity contours at (a) $x/h = 5$ for $l/h = 10$, (b) $x/h = 5$ for $l/h = 90$, (c) $x/h = 15$ for $l/h = 10$ (d) $x/h = 15$ for $l/h = 90$, (e) $x/h = 25$ for $l/h = 10$ (f) $x/h = 25$ for $l/h = 90$ (g) $x/h = 30$ for $l/h = 10$ and (h) $x/h = 30$ for $l/h = 90$	89
4.22 Turbulence kinetic energy $\left(k_n = k/u_{jet}^2\right)$ contours at (a) $x/h = 5$ for $l/h = 10$, (b) $x/h = 5$ for $l/h = 90$, (c) $x/h = 15$ for $l/h = 10$ (d) $x/h = 15$ for $l/h = 90$, (e) $x/h = 25$ for $l/h = 10$ (f) $x/h = 25$ for $l/h = 90$ (g) $x/h = 30$ for $l/h = 10$ and (h) $x/h = 30$ for $l/h = 90$	90
4.23 Self similar profile for Nozzle (a) YS model $l/h = 10$, (b) LS model $l/h = 10$, (c) YS model $l/h = 50$ (d) LS model $l/h = 50$ and (e) YS model $l/h = 90$ and (f) LS model $l/h = 90$	92
4.24 Self-similar profile comparison of YS and LS turbulence models for Nozzle $l/h = 90$ with present experiment and Hall and Ewing [9]	93
4.25 Self similar profile for Nozzle (a) YS model $l/h = 10$, (b) LS model $l/h = 10$, (c) YS model $l/h = 50$, (d) LS model $l/h = 50$ and (e) YS model $l/h = 90$ and (f) LS model $l/h = 90$	94
4.26 Self-similar profile comparison for Nozzle $l/h = 90$ with present experiment and Hall and Ewing [9]	95
4.27 Variation of skin friction coefficient for different jet inlet conditions	95
4.28 Reynolds shear stress in wall-normal direction at symmetry plane (a) $x/h = 5$ YS model, (b) $x/h = 15$ YS model, (c) $x/h = 25$ YS model, (d) Comparison of Reynolds shear stress $\langle u'v' \rangle / u_{max}^2$ at $x/h = 40$ for nozzle $l/h=10$	97

4.29 Reynolds shear stress in lateral direction at symmetry plane (a) $x/h = 5$ YS model, (b) $x/h = 15$ YS model, (c) $x/h = 25$ YS model, (d) Comparison of Reynolds shear stress $\langle u'w' \rangle / u_{max}^2$ at $x/h = 30$ for nozzle $l/h=10$	99
4.30 Maximum shear stress variation at symmetry plane	100
5.1 Centerline bottom wall temperature decay	105
5.2 Lateral surface temperature variation in configuration 1 and configuration 2, Conf 1 = Configuration 1, Conf 2 = Configuration 2	107
5.3 Centerline temperature decay for configuration 1 and configuration 2	108
5.4 Lateral temperature variation in configuration 1 and configuration 2, Conf 1 = Configuration 1, Conf 2 = Configuration 2	110
5.5 Normal temperature variation in configuration 1 and configuration 2, Conf 1 = Configuration 1, Conf 2 = Configuration 2	111
5.6 Lateral to normal thermal width ratio	112
5.7 Thermal half-width ($y_{t1/2}/h$ Vs x/h) in wall-normal direction for configurations 1 and 2 ($\Delta t_{jet} = 20^\circ C, 40^\circ C$) and compared with Koso and Ohashi [7] and Sforza and Stasi [18]	113
5.8 Thermal half-width ($z_{t1/2}/h$ Vs x/h) in lateral direction for configuration 1 and 2 ($\Delta t_{jet} = 20^\circ C, 40^\circ C$) and compared with Sforza and Stasi [18]	114
5.9 Self-similarity in lateral direction (a) Configuration 1 (b) Configuration 2	115
5.10 Self-similarity in wall-normal direction (a) Configuration 1 (b) Configuration 2	116
5.11 Temperature fluctuation for configuration 1 in (a) Lateral direction (b) Normal direction	118
5.12 Temperature fluctuation for configuration 2 in (a) Lateral direction (b) Normal direction	118
5.13 Centerline temperature fluctuation for configuration 1 and configuration 2	119
5.14 Centerline probability density function (PDF) for configuration 1 and configuration 2	121
5.15 Probability density function (PDF) for configuration 1 and configuration 2 at $x/h = 10$	123
5.16 Probability density function (PDF) for configuration 1 and configuration 2 at $x/h = 20$	124
5.17 Probability density function (PDF) for configuration 1 and configuration 2 at $x/h = 40$	125
5.18 Skewness and Flatness about centerline	126
5.19 Similarity behaviour (a) Configuration 1 (b) configuration 2	127

5.20 Decay of (a) Centerline temperature and (b) maximum velocity along the downstream direction	129
5.21 Contour plot at $x/h = 5$ for YS model (a) Temperature contour in configuration 1 and configuration 2 (b) u velocity contours in configuration 1 and configuration 2 (c) v velocity contour in configuration 1 and configuration 2 (d) w velocity contour in configuration 1 and configuration 2	132
5.22 Contour plot at $x/h = 25$ for YS model (a) Temperature contour in configuration 1 and configuration 2 (b) u velocity contours in configuration 1 and configuration 2 (c) v velocity contour in configuration 1 and configuration 2 (d) w velocity contour in configuration 1 and configuration 2	133
5.23 Variation of skin friction coefficient (C_{fw})	136
5.24 Mass entrainment ratio into the flowstream	137
5.25 Reynolds shear stress in wall-normal direction at jet centerline plane	139
5.26 Reynolds shear stress ($\langle u'w' \rangle / u_{max}^2$) in lateral direction at y_{max} plane	141
5.27 Turbulent heat flux (YS model) variation in wall-normal direction at (a) $x/h = 15$ and (b) $x/h = 30$	142
5.28 Turbulent heat flux (YS model) variation in lateral direction at (a) $x/h = 15$ and (b) $x/h = 30$	144
5.29 Turbulent heat flux comparison for YS and LS turbulence models in configuration 1 at $x/h = 40$ (a) wall-normal direction (b) lateral direction	145
6.1 Mean velocity profile in lateral direction at different axial locations (a) $x/h = 10$, (b) $x/h = 20$, (c) $x/h = 30$ and (d) $x/h = 40$	149
6.2 Mean velocity profile in wall-normal direction at different axial locations (a) $x/h = 10$, (b) $x/h = 20$, (c) $x/h = 30$ and (d) $x/h = 40$	150
6.3 (a) Maximum velocity decay in different regions of wall jet (b) Zoom view of maximum velocity decay in region 3	151
6.4 Jet velocity half-widths in wall-normal direction (a) Different SWEs and (b) Comparison 200mm SWE with Inoue et al. [10], Padmanabham and Gowda [2] and Abrahamsson et al. [12]	154
6.5 Jet velocity half-widths in lateral direction (a) Different SWEs and (b) Comparison 200mm SWE with Inoue et al. [10], Agelin-Chaab and Tachie [11] and Abrahamsson et al. [12]	154
6.6 Self-similar profile in wall-normal direction for (a) 140mm SWE, (b) 200mm SWE and (c) Comparison of self-similar profile at $x/h = 30$	155
6.7 Self-similar profile in lateral direction for (a) 140mm SWE, (b) 200mm SWE, and (c) Comparison of self-similar profile at $x/h = 20$	156

6.8 Velocity contour for (a) 140mm SWE at $x/h = 30$, (b) 160mm SWE at $x/h = 30$, (c) 180mm SWE at $x/h = 30$ and (d) 200mm SWE at $x/h = 30$	158
6.9 Velocity contour for (a) 140mm SWE at $x/h = 45$, (b) 160mm SWE at $x/h = 45$, (c) 180mm SWE at $x/h = 45$ and (d) 200mm SWE at $x/h = 45$	159
6.10 Spread in crossflow plane ($z - y$) at locations of (a) $x/h = 30$, (b) $x/h = 35$, (c) $x/h = 40$ and (d) $x/h = 45$	160
6.11 Self-similar behaviour in crossflow plane in lateral direction for (a) 140mm at $x/h = 35$, (b) 160mm at $x/h = 35$, (c) 180mm at $x/h = 35$, and (d) 200mm at $x/h = 35$	162
6.12 Self-similar behaviour in crossflow plane in lateral direction for (a) 140mm at $x/h = 45$, (b) 160mm at $x/h = 45$, (c) 180mm at $x/h = 45$, and (d) 200mm at $x/h = 45$	163
6.13 Centerline temperature decay for all the SWEs, and compared with Holland and Liburdy [19], Xu and Antonia [20], Koso and Ohashi [7]	165
6.14 Thermal spread width (a) lateral direction (b) wall-normal direction	165
6.15 Thermal self-similar profile in lateral direction for (a) 140mm SWE (b) 200mm SWE (c) Comparison of lateral similarity for different SWEs	168
6.16 Thermal self-similar profile in wall-normal direction for (a) 140mm SWE (b) 200mm SWE (c) Comparison of wall-normal similarity for different SWEs	169
6.17 Temperature contour plot for (a) 140mm SWE at $x/h = 30$, (b) 160mm SWE at $x/h = 30$, (c) 180mm SWE at $x/h = 30$, and (d) 200mm SWE at $x/h = 30$	171
6.18 Temperature contour plot for (a) 140mm SWE at $x/h = 45$, (b) 160mm SWE at $x/h = 45$, (c) 180mm SWE at $x/h = 45$, and (d) 200mm SWE at $x/h = 45$	172
6.19 Self-similar behaviour in transverse plane for (a) 140mm at $x/h = 35$ (b) 160mm at $x/h = 35$ (c) 180mm at $x/h = 35$ and (d) 200mm at $x/h = 35$	173
6.20 Self-similar behaviour in transverse plane for (a) 140mm at $x/h = 45$ (b) 160mm at $x/h = 45$ (c) 180mm at $x/h = 45$ and (d) 200mm at $x/h = 45$	174
6.21 Probability density function (PDF) in different downstream locations (a) $x/h = 1$, (b) $x/h = 5$, (c) $x/h = 10$, (d) $x/h = 15$, (e) $x/h = 20$, and (f) $x/h = 40$	176
6.22 Probability density function (PDF) at $x/h = 10$ in different lateral locations (a) $z/h = -1$, (b) $z/h = -2$, and (c) $z/h = -3$	177
6.23 Probability density function (PDF) at $x/h = 20$ in different lateral locations (a) $z/h = -1$, (b) $z/h = -2$, and (c) $z/h = -3$	178
6.24 Probability density function (PDF) at $x/h = 40$ in different lateral locations (a) $z/h = -1$, (b) $z/h = -2$, and (c) $z/h = -3$	179
6.25 Skewness and Flatness about jet centerline	180

6.26 Decay of maximum streamwise velocity (a) YS model (b) LS model	182
6.27 Entertainment in different SWEs (a) YS model (b) LS model	183
6.28 Variation of local Reynolds number (Re_x) along the x/h (a) YS model (b) LS model	184
6.29 Spread width in lateral direction (a) YS model (b) LS Model	186
6.30 Spread width in wall-normal direction (a) YS model (b) LS Model	186
6.31 Spread Ratio in different width of SWEs (a) YS model (b) LS model	187
6.32 Wall Shear stress (a) YS model (b) LS model, compared with Narain [21], Padmanabham and Gowda[2] and Khosronejad and Rennie [22]	188
6.33 Reynolds shear stresses in wall-normal direction (a) $x/h = 5$, (b) $x/h = 15$, (c) $x/h = 30$ and (d) Compared with Abrahamsson et al. [12] and Namgyal and Hall [23] at $x/h = 40$	190
6.34 Reynolds shear stresses in lateral direction (a) $x/h = 5$, (b) $x/h = 15$, (c) $x/h = 30$ and (d) Compared with Abrahamsson et al. [12] and Namgyal and Hall [23] at $x/h = 40$	192

List of Tables

1.1	Summary of three-dimensional turbulent wall jet for different initial conditions and boundary conditions	7
2.1	Summary of the free and wall jet for different initial conditions	15
2.2	Different boundary conditions on heated three-dimensional wall jet, BTW=bottom wall, BW= back wall, SW=sidewall.	23
2.3	Summarized literature details with different boundary conditions, BTW=bottom wall, BW=backwall, SW=sidewall,	28
2.4	Effect of back wall on spreading rate, reported by Eriksson et al. [24]	31
3.1	The maximum uncertainty of the primary and derived quantities	45
3.2	Definition of model function	48
3.3	Additional terms and wall boundary condition for low Reynolds number model	48
4.1	Decay of maximum mean velocity	74
4.2	Length of potential core at different initial conditions	79
4.3	Decay rate of maximum streamwise velocity	81
4.4	Comparison of y_{max}/h variation rate for nozzles $l/h = 10, 50$ and 90	82
4.5	Variation of jet spread rates in wall-normal direction	84
4.6	Variation of jet spread rates in lateral direction	85
5.1	Decay rate of centerline temperature and maximum velocity along the downstream direction	130
5.2	Generation of maximum turbulent kinetic energy and dissipation	135
5.3	Skin friction coefficient comparison	137

6.1	Decay rate of centerline temperature decay in SWEs	164
6.2	Lateral spread constant $140mm$, $160mm$, $180mm$, and $200mm$ SWEs	166
6.3	Wall-normal spread constant $140mm$, $160mm$, $180mm$, and $200mm$ SWEs . .	167
6.4	Decay rate of the streamwise maximum velocity, *Calculated through the au- thors data	182
6.5	Spread rate of different width of SWEs	186