

TABLE OF CONTENTS

CERTIFICATE	ii
DECLARATION BY THE CANDIDATE	iii
COPYRIGHT TRANSFER CERTIFICATE	iv
ACKNOWLEDGEMENT	v
DEDICATION	vi
TABLE OF CONTENTS	vii
LIST OF FIGURES	xiii
LIST OF TABLES	xix
LIST OF ABBREVIATIONS	xxi
LIST OF SYMBOLS	xxiii
PREFACE	xxvii
CHAPTER 1	1
INTRODUCTION	
1.1 Background	2
1.2 Contributions to Knowledge	6
1.3 Thesis Structure	8

CHAPTER 2	11
LITERATURE REVIEW	
2.1 Outline	11
2.2 Transduction Methods	13
2.2.1 <i>Electromagnetic</i>	13
2.2.2 <i>Electrostatic</i>	14
2.2.3 <i>Magnetostrictive</i>	15
2.2.4 <i>Piezoelectric</i>	16
2.3 Tapering Cross-section PVEH	17
2.3.1 <i>Tapered PVEHs for transverse excitation</i>	17
2.3.2 <i>Tapered PVEHs for rotational applications</i>	21
2.4 Mathematical Modeling of PVEHs and Performance Comparison	22
2.4.1 <i>Lumped parameter modeling and improvements</i>	23
2.4.2 <i>Nonlinear modeling of PVEHs</i>	24
2.4.2.1 Geometrically nonlinear modeling	24
2.4.2.2 Piezoelectric materially nonlinear modeling	25
2.4.3 <i>Performance comparison standards</i>	27
2.5 Research Gaps	30
2.5.1 <i>Research gaps related to harvester's shape</i>	30

2.5.2	<i>Research gaps related to mathematical modeling</i>	31
2.5.3	<i>Research gaps related to experimental methods</i>	32
2.6	Research Aims and Objectives	32
CHAPTER 3		35
PARABOLIC TAPERING WIDTH PVEH UNDER TRANSVERSE EXCITATION		
3.1	Outline	35
3.2	Nonlinear Mathematical Modeling	36
3.2.1	<i>Theoretical framework</i>	37
3.2.2	<i>Nonlinear electromechanical equations</i>	38
3.2.3	<i>Galerkin's discretization</i>	41
3.2.4	<i>Response analysis</i>	43
3.3	Mathematical Model Validation	46
3.3.1	<i>Validation through earlier models</i>	46
3.3.2	<i>Validation through experimental method</i>	47
3.4	Effects of the Taper Parameter	51
3.5	Effects of the Piezoelectric Patch Thickness	57
3.6	Summary	62

CHAPTER 4	65
PARABOLIC AND EXPONENTIALLY TAPERING PVEHs UNDER ROTATIONAL MOTION	
4.1 Outline	65
4.2 Mathematical Modeling	66
4.2.1 <i>Theoretical framework</i>	67
4.2.2 <i>Electromechanical constitutive relations</i>	68
4.2.3 <i>Discretization principle and equation of motion</i>	70
4.3 Model Validation	73
4.3.1 <i>Validation through FE simulation</i>	74
4.3.2 <i>Validation through experimental methods</i>	77
4.3.3 <i>Validation through earlier numerical models</i>	79
4.4 Performance Comparison	80
4.5 Summary	83
CHAPTER 5	85
PARAMETRIC ANALYSIS OF THE RVEHs	
5.1 Parametric Analysis of the Parabolic Tapering RVEH	85
5.1.1 <i>Taper parameter study</i>	86
5.1.2 <i>Thickness ratio study</i>	88

5.1.3	<i>Length of piezoelectric coupled beam study</i>	90
5.1.4	<i>Overall radius of rotation study</i>	91
5.2	Parametric Analysis of Exponentially Tapering RVEH	94
5.2.1	<i>Effect of taper parameter</i>	95
5.2.2	<i>Effect of the length of the piezoelectric coupled beam</i>	97
5.2.3	<i>Effect of hub radius</i>	99
5.3	Summary	106
 CHAPTER 6		109
CONCLUSIONS AND FUTURE SCOPES		
6.1	Overview	109
6.2	Conclusions	110
6.3	Proposals for Future Research	112
6.4	Publications	113
Appendix I		115
Appendix II		118
Appendix III		120
Appendix IV		124
Appendix V		127
References		129

This page is intentionally left blank

LIST OF FIGURES

Figure 1.1	Polarization of a piezoelectric element (a) randomly oriented polar domains before polarization (b) polarization in DC electric field	4
Figure 1.2	Generator actions of a polarized piezoelectric element, (a) after polarization (b) compressed (c) stretched	4
Figure 1.3	Piezoelectric transducer modelled as an electric unit (voltage generator)	5
Figure 3.1	Line diagram of the parabolic tapering width harvester	37
Figure 3.2	Schematics of the parabolic converging width PZT-coupled VEH with tip mass. The fixed end is at Y-axis and parallel to the Earth's surface (a) Isometric view, (b) front view, and (c) PZT-coupled beam cross-section	38
Figure 3.3	Output voltage for 10 g excitation amplitude with $t_p = 0.254$ mm, $l_e = 80$ mm, $\phi = 0.4$, $b_0 = 50$ mm, $t_h = 0.5$ mm, $M_{LM} = 15.1808$ gram considering and neglecting c_2 and c_4	49
Figure 3.4	The experimental and numerical output voltage for acceleration amplitude of 1 g, 4 g, 7 g, and 10 g. (N: Numerical, E: Experimental)	50
Figure 3.5	The generated output voltage from the PVEH models with taper parameters (a) $\phi = 0$, (b) $\phi = 0.2$, (c) $\phi = 0.4$, and (d) $\phi = 0.6$	52
Figure 3.6	The output voltage backbone curves for the four different models (Figures 3.5a-3.5d)	53

Figure 3.7	The output voltage backbone curves for the models with identical first natural frequencies	54
Figure 3.8	Comparison of the VPM using linear and nonlinear solutions for variation in taper parameters and excitation amplitudes	55
Figure 3.9	Comparison of the PPM calculated using linear and nonlinear solutions for variation in taper parameters and excitation amplitudes, across an optimum load resistance 300 k Ω	56
Figure 3.10	The output voltage from the PVEH models with $\phi = 0.2$ and piezoelectric patch thickness (a) $t_p = 0.15$ mm, (b) $t_p = 0.20$ mm, (c) $t_p = 0.25$ mm, and (d) $t_p = 0.30$ mm	57
Figure 3.11	The output voltage backbone curves for the four different models (Figures 3.8a – 3.8d)	59
Figure 3.12	The output voltage backbone curves for the models with identical first natural frequencies	59
Figure 3.13	Comparison of the linear and nonlinear solutions for variation in the piezoelectric patch thickness and excitation amplitudes (a) VPM and (b) PPM, across an optimum load resistance 300 k Ω	61
Figure 4.1	Schematics of the proposed parabolic varying cross-section piezoelectric harvester with tip load. The system is rotating about Y' -axis (a) Isometric view, (b) front view, and (c) left-hand side view	67
Figure 4.2	The FE layout of the proposed parabolic tapered RVEH's components and the thicknesses of the PZT-coupled beam	75

Figure 4.3	The voltage coupling to simulate the electrodes over the PZT surfaces	76
Figure 4.4	The FE model of the proposed exponentially tapered RVEH (a) The components of the RVEH and the thicknesses of the PZT-coupled beam (b) Voltage coupling used to replicate the electrodes on the PZT-surfaces	76
Figure 4.5	The peak OC voltage response of the parabolic tapering width RVEH against driving frequency	78
Figure 4.6	The peak open-circuit voltage response of the exponentially tapered RVEH against driving frequency	79
Figure 5.1	Effect of the variation of taper parameter on the RVEH's response, the peak open-circuit voltage against driving frequency	86
Figure 5.2	The VPM of the RVEH against the driving frequency for taper parameters 0 – 0.8	87
Figure 5.3	Effect of the variation of thickness ratio on the RVEH's response; the peak open-circuit voltage against driving frequency	88
Figure 5.4	The VPM against the driving frequency for thickness ratios 0.363 – 0.847	89
Figure 5.5	Effect of the variation of piezoelectric coupled beam length on the RVEH's response; the peak OC voltage against driving frequency	90
Figure 5.6	The VPM against the driving frequency for lengths 52 – 92 mm	91
Figure 5.7	Effect of the variation of overall radius of rotation on the RVEH's response; the peak OC voltage against driving frequency	92

Figure 5.8	The VPM against the driving frequency for overall radiuses 77 – 87 mm	93
Figure 5.9	The calculated VPM of the harvester and the respective fitting curves against (a) ϕ , (b) t_r , (c) l , and (d) r_o	94
Figure 5.10	For various taper parameters with $t_p = 0.15$ mm, $r = 20$ mm, $l = 60$ mm, $b_0 = 50$ mm, and $t_h = 0.45$ mm; the calculated resonant frequency against the rotational driving frequency	96
Figure 5.11	For various taper parameters with $t_p = 0.15$ mm, $r = 20$ mm, $l = 60$ mm, $b_0 = 50$ mm, and $t_h = 0.45$ mm; the output voltage response of the RVEH against the rotational driving frequency	97
Figure 5.12	For various piezoelectric coupled beam lengths with $t_p = 0.15$ mm, $r = 20$ mm, $\phi = 10$, $b_0 = 50$ mm, and $t_h = 0.45$ mm; the calculated resonant frequency against the rotational driving frequency	98
Figure 5.13	For various piezoelectric coupled beam lengths with $t_p = 0.15$ mm, $r = 20$ mm, $\phi = 10$, $b_0 = 50$ mm, and $t_h = 0.45$ mm; the output voltage response of the RVEH against the rotational driving frequency	99
Figure 5.14	For various hub radiuses with $t_p = 0.15$ mm, $l = 60$ mm, $\phi = 10$, $b_0 = 50$ mm, and $t_h = 0.45$ mm; the calculated resonant frequency against the rotational driving frequency	100

Figure 5.15	For various hub radiuses with $t_p = 0.15$ mm, $l = 60$ mm, $\phi = 10$, $b_0 = 50$ mm, and $t_h = 0.45$ mm; the generated voltage response of the RVEH against the rotational driving frequency	101
Figure 5.16	The VPM of the harvester against the driving rotational frequency for various values of ϕ , l , and r	102
Figure 5.17	Comparison of the calculated matched frequencies of the RVEH and the simulated frequencies of the peak output voltage against (a) ϕ (b) r (c) l	103
Figure 5.18	The (a) exponential taper parameter, (b) effective length of the PZT-coupled beam, and (c) hub radius, with driving frequency under the achieved frequency matching	104
Figure 5.19	Comparison of the generated power of the RVEH versus resistance R , functioning at its measured resonant frequencies related with hub radiuses equal to 20, 30, 40, and 50 mm with $t_p = 0.15$ mm, $l = 60$ mm, $\phi = 10$, $b_0 = 50$ mm, and $t_h = 0.45$ mm	105
Figure III.1	Experimental setup used to test the PVEH and validate the mathematical model	120
Figure III.2	Shaker arrangement with a fixture to mount the harvester	121
Figure III.3	The parabolic tapering width (a) brass host beam (b) harvester with surface bonded PZT 5H patch and (c) various load masses	122
Figure III.4	For 10 g acceleration, the signal from the DSO under (a) 15.43 Hz and (b) 20.08 Hz excitation frequency	122

Figure IV.1	Experimental setup used to test the RVEH and validate the mathematical model	125
Figure IV.2	Rotating shaft arrangement with a cross hub to mount the harvester	125
Figure IV.3	Exponentially tapering width PZT-coupled beam of the RVEH	126

LIST OF TABLES

Table 1.1	Physical properties of commonly used piezoelectric materials	3
Table 2.1	A comparison of the performance of some tapering cross-section PVEHs under transverse excitation	20
Table 2.2	A comparison of the performance of some tapering cross-section PVEHs for rotational motion	22
Table 3.1	Comparison of the output voltage from the VEH using different nonlinear formulations for 1g, 4g, 7g, and 10g base excitation amplitudes	47
Table 3.2	Physical properties of the PVEH's components	48
Table 3.3	Numerical values of the coefficients	49
Table 3.4	Comparison of the linear and nonlinear VPM of the PVEH for 7 g and 10 g base excitation amplitudes	56
Table 3.5	Comparison of the linear and nonlinear VPM of the PVEH for 4 g, 7 g, and 10 g base excitation amplitudes	61
Table 4.1	The element types used for various components of the RVEH	75
Table 4.2	Verification of the present model against the past reported rectangular harvesters	80
Table 4.3	Performance comparison of the proposed parabolic and exponentially tapered RVEHs with some other reported models	82

This page is intentionally left blank