

# Contents

<b>Certificate</b> .....	<b>iii</b>
<b>Declaration by the Candidate</b> .....	<b>v</b>
<b>Copyright Transfer Certificate</b> .....	<b>vii</b>
<b>Acknowledgements</b> .....	<b>viix</b>
<b>Contents</b> .....	<b>xi</b>
<b>List of Figures</b> .....	<b>xvii</b>
<b>List of Tables</b> .....	<b>xxvii</b>
<b>List of Symbols and Abbreviations</b> .....	<b>xxix</b>
<b>Preface</b> .....	<b>xxxiii</b>
<b>CHAPTER 1: Introduction and Literature Review</b> .....	<b>1</b>
1.1 Introduction .....	1
1.2 Fuel Cells: An Overview .....	3
1.2.1 Fuel Cell Efficiency .....	4
1.2.2 Fuel cell voltage .....	6
1.3 Fuel Cell Types .....	7
1.4 Solid oxide fuel cell (SOFC) .....	10
1.5 Operation Principle .....	11
1.6 Components of SOFC .....	13
1.6.1 Oxygen electrode (Cathode) .....	13
1.6.2 Fuel electrode (Anode) .....	14
1.6.3 Interconnect .....	14
1.6.4 Electrolyte .....	15
1.7 Factors influencing the ionic conductivity of an electrolyte .....	18
1.7.1 Conduction Process .....	19

1.7.2 Microstructural Control .....	23
1.8 Present scenario of electrolyte materials for solid oxide fuel cell.....	26
1.9 Materials for electrolytes.....	28
1.9.1 Fluorite structured electrolyte.....	28
1.9.2 Brownmillerite – type ceramics.....	31
1.9.3 La <sub>2</sub> Mo <sub>2</sub> O <sub>9</sub> (LAMO <sub>X</sub> ) based electrolyte materials.....	33
1.9.4 Apatite structure.....	35
1.9.5 Perovskite-based ceramics.....	36
1.9.6 Sodium Bismuth Titanate (Na <sub>0.5</sub> Bi <sub>0.5</sub> TiO <sub>3</sub> ).....	39
1.9.7 Pyrochlores based ceramics .....	40
1.9.8 δ-Bi <sub>2</sub> O <sub>3</sub> based ceramics .....	41
1.10 Tri-Yttrium Gallate (Y <sub>3</sub> GaO <sub>6</sub> ).....	43
1.11 Objective of the Present Research Work.....	45
<b>CHAPTER 2: Synthesis, Characterizations and Analysis Techniques .....</b>	<b>47</b>
2.1 Overview .....	47
2.1.1 Specification of Raw Materials .....	48
2.2 Materials Synthesis .....	49
2.2.1 Solid-State Reaction Route (SSR).....	49
2.2.2 Polyol-mediated synthesis route .....	50
2.3 Pelletization for Conductivity and Dilatometry Measurements .....	52
2.4 Characterization Techniques .....	53
2.4.1 Thermal Analysis (TGA-DTA) .....	53
2.4.2 X-Ray Diffraction Analysis (XRD).....	55
2.4.3 Bragg's law.....	55
2.4.4 Fourier Transform Infrared Spectroscopy (FTIR).....	58
2.4.5 Dilatometry .....	59
2.4.6 BET Surface Area Measurements .....	61

2.4.7 Raman Spectroscopy .....	62
2.4.8 X-Ray Photoelectron Spectroscopy (XPS) .....	65
2.4.9 Scanning Electron Microscopy (SEM) .....	67
2.4.10 Ultra-Violet Visible (UV-Vis) Spectroscopy .....	69
2.4.11 Photoluminescence Spectroscopy (PL) .....	70
2.4.12 Density Measurement .....	72
2.5 Electrical Data Analysis .....	73
2.5.1 Impedance Spectroscopy Analysis .....	75
2.5.2 Conductivity Spectroscopy Technique .....	80
2.6 Analysis Techniques .....	82
2.6.1 Rietveld Refinement Technique .....	82
2.6.2 Process of Analyzing the Obtained Data .....	87
2.7 Theoretical Studies .....	87
2.7.1 Bond Valance Energy-Based Approach .....	87
<b>CHAPTER 3: Effect of Sintering Temperature on Ion Dynamics of Na<sub>0.5</sub>Bi<sub>0.5</sub>TiO<sub>3</sub>.....</b>	<b>89</b>
3.1 Introduction .....	89
3.2 Experimental Procedure .....	90
3.3 Results and Discussion.....	91
3.3.1 Structural Studies.....	91
3.3.2 AC Conductivity Formalism.....	93
3.3.3 Scaling Mechanism.....	98
3.3.4 Differential Impedance Analysis .....	101
3.3.5 Correlation of structural and electrical behaviour .....	103
3.3.6 Stability under reducing atmosphere .....	106
3.4 Conclusion.....	107
<b>CHAPTER 4: Ion Dynamics of Non-Stoichiometric Na<sub>0.5+x</sub>Bi<sub>0.5-x</sub>TiO<sub>3-δ</sub>: A Degradation Study.....</b>	<b>109</b>
4.1 Introduction .....	109

4.2 Experimental Procedure .....	110
4.3 Results and Discussion.....	111
4.3.1 Structural Studies.....	111
4.3.2 Microstructural Analysis .....	114
4.3.3 X-ray Photoelectron Spectroscopy Analysis .....	115
4.3.4 Thermogravimetric Analysis (TGA) .....	120
4.3.5 AC Conductivity Formalism.....	121
4.4 Degradation Mechanism.....	124
4.4.1 Structural Properties Before and After Reduction.....	124
4.4.2 Electrical Properties before and after reduction .....	126
4.5 Conclusion.....	134
<b>CHAPTER 5: Investigation of Oxide Ion Migration in Bi-deficient Mg<sup>2+</sup> Doped Sodium Bismuth Titanate.....</b>	<b>135</b>
5.1 Introduction.....	135
5.2 Experimental Procedure .....	136
5.3 Results and Discussion.....	137
5.3.1 Structural Analysis.....	137
5.3.2 Migration Pathway Analysis.....	141
5.3.3 Surface Morphology Study .....	145
5.3.4 FTIR Study .....	146
5.3.5 Thermogravimetric Analysis .....	147
5.3.6 Raman Spectroscopy Study .....	148
5.3.7 Brunauer- Emmett-Teller (BET) Analysis .....	151
5.3.8 Electrical Conductivity Study .....	153
5.4 Conclusion.....	156
<b>CHAPTER 6: Oxide-ion conduction in alkaline earth metal doped Y<sub>3</sub>GaO<sub>6</sub>: Substitution on A site.....</b>	<b>159</b>
6.1 Introduction.....	159

6.2 Experimental Procedure .....	160
<b>PART A .....</b>	<b>162</b>
<b>Oxide Ion Conduction in Alkaline Earth Metal Doped <math>Y_3GaO_6</math>.....</b>	<b>162</b>
6.3 Results and Discussion.....	162
6.3.1 Structural Analysis.....	162
6.3.2 Conductivity Analysis .....	169
6.3.3 Photoluminescence (PL) Analysis .....	176
6.3.4 UV-Vis Analysis.....	177
6.3.5 FTIR Analysis.....	178
6.3.6 SEM Analysis .....	179
6.3.7 Thermal Expansion Study.....	180
6.4 Conclusion.....	183
<b>PART B.....</b>	<b>162</b>
<b>Examining the consequences of calcium substitution on the structural and electrical properties of <math>Y_3GaO_6</math>.....</b>	<b>184</b>
6.5 Results and Discussion.....	184
6.5.1 Structural Studies.....	184
6.5.2 Surface morphology and density .....	189
6.5.3 UV-Vis Analysis.....	190
6.5.4 Impedance Analysis.....	191
6.5.5 Electron density map .....	194
6.5.6 PL Analysis.....	197
6.5.7 Scaling behaviour and conduction mechanism.....	199
6.5.8 Cyclic Voltammetry.....	200
6.6 Conclusions .....	202
<b>CHAPTER 7: Conclusions and Future Scopes.....</b>	<b>205</b>
7.1 Conclusion of the Present Investigation.....	205
7.2 Outlook for Future Perspective .....	207

**References..... 211**  
**List of Publications ..... 230**

---

---

## LIST OF FIGURES

---

---

		Page No.
<b>Chapter I</b>	<b>Introduction and Literature review</b>	
<b>Fig. 1.1</b>	(a) World energy consumption by different energy sources with projection from 2010 to 2050. (b) Energy consumption by fuel type	<b>2</b>
<b>Fig. 1.2</b>	William Groves battery diagram	<b>4</b>
<b>Fig. 1.3</b>	Maximum efficiency of hydrogen fuel cell with the steam produced compared to Carnot limit with 50 °C exhaust temperature	<b>5</b>
<b>Fig. 1.4</b>	Plot indicating for a low temperature fuel cell fed with air and hydrogen	<b>7</b>
<b>Fig. 1.5</b>	Reactions at electrodes for different types of fuel cells	<b>10</b>
<b>Fig. 1.6</b>	Schematic of working principle of (a) oxide ion conducting (b) proton-conducting SOFC	<b>12</b>
<b>Fig. 1.7</b>	Schematic of ion diffusion mechanism (a) vacancy diffusion (b) Interstitial diffusion (c) ions exchange in solid state structure	<b>17</b>
<b>Fig. 1.8</b>	Comparative of bulk conductivity of prominent oxide ion conductors	<b>18</b>
<b>Fig. 1.9</b>	(a) Sources of ionic carriers in oxides (b) Correlation between composition, microstructure, processing, and electrical conductivity of polycrystalline materials	<b>19</b>
<b>Fig. 1.10</b>	Present scenario of electrolyte materials	<b>28</b>
<b>Fig. 1.11</b>	Fluorite structure	<b>29</b>
<b>Fig. 1.12</b>	Brownmillerite crystal structure	<b>33</b>
<b>Fig. 1.13</b>	Comparison of the cationic environment of $\beta$ -SnWO <sub>4</sub> and $\beta$ -La <sub>2</sub> Mo <sub>2</sub> O <sub>9</sub>	<b>34</b>
<b>Fig. 1.14</b>	Structural defects position and conduction mechanism	<b>36</b>

<b>Fig. 1.15</b>	(a) Perovskite structure $ABO_3$ (b) Schematic of the curved pathway of oxide ion migration along the $BO_6$ octahedron (c) Saddle point configuration of oxide ion migration showing relaxation	<b>37</b>
<b>Fig. 1.16</b>	Visualization of $\delta$ - $Bi_2O_3$ unit cell	<b>41</b>
<b>Fig. 1.17</b>	Crystal structure of $Y_3GaO_6$ along 001 direction showing $GaO_4$ tetrahedra. Green, red and blue sphere represents the $Y^{3+}$ , $O^{2-}$ , and $Ga^{3+}$ ions, respectively. Y1 and Y2 of the crystallographic positions of Y	<b>44</b>
<b>Chapter II</b>	<b>Synthesis, Characterizations and Analysis Techniques</b>	
<b>Fig. 2.1</b>	Schematic of Solid-state reaction route	<b>50</b>
<b>Fig. 2.2</b>	Schematics of polyol mediated synthesis process	<b>52</b>
<b>Fig. 2.3</b>	Experimental setup of hydraulic press machine	<b>53</b>
<b>Fig. 2.4</b>	(a) The schematic representation and (b) experimental setup of TGA/DSC (right) [Central instrument facility (CIF) IIT (BHU)]	<b>54</b>
<b>Fig. 2.5</b>	(a) Visualization of Bragg's law (b) Schematic representation of $\theta/2\theta$ diffraction in Bragg-Brentano geometry	<b>56</b>
<b>Fig. 2.6</b>	Experimental setup of X-ray diffractometer CIF IIT (BHU) [Rigaku Miniflex II, Japan].	<b>57</b>
<b>Fig. 2.7</b>	(a) Mechanism and (b) experimental setup of Fourier transform infrared spectroscopy	<b>58</b>
<b>Fig. 2.8</b>	Experimental setup of Dilatometry for TEC measurement [NETZSCH DIL, 402 PC/4]	<b>60</b>
<b>Fig. 2.9</b>	(a) Mechanism and (b) Experimental setup of porosity and BET surface area analyzer [Micromeritics ASAP 2020]	<b>62</b>
<b>Fig. 2.10</b>	Schematic representation of the principle of Raman spectroscopy	<b>64</b>
<b>Fig. 2.11</b>	Experimental setup of DXRxi Raman measurement	<b>65</b>
<b>Fig. 2.12</b>	(a) Mechanism and (b) Experimental setup for the XPS spectroscopy (Kratos Amicus)	<b>66</b>



<b>Fig. 2.13</b>	(a) Mechanism and (b) Experimental setup of SEM measurement (CIF-IIT (BHU))	<b>68</b>
<b>Fig. 2.14</b>	Experimental setup of UV-Visible measurement [JASCO V-770 UV-Vis spectrometer]	<b>70</b>
<b>Fig. 2.15</b>	(a) Mechanism and (b) Experimental setup of photoluminescence spectroscopy	<b>72</b>
<b>Fig. 2.16</b>	Density measurement kit by Sartorius, BSA2245-CW	<b>73</b>
<b>Fig. 2.17</b>	Experimental set up of automated impedance analyzer along with sample holder and furnace (6500 P Wayne Kerr, UK)	<b>74</b>
<b>Fig. 2.18</b>	Experimental set up of automated impedance analyzer along with sample holder and furnace (6500 P Wayne Kerr, UK)	<b>79</b>
<b>Fig. 2.19</b>	A typical conductivity spectra of a polycrystalline material	<b>81</b>
<b>Fig. 2.20</b>	A typical FullProf software interface during the Rietveld refinement process	<b>84</b>
<b>Chapter III</b>	<b>Effect of Sintering Temperature on Ion Dynamics of <math>\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3</math></b>	
<b>Fig. 3.1</b>	(a) Rietveld refinement of XRD pattern for different sintering temperatures (b) FTIR of the sample sintered at 1100 °C	<b>91</b>
<b>Fig. 3.2</b>	Depicts the variation of $\log \sigma$ vs $\log \nu$ from 500 °C to 700 °C at the step of 20 °C for the samples synthesized under different sintering temperatures (a) 1000 °C (b) 1050 °C (c) 1100 °C (d) 1150 °C	<b>94</b>
<b>Fig. 3.3</b>	(a) Variation of $\log \sigma_{dc}$ vs $\log \nu_h$ (b) Arrhenius plot for estimation of activation energy for the samples synthesized under different sintering temperatures, (c) Variation of $E_a$ with sintering temperature and (d) SEM micrographs of the samples sintered at different sintering temperatures and respective insets shows their grain size histograms	<b>94</b>
<b>Fig.3.4</b>	Variation of ‘n’ with temperature for the samples synthesized under different sintering temperatures	<b>96</b>
<b>Fig.3.5</b>	Variation of charge carrier concentration factor ‘N’ with temperature for the samples synthesized under different sintering temperatures	<b>98</b>
<b>Fig.3.6</b>	Ghosh scaling for the samples synthesized under different sintering temperatures	<b>99</b>

<b>Fig. 3.7</b>	Summerfield scaling for the samples synthesized under different sintering temperatures	<b>100</b>
<b>Fig. 3.8</b>	Modulus scaling ( $M''/M''_{\max}$ vs $\nu/\nu_{\max}$ ) with the variation of sintering temperature (a) 1000 °C (b) 1050 °C (c) 1100 °C (d) 1150 °C	<b>100</b>
<b>Fig. 3.9</b>	Variation of Na/Bi-Ti bond with the sintering temperature (inset) structure of NBT from Diamond	<b>101</b>
<b>Fig. 3.10</b>	Estimation of K using relation $ Z _{adj} = f^{-K}$ from $\log  Z $ vs $\log \nu$ for all the studied samples	<b>102</b>
<b>Fig. 3.11</b>	Variation of K with temperature ranging from 500 °C to 700 °C for all the studied samples	<b>103</b>
<b>Fig. 3.12</b>	(a) Normalized $M''$ and $Z''$ isotherms with frequency in the temperature range of 500 °C to 700 °C with the variation of sintering temperature (b) Variation of relaxation hopping frequency with temperature for the samples sintered at 1000 °C and 1150 °C (c) Range of $\Delta\nu_r$ for all the studied samples	<b>103</b>
<b>Fig. 3.13</b>	(a) Plot of XRD intensity of peak ( $2\theta \sim 32^\circ$ ) vs $2\theta - \delta$ ( $^\circ$ ) where $\delta$ is the angle at which maxima occurs showing diffuseness of XRD peak with the sintering temperature, (b) Variation of coherence length, $L_{\text{coh}}$ and lattice constant, $a$ with the sintering temperature	<b>105</b>
<b>Fig. 3.14</b>	X-ray diffractograms of the NBT sample and the sample dipped in propan-2-ol ( $\text{C}_3\text{H}_7\text{OH}$ ) for two days (i) $\log \sigma$ vs $\log \nu$ for the NBT sample and sample dipped in propan-2-ol (ii) Modulus Nyquist plots at room temperature for the NBT sample and sample dipped in propan-2-ol (iii) Gray highlighted region of inset (ii) showing modulus Nyquist plots of pure NBT sample at room temperature	<b>107</b>
<b>Chapter IV</b>	<b>Ion Dynamics of Non-Stoichiometric <math>\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}</math>: A Degradation Study</b>	
<b>Fig. 4.1</b>	X-ray diffractograms of the $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, -0.01, 0.0, 0.01$ and $0.02$ ) compositions	<b>111</b>
<b>Fig. 4.2</b>	Rietveld refined X-ray diffractograms of the studied $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, -0.01, 0.0, 0.01$ and $0.02$ ) compositions	<b>112</b>
<b>Fig. 4.3</b>	Volume and tolerance factor of the studied $\text{Na}_{0.50+x}\text{Bi}_{0.50-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, -0.01, 0.0, 0.01$ and $0.02$ ) compositions	<b>114</b>

<b>Fig. 4.4</b>	SEM micrographs of the studied $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, -0.01, 0.0, 0.01$ and $0.02$ , (a-e)) compositions	<b>115</b>
<b>Fig. 4.5</b>	Wide range X-Ray photoelectron spectra of $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, 0.00, 0.01$ and $0.02$ ) compositions showing the presence of Na, Bi, Ti and O	<b>117</b>
<b>Fig. 4.6</b>	X-ray photoelectron spectroscopy measurements (deconvoluted peaks) of the studied $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, 0.0, 0.01$ and $0.02$ ) compositions	<b>117</b>
<b>Fig. 4.7</b>	Depicts the Na/Bi ratio and grain size obtained from XPS and grain histograms, respectively	<b>119</b>
<b>Fig. 4.8</b>	Thermogravimetric analysis of the studied $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.01, 0.0$ and $0.01$ ) compositions	<b>120</b>
<b>Fig. 4.9</b>	(a) Variation of $\log \sigma$ vs $\log \nu$ for $x = 0.0$ sample (for instance), (b) Variation of exponent with temperature, (c) Variation of $\log \sigma_{dc}$ vs $\log \nu_h$ and (d) Arrhenius fitting of conductivity	<b>123</b>
<b>Fig. 4.10</b>	(a) Comparative of X-ray diffractograms of the fresh and reduced samples and (b) Visualization of unit cell structure of fresh and reduced sample of composition with $x = 0$	<b>124</b>
<b>Fig. 4.11</b>	Comparative of $\log \sigma$ vs $\log \nu$ of the fresh and reduced $x = 0.0$ sample	<b>127</b>
<b>Fig. 4.12</b>	Comparative of $\ln \sigma$ vs $1000/T$ , exponent vs temperature with error bars and $\log \sigma_{dc}$ and $\log \nu_h$ of the fresh and reduced $x = -0.01, 0.0$ and $0.01$ samples	<b>128</b>
<b>Fig. 4.13</b>	Comparative of $\log \tau_o$ vs $x$ of the fresh and reduced $x = -0.01, 0.0$ and $0.01$ samples, (inset) Linear fitting of $\log \nu_h$ vs $1000/T$ of the fresh $x = -0.01, 0.0$ and $0.01$ samples	<b>129</b>
<b>Fig. 4.14</b>	Variation of the value of concentration of mobile charge ions with temperature of the fresh and reduced $x = -0.01, 0.0$ and $0.01$ samples	<b>130</b>
<b>Fig. 4.15</b>	Variation of $\tan \delta$ with temperature of the fresh and reduced $x = -0.01, 0.0$ and $0.01$ samples	<b>131</b>
<b>Fig. 4.16</b>	Thermogravimetric analysis of the reduced $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.01, 0.0$ and $0.01$ ) compositions	<b>132</b>
<b>Chapter V</b>	<b>Investigation of Oxide Ion Migration in Bi-deficient <math>\text{Mg}^{2+}</math> Doped Sodium Bismuth Titanate</b>	

<b>Fig. 5.1</b>	(a) X-ray diffractogram pattern of $\text{Na}_{0.5}\text{Bi}_{0.49}\text{Ti}_{(1-x)}\text{Mg}_{(x)}\text{O}_{3-\delta}$ ( $x = 0.00, 0.01, 0.02, 0.03$ ) (b) Representative crystal structure in 3D view	<b>138</b>
<b>Fig. 5.2</b>	Rietveld refinement pattern of NBT4900, NBT4901, NBT4902 and NBT4903. Black circles represent the experimental data, and red lines are the fit.	<b>139</b>
<b>Fig. 5.3</b>	(a) Variation of lattice parameters $a$ , $c$ and, volume (b) Octahedral tilting ( $\phi$ ) with composition obtained from Rietveld refinement	<b>140</b>
<b>Fig. 5.4</b>	(i) Bond valence energy landscape (BVEL) of all the investigated system at the iso-surface value 2.5 eV (ii) Oxide ion migration channel of studied composition in the b-c plane obtained from BVE method.	<b>142</b>
<b>Fig. 5.5</b>	(a-d) Oxide ion diffusion energy migration barrier landscape for NBT4900, NBT4901, NBT4902 and NBT4903, respectively. All the sample are showing 3D migration channel except NBT4903 in which 2D migration is predominating (e) A representative BVEL of NBT4902 unit cell	<b>144</b>
<b>Fig. 5.6</b>	SEM Micrographs of the sintered samples. Inset shows grain size distribution histogram	<b>145</b>
<b>Fig. 5.7</b>	FTIR spectrum of $\text{Na}_{0.5}\text{Bi}_{0.49}\text{Ti}_{(1-x)}\text{Mg}_{(x)}\text{O}_{3-\delta}$ ( $x = 0.00, 0.01, 0.02, 0.03$ )	<b>146</b>
<b>Fig. 5.8</b>	TGA of $\text{Na}_{0.5}\text{Bi}_{0.49}\text{Ti}_{(1-x)}\text{Mg}_{(x)}\text{O}_{3-\delta}$ ( $x = 0.00, 0.01, 0.02, 0.03$ ) in $\text{N}_2$ atmosphere	<b>148</b>
<b>Fig. 5.9</b>	Room temperature Raman spectra of the studied compositions	<b>149</b>
<b>Fig. 5.10</b>	Deconvoluted Raman spectra using 13 peaks showing the presence of R3c symmetry	<b>150</b>
<b>Fig. 5.11</b>	FWHM variation in Raman spectra for E(TO4) and E(LO9) mode of all the investigated compositions	<b>151</b>
<b>Fig. 5.12</b>	BET nitrogen adsorption isotherm as a function of relative pressure	<b>152</b>
<b>Fig. 5.13</b>	(a) Representative AC impedance spectra at 500 °C (b) Arrhenius plot for total conductivity (c) Variation of	<b>155</b>

migration barrier and activation energy for  $\text{Na}_{0.5}\text{Bi}_{0.49}\text{Ti}_{(1-x)}\text{Mg}_{(x)}\text{O}_{3-\delta}$  ( $x = 0.00, 0.01, 0.02, 0.03$ )

<b>Chapter VI</b>	<b>Oxide-ion conduction in alkaline earth metal doped <math>\text{Y}_3\text{GaO}_6</math>: Substitution on A site</b>	
<b>Fig. 6.1</b>	(a) Room-temperature XRD pattern of the studied samples and XRD of $\text{Y}_3\text{GaO}_6$ taken from ICSD database (b) 3D polyhedral representation of crystal structure	<b>164</b>
<b>Fig. 6.2</b>	Rietveld refined patterns with observed (black circles), calculated (solid red line), Bragg reflections (green vertical ticks) and (blue line) difference profiles for the studied compositions sintered at 1350 °C for 6h	<b>164</b>
<b>Fig. 6.3</b>	(a) Schematic of the energy barrier landscape of single oxide ion migration inside the crystal lattice (b) Crystal structure, including migration iso-surface of at 2.7 eV in $\text{Y}_3\text{GaO}_6$ . Yellow colour represents the iso-surface.	<b>166</b>
<b>Fig. 6.4</b>	(a-b) Bond valance energy landscape for oxide ion migration viewed along c axis with various iso-surface. Yellow iso-surface in Fig. (a) represents the presence of migration pathway and the rejected iso-surface in Fig. (b) represents the absence of migration channel. The energy difference between fig. a and b gives the Energy barrier $E_b$ for migration at room temperature (c) Energy barrier histogram at room temperature for studied compositions.	<b>167</b>
<b>Fig. 6.5</b>	Oxygen ion diffusion iso-surface channel of YGO and YCGO along c-axis at (a) 2.80 eV (b) at 3.90 eV derived from the bond valance energy landscape using VESTA software.	<b>168</b>
<b>Fig. 6.6</b>	(a) Complex Impedance plot of studied compositions at 600 °C in the air. (b) Complex Impedance plot for YCGO and YSGO sample. (c) Arrhenius plot (Variation of $\log [\sigma_{\text{bulk}}*T]$ with the inverse of temperature) of the studied compositions with the inversed of temperature.	<b>172</b>
<b>Fig. 6.7</b>	Dependence of (a) total conductivity (b) oxide ion conductivity on the dopant ionic radii at 700 °C	<b>173</b>
<b>Fig. 6.8</b>	Intrinsic strain developed inside the crystal due to defects, grain boundary and faults calculated using Williamson-Hall analysis	<b>175</b>

<b>Fig. 6.9</b>	Oxygen partial-pressure dependence of total electrical conductivity of YGO, YCGO, and YSGO samples at (a) 700 and (b) 800 °C, respectively.	<b>175</b>
<b>Fig. 6.10</b>	Room temperature photoluminescence spectra under an excitation wavelength of 260 nm and slit width 1nm	<b>176</b>
<b>Fig. 6.11</b>	(a) Tauc's plot for direct band-gap calculation of YGO, YCGO, YSGO and YBGO samples. (b) Corresponding band structure.	<b>177</b>
<b>Fig. 6.12</b>	Room temperature FTIR spectra of YGO, YCGO, YSGO and YBGO samples. Figure in the inset shows the decrease in the metal-oxygen bond intensity with the increase in the atomic mass of dopant	<b>179</b>
<b>Fig. 6.13</b>	(a-d) SEM Micrographs of YGO, YCGO, YSGO and YBGO samples. Inset in the figure shows grain size distribution (e) Grain size variation of the studied compositions	<b>180</b>
<b>Fig. 6.14</b>	Thermal expansion curve of YGO, YCGO and YSGO compositions from Room temperature to 1000 °C	<b>182</b>
<b>Fig. 6.15</b>	(a) XRD patterns of studied compositions (b) Crystal structure of $Y_3GaO_6$	<b>185</b>
<b>Fig. 6.16</b>	The percentage of phase purity with the increase in calcium concentration in $Y_3GaO_6$	<b>187</b>
<b>Fig. 6.17</b>	(a) Rietveld refinement fit pattern of all the studied systems (b) Full structure refinement of 0Ca and 2Ca composition.	<b>188</b>
<b>Fig. 6.18</b>	(a-c) Variation of lattice parameters and volume with dopant concentration for orthorhombic ( $Y_3GaO_6$ ), cubic ( $Y_2O_3$ ) and triclinic ( $CaCO_3$ ) phases, respectively (d) Oxygen percentage change for all the compositions analyzed from Rietveld refinement and SEM-EDX studies.	<b>189</b>
<b>Fig. 6.19</b>	(a-e) SEM micrographs of $Y_{3(1-x)}Ca_{3x}GaO_6$ ( $x = 0, 0.02, 0.04, 0.08, 0.12$ ) compositions.	<b>189</b>
<b>Fig. 6.20</b>	Tauc plot showing the variation of $(\alpha h\nu)^2$ vs $h\nu$ with dopant concentration	<b>191</b>
<b>Fig. 6.21</b>	(a) Impedance Nyquist plot at 700 °C. Inset depicts the equivalent circuit to fit the impedance spectra along with impedance plot of Ca doped compositions (b) Arrhenius plot	<b>193</b>

	for total conductivity of studied compositions. Inset depicts the conductivity histogram at 700 °C	
<b>Fig. 6.22</b>	Arrhenius plot for (a) grain (b) grain-boundary conductivity of studied compositions	<b>194</b>
<b>Fig. 6.23</b>	Electron density contour map of all studied compositions in the z-y plane	<b>196</b>
<b>Fig. 6.24</b>	Space charge ionic fitting model for all the studied specimens	<b>197</b>
<b>Fig. 6.25</b>	(a-b) Room temperature photoluminescence spectra with an excitation wavelength of 305 nm	<b>198</b>
<b>Fig. 6.26</b>	Modulus scaling behaviour for all the samples at different temperatures	<b>199</b>
<b>Fig. 6.27</b>	(a-b) Cyclic voltammogram curve with the various scan rate (c) Specific capacitance at different scan rate for 0Ca and 2Ca sample (d) Chronoamperometry plot of undoped $Y_3GaO_6$ sample at 1.5 V	<b>201</b>





---

---

## LIST OF TABLES

---

---

		Page No.
<b>Chapter I</b>	<b>Introduction and Literature review</b>	
Table 1.1	Different types of fuel cells with their characteristics	9
<b>Chapter II</b>	<b>Synthesis, Characterizations and Analysis Techniques</b>	
Table 2.1	Description of the raw materials with their chemical formula, purity, and manufacturer used for the preparation of proposed compositions	48
<b>Chapter III</b>	<b>Effect of Sintering Temperature on Ion Dynamics of <math>\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3</math></b>	
Table 3.1	Atomic positions and R-factors obtained after refinement for the $\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3$ samples sintered at different temperature	92
<b>Chapter IV</b>	<b>Ion Dynamics of Non-Stoichiometric <math>\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}</math>: A Degradation Study</b>	
Table 4.1	Lattice parameters, atomic positions and goodness of fitting parameters of the studied $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.02, -0.01, 0.0, 0.01$ and $0.02$ compositions)	113
Table 4.2	Area of the peaks obtained from XPS peak fitting	118
Table 4.3	$\delta$ obtained from TGA and XPS	121
Table 4.4	Lattice parameters, atomic positions and goodness of fitting parameters of the studied $\text{Na}_{0.5+x}\text{Bi}_{0.5-x}\text{TiO}_{3-\delta}$ ( $x = -0.01, 0.0, 0.01$ ) compositions after reducing	125
Table 4.5	Lattice parameters, atomic positions and goodness of fitting parameters of the sample dipped in propanol for 48h	125
<b>Chapter V</b>	<b>Investigation of Oxide Ion Migration in Bi-deficient <math>\text{Mg}^{2+}</math> Doped Sodium Bismuth Titanate</b>	
Table 5.1	Position coordinates and Rietveld fitting parameters and for all the studied samples	140
Table 5.2	Average crystallite size, micro-strain and density of the investigated compositions	141
Table 5.3	Oxygen vacancy estimated from TGA data and electrical conductivity	148

Table 5.4	BET surface area, pore size and pore volume of all investigated compositions	<b>152</b>
<b>Chapter VI</b>	<b>Oxide-ion conduction in alkaline earth metal doped <math>Y_3GaO_6</math>: Substitution on A site</b>	
Table 6.1	Rietveld refined lattice parameters, volume, density and porosity of the studied compositions	<b>163</b>
Table 6.2	Value of grain, grain-boundary capacitance, total conductivity at 600 °C, and activation energy of studied compositions	<b>170</b>
Table 6.3	Bonding strength with the oxygen of di-valent A-site dopant	<b>173</b>
Table 6.4	TEC of the measured sample between room temperature and 1000 °C	<b>182</b>
Table 6.5	Crystallite size, lattice strain, density and FWHM of the studied samples	<b>188</b>
Table 6.6	Energy band gap	<b>191</b>
Table 6.7	Comparison of grain, grain-boundary conductivity and activation energy of Ca doped samples	<b>194</b>