

## Contents

<b>Abstract</b> .....	<b>v-vi</b>
<b>Acknowledgements</b> .....	<b>vii-viii</b>
<b>Contents</b> .....	<b>ix-xii</b>
<b>List of Figures</b> .....	<b>xiii-xix</b>
<b>List of Tables</b> .....	<b>xxi</b>
<b>Abbreviations</b> .....	<b>xxiii</b>
<b>Nomenclature</b> .....	<b>xxv-xxvii</b>
<b>Preface</b> .....	<b>xxix-xxxii</b>
<b>Chapter 1 Introduction</b> .....	<b>1-14</b>
1.1. Piezoelectricity.....	1
1.2. Piezoelectric Effect- Basic Mathematical Formulation.....	5
1.3. Piezoelectric Composites.....	7
<i>1.3.1. Background</i> .....	7
<i>1.3.2. Connectivity Patterns</i> .....	8
<i>1.3.3. Composite Effects</i> .....	11
1.4. Motivation.....	13
1.5 Summary.....	14
<b>Chapter 2 Literature Review</b> .....	<b>15-31</b>
2.1. Analytical Models.....	15
2.2. Numerical Approaches.....	19
2.3. Experimental Characterization.....	24
2.4. Objective of the Present Thesis.....	29
<b>Chapter 3 Micromechanics of Piezoelectric Inclusion and Inhomogeneities</b> ...33-76	
3.1. Introduction.....	33

3.2. Governing Equations of Piezoelectricity .....	35
3.3. Piezoelectric Inclusion and Inhomogeneities .....	38
3.3.1. <i>Evaluation of Electroelastic Green's Functions</i> .....	45
3.3.2. <i>Electroelastic Eshelby Tensors for Spheroidal Inclusion</i> .....	49
3.4. Effective Electroelastic Moduli .....	54
3.4.1. <i>Traction-electric displacement prescribed</i> .....	54
3.4.2. <i>Elastic displacement-electric field prescribed</i> .....	58
3.5. Results and Discussion .....	60
3.6. Summary .....	76
<b>Chapter 4 Effective Properties of Short-fiber Piezoelectric Composites.....</b>	<b>77-105</b>
4.1. Introduction .....	77
4.2. Coupled Electro-Elastic Fields Modeling inside an Inclusion .....	79
4.3. Calculation of Effective Properties .....	84
4.4. Finite Element Modeling .....	87
4.4.1. <i>Calculation of Effective Properties through FEM</i> .....	90
4.4.2. <i>Boundary Conditions and Parameter Calculations</i> .....	92
4.5. Results and Discussion .....	97
4.6. Summary .....	104
<b>Chapter 5 Effective Properties of Long-fiber Piezoelectric Composites.....</b>	<b>107-156</b>
5.1. Introduction .....	107
5.2. Constitutive Relations .....	110
5.3. Micromechanics Model .....	114
5.3.1. <i>Modified Strength of Materials Method (MSM) Model</i> .....	114
5.3.2. <i>Strain Energy Method</i> .....	122
5.3.3. <i>Results and Discussion</i> .....	126

5.4. Numerical Model.....	136
5.4.1. Finite Element Method (FEM).....	136
5.4.2. Periodic Boundary Conditions.....	137
5.4.3. Calculation of Effective Coefficients through FEM.....	138
5.4.4. Results and Discussion.....	146
5.5. Summary.....	154
<b>Chapter 6 Effective Performance Parameters of Piezoelectric Composites.....</b>	<b>157-182</b>
6.1. Introduction.....	157
6.2. Governing Equation of Piezoelectricity.....	161
6.3. Modified Strength of Materials (MSM) Model.....	162
6.4. Analytical Model base on Mori-Tanaka Approach.....	166
6.5. Performance Parameters of 1-3 Piezocomposite.....	168
6.5.1. Piezoelectric Charge Coefficient.....	168
6.5.2. Hydrostatic Electromechanical Coupling Factor.....	169
6.5.3. Electromechanical Coupling Constant.....	169
6.5.4. The Acoustic Impedance.....	170
6.5.5. Stiffened Longitudinal Velocity.....	170
6.6. Results and Discussion.....	171
6.7. Summary.....	181
<b>Chapter 7 Conclusions and Suggestions for Future Work.....</b>	<b>183-186</b>
7.1. General Conclusions.....	183
7.2. Suggestions for Future Work.....	185
<b>References.....</b>	<b>187-204</b>
<b>Appendix A.....</b>	<b>205</b>

<b>Appendix B.....</b>	<b>207-208</b>
<b>Appendix C.....</b>	<b>209-210</b>
<b>List of Publications.....</b>	<b>211</b>

## List of Figures

Figure 1.1 Piezoelectricity: An intermingling of elastic and electric phenomenon.....	1
Figure 1.2 Piezoelectric materials in sensing and actuating applications; (a) P-E hysteresis plot (top) and S-E plot (bottom); (b) The piezoelectric material before and after poling; (c) Change in dimension when applied voltage has polarity similar to that of poling voltage; (d) Change in dimension when the applied voltage has polarity opposite to that of poling voltage; (e) The voltage generated equivalent to poling voltage when compressive force is applied in poling direction; (f) The voltage generated equivalent to poling voltage when tensile force is applied in poling direction.....	4
Figure 1.3 Connectivity families for diphasic composites. The total number of connectivity patterns arising out of 10 families depicted is 16 due to permutations of order involved in families; {0-2}, {0-3}, {1-0}, {1-3}, {2-1}, {2-3}.....	9
Figure 1.4 Schematic diagram showing composites with various connectivity patterns realized over the past 40 years.....	10
Figure 1.5 Composite effects: (a) sum effect; (b) combination effect;(c) product effect..	12
Figure 3.1(a) Schematic of an ellipsoidal inclusion in a matrix medium.....	39
Figure 3.1(b) Schematic of a spheroidal inclusion in a matrix medium.....	50
Figure 3.2 The distribution of the Green's function $G_{11}$ in space.....	61
Figure 3.3 The distribution of the Green's function $G_{12}$ in space.....	62
Figure 3.4 The distribution of the Green's function $G_{13}$ in space.....	62
Figure 3.5 The distribution of the Green's function $G_{14}$ in space.....	63
Figure 3.6 The distribution of the Green's function $G_{22}$ in space.....	63

Figure 3.7 The distribution of the Green's function $G_{23}$ in space.....	64
Figure 3.8 The distribution of the Green's function $G_{24}$ in space.....	64
Figure 3.9 The distribution of the Green's function $G_{33}$ in space.....	65
Figure 3.10 The distribution of the Green's function $G_{34}$ in space.....	65
Figure 3.11 The distribution of the Green's function $G_{44}$ in space.....	66
Figure 3.12 Vanishing Eshelby tensors at infinite aspect ratio.....	67
Figure 3.13 Non-vanishing Eshelby tensors at infinite aspect ratio.....	68
Figure 3.14 Eshelby tensors involving interaction between elastic and electric fields....	68
Figure 3.15 The composite normal modulus $E_{1111}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	70
Figure 3.16 The composite normal modulus $E_{1122}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	70
Figure 3.17 The composite normal modulus $E_{1133}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	71
Figure 3.18 The composite normal modulus $E_{3333}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	71
Figure 3.19 The composite shear modulus $E_{2323}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	72
Figure 3.20 The composite shear modulus $E_{1212}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	72
Figure 3.21 The composite piezoelectric constant $E_{4311}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	73
Figure 3.22 The composite piezoelectric constant $E_{4333}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	73

Figure 3.23 The composite dielectric constant $E_{4141}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	74
Figure 3.24 The composite dielectric constant $E_{4343}$ against fiber volume fraction for various aspect ratios, $\alpha_f$ .....	74
Figure 4.1(a) FEA model of an active composite containing spheroid inclusion; (i) Structure of composite (mesh element view); (ii) RVE of SC fiber arrangement (inner inclusion view); (iii) RVE of BCC fiber arrangement (inner inclusion view).....	91
Figure 4.1(b) The convergence graph for determining ideal mesh size for the FE Analysis.....	92
Figure 4.2 Representative Volume Element (RVE) depicting von Mises stress distribution containing spheroid inclusion in SC arrangement (Fiber volume fraction ranging from 0.1-0.5), (a) 0.1, (b) 0.2, (c) 0.3, (d) 0.4, (e) 0.5.....	95
Figure 4.3 Representative Volume Element (RVE) depicting von Mises stress distribution containing spheroid inclusion in BCC arrangement (Fiber volume fraction ranging from 0.1-0.5), (a) 0.1, (b) 0.2, (c) 0.3, (d) 0.4, (e)0.5.....	96
Figure 4.4 Comparison of the predicted effective elastic coefficient $C_{11}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	97
Figure 4.5 Comparison of the predicted effective elastic coefficient $C_{12}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	98
Figure 4.6 Comparison of the predicted effective elastic coefficient $C_{13}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	98

Figure 4.7 Comparison of the predicted effective elastic coefficient $C_{33}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	99
Figure 4.8 Comparison of the predicted effective elastic coefficient $C_{44}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	99
Figure 4.9 Comparison of the predicted effective elastic coefficient $C_{66}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	100
Figure 4.10 Comparison of the predicted effective piezoelectric coefficient $e_{31}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	101
Figure 4.11 Comparison of the predicted effective piezoelectric coefficient $e_{33}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	101
Figure 4.12 Comparison of the predicted effective piezoelectric coefficient $e_{15}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	102
Figure 4.13 Comparison of the predicted effective dielectric coefficient $\kappa_{11}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	103
Figure 4.14 Comparison of the predicted effective dielectric coefficient $\kappa_{33}$ of BaTiO <sub>3</sub> /PZT-5H composite with respect to fiber volume fraction for the analytical Eshelby Method and numerical FEM Method.....	103
Figure 5.1 (a) Schematic of a piezoelectric fiber reinforced composite PFRC (1-3	



piezocomposite).....	116
Figure 5.1 (b) A representative volume element (RVE).....	116
Figure 5.2 Transverse cross-section of a representative volume element of PFRC (1-3 piezocomposite).....	117
Figure 5.3 The effective elastic coefficient $C_{11}$ as predicted by the model developed in the present study (MSM), SM Model and Energy Model with change in fiber volume fraction.....	127
Figure 5.4 The effective elastic coefficient $C_{12}$ as predicted by the model developed in the present study (MSM), SM Model and Energy Model with change in fiber volume fraction.....	128
Figure 5.5 The effective elastic coefficient $C_{13}$ as predicted by the model developed in the present study (MSM), SM Model and Energy Model with change in fiber volume fraction.....	128
Figure 5.6 The effective elastic coefficient $C_{33}$ as predicted by the model developed in the present study (MSM), SM Model and Energy Model with change in fiber volume fraction.....	130
Figure 5.7 Comparison of predicted parameter $R_{31}$ with change in fiber volume fractions.....	131
Figure 5.8 Comparison of predicted parameter $R_{32}$ with change in fiber volume fractions.....	132
Figure 5.9 Comparison of predicted parameter $R_{33}$ with change in fiber volume fractions.....	132
Figure 5.10 Comparison of predicted effective dielectric constant $\kappa_{33}$ with change in fiber volume fractions.....	135
Figure 5.11 The convergence graph for determining ideal mesh size for the FE	

analysis.....	139
Figure 5.12(a) RVE of finite element analysis (FEA): Fiber volume fractions (0.1-0.6 with step size of 0.1) taken to evaluate effective properties.....	144
Figure 5.12(b) The distribution of stress/electric field in the RVE when the mechanical load (in z-direction) and boundary conditions are applied; (i) stress in direction-1 (x-axis); (ii) stress in direction-2 (y-axis); (iii) stress in direction-3 (z-axis); (iv) electric field distribution in direction-3 (z-axis).....	145
Figure 5.13 The predicted effective elastic coefficient $C_{11}^c$ with change in fiber volume fraction estimated by strength of materials model, present micromechanics model and FEM model.....	149
Figure 5.14 The predicted effective elastic coefficient $C_{12}^c$ with change in fiber volume fraction estimated by strength of materials model, present micromechanics model and FEM model.....	149
Figure 5.15 The predicted effective elastic coefficient $C_{13}^c$ with change in fiber volume fraction estimated through strength of materials model, present micromechanics model and FEM model.....	150
Figure 5.16 The predicted effective elastic coefficient $C_{33}^c$ with change in fiber volume fraction estimated by strength of materials model, present micromechanics model and FEM model.....	150
Figure 5.17 The predicted effective piezoelectric coefficient $e_{31}^c$ with change in fiber volume fraction estimated by strength of materials model, present micromechanics model and FEM model.....	152
Figure 5.18 The predicted effective piezoelectric coefficient $e_{33}^c$ with change in fiber volume fraction estimated by strength of materials model, present	

micromechanics model and FEM model.....	152
Figure 5.19 The predicted effective dielectric constant $\kappa_{33}^c$ with change in fiber volume fraction estimated by strength of materials model, present micromechanics model and FEM model.....	153
Figure 6.1 Schematic of a 1-3 piezoelectric composite.....	163
Figure 6.2 Transverse cross-section of a representative volume element (RVE) of 1-3 piezoelectric composite.....	164
Figure 6.3 Comparison of effective electromechanical coupling constant $K_t$ of 1-3 piezoelectric composite between experimental measurements and present analysis as a function of fiber volume fraction.....	173
Figure 6.4 Comparison of effective acoustic impedance $Z$ of 1-3 piezoelectric composite between experimental measurements and present analysis as a function of fiber volume fraction.....	174
Figure 6.5 Comparison of effective stiffened longitudinal velocity $V_{33}^D$ of 1-3 piezoelectric composite between experimental measurements and present analysis as a function of fiber volume fraction.....	176
Figure 6.6 Comparison of effective short-circuit stiffness constant $C_{33}^D$ of 1-3 piezoelectric composite between experimental measurements and present analysis as a function of fiber volume fraction.....	178
Figure 6.7 Comparison of effective short-circuit stiffness constant $C_{33}^E$ of 1-3 piezoelectric composite between experimental measurements and present analysis as a function of fiber volume fraction.....	179
Figure 6.8 Comparison of effective hydrostatic charge coefficient $d_h$ of 1-3 piezoelectric composite between experimental measurements and present analysis as a function of fiber volume fraction.....	180

## **List of Tables**

Table 2.1 A summary of the analytical models and numerical models developed to predict effective coefficients of piezocomposites.....	25
Table 3.1 Electroelastic constants of the constituent materials.....	61
Table 4.1 Material properties of fiber and matrix phases.....	89
Table 5.1. Material properties of fiber and matrix phases.....	126
Table 5.2: Material properties of the fiber and matrix phases for FEM calculations.....	140
Table 5.3 List of boundary conditions applied on RVE and formula for calculation of effective coefficients.....	142
Table 5.4 Classifications of coefficients in groups according to the boundary conditions used for FEM analysis.....	146
Table 6.1 Material properties of constituents (fiber and matrix phases).....	172