

## LIST OF FIGURES

| Figure No.       | Figure Caption  | Page No. |
|------------------|---|----------|
| <b>Fig 1.1:</b>  | Typical composition and structure of engine exhaust particles [Kittelsohn 1998]   | 03       |
| <b>Fig 1.2:</b>  | Typical particle composition for a heavy-duty diesel engine tested in a heavy duty transient cycle. [Kittelsohn 1998]                               | 04       |
| <b>Fig 1.3:</b>  | Schematic diagram of a steady burning jet on the basis of laser measurements  | 05       |
| <b>Fig 1.4:</b>  | Formation of PM [Tree and Svensson 2007]  | 07       |
| <b>Fig 1.5:</b>  | Typical Structure of Soot   | 08       |
| <b>Fig 1.6:</b>  | Schematic of mass and number based particle size distributions from diesel engines  | 09       |
| <b>Fig 1.7:</b>  | Transport of the PM with breath according to their size   | 10       |
| <b>Fig 1.8:</b>  | Effect of soot on vegetation  | 11       |
| <b>Fig 1.9:</b>  | Localized Effect of soot on environment   | 14       |
| <b>Fig1.10:</b>  | Effect of soot emission on monuments  | 15       |
| <b>Fig1.11:</b>  | Overall pollution control units in a typical diesel engine exhaust pipe   | 19       |
| <b>Fig1.12:</b>  | Schematic diagram of DPF  | 20       |
| <b>Fig1.13:</b>  | Diesel Oxidation catalyst   | 21       |
| <b>Fig1.14:</b>  | Diesel Particulate Filter   | 22       |
| <b>Fig1.15:</b>  | Active Regeneration of DPF (a) electrical heater, (b) fuel burner   | 23       |
| <b>Fig1.16:</b>  | Passive Regeneration of DPF   | 24       |
| <b>Fig1.17:</b>  | Flow pattern in wall flow monolith  | 26       |
| <b>Fig1.18:</b>  | Wash coated filter  | 27       |
| <b>Fig1.19:</b>  | Partial flow diesel particulate filter  | 29       |
| <b>Fig1.20:</b>  | CRT filter system   | 30       |
| <b>Fig 1.21:</b> | Flow diagram of catalyst Reclamation  | 34       |
| <b>Fig 2.1:</b>  | (a) $ABO_3$ ideal cubic perovskite structure (b) perovskite framework   | 47       |
| <b>Fig 2.2:</b>  | SEM images of catalyst-soot mixture with (a) tight contact and (b) loose contact  | 57       |
| <b>Fig 2.3:</b>  | Temperature programmed oxidations of soot over $K_2Ti_2O_5$ with different types of contact. The inset shows the atomic structure of $K_2Ti_2O_5$ . | 58       |
| <b>Fig 3.1:</b>  | Schematic diagram for perovskite catalyst preparation by co-precipitation method  | 61       |
| <b>Fig 3.2:</b>  | Flow diagram of Sol-gel method  | 63       |

|                 |   |     |
|-----------------|---|-----|
| <b>Fig 3.3:</b> | Flow diagram of SCS method  | 65  |
| <b>Fig 3.4:</b> | Thermograms of lanthanum nitrate-chromium nitrate-urea precursor [Biamino and Badini 2004]                          | 66  |
| <b>Fig 3.5:</b> | Flow diagram of reactive grinding method  | 67  |
| <b>Fig 3.6</b>  | (a) Planetary ball mill, (b) Jar and grinding balls ( $ZrO_2$ )   | 68  |
| <b>Fig 3.7</b>  | General view of the Bomb Calorimeter  | 71  |
| <b>Fig 3.8</b>  | Schematic diagram of Experimental Setup   | 82  |
| <b>Fig 3.9</b>  | Schematic diagram of the Reactor  | 83  |
| <b>Fig 3.10</b> | General view of the Experiment Assembly   | 84  |
| <b>Fig 3.11</b> | General view of the Gas Chromatograph   | 85  |
| <b>Fig 3.12</b> | Schematic diagram of Gas Chromatograph  | 86  |
| <b>Fig 3.13</b> | Injector diagram for Gas Chromatograph  | 87  |
| <b>Fig 3.14</b> | Schematic diagram of the Flame Ionization Detector.   | 89  |
| <b>Fig 3.15</b> | A typical plot of chromatogram area of $CO_2$ formed by soot oxidation vs. Temperature                              | 91  |
| <b>Fig 3.16</b> | Atypical plot of soot conversion vs. temperature  | 91  |
| <b>Fig 4.1</b>  | Schematic diagram of preparation of diesel soot   | 92  |
| <b>Fig 4.2</b>  | Particle size analysis based on particle number density   | 94  |
| <b>Fig 4.3</b>  | Particle size analysis based on particle volume density   | 95  |
| <b>Fig 4.2</b>  | X-Ray pattern of the laboratory prepared diesel soot  | 95  |
| <b>Fig 4.3</b>  | SEM images of the laboratory prepared diesel soot   | 96  |
| <b>Fig 5.1</b>  | $N_2$ Physisorption isotherms of catalysts (a) A-750 (b) C-750 and (c) B-750, calcined at $750^\circ C$             | 103 |
| <b>Fig 5.2</b>  | Pore size distribution curves of catalysts (a) A-750 (b) C-750 and (c) B-750  | 104 |
| <b>Fig 5.3</b>  | XRD patterns of $LaCoO_3$ prepared by (A) Co-ppt, (B) SCS, (C) SG and calcined at $750^\circ C$                     | 106 |
| <b>Fig 5.4</b>  | XRD analysis of $LaCoO_3$ calcined at different temperatures, 600, 750 and $800^\circ C$                            | 107 |
| <b>Fig 5.5</b>  | FTIR spectra of the $LaCoO_3$ (co-ppt) catalyst   | 108 |
| <b>Fig 5.6</b>  | XPS spectra of catalyst A-750   | 110 |
| <b>Fig 5.7</b>  | SEM images of $LaCoO_3$ prepared by (a) Co-ppt, (b) SG, (c) SCS and calcined at $750^\circ C$                       | 111 |
| <b>Fig 5.8</b>  | Effect of preparation method on soot oxidation over $LaCoO_3$ calcined at $750^\circ C$                             | 112 |
| <b>Fig 5.9</b>  | Effect of calcination temperature on soot oxidation over $LaCoO_3$ prepared by (a) Co-ppt (b) SG and (c) SCS method | 114 |

|                 |   |     |
|-----------------|---|-----|
| <b>Fig 6.1</b>  | N <sub>2</sub> Physisorption isotherms of catalysts (a) La <sub>0.9</sub> Sr <sub>0.1</sub> CoO <sub>3</sub> , (b) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Ni <sub>0.5</sub> O <sub>3</sub> , (c) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Cu <sub>0.5</sub> O <sub>3</sub> and (d) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Fe <sub>0.5</sub> O <sub>3</sub> | 123 |
| <b>Fig 6.2</b>  | Pore size distribution curves of catalysts (a) La <sub>0.9</sub> Sr <sub>0.1</sub> CoO <sub>3</sub> , (b) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Ni <sub>0.5</sub> O <sub>3</sub> , (c) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Cu <sub>0.5</sub> O <sub>3</sub> and (d) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Fe <sub>0.5</sub> O <sub>3</sub>          | 124 |
| <b>Fig 6.3</b>  | XRD Pattern of (A) LaCoO <sub>3</sub> , (B) LaFeO <sub>3</sub> , (C) LaNiO <sub>3</sub> and (D) LaZnO <sub>y</sub>  | 126 |
| <b>Fig 6.4</b>  | XRD Pattern of Pure and Substituted Perovskite Catalysts  | 128 |
| <b>Fig 6.5</b>  | FTIR spectra of (A) LaCoO <sub>3</sub> , (B) LaFeO <sub>3</sub> , (C) LaNiO <sub>3</sub>  | 129 |
| <b>Fig 6.6</b>  | FTIR spectra of the LaZnO <sub>y</sub>  | 129 |
| <b>Fig 6.7</b>  | FTIR spectra of Pure and Substituted Perovskite Catalysts   | 130 |
| <b>Fig 6.8</b>  | XPS Spectra of LaCoO <sub>3</sub>   | 132 |
| <b>Fig 6.9</b>  | XPS Spectra of LaFeO <sub>3</sub>   | 133 |
| <b>Fig 6.10</b> | XPS Spectra of La <sub>0.9</sub> Sr <sub>0.1</sub> CoO <sub>3</sub>   | 134 |
| <b>Fig 6.11</b> | XPS Spectra of La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Ni <sub>0.5</sub> O <sub>3</sub>   | 134 |
| <b>Fig 6.12</b> | XPS Spectra of La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Cu <sub>0.5</sub> O <sub>3</sub>   | 135 |
| <b>Fig 6.13</b> | XPS Spectra of La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Fe <sub>0.5</sub> O <sub>3</sub>   | 136 |
| <b>Fig 6.14</b> | SEM images of LaZnO <sub>y</sub> catalyst; (A) 1000x (B) 2,000x (C) 5,000xs and (D) 10,000x magnification   | 137 |
| <b>Fig 6.15</b> | SEM images of (E) LaCoO <sub>3</sub> , (F) LaFeO <sub>3</sub> , (G) LaNiO <sub>3</sub>  | 137 |
| <b>Fig 6.16</b> | SEM images of (H) La <sub>0.9</sub> Sr <sub>0.1</sub> CoO <sub>3</sub> , (I) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Ni <sub>0.5</sub> O <sub>3</sub> , (J) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Cu <sub>0.5</sub> O <sub>3</sub> and (K) La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Fe <sub>0.5</sub> O <sub>3</sub>                                       | 138 |
| <b>Fig 6.17</b> | Soot conversion over Perovskite-type Catalysts, Calcined at 750 °C, Catalyst/ Soot: 10/1, Tight Contact, Air flow rate: 150ml/min   | 140 |
| <b>Fig 6.18</b> | Soot conversion over single Sr-substituted Perovskite-type Catalysts, Calcined at 750 °C, Catalyst/ Soot: 10/1, Tight Contact, Air flow rate: 150ml/min   | 141 |
| <b>Fig 6.19</b> | Soot conversion over substituted Perovskite-type Catalysts, Calcined at 750 °C, Catalyst/ Soot: 10/1, Tight Contact, Air flow rate: 150ml/min   | 142 |
| <b>Fig 6.20</b> | Effect of gas hourly space velocity on soot oxidation, by La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Fe <sub>0.5</sub> O <sub>3</sub> , (Catalyst/Soot: 10/1)  | 143 |
| <b>Fig 6.21</b> | Effect of contact type on soot oxidation on LaCoO <sub>3</sub> catalyst, Calcination 750°C Catalyst/Soot: 10/1, air flow rate: 150ml/min  | 145 |
| <b>Fig 6.22</b> | Comparison of soot conversion over transition metal and noble metal based Perovskite-type Catalysts   | 146 |
| <b>Fig 7.1</b>  | (a) N <sub>2</sub> Physisorption isotherms and (b) Pore size distribution of Cat-CC   | 152 |
| <b>Fig 7.2</b>  | (a) N <sub>2</sub> Physisorption isotherms and (b) Pore size distribution of Cat-RC   | 152 |
| <b>Fig 7.3</b>  | X-Ray Patterns of Cat-CC and Cat-RC Perovskite Catalysts  | 153 |
| <b>Fig 7.4</b>  | XPS Spectra of Cat-CC (La <sub>0.9</sub> Sr <sub>0.1</sub> Co <sub>0.5</sub> Fe <sub>0.5</sub> O <sub>3</sub> )   | 155 |

|                 |   |     |
|-----------------|---|-----|
| <b>Fig 7.5</b>  | XPS Spectra of Cat -RC ( $\text{La}_{0.9}\text{Sr}_{0.1}\text{Co}_{0.5}\text{Fe}_{0.5}\text{O}_3$ )   | 156 |
| <b>Fig 7.6</b>  | FTIR spectra of pure and substituted perovskite catalysts   | 157 |
| <b>Fig 7.7</b>  | SEM images of (A) Cat-CC and (B) Cat-RC perovskite catalyst   | 158 |
| <b>Fig 7.8</b>  | EDX spectra of (A) Cat-CC and (B) Cat-RC perovskite catalyst  | 159 |
| <b>Fig 7.9</b>  | Conversion of soot with Air and RC- $\text{La}_{0.9}\text{Sr}_{0.1}\text{Co}_{0.5}\text{Fe}_{0.5}\text{O}_3$ Perovskite Catalysts   | 159 |
| <b>Fig 7.10</b> | Conversion of soot with different Cat-Soot ratio over RC- $\text{La}_{0.9}\text{Sr}_{0.1}\text{Co}_{0.5}\text{Fe}_{0.5}\text{O}_3$  | 160 |
| <b>Fig 7.11</b> | Conversion of soot with different Cat-Soot Contact Conditions over RC- $\text{La}_{0.9}\text{Sr}_{0.1}\text{Co}_{0.5}\text{Fe}_{0.5}\text{O}_3$   | 160 |
| <b>Fig 8.1</b>  | Cat-CC (a) $\text{N}_2$ adsorption/desorption isotherms and (b) pore size distribution curves   | 167 |
| <b>Fig 8.2</b>  | Cat-RGA (a) $\text{N}_2$ sorption/desorption isotherms, (b) pore size distribution curves   | 168 |
| <b>Fig 8.3</b>  | X-Ray patterns of SG and RG prepared Perovskite Catalysts   | 169 |
| <b>Fig 8.4</b>  | FTIR spectra of SG and RG prepared Perovskite Catalysts   | 170 |
| <b>Fig 8.5</b>  | XPS Spectra of Cat-CC   | 171 |
| <b>Fig 8.6</b>  | XPS Spectra of Cat-RGA  | 172 |
| <b>Fig 8.7</b>  | SEM images of Perovskite Catalysts  | 173 |
| <b>Fig 8.8</b>  | EDX spectra of (A) Cat-CC and (B) Cat-RGA perovskite catalyst   | 174 |
| <b>Fig 8.9</b>  | Performance of the catalysts for Diesel Soot Oxidation  | 175 |
| <b>Fig 8.10</b> | The Performance of the Cat-RGA for Diesel Soot Oxidation in Loose and Tight contact   | 176 |
| <b>Fig 9.1</b>  | Schematic diagram of the semi-batch reactor   | 183 |
| <b>Fig 9.2</b>  | XRD pattern and FTIR spectra of the Perovskite Catalyst   | 184 |
| <b>Fig 9.3</b>  | SEM images of the perovskite Catalyst at different magnifications   | 185 |
| <b>Fig 9.4</b>  | Soot conversion over $\text{La}_{0.9}\text{Sr}_{0.1}\text{Co}_{0.5}\text{Fe}_{0.5}\text{O}_3$ , calcinations at $750^\circ\text{C}$ , catalyst/soot: 10/1, tight contact, air flow rate: 150 ml/min | 186 |
| <b>Fig 9.5</b>  | Plot of chromatogram area of $\text{CO}_2$ ( $\text{ACO}_2$ ) vs time at four constant temperatures over $\text{La}_{0.9}\text{Sr}_{0.1}\text{Co}_{0.5}\text{Fe}_{0.5}\text{O}_3$                   | 187 |
| <b>Fig 9.6</b>  | First order kinetics model for catalytic oxidation of soot at different temperature   | 188 |
| <b>Fig 9.7</b>  | Arrhenius plot for catalytic oxidation of soot  | 189 |